



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
RESEARCH TRIANGLE PARK, NC 27711

APR 15 2011

OFFICE OF
AIR QUALITY PLANNING
AND STANDARDS

Mr. William J. Hofert
Controller and Acting Regulatory Affairs Manager
DeVilbiss Automotive Refinishing
11360 S. Airfield Road
Swanton, Ohio 43558

Dear Mr. Hofert:

This letter is in response to your November 1, 2010, request for approval of the DeVilbiss CVI High Efficiency, GTI Pro High Efficiency, GFG-670 (Plus), and ITW Tekna High Efficiency spray guns, hereinafter referred to as the DeVilbiss spray guns, as equivalent to the transfer efficiency achieved by high-volume, low-pressure (HVLP) spray guns for use when spray applying automotive refinish coatings under subpart HHHHHH of 40 CFR part 63.

We have completed our review of your reports entitled:

“Evaluation of the DeVilbiss CVI, GTI Pro, and ITW Tekna High Efficiency (HE) spray guns for use in the South Coast Air Quality Management District (SCAQMD)” dated May 2008 including the supplemental information dated October 22, 2008, and

“Evaluation of the DeVilbiss Plus spray gun for use in the SCAQMD area” dated June 6, 2002, including the accompanying laboratory data dated April 23, 2002, and supplemental information dated June 12, 2002.

The results of the transfer efficiency testing performed indicate that the DeVilbiss spray guns are capable of achieving equivalent or better transfer efficiency than HVLP spray equipment. As a result, the DeVilbiss spray guns are approved for operations subject to §63.11173(e)(3) of 40 CFR part 63 subpart HHHHHH, Paint Stripping and Miscellaneous Surface Coating Operations. This approval is subject to the following conditions.

1. DeVilbiss Automotive Refinishing shall supply written notification with each DeVilbiss spray gun sold or distributed that the spray gun is approved as providing equivalent transfer efficiency as HVLP spray guns for the application of coatings subject to 40 CFR part 63 subpart HHHHHH.

2. This approval is only valid for the DeVilbiss spray guns if the air pressure supplied is equal to or less than that stated for each spray gun below:

GFG-670 (Plus)	40 psig
CVI High Efficiency	26 psig
GTI Pro High Efficiency	26 psig
ITW Tekna High Efficiency	22 psig


Additionally, DeVilbiss Automotive Refinishing shall supply written notification with each DeVilbiss spray gun sold or distributed that the maximum air pressure supplied to the spray gun shall not exceed the values stated above for each spray gun for the application of coatings subject to 40 CFR part 63 subpart HHHHHH.

3. DeVilbiss Automotive Refinishing shall supply an appropriate pressure gauge to allow precise measurement of the inlet air pressure, reflecting the maximum air pressure for the specific gun, with each DeVilbiss spray gun sold or distributed for the application of coatings subject to 40 CFR part 63 subpart HHHHHH. DeVilbiss Automotive Refinishing shall supply written notification with each DeVilbiss spray gun sold or distributed that the pressure gauge shall be attached to the spray gun and be in good working condition whenever the spray gun is in operation for the application of coatings subject to 40 CFR part 63 subpart HHHHHH.

4. This approval is only valid if during actual operation the DeVilbiss spray gun is equipped with a properly operating pressure gauge as described in condition number 3.

If you have any questions regarding this approval, please contact Kim Teal, of my staff, at (919) 541-5580 or teal.kim@epa.gov.

Sincerely,



Stephen D. Page
Director
Office of Air Quality Planning
and Standards