

Statement of Basis of the Federal Operating Permit

Shell Oil Company

Site Name: Refinery
Area Name: Chemical Plant Deer Park
Physical Location: 5900 Highway 225
Nearest City: Deer Park
County: Harris

Permit Number: O1669
Project Type: Reopening

Standard Industrial Classification (SIC) Code: 2911
SIC Name: Petroleum Refining

This Statement of Basis sets forth the legal and factual basis for the draft changes to the permit conditions resulting from the project in accordance with 30 TAC §122.201(a)(4). This document may include the following information:

- A description of the facility/area process description;
- A description of the revision project;
- A basis for applying permit shields;
- A list of the federal regulatory applicability determinations;
- A table listing the determination of applicable requirements;
- A list of the New Source Review Requirements;
- The rationale for periodic monitoring methods selected;
- The rationale for compliance assurance methods selected;
- A compliance status; and
- A list of available unit attribute forms.

Prepared on: March 3, 2016

Operating Permit Basis of Determination

Description of Revisions

In response to an EPA Order dated December 21, 2015, TCEQ reopened Shell Oil Company, Federal Operating Permit (FOP) O1669 to identify which PBRs apply to which emission units and which preconstruction authorizations (PBRs) apply generally or site-wide in the New Source Review Authorizations table. All registration numbers for specific units with registered preconstruction authorizations (PBRs) have been added to the New Source Review Authorizations by Emission Unit table.

Permit Area Process Description

Shell Deer Park Refining Company is primarily engaged in the production of fuels and lubricants derived from various crude oils or unfinished petroleum derivatives. These products include, but are not limited to, gasoline, naphtha, kerosene, jet fuels, distillate fuel oils, residual fuel oils, other transportation fuels, heating fuels, lubricating oils and base stocks, asphalt, and sulfonates. Various by-products are also produced including sulfur, spent sulfuric acid, coke and hazardous and non-hazardous wastes. To produce the required quality and quantity of fuels and lubricants products, crude oil must undergo several processing steps (units). These processing steps can be grouped into the following categories: distillation, conversion, and treating.

Distillation: Typically the first phase in the refining process is to separate crude oil into its major constituents using distillation, which produces liquids that contain components within specified boiling point ranges. Distillation is also used in other stages of the refining process.

Conversion: Conversion processes are used to convert low value constituents of crude oil (residual oils, fuel oils and light ends) into higher demand/value products such as gasoline, jet fuel and diesel fuel. Coking and cracking processes are used to break large hydrocarbon molecules (as found in residual oils and fuel oils) into smaller ones. Alkylation and dimerization are used to combine small petroleum molecules (light ends) into larger ones. Isomerization and reforming processes rearrange the structure of the molecules to improve the quality/octane of the product.

Treating: Treating processes are used to stabilize and upgrade petroleum products, by changing or removing elements which cause pollution or problems in the refining process. Nitrogen, sulfur, olefins and aromatics are removed by hydrotreating and furfural extraction. Other processes, such as sulfonation, improve physical properties of lube products.

Emission sources consist of storage vessels, combustion sources, loading racks, process vents, control devices, wastewater collection and treatment system, equipment leaks, and vacuum-producing systems.

FOPs at Site

Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). The “area” consists of the emission units and that portion of the site included in this permit. When there is only one area for the site, then the permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: O1668

Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC, SO ₂ , PM, NO _X , HAPS, CO, GHG
------------------	--

Reading State of Texas's Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as “applicable requirements”) that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
 - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
 - Additional Monitoring Requirements
 - New Source Review Authorization Requirements
 - Compliance Requirements
 - Protection of Stratosphere Ozone
 - Permit Location
 - Permit Shield (30 TAC § 122.148)
- Attachments
 - Applicable Requirements Summary
 - Unit Summary
 - Applicable Requirements Summary
 - Additional Monitoring Requirements
 - Permit Shield
 - New Source Review Authorization References
 - Compliance Plan
 - Alternative Requirements
- Appendix A
 - Acronym list
- Appendix B
 - Copies of major NSR authorizations

General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a

requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

Attachments

Applicable Requirements Summary. The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the “index number,” detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

Additional Monitoring Requirement. The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References. All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified.

The NSR Authorization References Table is a list of all NSR authorizations including PBRs for the permit area as explained under the New Source Review Requirements section of the Statement of Basis. This table is a catalog of all NSR permits which can be used by the TCEQ, EPA, and the public to reference in a single tabular format.

The NSR Authorization References by Emissions Unit Table is a list of the NSR authorizations for specific emission units. The table also lists a unit description for the emission unit ID numbers in the permit.

While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan. A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements. This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

Appendix A

Acronym list. This attachment lists the common acronyms used when discussing the FOPs.

Appendix B

Copies of major NSR authorizations applicable to the units covered by this permit have been included in this Appendix, to ensure that all interested persons can access those authorizations.

Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed after January 31, 1972 which are limited, over a six-minute average, to 20% opacity as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3 for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or

perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

Stationary Vents subject to 30 TAC Chapter 111 not addressed in the Special Terms and Conditions

All other stationary vents subject to 30 TAC Chapter 111 not covered in the Special Terms and Conditions are listed in the permit’s Applicable Requirement Summary. The basis for the applicability determinations for these vents are listed in the Determination of Applicable Requirements table.

Federal Regulatory Applicability Determinations

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

Regulatory Program	Applicability (Yes/No)
Prevention of Significant Deterioration (PSD)	Yes
Nonattainment New Source Review (NNSR)	No
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	Yes
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Yes
40 CFR Part 63 - NESHAPs for Source Categories	Yes
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	Yes
CAIR (Clean Air Interstate Rule)	No

Basis for Applying Permit Shields

An operating permit applicant has the opportunity to specifically request a permit shield to document that specific applicable requirements do not apply to emission units in the permit. A permit shield is a special condition stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements. A permit shield has been requested in the application for specific emission units. For the permit shield requests that have been approved, the basis of determination for regulations that the owner/operator need not comply with are located in the “Permit Shield” attachment of the permit.

Insignificant Activities

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

1. Office activities such as photocopying, blueprint copying, and photographic processes.
2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
4. Outdoor barbecue pits, campfires, and fireplaces.
5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.
6. Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
9. Vehicle exhaust from maintenance or repair shops.
10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
15. Well cellars.
16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
18. Equipment used exclusively for the melting or application of wax.
19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
20. Shell core and shell mold manufacturing machines.
21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
22. Equipment used for inspection of metal products.
23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
25. Battery recharging areas.
26. Brazing, soldering, or welding equipment.

Determination of Applicable Requirements

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html.

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS). These flowcharts can be accessed via the internet at www.tceq.texas.gov/permitting/air/nav/air_supportsys.html. The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column "Changes and Exceptions to RRT." If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word "None" will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled "Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected."

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled "Basis for Applying Permit Shields" specifies which units, if any, have a permit shield.

Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

Determination of Applicable Requirements

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
P-87107	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Horsepower Rating = GOP 150+ hp</p> <p>RACT Date Placed in Service = After June 9, 1993 and on or after the final compliance date specified in 30 TAC §§ 117.9000, 117.9010 or 117.9020</p> <p>Functionally Identical Replacement = Unit is not a functionally identical replacement</p> <p>Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)]</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>	
A312-R1	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
A312-R1	40 CFR Part 60, Subpart Kb	60KB-1	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>	
A312-R1	40 CFR Part 63, Subpart CC	63CC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p>	
A333	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Product Stored = Crude oil and/or condensate</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
A333	40 CFR Part 63, Subpart CC	63CC-1	<p>Product Stored = Crude oil</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia	
AP7-R1	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
AP7-R1	40 CFR Part 60, Subpart Kb	60KB-1	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>	
AP7-R1	40 CFR Part 63, Subpart CC	63CC-1	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is part of a process specified in 40 CFR § 63.640(g)(1) - (6).	
F325	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
F325	30 TAC Chapter 115, Storage of VOCs	R5112-3	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
F325	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal	
F325	40 CFR Part 63, Subpart CC	63CC-2	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.	
FP200	30 TAC Chapter 115, Storage of VOCs	R5112-6	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
FP200	40 CFR Part 60, Subpart Kb	60KB-1	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia	
G357	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	
G363	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
G363	40 CFR Part 60, Subpart Kb	60KB-1	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia	
G363	40 CFR Part 63, Subpart CC	63CC-1	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is part of a process specified in 40 CFR § 63.640(g)(1) - (6).	
GRPBENZIGF	40 CFR Part 60, Subpart Kb	60Kb-1	Product Stored = Waste mixture of indeterminate or variable composition Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia	
GRPBENZIGF	40 CFR Part 60, Subpart Kb	60Kb-2	Product Stored = Waste mixture of indeterminate or variable composition Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Vessel Description = Closed vent system (CVS) with a flare used as the control device (fixed roof)	
GRPBENZIGF	40 CFR Part 60, Subpart Kb	60Kb-3	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Closed vent system (CVS) with a flare used as the control device (fixed roof)</p>	
GRPBENZIGF	40 CFR Part 61, Subpart FF	61FF-1	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
GRPBENZIGF	40 CFR Part 63, Subpart G	63CC-1	<p>Negative Pressure = The fixed roof and closed vent systems are not operated and maintained under negative pressure.</p> <p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is used for heating wastewater, treating by means of an exothermic reaction, or the contents of the tank are sparged.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.148</p> <p>By-pass Lines = Closed vent system has no by-pass lines</p> <p>Emission Control Type = Fixed roof tank vented through a closed vent system that routes the organic HAP vapors vented from the wastewater tank to a control device</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Control Device Type = Flare</p> <p>New Source = The source is an existing source.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or approved.</p>	
GRPBENZTK	40 CFR Part 61, Subpart FF	61FF-1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using an external floating roof that meets the requirements of 40 CFR § 60.112b(a)(2)</p> <p>Seal Type = Liquid-mounted primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPBENZTK	40 CFR Part 63, Subpart G	63CC-1	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>Emission Control Type = External floating roof that meets the requirements specified in 40 CFR § 63.119(c), 40 CFR § 63.120(b)(5), and 40 CFR § 63.120(b)(6)</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Control Device Type = ALTERNATE CONTROL DEVICE APPROVED BY ADMINISTRATOR</p> <p>New Source = The source is an existing source.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or approved.</p>	
GRPBWNTK1	40 CFR Part 60, Subpart Kb	60Kb-1	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>	
GRPBWNTK1	40 CFR Part 60, Subpart Kb	60Kb-2	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with liquid-mounted primary seal</p>	
GRPBWNTK1	40 CFR Part 60, Subpart Kb	60Kb-3	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with liquid-mounted primary seal</p>	
GRPBWNTK1	40 CFR Part 61, Subpart FF	61FF-1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using an external floating roof that meets the requirements of 40 CFR § 60.112b(a)(2)</p> <p>Seal Type = Liquid-mounted primary seal</p>	
GRPBWNTK1	40 CFR Part 63, Subpart G	63CC-1	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank greater than or equal to 151m³ and vapor pressure of liquid stored is less than 5.2 kPa</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Control Device Type = ALTERNATE CONTROL DEVICE APPROVED BY ADMINISTRATOR</p> <p>New Source = The source is an existing source.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or approved.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP BWNTK1	40 CFR Part 63, Subpart G	63CC-2	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>Emission Control Type = External floating roof that meets the requirements specified in 40 CFR § 63.119(c), 40 CFR § 63.120(b)(5), and 40 CFR § 63.120(b)(6)</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Control Device Type = ALTERNATE CONTROL DEVICE APPROVED BY ADMINISTRATOR</p> <p>New Source = The source is an existing source.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or approved.</p>	
GRP BWNTK2	40 CFR Part 60, Subpart Kb	60Kb-1	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>	
GRP BWNTK2	40 CFR Part 60, Subpart Kb	60Kb-2	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with liquid-mounted primary seal</p>	
GRP BWNTK2	40 CFR Part 60, Subpart Kb	60Kb-3	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with liquid-mounted primary seal</p>	
GRP BWNTK2	40 CFR Part 61, Subpart FF	61FF-1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using an external floating roof that meets the requirements of 40 CFR § 60.112b(a)(2)</p> <p>Seal Type = Liquid-mounted primary seal</p>	
GRP BWNTK2	40 CFR Part 63, Subpart G	63CC-1	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank greater than or equal to 151m³ and vapor pressure of liquid stored is less than 5.2 kPa</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Control Device Type = Flare</p> <p>New Source = The source is an existing source.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			approved.	
GRPBWNTK2	40 CFR Part 63, Subpart G	63CC-2	<p>Negative Pressure = The fixed roof and closed vent systems are not operated and maintained under negative pressure.</p> <p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.148</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>By-pass Lines = Closed vent system has no by-pass lines</p> <p>Emission Control Type = Fixed roof tank vented through a closed vent system that routes the organic HAP vapors vented from the wastewater tank to a control device</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Control Device Type = Flare</p> <p>New Source = The source is an existing source.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or approved.</p>	
GRPTKEFR1	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Primary Seal = Liquid-mounted foam</p> <p>Product Stored = Crude oil and/or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR1	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Liquid-mounted foam</p> <p>Product Stored = Crude oil and/or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR1	30 TAC Chapter 115, Storage of VOCs	R5112-5	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Primary Seal = Liquid-mounted foam</p> <p>Product Stored = Crude oil and/or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPTKEFR1	40 CFR Part 60, Subpart Ka	60KA-1	Product Stored = Crude oil stored, processed, and/or treated prior to custody transfer Storage Capacity = Capacity is 420,000 gallons (1,589,873 liters) or greater True Vapor Pressure = TVP is greater than or equal to 1.5 but less than or equal to 11.1 psia Storage Vessel Description = Pontoon-type or double-deck-type EFR with liquid-mounted primary seal Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia	
GRPTKEFR1	40 CFR Part 60, Subpart Ka	60KA-2	Product Stored = Crude oil stored, processed, and/or treated prior to custody transfer Storage Capacity = Capacity is 420,000 gallons (1,589,873 liters) or greater True Vapor Pressure = TVP is less than 1.5 psia Storage Vessel Description = Pontoon-type or double-deck-type EFR with liquid-mounted primary seal Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia Maximum True Vapor Pressure = Maximum true vapor pressure is not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized	
GRPTKEFR1	40 CFR Part 63, Subpart CC	63CC-1	Existing Source = The storage vessel is at an existing source. Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = External floating roof Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641) Seal Type = LIQUID-MOUNTED PRIMARY SEAL AS OF JULY 15, 1994	
GRPTKEFR1	40 CFR Part 63, Subpart CC	63CC-2	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Ka Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with liquid-mounted primary seal Reid Vapor Pressure = RVP is greater than or equal to 2.0 psia	
GRPTKEFR10	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Welded tank using an external floating roof True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Primary Seal = Liquid-mounted foam Product Stored = Crude oil and/or condensate Storage Capacity = Capacity is greater than 40,000 gallons	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPTKEFR10	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Liquid-mounted foam</p> <p>Product Stored = Crude oil and/or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR10	30 TAC Chapter 115, Storage of VOCs	R5112-5	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Primary Seal = Liquid-mounted foam</p> <p>Product Stored = Crude oil and/or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR10	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = LIQUID-MOUNTED PRIMARY SEAL AS OF JULY 15, 1994</p>	
GRPTKEFR10	40 CFR Part 63, Subpart CC	63CC-2	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
GRPTKEFR11	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Product Stored = Crude oil and/or condensate</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR11	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Product Stored = Crude oil and/or condensate</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR11	30 TAC Chapter 115, Storage of VOCs	R5112-5	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Product Stored = Crude oil and/or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR11	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal</p>	
GRPTKEFR11	40 CFR Part 63, Subpart CC	63CC-2	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
GRPTKEFR12	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR12	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Welded tank using an external floating roof True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Primary Seal = Mechanical shoe Product Stored = VOC other than crude oil or condensate Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR12	30 TAC Chapter 115, Storage of VOCs	R5112-3	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Welded tank using an external floating roof True Vapor Pressure = True vapor pressure is less than 1.0 psia Primary Seal = Mechanical shoe Product Stored = VOC other than crude oil or condensate Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR12	40 CFR Part 63, Subpart CC	63CC-1	Existing Source = The storage vessel is at an existing source. Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = External floating roof Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641) Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal	
GRPTKEFR12	40 CFR Part 63, Subpart CC	63CC-2	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.	
GRPTKEFR2	30 TAC Chapter 115, Storage of	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOCs		Tank Description = Welded tank using an external floating roof True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Primary Seal = Liquid-mounted foam Product Stored = Crude oil and/or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR2	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Welded tank using an external floating roof True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Primary Seal = Liquid-mounted foam Product Stored = Crude oil and/or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR2	30 TAC Chapter 115, Storage of VOCs	R5112-5	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Welded tank using an external floating roof True Vapor Pressure = True vapor pressure is less than 1.0 psia Primary Seal = Liquid-mounted foam Product Stored = Crude oil and/or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR2	40 CFR Part 60, Subpart K	60K-1	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters) Product Stored = Crude oil True Vapor Pressure = True vapor pressure is less than 1.5 psia Storage Vessel Description = Floating roof (internal or external) Reid Vapor Pressure = Reid vapor pressure is at least 2.0 psia Maximum True Vapor Pressure = Maximum true vapor pressure is not determined	
GRPTKEFR2	40 CFR Part 60, Subpart K	60K-2	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters) Product Stored = Crude oil True Vapor Pressure = True vapor pressure is at least 1.5 psia and less than 11.1 psia Storage Vessel Description = Floating roof (internal or external) Reid Vapor Pressure = Reid vapor pressure is at least 2.0 psia	
GRPTKEFR2	40 CFR Part 63, Subpart CC	63CC-1	Existing Source = The storage vessel is at an existing source. Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart K</p> <p>Seal Type = LIQUID-MOUNTED PRIMARY SEAL AS OF JULY 15, 1994</p>	
GRPTKEFR2	40 CFR Part 63, Subpart CC	63CC-2	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart K</p>	
GRPTKEFR3	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Primary Seal = Liquid-mounted foam</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR3	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Liquid-mounted foam</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR3	30 TAC Chapter 115, Storage of VOCs	R5112-4	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Primary Seal = Liquid-mounted foam</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR3	40 CFR Part 60, Subpart K	60K-1	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p> <p>Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters)</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = Petroleum liquid (other than petroleum or condensate) True Vapor Pressure = True vapor pressure is less than 1.5 psia Storage Vessel Description = Floating roof (internal or external) Reid Vapor Pressure = Reid vapor pressure not determined Maximum True Vapor Pressure = Maximum true vapor pressure is not determined	
GRPTKEFR3	40 CFR Part 60, Subpart K	60K-2	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters) Product Stored = Petroleum liquid (other than petroleum or condensate) True Vapor Pressure = True vapor pressure is at least 1.5 psia and less than 11.1 psia Storage Vessel Description = Floating roof (internal or external) Reid Vapor Pressure = Reid vapor pressure not determined	
GRPTKEFR3	40 CFR Part 63, Subpart CC	63CC-1	Existing Source = The storage vessel is at an existing source. Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = External floating roof Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart K Seal Type = LIQUID-MOUNTED PRIMARY SEAL AS OF JULY 15, 1994	
GRPTKEFR3	40 CFR Part 63, Subpart CC	63CC-2	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart K	
GRPTKEFR4	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Welded tank using an external floating roof True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Primary Seal = Vapor mounted Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR4	30 TAC Chapter 115, Storage of	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOCs		Tank Description = Welded tank using an external floating roof True Vapor Pressure = True vapor pressure is less than 1.0 psia Primary Seal = Vapor mounted Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR4	30 TAC Chapter 115, Storage of VOCs	R5112-3	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Welded tank using an external floating roof True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Primary Seal = Liquid-mounted foam Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR4	40 CFR Part 63, Subpart CC	63CC-1	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.	
GRPTKEFR5	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank (other than welded) using an external floating roof (EFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Primary Seal = Mechanical shoe Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR5	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank (other than welded) using an external floating roof (EFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Primary Seal = Liquid-mounted foam Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR5	30 TAC Chapter 115, Storage of VOCs	R5112-3	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank (other than welded) using an external floating roof (EFR) True Vapor Pressure = True vapor pressure is less than 1.0 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Primary Seal = Mechanical shoe Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR5	40 CFR Part 63, Subpart CC	63CC-1	Existing Source = The storage vessel is at an existing source. Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = External floating roof Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641) Seal Type = LIQUID-MOUNTED PRIMARY SEAL AS OF JULY 15, 1994	
GRPTKEFR5	40 CFR Part 63, Subpart CC	63CC-2	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.	
GRPTKEFR6	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Welded tank using an external floating roof True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Primary Seal = Liquid-mounted foam Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR6	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Welded tank using an external floating roof True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Primary Seal = Liquid-mounted foam Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR6	30 TAC Chapter 115, Storage of VOCs	R5112-4	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Welded tank using an external floating roof True Vapor Pressure = True vapor pressure is less than 1.0 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Primary Seal = Liquid-mounted foam</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR6	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = LIQUID-MOUNTED PRIMARY SEAL AS OF JULY 15, 1994</p>	
GRPTKEFR6	40 CFR Part 63, Subpart CC	63CC-2	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
GRPTKEFR7	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Primary Seal = Liquid-mounted foam</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR7	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Liquid-mounted foam</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR7	30 TAC Chapter 115, Storage of VOCs	R5112-4	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Primary Seal = Liquid-mounted foam Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR7	40 CFR Part 63, Subpart CC	63CC-1	Existing Source = The storage vessel is at an existing source. Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = External floating roof Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641) Seal Type = LIQUID-MOUNTED PRIMARY SEAL AS OF JULY 15, 1994	
GRPTKEFR7	40 CFR Part 63, Subpart CC	63CC-2	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.	
GRPTKEFR9	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank (other than welded) using an external floating roof (EFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Primary Seal = Mechanical shoe Product Stored = Crude oil and/or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR9	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank (other than welded) using an external floating roof (EFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Primary Seal = Liquid-mounted foam Product Stored = Crude oil and/or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKEFR9	30 TAC Chapter 115, Storage of VOCs	R5112-3	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank (other than welded) using an external floating roof (EFR) True Vapor Pressure = True vapor pressure is less than 1.0 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Primary Seal = Mechanical shoe</p> <p>Product Stored = Crude oil and/or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKEFR9	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = LIQUID-MOUNTED PRIMARY SEAL AS OF JULY 15, 1994</p>	
GRPTKEFR9	40 CFR Part 63, Subpart CC	63CC-2	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
GRPTKFXD1	30 TAC Chapter 115, Storage of VOCs	R5112-6	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKFXD1	40 CFR Part 63, Subpart CC	63CC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
GRPTKFXD3	30 TAC Chapter 115, Storage of VOCs	R5112-6	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPTKFXD3	40 CFR Part 60, Subpart Kb	60KB-1	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia	
GRPTKFXD4	30 TAC Chapter 115, Storage of VOCs	R5112-6	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKFXD4	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	
GRPTKFXD5	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank (other than welded) using an external floating roof (EFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is less than 25,000 gallons	
GRPTKFXD5	40 CFR Part 63, Subpart CC	63CC-1	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.	
GRPTKFXD6	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank (other than welded) using an external floating roof (EFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is less than 25,000 gallons	
GRPTKFXD6	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	
GRPTKIFR1	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKIFR1	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKIFR1	40 CFR Part 63, Subpart CC	63CC-1	Existing Source = The storage vessel is at an existing source. Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Fixed roof and an internal floating roof Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641) Seal Type = VAPOR-MOUNTED SEAL AS OF DECEMBER 31, 1992	
GRPTKIFR1	40 CFR Part 63, Subpart CC	63CC-2	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.	
GRPTKIFR10	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKIFR10	40 CFR Part 60, Subpart K	60K-1	Construction/Modification Date = After June 11, 1973 And on or before March 8, 1974 Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters) Product Stored = Petroleum liquid (other than petroleum or condensate) True Vapor Pressure = True vapor pressure is at least 1.5 psia and less than 11.1 psia Storage Vessel Description = Floating roof (internal or external) Reid Vapor Pressure = Reid vapor pressure at least 1.0 psia	
GRPTKIFR10	40 CFR Part 63, Subpart CC	63CC-1	Existing Source = The storage vessel is at an existing source. Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = VAPOR-MOUNTED SEAL AS OF DECEMBER 31, 1992</p>	
GRPTKIFR2	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = Crude oil and/or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKIFR2	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = Crude oil and/or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKIFR2	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = VAPOR-MOUNTED SEAL AS OF DECEMBER 31, 1992</p>	
GRPTKIFR2	40 CFR Part 63, Subpart CC	63CC-2	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
GRPTKIFR3	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Tank Description = Tank using an internal floating roof (IFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKIFR3	40 CFR Part 60, Subpart K	60K-1	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters) Product Stored = Petroleum liquid (other than petroleum or condensate) True Vapor Pressure = True vapor pressure is at least 1.5 psia and less than 11.1 psia Storage Vessel Description = Floating roof (internal or external) Reid Vapor Pressure = Reid vapor pressure at least 1.0 psia	
GRPTKIFR3	40 CFR Part 63, Subpart CC	63CC-1	Existing Source = The storage vessel is at an existing source. Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Fixed roof and an internal floating roof Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641) Seal Type = VAPOR-MOUNTED SEAL AS OF DECEMBER 31, 1992	
GRPTKIFR4	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKIFR4	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKIFR4	40 CFR Part 63, Subpart CC	63CC-1	Existing Source = The storage vessel is at an existing source. Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = VAPOR-MOUNTED SEAL AS OF DECEMBER 31, 1992</p>	
GRPTKIFR4	40 CFR Part 63, Subpart CC	63CC-2	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
GRPTKIFR5	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKIFR5	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKIFR5	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = VAPOR-MOUNTED SEAL AS OF DECEMBER 31, 1992</p>	
GRPTKIFR5	40 CFR Part 63, Subpart CC	63CC-2	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
GRPTKIFR6	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKIFR6	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKIFR6	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = VAPOR-MOUNTED SEAL AS OF DECEMBER 31, 1992</p>	
GRPTKIFR6	40 CFR Part 63, Subpart CC	63CC-2	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
GRPTKIFR7	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPTKIFR7	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKIFR7	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Liquid-mounted seal</p>	
GRPTKIFR7	40 CFR Part 63, Subpart CC	63CC-2	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
GRPTKIFR8	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPTKIFR8	40 CFR Part 60, Subpart Kb	60KB-1	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	
GRPTKIFR8	40 CFR Part 63, Subpart CC	63CC-1	<p>Product Stored = Volatile organic liquid other than crude oil, refined petroleum products or waste of variable or indeterminate composition</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb. Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb	
GRPTKIFR9	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKIFR9	40 CFR Part 60, Subpart Kb	60KB-1	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Fixed roof with an internal floating roof using a liquid-mounted seal	
GRPTKIFR9	40 CFR Part 63, Subpart CC	63CC-1	Product Stored = Volatile organic liquid other than crude oil, refined petroleum products or waste of variable or indeterminate composition Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters) Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb. Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Fixed roof with an internal floating roof using a liquid-mounted seal Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb	
GRPTKLUB1	30 TAC Chapter 115, Storage of VOCs	R5112-6	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKLUB1	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	
GRPTKLUB3	30 TAC Chapter 115, Storage of VOCs	R5112-6	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRPTKLUB3	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	
J317	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
J317	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
J317	40 CFR Part 63, Subpart CC	63CC-1	Existing Source = The storage vessel is at an existing source. Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Fixed roof and an internal floating roof Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641) Seal Type = VAPOR-MOUNTED SEAL AS OF DECEMBER 31, 1992	
J317	40 CFR Part 63, Subpart CC	63CC-2	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.	
J318	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
J318	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
J318	40 CFR Part 60, Subpart Kb	60KB-1	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Fixed roof with an internal floating roof using two seals mounted one above the other to form a continuous closure	
J318	40 CFR Part 60, Subpart Kb	60KB-2	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia Storage Vessel Description = Fixed roof with an internal floating roof using two seals mounted one above the other to form a continuous closure	
J318	40 CFR Part 60, Subpart Kb	60KB-3	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia	
J318	40 CFR Part 63, Subpart CC	63CC-1	Product Stored = Refined petroleum products Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters) Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb. Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Fixed roof with an internal floating roof using two seals mounted one above the other to form a continuous closure	
J318	40 CFR Part 63, Subpart CC	63CC-2	Product Stored = Refined petroleum products Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters) Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Maximum TVP = True vapor pressure is less than 0.75 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using two seals mounted one above the other to form a continuous closure</p>	
S339	40 CFR Part 61, Subpart FF	61FF-1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the vessel and the edge of the internal floating roof.</p>	
S429	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Primary Seal = Vapor mounted</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
S429	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Vapor mounted</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
S429	30 TAC Chapter 115, Storage of VOCs	R5112-3	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Primary Seal = Vapor mounted</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
S429	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = VAPOR-MOUNTED PRIMARY AND SECONDARY SEAL (AS DEFINED IN 40 CFR § 63.111) AS OF JULY 15, 1994</p>	
S429	40 CFR Part 63, Subpart CC	63CC-2	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
SS425	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
SS425	40 CFR Part 60, Subpart Kb	60KB-1	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	
SS425	40 CFR Part 63, Subpart CC	63CC-1	<p>Product Stored = Volatile organic liquid other than crude oil, refined petroleum products or waste of variable or indeterminate composition</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
T1F348	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 40,000 gallons	
T1F348	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
T1F348	30 TAC Chapter 115, Storage of VOCs	R5112-4	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
T1F348	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = METALLIC SHOE PRIMARY SEAL AS OF JULY 15, 1994</p>	
T1F348	40 CFR Part 63, Subpart CC	63CC-2	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
T304	40 CFR Part 60, Subpart Kb	60Kb-1	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>	
T304	40 CFR Part 60,	60Kb-2	Product Stored = Waste mixture of indeterminate or variable composition	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with liquid-mounted primary seal	
T304	40 CFR Part 60, Subpart Kb	60Kb-3	Product Stored = Waste mixture of indeterminate or variable composition Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with liquid-mounted primary seal	
T304	40 CFR Part 61, Subpart FF	61FF-1	Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF. Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351. Kb Tank Type = Using an external floating roof that meets the requirements of 40 CFR § 60.112b(a)(2) Seal Type = Liquid-mounted primary seal	
T304	40 CFR Part 63, Subpart G	63CC-1	Negative Pressure = The fixed roof and closed vent systems are not operated and maintained under negative pressure. Process Wastewater = The tank receives, manages, or treats process wastewater streams Wastewater Tank Usage = The wastewater tank is used for heating wastewater, treating by means of an exothermic reaction, or the contents of the tank are sparged. Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.148 Wastewater Tank Properties = Properties do not qualify for exemption By-pass Lines = Closed vent system has no by-pass lines Emission Control Type = Fixed roof tank vented through a closed vent system that routes the organic HAP vapors vented from the wastewater tank to a control device Combination of Control Devices = The vent stream is treated using a single control device. Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G. Control Device Type = Flare New Source = The source is an existing source. Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or approved.	
T316	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T316	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T316	40 CFR Part 63, Subpart CC	63CC-1	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.	
T93002	30 TAC Chapter 115, Storage of VOCs	R5112-6	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
T93002	40 CFR Part 60, Subpart Kb	60KB-1	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia	
T93002	40 CFR Part 63, Subpart CC	63CC-1	Product Stored = Volatile organic liquid other than crude oil, refined petroleum products or waste of variable or indeterminate composition Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters) Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb. Maximum TVP = True vapor pressure is less than 0.75 psia Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal	
TK305	30 TAC Chapter 115, Storage of VOCs	R5112-6	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
V1111	40 CFR Part 63, Subpart CC	63CC-1	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
V329	40 CFR Part 63, Subpart CC	63CC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
X322	40 CFR Part 61, Subpart FF	61FF-1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the vessel and the edge of the internal floating roof.</p>	
X322	40 CFR Part 63, Subpart G	63CC-1	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank greater than or equal to 151m³ and vapor pressure of liquid stored is less than 5.2 kPa</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Control Device Type = ALTERNATE CONTROL DEVICE APPROVED BY ADMINISTRATOR</p> <p>New Source = The source is an existing source.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or approved.</p>	
X323	40 CFR Part 61, Subpart FF	61FF-1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the vessel and the edge of the internal floating roof.</p>	
X323	40 CFR Part 63, Subpart G	63CC-1	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank greater than or equal to 151m³ and vapor pressure of liquid stored is less than 5.2 kPa</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Control Device Type = ALTERNATE CONTROL DEVICE APPROVED BY ADMINISTRATOR</p> <p>New Source = The source is an existing source.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			approved.	
X330	40 CFR Part 60, Subpart Kb	60Kb-1	Product Stored = Waste mixture of indeterminate or variable composition Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia	
X330	40 CFR Part 60, Subpart QQQ	60QQQ-1	Construction/Modification Date = After May 4, 1987 Control Device Type = No control device Alternate Means of Emission Limitation = The EPA Administrator has not approved an alternate means of emission limitation. Alternative Monitoring = No alternative operational or process parameter is monitored. Alternative Standard = The storage vessel, slop oil tank, or auxiliary tank is not equipped with a floating roof. Subject to 40 CFR Part 60, Subpart K, Ka or Kb = Yes	
ACIDLOAD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline. Transfer Type = Loading and unloading. True Vapor Pressure = True vapor pressure less than 0.5 psia.	
DEALOAD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline. Transfer Type = Only loading. True Vapor Pressure = True vapor pressure less than 0.5 psia.	
GRPLUBLOAD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline. Transfer Type = Only loading. True Vapor Pressure = True vapor pressure less than 0.5 psia.	
GRPMARLOAD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Control Device Type = No control device. Chapter 115 Facility Type = Marine terminal Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected. Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline. Marine Terminal Exemptions = The marine terminal is not claiming one or more of the exemptions in 30 TAC §	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>115.217(a)(5)(B).</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
GRPMARLOAD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-2	<p>Chapter 115 Facility Type = Marine terminal</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>	
GRPMARLOAD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-3	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Marine terminal</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Marine Terminal Exemptions = The marine terminal is not claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B).</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
GRPMARLOAD	40 CFR Part 63, Subpart CC	63CC-1	<p>Specified in 63.640(g)(1)-(6) = The gasoline loading rack or marine vessel loading operation is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The gasoline loading rack or marine vessel loading operation is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Unit Type = Marine vessel loading operation at a petroleum refinery meeting the applicability criteria of 40 CFR § 63.560.</p>	
GRPMARLOAD	40 CFR Part 63, Subpart Y	63Y-1	<p>CEMS = Continuous emissions monitoring system (CEMS) is not being used.</p> <p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Balancing System = Emissions are reduced by a vapor balancing system.</p> <p>Documenting Vapor Tightness = Electing to comply with the emissions reporting requirements in 40 CFR § 63.567(b)(5)(i).</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Subpart Y Control Device Type = Control device other than a flare, boiler, combustion unit other than a boiler or flare, carbon adsorber, or condenser.</p> <p>Material Loaded = Gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Performance Test = Baseline temperature from manufacturer.</p> <p>Alternate Monitoring = Complying with the control device specific monitoring procedures in 40 CFR § 63.564.</p> <p>Source Emissions = Source with emissions of 10 or 25 tons.</p> <p>Alternate Test Procedure = Complying with the test procedures in 40 CFR § 63.565.</p> <p>Throughput = Source with throughput less than 10 M barrels and 200 M barrels.</p> <p>Vent Stream By-Pass = There are valves that could route displaced vapors to the atmosphere.</p> <p>Bypass Flow Indicator = Flow indicator with audio or visual alarm.</p>	
GRPMARLOAD	40 CFR Part 63, Subpart Y	63Y-2	<p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Pressure = Vapor pressure is less than 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p>	
GRPMARLOAD	40 CFR Part 63, Subpart Y	63Y-3	<p>CEMS = Continuous emissions monitoring system (CEMS) is not being used.</p> <p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Balancing System = Emissions are not reduced by a vapor balancing system.</p> <p>Documenting Vapor Tightness = Electing to comply with the emissions reporting requirements in 40 CFR § 63.567(b)(5)(i).</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p> <p>Subpart Y Control Device Type = Flare.</p> <p>Material Loaded = Material other than crude oil or gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Alternate Monitoring = Complying with the control device specific monitoring procedures in 40 CFR § 63.564.</p> <p>Source Emissions = Source with emissions of 10 or 25 tons.</p> <p>Alternate Test Procedure = Complying with the test procedures in 40 CFR § 63.565.</p> <p>Vent Stream By-Pass = There are no valves that could route displaced vapors to the atmosphere.</p>	
GTTLR	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	<p>Chapter 115 Facility Type = Gasoline bulk plant</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Gasoline</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Daily Throughput = Loading less than 4,000 gallons of gasoline into transport vessels per day.	
GRP-FURN	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr.</p> <p>CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>NO_x Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NO_x Reduction = Induced flue gas recirculation</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NO_x Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NO_x Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
GRP-FURN	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
GRPHTR7	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr.</p> <p>CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>NO_x Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NO_x Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NO_x Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NO_x Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
GRPHTR7	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H1000	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr.</p> <p>CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H1000	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H1001	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000]</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H1001	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H1010	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000]</p> <p>Annual Heat Input = Annual heat input is greater than 2.8(10¹¹) Btu/yr, based on a rolling 12-month average.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H1010	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H1011	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000]</p> <p>Annual Heat Input = Annual heat input is greater than 2.8(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H1011	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H1100	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000]</p> <p>Annual Heat Input = Annual heat input is greater than 2.8(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H1100	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H1170	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] Annual Heat Input = Annual heat input is greater than 2.8(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H1170	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H31003	30 TAC Chapter 117, Subchapter B	R7ICI-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Unit vents to a common stack with a NO _x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr. CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1). NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = Induced flue gas recirculation Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Continuous emissions monitoring system Annual Heat Input = Annual heat input is greater than 2.2(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H31003	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H3300	30 TAC Chapter 117, Subchapter B	R7ICI-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] Annual Heat Input = Annual heat input is less than or equal to 2.8(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H3300	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H36100	30 TAC Chapter 117, Subchapter B	R7ICI-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] Annual Heat Input = Annual heat input is greater than 2.2(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H36100	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5101	30 TAC Chapter 117, Subchapter B	R7ICI-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Unit vents to a common stack with a NO _x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr. CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1). NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Continuous emissions monitoring system Annual Heat Input = Annual heat input is greater than 2.2(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H5101	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
H5102	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 100 MMBtu/hr, but less than 200 MMBtu/hr.</p> <p>CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>NO_x Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NO_x Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NO_x Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NO_x Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H5102	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5103	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 100 MMBtu/hr, but less than 200 MMBtu/hr.</p> <p>CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>NO_x Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NO_x Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NO_x Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NO_x Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H5103	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5104	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1). NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Continuous emissions monitoring system Annual Heat Input = Annual heat input is greater than 2.2(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H5104	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5105	30 TAC Chapter 117, Subchapter B	R7ICI-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] Annual Heat Input = Annual heat input is greater than 2.2(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H5105	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5200	30 TAC Chapter 117, Subchapter B	R7ICI-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] Annual Heat Input = Annual heat input is greater than 2.8(10 ¹¹) Btu/yr, based on a rolling 12-month average.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H5200	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5301	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr.</p> <p>CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NH₃ Emission Limitation = Title 30 TAC § 117.310(c)(2)</p> <p>NOx Reduction = Post combustion control technique with ammonia injection</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NH₃ Monitoring = Continuous emission monitoring system.</p> <p>NOx Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H5301	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5302	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr.</p> <p>CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NH₃ Emission Limitation = Title 30 TAC § 117.310(c)(2)</p> <p>NOx Reduction = Post combustion control technique with ammonia injection</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NH₃ Monitoring = Continuous emission monitoring system.</p> <p>NOx Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H5302	40 CFR Part 63,	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart DDDDD			
H5303	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 100 MMBtu/hr, but less than 200 MMBtu/hr.</p> <p>CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>NO_x Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NH₃ Emission Limitation = Title 30 TAC § 117.310(c)(2)</p> <p>NO_x Reduction = Post combustion control technique with ammonia injection</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NH₃ Monitoring = Continuous emission monitoring system.</p> <p>NO_x Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NO_x Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H5303	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5304	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 100 MMBtu/hr, but less than 200 MMBtu/hr.</p> <p>CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>NO_x Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NH₃ Emission Limitation = Title 30 TAC § 117.310(c)(2)</p> <p>NO_x Reduction = Post combustion control technique with ammonia injection</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NH₃ Monitoring = Continuous emission monitoring system.</p> <p>NO_x Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NO_x Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H5304	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
H5305	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr.</p> <p>CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>NO_x Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NH₃ Emission Limitation = Title 30 TAC § 117.310(c)(2)</p> <p>NO_x Reduction = Post combustion control technique with ammonia injection</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NH₃ Monitoring = Continuous emission monitoring system.</p> <p>NO_x Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.8(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NO_x Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H5305	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5350	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr.</p> <p>CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>NO_x Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NH₃ Emission Limitation = Title 30 TAC § 117.310(c)(2)</p> <p>NO_x Reduction = Post combustion control technique with ammonia injection</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NH₃ Monitoring = Continuous emission monitoring system.</p> <p>NO_x Monitoring System = Continuous emissions monitoring system</p> <p>NO_x Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H5350	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5400	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] Annual Heat Input = Annual heat input is greater than 2.8(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H5400	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5403	30 TAC Chapter 117, Subchapter B	R7ICI-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] Annual Heat Input = Annual heat input is greater than 2.8(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H5403	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5404	30 TAC Chapter 117, Subchapter B	R7ICI-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Unit vents to a common stack with a NO _x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr. CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1). NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Continuous emissions monitoring system Annual Heat Input = Annual heat input is greater than 2.2(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H5404	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5500	30 TAC Chapter 117, Subchapter B	R7ICI-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Unit vents to a common stack with a NO _x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr. CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1). NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Continuous emissions monitoring system Annual Heat Input = Annual heat input is greater than 2.2(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H5500	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H5600	30 TAC Chapter 117, Subchapter B	R7ICI-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Unit vents to a common stack with a NO _x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 100 MMBtu/hr, but less than 200 MMBtu/hr. CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1). NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Continuous emissions monitoring system Annual Heat Input = Annual heat input is greater than 2.2(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H5600	40 CFR Part 63,	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart DDDDD			
H600	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NO_x Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NH₃ Emission Limitation = Title 30 TAC § 117.310(c)(2)</p> <p>NO_x Reduction = Post combustion control technique with ammonia injection</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NH₃ Monitoring = Continuous emission monitoring system.</p> <p>NO_x Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NO_x Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H613	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Unit vents to a common stack with a NO_x and diluent CEMS and utilizes a single totalizing fuel flow meter per 30 TAC §§ 117.140(a)(2)(B), 117.340(a)(2)(B) or 117.440(a)(2)(B).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 100 MMBtu/hr, but less than 200 MMBtu/hr.</p> <p>CO Monitoring System = Continuous emission monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>NO_x Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NO_x Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NO_x Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NO_x Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H613	40 CFR Part 63, Subpart DDDDD	63DDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H63000	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000]</p> <p>Annual Heat Input = Annual heat input is greater than 2.8(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H63000	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H70001	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000]</p> <p>Annual Heat Input = Annual heat input is greater than 2.8(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
H70001	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H70002	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 40 MMBtu/hr, but less than 100 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000]</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Annual Heat Input = Annual heat input is greater than 2.8(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H70002	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
H9150	30 TAC Chapter 117, Subchapter B	R7ICI-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
H9150	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
GRP-DUCT	30 TAC Chapter 117, Subchapter B	R7ICI	NOx Emission Limitation = Title 30 TAC § 117.310(d)(3) [relating to mass emissions cap and trade in 30 TAC Chapter 101, Subchapter H, Division 3 and Emission Specifications for Attainment Demonstration]. Unit Type = Other industrial, commercial, or institutional boiler. Maximum Rated Capacity = MRC is greater than 2 MMBtu/hr but less than 40 MMBtu/hr. NOx Monitoring System = Continuous emissions monitoring system. Fuel Flow Monitoring = Unit operates with a NO _x and diluent CEMS and monitors stack exhaust flow per 30 TAC §§ 117.140(a)(2)(A), 117.340(a)(2)(A) or 117.440(a)(2)(A). CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option. CO Monitoring System = Continuous emissions monitoring system complying with 30 TAC § 117.8100(a)(1). EGF System Cap Unit = The unit is not used as an electric generating facility to generate electricity for sale to the electric grid. Fuel Type #1 = Gaseous fuel other than natural gas landfill gas or renewable non-fossil fuel gases. Fuel Type #2 = Natural gas. NH ₃ Emission Limitation = Title 30 TAC § 117.310(c)(2). NOx Emission Limit Average = Emission limit in pounds/MMBtu on a rolling 30-day average. NOx Reductions = Post combustion control technique with ammonia injection.	
GRP-DUCT	40 CFR Part 60, Subpart Db	60Db-1	Construction/Modification Date = On or after November 25, 1986, and on or before July 9, 1997. D-Series Fuel Type #1 = Gaseous fossil fuel other than natural gas and coal-derived synthetic fuel meeting the definition of natural gas.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>D-Series Fuel Type #2 = Natural gas.</p> <p>Heat Input Capacity = Heat input capacity is greater than 100 MMBtu/hr (29 MW) but less than or equal to 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Facility Type = The affected facility includes a fuel gas combustion device.</p> <p>Opacity Monitoring Type = No particulate (opacity) monitoring.</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>Monitoring Device = An instrument is in place for continuous monitoring and recording the concentration (dry basis) of hydrogen sulfide in fuel gasses before being burned in any fuel gas combustion device.</p> <p>NOx Monitoring Type = Continuous emission monitoring system.</p> <p>Subpart D = The affected facility does not meet the applicability requirements of 40 CFR Part 60, Subpart D.</p> <p>Common Fuel Source = The fuel gas combustion device has a common fuel source with other fuel gas combustion devices.</p> <p>SO2 Monitoring Type = No SO₂ monitoring.</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart E = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart E.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = Other conventional technology.</p> <p>ACF Option - SO₂ = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = Duct burner as part of combined cycle system (compliance with NO_x limitations is determined by conducting a performance test).</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>ACF Option - NO_x = Other ACF or no ACF.</p> <p>Fuel Heat Input = The heat input is greater than 30% from combustion of coal and oil in the duct burner and heat input is less than 70% from the exhaust gases entering the duct burner.</p>	
HB00200	30 TAC Chapter 117, Subchapter B	R7310	<p>Fuel Type Heat Input = Boiler is fired with a single fuel type, no fuel combinations are used.</p> <p>NOx Emission Limitation = Title 30 TAC § 117.310(d)(3) [relating to mass emissions cap and trade in 30 TAC Chapter 101, Subchapter H, Division 3 and Emission Specifications for Attainment Demonstration].</p> <p>Unit Type = Other industrial, commercial, or institutional boiler.</p> <p>Maximum Rated Capacity = MRC is greater than or equal to 250 MMBtu/hr.</p> <p>NOx Monitoring System = Continuous emissions monitoring system.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>117.440(a). Chapter 116 Permit Limit = NO_x emission limit in 30 TAC § 117.105 applies for purposes of 30 TAC Chapter 117. CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option. CO Monitoring System = Continuous emissions monitoring system complying with 30 TAC § 117.8100(a)(1). EGF System Cap Unit = The unit is not used as an electric generating facility to generate electricity for sale to the electric grid. Fuel Type #1 = Gaseous fuel other than natural gas landfill gas or renewable non-fossil fuel gases. Fuel Type #2 = Natural gas. NH₃ Emission Limitation = Title 30 TAC § 117.310(c)(2). NO_x Emission Limit Average = Emission limit in pounds/hour on a block one-hour average. NH₃ Emission Monitoring = Continuous emissions monitoring system. NO_x Reductions = Post combustion control technique with ammonia injection. Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on rolling 12-month average. Common Stack Combined = The unit is vented through a common stack; the total rated heat input from combined units is greater than or equal to 250 MMBtu/hr; and the annual combined heat input is greater than 2.2(10¹¹) Btu/yr.</p>	
HB00200	40 CFR Part 60, Subpart D	60D-1	<p>Construction/Modification Date = After September 18, 1978. Covered Under Subpart Da = The steam generating unit is not covered under 40 CFR Part 60, Subpart Da. Changes to Existing Affected Facility = No change has been made to the existing fossil fuel-fired steam generating unit. Heat Input Rate = Heat input rate is less than or equal to 250 MMBtu/hr (73 MW).</p>	
HB00200	40 CFR Part 60, Subpart Db	60Db-1	<p>60.42b(k)(2) Low Sulfur Exemption = The § 60.42b(k)(2) exemption does not apply. Construction/Modification Date = Modified after February 28, 2005. D-Series Fuel Type #1 = Natural gas. 60.42b(k)(4) Alternative = The requirements of § 60.42b(k)(1) are used. D-Series Fuel Type #2 = Gaseous fossil fuel other than natural gas and coal-derived synthetic fuel meeting the definition of natural gas. Heat Input Capacity = Heat input capacity is greater than 100 MMBtu/hr (29 MW) but less than or equal to 250 MMBtu/hr (73 MW). PM Monitoring Type = No particulate monitoring. Facility Type = The affected facility includes a fuel gas combustion device. Opacity Monitoring Type = No particulate (opacity) monitoring. Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da. 60.43b(h)(2) Alternative = The facility is not electing to use the alternative requirements of § 60.43b(h)(2) for PM. Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281. Monitoring Device = An instrument is in place for continuous monitoring and recording the concentration (dry basis) of hydrogen sulfide in fuel gasses before being burned in any fuel gas combustion device. NO_x Monitoring Type = Continuous emission monitoring system.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Subpart D = The affected facility does not meet the applicability requirements of 40 CFR Part 60, Subpart D.</p> <p>Common Fuel Source = The fuel gas combustion device has a common fuel source with other fuel gas combustion devices.</p> <p>Electrical or Mechanical Output = 10% or less of the annual output is electrical or mechanical.</p> <p>SO2 Monitoring Type = Fuel certification (based on fuel analysis per § 60.49b(r)(2)).</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart E = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart E.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = None.</p> <p>ACF Option - SO2 = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = OTHER UNIT TYPE</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>60.49Da(n) Alternative = The facility is not using the § 60.49Da(n) alternative.</p> <p>ACF Option - NOx = Other ACF or no ACF.</p> <p>60.49Da(m) Alternative = The facility is not using the § 60.49Da(m) alternative.</p>	
HB00200	40 CFR Part 63, Subpart DDDDD	63DDDDD	Construction/Reconstruction Date = Construction or reconstruction began after June 4, 2010.	
FLARECCU	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.</p>	
FLARECCU	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Monitoring Requirements = Flare is complying with rule base requirements other than the continuous monitoring requirements of § 115.725(d).</p> <p>Out of Service = Flare was not permanently out of service by April 1, 2006.</p> <p>Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time.</p> <p>Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time.</p> <p>Exempt Date = Flare has not become exempt.</p> <p>Alternative Monitoring = No alternative monitoring and test methods are used.</p> <p>Monitoring Operations = Using process knowledge.</p> <p>§115.725(h)(4) Alternative = Choosing to implement monitoring options in § 115.725(h)(4)(A) or § 115.725(h)(4)(B) in lieu of the continuous monitoring requirements in § 115.725(d)(2).</p> <p>Minor Modificaiton = No minor modifications to the monitoring and test methods are used.</p> <p>Flare Type = Flare is in temporary service and temporarily receives HRVOC emissions.</p>	
FLARECCU	40 CFR Part 60, Subpart A	60A-1	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
FLARECCU	40 CFR Part 63, Subpart A	63A-1	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
FLARECOKE	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.</p>	
FLARECOKE	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Monitoring Requirements = Flare is complying with the continuous monitoring requirements of § 115.725(d).</p> <p>Out of Service = Flare was not permanently out of service by April 1, 2006.</p> <p>Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time.</p> <p>Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time.</p> <p>Multi-Purpose Usage = Flare is used for abatement of emissions from scheduled or undcheduled maintenance, startup or shutdown activities AND as an emergency flare.</p> <p>Exempt Date = Flare has not become exempt.</p> <p>Flow Rate = Flow rate of the gas routed to the flare is determined using the requirements of § 115.725(d)(1).</p> <p>Alternative Monitoring = No alternative monitoring and test methods are used.</p> <p>Physical Seal = Flare is equipped with a physical seal.</p> <p>Minor Modificaiton = No minor modifications to the monitoring and test methods are used.</p> <p>Tank Service = Flare is not in dedicated service for storage tanks with 95% or greater of an individual HRVOC.</p> <p>Flare Type = Flare is in multi-purpose service.</p>	
FLARECOKE	40 CFR Part 60, Subpart A	60A-1	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
FLAREEP	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.</p>	
FLAREEP	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Monitoring Requirements = Flare is complying with the continuous monitoring requirements of § 115.725(d).</p> <p>Out of Service = Flare was not permanently out of service by April 1, 2006.</p> <p>Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time.</p> <p>Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time.</p> <p>Multi-Purpose Usage = Flare is used for abatement of emissions from scheduled or undcheduled maintenance, startup or</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>shutdown activities AND as an emergency flare.</p> <p>Exempt Date = Flare has not become exempt.</p> <p>Flow Rate = Flow rate of the gas routed to the flare is determined using the requirements of § 115.725(d)(1).</p> <p>Alternative Monitoring = No alternative monitoring and test methods are used.</p> <p>Physical Seal = Flare is equipped with a flow monitor or indicator.</p> <p>Minor Modificaiton = No minor modifications to the monitoring and test methods are used.</p> <p>Tank Service = Flare is not in dedicated service for storage tanks with 95% or greater of an individual HRVOC.</p> <p>Flare Type = Flare is in multi-purpose service.</p>	
FLAREEP	40 CFR Part 60, Subpart A	60A-1	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
FLAREEP	40 CFR Part 63, Subpart A	63A-1	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
FLAREGIRB	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Monitoring Requirements = Flare is complying with the continuous monitoring requirements of § 115.725(d).</p> <p>Out of Service = Flare was not permanently out of service by April 1, 2006.</p> <p>Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time.</p> <p>Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time.</p> <p>Multi-Purpose Usage = Flare is used for abatement of emissions from scheduled or undcheduled maintenance, startup or shutdown activities AND as an emergency flare.</p> <p>Exempt Date = Flare has not become exempt.</p> <p>Flow Rate = Flow rate of the gas routed to the flare is determined using the requirements of § 115.725(d)(1).</p> <p>Alternative Monitoring = No alternative monitoring and test methods are used.</p> <p>Physical Seal = Flare is equipped with a flow monitor or indicator.</p> <p>Minor Modificaiton = No minor modifications to the monitoring and test methods are used.</p> <p>Tank Service = Flare is not in dedicated service for storage tanks with 95% or greater of an individual HRVOC.</p> <p>Flare Type = Flare is in multi-purpose service.</p>	
FLAREGIRB	40 CFR Part 60, Subpart A	60A-1	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
FLAREGIRB	40 CFR Part 63, Subpart A	63A-1	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
FLARELHT	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.	
FLARELHT	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	Out of Service = Flare was permanently out of service by April 1, 2006.	
FLARENP	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.	
FLARENP	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	Monitoring Requirements = Flare is complying with the continuous monitoring requirements of § 115.725(d). Out of Service = Flare was not permanently out of service by April 1, 2006. Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time. Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time. Multi-Purpose Usage = Flare is used for abatement of emissions from scheduled or undcheduled maintenance, startup or shutdown activities AND as an emergency flare. Exempt Date = Flare has not become exempt. Flow Rate = Flow rate of the gas routed to the flare is determined using the requirements of § 115.725(d)(1). Alternative Monitoring = No alternative monitoring and test methods are used. Physical Seal = Flare is equipped with a physical seal. Minor Modificaiton = No minor modifications to the monitoring and test methods are used. Tank Service = Flare is not in dedicated service for storage tanks with 95% or greater of an individual HRVOC. Flare Type = Flare is in multi-purpose service.	
FLARENP	40 CFR Part 60, Subpart A	60A-1	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm)	
FLARENP	40 CFR Part 63, Subpart A	63A-1	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm).</p>	
FLARESOUTH	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.</p>	
FLARESOUTH	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Monitoring Requirements = Flare is complying with rule base requirements other than the continuous monitoring requirements of § 115.725(d).</p> <p>Out of Service = Flare was not permanently out of service by April 1, 2006.</p> <p>Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time.</p> <p>Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time.</p> <p>Exempt Date = Flare has not become exempt.</p> <p>Alternative Monitoring = No alternative monitoring and test methods are used.</p> <p>Monitoring Operations = Using process knowledge.</p> <p>§115.725(h)(4) Alternative = Choosing to implement monitoring options in § 115.725(h)(4)(A) or § 115.725(h)(4)(B) in lieu of the continuous monitoring requirements in § 115.725(d)(2).</p> <p>Minor Modificaiton = No minor modifications to the monitoring and test methods are used.</p> <p>Flare Type = Flare is in temporary service and temporarily receives HRVOC emissions.</p>	
FLARESOUTH	40 CFR Part 60, Subpart A	60A-1	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
FLARESOUTH	40 CFR Part 63, Subpart A	63A-1	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
FLAREWP	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.</p>	
FLAREWP	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Monitoring Requirements = Flare is complying with the continuous monitoring requirements of § 115.725(d).</p> <p>Out of Service = Flare was not permanently out of service by April 1, 2006.</p> <p>Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time.</p> <p>Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time.</p> <p>Multi-Purpose Usage = Flare is used for abatement of emissions from marine loading or transport vessel loading and unloading operations AND for abatement of emissions from scheduled or unscheduled maintenance, startup or shutdown activities AND as an emergency flare.</p> <p>Exempt Date = Flare has not become exempt.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Flow Rate = Flow rate of the gas routed to the flare is determined using the requirements of § 115.725(d)(1).</p> <p>Alternative Monitoring = No alternative monitoring and test methods are used.</p> <p>Physical Seal = Flare is equipped with a physical seal.</p> <p>Minor Modificaiton = No minor modifications to the monitoring and test methods are used.</p> <p>Tank Service = Flare is not in dedicated service for storage tanks with 95% or greater of an individual HRVOC.</p> <p>Flare Type = Flare is in multi-purpose service.</p>	
FLAREWP	40 CFR Part 60, Subpart A	60A-1	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
FLAREWP	40 CFR Part 63, Subpart A	63A-1	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
GRP-TURB	30 TAC Chapter 117, Subchapter B	R7201	<p>Megawatt Rating = MR is greater than or equal to 30 MW.</p> <p>Service Type = Used in research and testing, performance verification, to power other engines or turbines during startup, in response to and during any officially declared disaster or state of emergency, exclusively in agriculture or as chemical processing turbine.</p>	
GRP-TURB	40 CFR Part 60, Subpart GG	60GG-1	<p>Duct Burner = The turbine is part of a combined cycle turbine system equipped with supplemental heat (duct burner).</p> <p>NOx Control Method = Selective catalytic reduction.</p> <p>Peak Load Heat Input = Heat Input is greater than 100 MMBtu/hr (107.2 GJ/hr)</p> <p>Construction/Modification Date = On or after October 3, 1982 and before July 8, 2004.</p> <p>NOx Allowance = The owner or operator is not electing to use a NO_x allowance in determining emission limits in 40 CFR § 60.332(a).</p> <p>NOx Monitoring Method = Continuous emission monitoring system.</p> <p>Turbine Cycle = Unit recovers heat from the gas turbine exhaust to heat water or generate steam.</p> <p>Fuel Type Fired = Natural gas meeting the definition in § 60.331(u).</p> <p>Regulated Under Part 75 = Monitoring parameters are established under § 60.334(f) of Subpart GG.</p> <p>Subpart GG Service Type = Electric utility generation.</p> <p>Fuel Supply = Stationary gas turbine is supplied its fuel without intermediate bulk storage.</p> <p>Fuel Monitoring Schedule = Fuel meets the definition of natural gas in 40 CFR § 60.331(u) and is not monitored.</p>	
GRP-TURB	40 CFR Part 63, Subpart YYYY	63YYYY-1	<p>Construction/Reconstruction Date = Turbine was constructed, modified or reconstructed on or before 1/14/2003.</p>	
FUGCCU	30 TAC Chapter 115, HRVOC	R5780-1	<p>Compressor Seals = The fugitive unit contains compressor seals.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Fugitive Emissions		<p>Title 30 TAC §115.780 Applicable = The fugitive unit contains a defined process and Highly Reactive VOC.</p> <p>Valves (not pressure relief, open-ended or bypass line valves) = The fugitive unit contains valves other than pressure relief, open-ended or bypass line valves.</p> <p>Weight Percent HRVOC = Components in the fugitive unit contact process fluids that contain less than 5.0% HRVOC by weight and process fluids that contain HRVOC at 5.0%, or greater, by weight on an annual average basis.</p> <p>Flanges or Other Connectors = The fugitive unit contains flanges or other connectors.</p> <p>Heat Exchanger Heads, etc. = The fugitive unit contains heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolter manways, hatches, sump covers, junction vent boxes or covers and seals on VOC water separators.</p> <p>Pressure Relief Valves = The fugitive unit contains pressure relief valves.</p> <p>Pump Seals = The fugitive unit contains pump seals.</p>	
FUGCCU	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.	
FUGCCU	40 CFR Part 60, Subpart VV	60VVALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in VOC service subject to 40 CFR Part 60, Subpart VV with no alternate control or control devices.	
FUGCCU	40 CFR Part 63, Subpart CC	R63CCVALL	<p>COMPRESSOR IN HYDROGEN SERVICE = YES</p> <p>ENCLOSED COMBUSTION DEVICE = NO</p> <p>EXISTING SOURCE = YES</p> <p>FLARE = NO</p> <p>OPEN-ENDED VALVES OR LINES = YES</p> <p>PRESSURE RELIEF DEVICE IN GAS/VAPOR SERVICE = YES</p> <p>VACUUM SERVICE = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE = YES</p> <p>VAPOR RECOVERY SYSTEM = NO</p> <p>COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES</p> <p>COMPRESSOR NOT IN HYDROGEN SERVICE = YES</p> <p>OPEN-ENDED VALVES OR LINES EQUIVALENT EMISSION LIMITATION = NO</p> <p>PRESSURE RELIEF DEVICE COMPLYING WITH § 60.482-4(A)-(B) = YES</p> <p>PUMP IN LIGHT LIQUID SERVICE = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>COMPRESSOR EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP EQUIVALENT EMISSION LIMITATION = NO</p> <p>OPEN-ENDED VALVES OR LINES COMPLYING WITH § 60.482-6 = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE COMPLYING WITH § 60.482-8 = YES</p> <p>COMPRESSOR COMPLYING WITH § 60.482-3 = YES</p> <p>FLANGES AND OTHER CONNECTORS = YES</p> <p>PUMP COMPLYING WITH § 60.482-2 = YES</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			SAMPLING CONNECTION SYSTEMS = YES VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE = YES FLANGES AND OTHER CONNECTORS EQUIVALENT EMISSION LIMITATION = NO PUMP IN HEAVY LIQUID SERVICE = YES SAMPLING CONNECTION SYSTEM EQUIVALENT EMISSION LIMITATION = NO VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO PUMP EQUIVALENT EMISSION LIMITATION = NO FLANGES AND OTHER CONNECTORS COMPLYING WITH § 60.482-8 = YES SAMPLING CONNECTION SYSTEMS COMPLYING WITH § 60.482-5 = YES VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE COMPLYING WITH § 60.482-7 = YES PUMP COMPLYING WITH § 60.482-8 = YES	
FUGDISP	30 TAC Chapter 115, HRVOC Fugitive Emissions	R5780-1	Compressor Seals = The fugitive unit does not contain compressor seals. Title 30 TAC §115.780 Applicable = The fugitive unit contains a defined process and Highly Reactive VOC. Valves (not pressure relief, open-ended or bypass line valves) = The fugitive unit contains valves other than pressure relief, open-ended or bypass line valves. Weight Percent HRVOC = Components in the fugitive unit contact process fluids that contain less than 5.0% HRVOC by weight and process fluids that contain HRVOC at 5.0%, or greater, by weight on an annual average basis. Flanges or Other Connectors = The fugitive unit contains flanges or other connectors. Heat Exchanger Heads, etc. = The fugitive unit contains heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolter manways, hatches, sump covers, junction vent boxes or covers and seals on VOC water separators. Pressure Relief Valves = The fugitive unit contains pressure relief valves. Pump Seals = The fugitive unit contains pump seals.	
FUGDISP	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.	
FUGDISP	40 CFR Part 60, Subpart VV	60VVALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in VOC service subject to 40 CFR Part 60, Subpart VV with no alternate control or control devices.	
FUGDISP	40 CFR Part 63, Subpart CC	R63CCVALL	COMPRESSOR IN HYDROGEN SERVICE = YES ENCLOSED COMBUSTION DEVICE = NO EXISTING SOURCE = YES FLARE = NO OPEN-ENDED VALVES OR LINES = YES PRESSURE RELIEF DEVICE IN GAS/VAPOR SERVICE = YES VACUUM SERVICE = YES VALVES IN HEAVY LIQUID SERVICE = YES VAPOR RECOVERY SYSTEM = NO COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>COMPRESSOR NOT IN HYDROGEN SERVICE = YES</p> <p>OPEN-ENDED VALVES OR LINES EQUIVALENT EMISSION LIMITATION = NO</p> <p>PRESSURE RELIEF DEVICE COMPLYING WITH § 60.482-4(A)-(B) = YES</p> <p>PUMP IN LIGHT LIQUID SERVICE = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>COMPRESSOR EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP EQUIVALENT EMISSION LIMITATION = NO</p> <p>OPEN-ENDED VALVES OR LINES COMPLYING WITH § 60.482-6 = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE COMPLYING WITH § 60.482-8 = YES</p> <p>COMPRESSOR COMPLYING WITH § 60.482-3 = YES</p> <p>FLANGES AND OTHER CONNECTORS = YES</p> <p>PUMP COMPLYING WITH § 60.482-2 = YES</p> <p>SAMPLING CONNECTION SYSTEMS = YES</p> <p>VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE = YES</p> <p>FLANGES AND OTHER CONNECTORS EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP IN HEAVY LIQUID SERVICE = YES</p> <p>SAMPLING CONNECTION SYSTEM EQUIVALENT EMISSION LIMITATION = NO</p> <p>VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP EQUIVALENT EMISSION LIMITATION = NO</p> <p>FLANGES AND OTHER CONNECTORS COMPLYING WITH § 60.482-8 = YES</p> <p>SAMPLING CONNECTION SYSTEMS COMPLYING WITH § 60.482-5 = YES</p> <p>VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE COMPLYING WITH § 60.482-7 = YES</p> <p>PUMP COMPLYING WITH § 60.482-8 = YES</p>	
FUGDU1	30 TAC Chapter 115, HRVOC Fugitive Emissions	R5780-1	<p>Compressor Seals = The fugitive unit does not contain compressor seals.</p> <p>Title 30 TAC §115.780 Applicable = The fugitive unit contains a defined process and Highly Reactive VOC.</p> <p>Valves (not pressure relief, open-ended or bypass line valves) = The fugitive unit contains valves other than pressure relief, open-ended or bypass line valves.</p> <p>Weight Percent HRVOC = Components in the fugitive unit contact process fluids that contain less than 5.0% HRVOC by weight and process fluids that contain HRVOC at 5.0%, or greater, by weight on an annual average basis.</p> <p>Flanges or Other Connectors = The fugitive unit contains flanges or other connectors.</p> <p>Heat Exchanger Heads, etc. = The fugitive unit contains heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolter manways, hatches, sump covers, junction vent boxes or covers and seals on VOC water separators.</p> <p>Pressure Relief Valves = The fugitive unit contains pressure relief valves.</p> <p>Pump Seals = The fugitive unit does not contain pump seals.</p>	
FUGDU1	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
FUGDU1	40 CFR Part 60, Subpart VV	60VVALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in VOC service subject to 40 CFR Part 60, Subpart VV with no alternate control or control devices.	
FUGDU1	40 CFR Part 63, Subpart CC	R63CCVALL	<p>COMPRESSOR IN HYDROGEN SERVICE = YES</p> <p>ENCLOSED COMBUSTION DEVICE = NO</p> <p>EXISTING SOURCE = YES</p> <p>FLARE = NO</p> <p>OPEN-ENDED VALVES OR LINES = YES</p> <p>PRESSURE RELIEF DEVICE IN GAS/VAPOR SERVICE = YES</p> <p>VACUUM SERVICE = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE = YES</p> <p>VAPOR RECOVERY SYSTEM = NO</p> <p>COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES</p> <p>COMPRESSOR NOT IN HYDROGEN SERVICE = YES</p> <p>OPEN-ENDED VALVES OR LINES EQUIVALENT EMISSION LIMITATION = NO</p> <p>PRESSURE RELIEF DEVICE COMPLYING WITH § 60.482-4(A)-(B) = YES</p> <p>PUMP IN LIGHT LIQUID SERVICE = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>COMPRESSOR EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP EQUIVALENT EMISSION LIMITATION = NO</p> <p>OPEN-ENDED VALVES OR LINES COMPLYING WITH § 60.482-6 = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE COMPLYING WITH § 60.482-8 = YES</p> <p>COMPRESSOR COMPLYING WITH § 60.482-3 = YES</p> <p>FLANGES AND OTHER CONNECTORS = YES</p> <p>PUMP COMPLYING WITH § 60.482-2 = YES</p> <p>SAMPLING CONNECTION SYSTEMS = YES</p> <p>VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE = YES</p> <p>FLANGES AND OTHER CONNECTORS EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP IN HEAVY LIQUID SERVICE = YES</p> <p>SAMPLING CONNECTION SYSTEM EQUIVALENT EMISSION LIMITATION = NO</p> <p>VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP EQUIVALENT EMISSION LIMITATION = NO</p> <p>FLANGES AND OTHER CONNECTORS COMPLYING WITH § 60.482-8 = YES</p> <p>SAMPLING CONNECTION SYSTEMS COMPLYING WITH § 60.482-5 = YES</p> <p>VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE COMPLYING WITH § 60.482-7 = YES</p> <p>PUMP COMPLYING WITH § 60.482-8 = YES</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
FUGDU2	30 TAC Chapter 115, HRVOC Fugitive Emissions	R5780-1	<p>Compressor Seals = The fugitive unit does not contain compressor seals.</p> <p>Title 30 TAC §115.780 Applicable = The fugitive unit contains a defined process and Highly Reactive VOC.</p> <p>Valves (not pressure relief, open-ended or bypass line valves) = The fugitive unit contains valves other than pressure relief, open-ended or bypass line valves.</p> <p>Weight Percent HRVOC = Components in the fugitive unit contact process fluids that contain less than 5.0% HRVOC by weight and process fluids that contain HRVOC at 5.0%, or greater, by weight on an annual average basis.</p> <p>Flanges or Other Connectors = The fugitive unit contains flanges or other connectors.</p> <p>Heat Exchanger Heads, etc. = The fugitive unit contains heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolter manways, hatches, sump covers, junction vent boxes or covers and seals on VOC water separators.</p> <p>Pressure Relief Valves = The fugitive unit contains pressure relief valves.</p> <p>Pump Seals = The fugitive unit does not contain pump seals.</p>	
FUGDU2	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.	
FUGDU2	40 CFR Part 60, Subpart VV	60VVALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in VOC service subject to 40 CFR Part 60, Subpart VV with no alternate control or control devices.	
FUGDU2	40 CFR Part 63, Subpart CC	R63CCVALL	<p>COMPRESSOR IN HYDROGEN SERVICE = YES</p> <p>ENCLOSED COMBUSTION DEVICE = NO</p> <p>EXISTING SOURCE = YES</p> <p>FLARE = NO</p> <p>OPEN-ENDED VALVES OR LINES = YES</p> <p>PRESSURE RELIEF DEVICE IN GAS/VAPOR SERVICE = YES</p> <p>VACUUM SERVICE = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE = YES</p> <p>VAPOR RECOVERY SYSTEM = NO</p> <p>COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES</p> <p>COMPRESSOR NOT IN HYDROGEN SERVICE = YES</p> <p>OPEN-ENDED VALVES OR LINES EQUIVALENT EMISSION LIMITATION = NO</p> <p>PRESSURE RELIEF DEVICE COMPLYING WITH § 60.482-4(A)-(B) = YES</p> <p>PUMP IN LIGHT LIQUID SERVICE = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>COMPRESSOR EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP EQUIVALENT EMISSION LIMITATION = NO</p> <p>OPEN-ENDED VALVES OR LINES COMPLYING WITH § 60.482-6 = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE COMPLYING WITH § 60.482-8 = YES</p> <p>COMPRESSOR COMPLYING WITH § 60.482-3 = YES</p> <p>FLANGES AND OTHER CONNECTORS = YES</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			PUMP COMPLYING WITH § 60.482-2 = YES SAMPLING CONNECTION SYSTEMS = YES VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE = YES FLANGES AND OTHER CONNECTORS EQUIVALENT EMISSION LIMITATION = NO PUMP IN HEAVY LIQUID SERVICE = YES SAMPLING CONNECTION SYSTEM EQUIVALENT EMISSION LIMITATION = NO VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO PUMP EQUIVALENT EMISSION LIMITATION = NO FLANGES AND OTHER CONNECTORS COMPLYING WITH § 60.482-8 = YES SAMPLING CONNECTION SYSTEMS COMPLYING WITH § 60.482-5 = YES VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE COMPLYING WITH § 60.482-7 = YES PUMP COMPLYING WITH § 60.482-8 = YES	
FUGHDU1	30 TAC Chapter 115, HRVOC Fugitive Emissions	R5780-1	Compressor Seals = The fugitive unit does not contain compressor seals. Title 30 TAC §115.780 Applicable = The fugitive unit contains a defined process and Highly Reactive VOC. Valves (not pressure relief, open-ended or bypass line valves) = The fugitive unit contains valves other than pressure relief, open-ended or bypass line valves. Weight Percent HRVOC = Components in the fugitive unit contact process fluids that contain less than 5.0% HRVOC by weight and process fluids that contain HRVOC at 5.0%, or greater, by weight on an annual average basis. Flanges or Other Connectors = The fugitive unit contains flanges or other connectors. Heat Exchanger Heads, etc. = The fugitive unit contains heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolter manways, hatches, sump covers, junction vent boxes or covers and seals on VOC water separators. Pressure Relief Valves = The fugitive unit contains pressure relief valves. Pump Seals = The fugitive unit does not contain pump seals.	
FUGHDU1	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.	
FUGHDU1	40 CFR Part 60, Subpart VV	60VVALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in VOC service subject to 40 CFR Part 60, Subpart VV with no alternate control or control devices.	
FUGHDU1	40 CFR Part 63, Subpart CC	R63CCVALL	COMPRESSOR IN HYDROGEN SERVICE = YES ENCLOSED COMBUSTION DEVICE = NO EXISTING SOURCE = YES FLARE = NO OPEN-ENDED VALVES OR LINES = YES PRESSURE RELIEF DEVICE IN GAS/VAPOR SERVICE = YES VACUUM SERVICE = YES VALVES IN HEAVY LIQUID SERVICE = YES VAPOR RECOVERY SYSTEM = NO	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES</p> <p>COMPRESSOR NOT IN HYDROGEN SERVICE = YES</p> <p>OPEN-ENDED VALVES OR LINES EQUIVALENT EMISSION LIMITATION = NO</p> <p>PRESSURE RELIEF DEVICE COMPLYING WITH § 60.482-4(A)-(B) = YES</p> <p>PUMP IN LIGHT LIQUID SERVICE = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>COMPRESSOR EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP EQUIVALENT EMISSION LIMITATION = NO</p> <p>OPEN-ENDED VALVES OR LINES COMPLYING WITH § 60.482-6 = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE COMPLYING WITH § 60.482-8 = YES</p> <p>COMPRESSOR COMPLYING WITH § 60.482-3 = YES</p> <p>FLANGES AND OTHER CONNECTORS = YES</p> <p>PUMP COMPLYING WITH § 60.482-2 = YES</p> <p>SAMPLING CONNECTION SYSTEMS = YES</p> <p>VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE = YES</p> <p>FLANGES AND OTHER CONNECTORS EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP IN HEAVY LIQUID SERVICE = YES</p> <p>SAMPLING CONNECTION SYSTEM EQUIVALENT EMISSION LIMITATION = NO</p> <p>VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP EQUIVALENT EMISSION LIMITATION = NO</p> <p>FLANGES AND OTHER CONNECTORS COMPLYING WITH § 60.482-8 = YES</p> <p>SAMPLING CONNECTION SYSTEMS COMPLYING WITH § 60.482-5 = YES</p> <p>VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE COMPLYING WITH § 60.482-7 = YES</p> <p>PUMP COMPLYING WITH § 60.482-8 = YES</p>	
FUGSGP	30 TAC Chapter 115, HRVOC Fugitive Emissions	R5780-1	<p>Compressor Seals = The fugitive unit does not contain compressor seals.</p> <p>Title 30 TAC §115.780 Applicable = The fugitive unit contains a defined process and Highly Reactive VOC.</p> <p>Valves (not pressure relief, open-ended or bypass line valves) = The fugitive unit contains valves other than pressure relief, open-ended or bypass line valves.</p> <p>Weight Percent HRVOC = Components in the fugitive unit contact process fluids that contain less than 5.0% HRVOC by weight and process fluids that contain HRVOC at 5.0%, or greater, by weight on an annual average basis.</p> <p>Flanges or Other Connectors = The fugitive unit contains flanges or other connectors.</p> <p>Heat Exchanger Heads, etc. = The fugitive unit contains heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolter manways, hatches, sump covers, junction vent boxes or covers and seals on VOC water separators.</p> <p>Pressure Relief Valves = The fugitive unit contains pressure relief valves.</p> <p>Pump Seals = The fugitive unit does not contain pump seals.</p>	
FUGSGP	30 TAC Chapter 115, Pet. Refinery	R5352ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	& Petrochemicals		Chapter 115, Subchapter D, Division 3 with no alternate control or control device.	
FUGSGP	40 CFR Part 60, Subpart VV	60VVALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in VOC service subject to 40 CFR Part 60, Subpart VV with no alternate control or control devices.	
FUGSGP	40 CFR Part 63, Subpart CC	R63CCVALL	<p>COMPRESSOR IN HYDROGEN SERVICE = YES</p> <p>ENCLOSED COMBUSTION DEVICE = NO</p> <p>EXISTING SOURCE = YES</p> <p>FLARE = NO</p> <p>OPEN-ENDED VALVES OR LINES = YES</p> <p>PRESSURE RELIEF DEVICE IN GAS/VAPOR SERVICE = YES</p> <p>VACUUM SERVICE = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE = YES</p> <p>VAPOR RECOVERY SYSTEM = NO</p> <p>COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES</p> <p>COMPRESSOR NOT IN HYDROGEN SERVICE = YES</p> <p>OPEN-ENDED VALVES OR LINES EQUIVALENT EMISSION LIMITATION = NO</p> <p>PRESSURE RELIEF DEVICE COMPLYING WITH § 60.482-4(A)-(B) = YES</p> <p>PUMP IN LIGHT LIQUID SERVICE = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>COMPRESSOR EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP EQUIVALENT EMISSION LIMITATION = NO</p> <p>OPEN-ENDED VALVES OR LINES COMPLYING WITH § 60.482-6 = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE COMPLYING WITH § 60.482-8 = YES</p> <p>COMPRESSOR COMPLYING WITH § 60.482-3 = YES</p> <p>FLANGES AND OTHER CONNECTORS = YES</p> <p>PUMP COMPLYING WITH § 60.482-2 = YES</p> <p>SAMPLING CONNECTION SYSTEMS = YES</p> <p>VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE = YES</p> <p>FLANGES AND OTHER CONNECTORS EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP IN HEAVY LIQUID SERVICE = YES</p> <p>SAMPLING CONNECTION SYSTEM EQUIVALENT EMISSION LIMITATION = NO</p> <p>VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP EQUIVALENT EMISSION LIMITATION = NO</p> <p>FLANGES AND OTHER CONNECTORS COMPLYING WITH § 60.482-8 = YES</p> <p>SAMPLING CONNECTION SYSTEMS COMPLYING WITH § 60.482-5 = YES</p> <p>VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE COMPLYING WITH § 60.482-7 = YES</p> <p>PUMP COMPLYING WITH § 60.482-8 = YES</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
FUGWBT	30 TAC Chapter 115, HRVOC Fugitive Emissions	R5780-1	<p>Compressor Seals = The fugitive unit does not contain compressor seals.</p> <p>Title 30 TAC §115.780 Applicable = The fugitive unit contains a defined process and Highly Reactive VOC.</p> <p>Valves (not pressure relief, open-ended or bypass line valves) = The fugitive unit contains valves other than pressure relief, open-ended or bypass line valves.</p> <p>Weight Percent HRVOC = Components in the fugitive unit contact process fluids that contain less than 5.0% HRVOC by weight and process fluids that contain HRVOC at 5.0%, or greater, by weight on an annual average basis.</p> <p>Flanges or Other Connectors = The fugitive unit contains flanges or other connectors.</p> <p>Heat Exchanger Heads, etc. = The fugitive unit contains heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolter manways, hatches, sump covers, junction vent boxes or covers and seals on VOC water separators.</p> <p>Pressure Relief Valves = The fugitive unit contains pressure relief valves.</p> <p>Pump Seals = The fugitive unit does not contain pump seals.</p>	
FUGWBT	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.	
FUGWBT	40 CFR Part 60, Subpart VV	60VVALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in VOC service subject to 40 CFR Part 60, Subpart VV with no alternate control or control devices.	
FUGWBT	40 CFR Part 63, Subpart CC	R63CCVALL	<p>COMPRESSOR IN HYDROGEN SERVICE = YES</p> <p>ENCLOSED COMBUSTION DEVICE = NO</p> <p>EXISTING SOURCE = YES</p> <p>FLARE = NO</p> <p>OPEN-ENDED VALVES OR LINES = YES</p> <p>PRESSURE RELIEF DEVICE IN GAS/VAPOR SERVICE = YES</p> <p>VACUUM SERVICE = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE = YES</p> <p>VAPOR RECOVERY SYSTEM = NO</p> <p>COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES</p> <p>COMPRESSOR NOT IN HYDROGEN SERVICE = YES</p> <p>OPEN-ENDED VALVES OR LINES EQUIVALENT EMISSION LIMITATION = NO</p> <p>PRESSURE RELIEF DEVICE COMPLYING WITH § 60.482-4(A)-(B) = YES</p> <p>PUMP IN LIGHT LIQUID SERVICE = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>COMPRESSOR EQUIVALENT EMISSION LIMITATION = NO</p> <p>PUMP EQUIVALENT EMISSION LIMITATION = NO</p> <p>OPEN-ENDED VALVES OR LINES COMPLYING WITH § 60.482-6 = YES</p> <p>VALVES IN HEAVY LIQUID SERVICE COMPLYING WITH § 60.482-8 = YES</p> <p>COMPRESSOR COMPLYING WITH § 60.482-3 = YES</p> <p>FLANGES AND OTHER CONNECTORS = YES</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			PUMP COMPLYING WITH § 60.482-2 = YES SAMPLING CONNECTION SYSTEMS = YES VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE = YES FLANGES AND OTHER CONNECTORS EQUIVALENT EMISSION LIMITATION = NO PUMP IN HEAVY LIQUID SERVICE = YES SAMPLING CONNECTION SYSTEM EQUIVALENT EMISSION LIMITATION = NO VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO PUMP EQUIVALENT EMISSION LIMITATION = NO FLANGES AND OTHER CONNECTORS COMPLYING WITH § 60.482-8 = YES SAMPLING CONNECTION SYSTEMS COMPLYING WITH § 60.482-5 = YES VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE COMPLYING WITH § 60.482-7 = YES PUMP COMPLYING WITH § 60.482-8 = YES	
GRPHVROCFUG	30 TAC Chapter 115, HRVOC Fugitive Emissions	R5780-ALL	Owner/operator assumes HRVOC fugitive control requirements for all components subject to 30 tac chapter 115 with no alternate control or control device	
GRPMTBEFUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.	
GRPMTBEFUG	40 CFR Part 63, Subpart CC	63CCVV-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC/VHAP FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO MACT CC AND COMPLYING WITH NSPS VV REQUIREMENTS WITH NO ALTERNATE CONTROL OR CONTROL DEVICES	
GRPREFUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.	
GRPREFUG	40 CFR Part 60, Subpart VV	60VVALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in VOC service subject to 40 CFR Part 60, Subpart VV with no alternate control or control devices.	
GRPREFUG	40 CFR Part 63, Subpart CC	R63CCVVALL	COMPRESSOR IN HYDROGEN SERVICE = YES ENCLOSED COMBUSTION DEVICE = NO EXISTING SOURCE = YES FLARE = NO OPEN-ENDED VALVES OR LINES = YES PRESSURE RELIEF DEVICE IN GAS/VAPOR SERVICE = YES VACUUM SERVICE = YES VALVES IN HEAVY LIQUID SERVICE = YES VAPOR RECOVERY SYSTEM = NO COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES COMPRESSOR NOT IN HYDROGEN SERVICE = YES	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>OPEN-ENDED VALVES OR LINES EQUIVALENT EMISSION LIMITATION = NO PRESSURE RELIEF DEVICE COMPLYING WITH § 60.482-4(A)-(B) = YES PUMP IN LIGHT LIQUID SERVICE = YES VALVES IN HEAVY LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO COMPRESSOR EQUIVALENT EMISSION LIMITATION = NO PUMP EQUIVALENT EMISSION LIMITATION = NO OPEN-ENDED VALVES OR LINES COMPLYING WITH § 60.482-6 = YES VALVES IN HEAVY LIQUID SERVICE COMPLYING WITH § 60.482-8 = YES COMPRESSOR COMPLYING WITH § 60.482-3 = YES FLANGES AND OTHER CONNECTORS = YES PUMP COMPLYING WITH § 60.482-2 = YES SAMPLING CONNECTION SYSTEMS = YES VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE = YES FLANGES AND OTHER CONNECTORS EQUIVALENT EMISSION LIMITATION = NO PUMP IN HEAVY LIQUID SERVICE = YES SAMPLING CONNECTION SYSTEM EQUIVALENT EMISSION LIMITATION = NO VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE EQUIVALENT EMISSION LIMITATION = NO PUMP EQUIVALENT EMISSION LIMITATION = NO FLANGES AND OTHER CONNECTORS COMPLYING WITH § 60.482-8 = YES SAMPLING CONNECTION SYSTEMS COMPLYING WITH § 60.482-5 = YES VALVES IN GAS/VAPOR OR LIGHT LIQUID SERVICE COMPLYING WITH § 60.482-7 = YES PUMP COMPLYING WITH § 60.482-8 = YES</p>	
HB00200	40 CFR Part 60, Subpart GGGa	60GGGa	<p>Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006. Equipment Components = Components are present.</p>	
CWT10	30 TAC Chapter 115, HRVOC Cooling Towers	R5720-1	<p>Cooling Tower Heat Exchange System Exemptions = Each individual heat exchanger of the cooling tower heat exchange system does not have greater than 100 ppmw HRVOCs in the process side fluid.</p>	
CWT11	30 TAC Chapter 115, HRVOC Cooling Towers	R5720-1	<p>Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an exemption. Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor. Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764. Design Capacity = Design capacity to circulate 8000 gpm or greater. Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a). Modified Monitoring = Minor modifications to the monitoring and testing methods approved by the executive director as allowed in § 115.764(f) are being used. Flow Monitoring/Testing Method = Choosing to monitor cooling water flow rate at a location representative of the total flow rate to the cooling tower in accordance with § 115.764(g)(2).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Total Strippalbe VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a).</p> <p>On-Line Monitor = A continuous on-line monitor capable of providing total HRVOC and speciated HRVOCs in ppbw is being used.</p>	
CWT12	30 TAC Chapter 115, HRVOC Cooling Towers	R5720-1	<p>Cooling Tower Heat Exchange System Exemptions = The stream directed to the cooling tower heat exchange system contains less than 5.0% by weight HRVOC.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p> <p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = NOT USING MINOR MODIFICATIONS TO THE MONITORING AND TESTING METHODS IN 30 TAC § 115.764.</p> <p>Flow Monitoring/Testing Method = Choosing to monitor cooling water flow rate at a location representative of the total flow rate to the cooling tower in accordance with § 115.764(g)(2).</p> <p>Total Strippalbe VOC = Each individual heat exchanger in the cooling tower heat exchange system has less than 5.0% HRVOC in the process side and compliance with §115.764(d) is chosen.</p> <p>On-Line Monitor = Speciated strippable HRVOC concentration is being determined by sampling.</p>	
CWT15	30 TAC Chapter 115, HRVOC Cooling Towers	R5720-1	<p>Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an exemption.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p> <p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = Minor modifications to the monitoring and testing methods approved by the executive director as allowed in § 115.764(f) are being used.</p> <p>Flow Monitoring/Testing Method = Choosing to use a continuous flow monitor on each inlet of each cooling tower in accordance with § 115.764(a)(1), (b)(1), or (h)(1).</p> <p>Total Strippalbe VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a).</p> <p>On-Line Monitor = A continuous on-line monitor capable of providing total HRVOC and speciated HRVOCs in ppbw is being used.</p>	
CWT16	30 TAC Chapter 115, HRVOC Cooling Towers	R5720-1	<p>Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an exemption.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p> <p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = Minor modifications to the monitoring and testing methods approved by the executive director as allowed in § 115.764(f) are being used.</p> <p>Flow Monitoring/Testing Method = Choosing to monitor cooling water flow rate at a location representative of the total flow rate to the cooling tower in accordance with § 115.764(g)(2).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Total Strippalbe VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a).</p> <p>On-Line Monitor = A continuous on-line monitor capable of providing total HRVOC and speciated HRVOCs in ppbw is being used.</p>	
CWT17	30 TAC Chapter 115, HRVOC Cooling Towers	R5720-1	<p>Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an exemption.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p> <p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = Minor modifications to the monitoring and testing methods approved by the executive director as allowed in § 115.764(f) are being used.</p> <p>Flow Monitoring/Testing Method = Choosing to monitor cooling water flow rate at a location representative of the total flow rate to the cooling tower in accordance with § 115.764(g)(2).</p> <p>Total Strippalbe VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a).</p> <p>On-Line Monitor = A continuous on-line monitor capable of providing total HRVOC and speciated HRVOCs in ppbw is being used.</p>	
CWT6	30 TAC Chapter 115, HRVOC Cooling Towers	R5720-1	<p>Cooling Tower Heat Exchange System Exemptions = The stream directed to the cooling tower heat exchange system contains less than 5.0% by weight HRVOC.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate less than 8000 gpm.</p> <p>Modified Monitoring = NOT USING MINOR MODIFICATIONS TO THE MONITORING AND TESTING METHODS IN 30 TAC § 115.764.</p> <p>Flow Monitoring/Testing Method = Choosing to monitor cooling water flow rate at a location representative of the total flow rate to the cooling tower in accordance with § 115.764(g)(2).</p> <p>Total Strippalbe VOC = Each individual heat exchanger in the cooling tower heat exchange system has less than 5.0% HRVOC in the process side and compliance with §115.764(d) is chosen.</p>	
CWT7	30 TAC Chapter 115, HRVOC Cooling Towers	R5720-1	<p>Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an exemption.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p> <p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = Minor modifications to the monitoring and testing methods approved by the executive director as allowed in § 115.764(f) are being used.</p> <p>Flow Monitoring/Testing Method = Choosing to monitor cooling water flow rate at a location representative of the total flow rate to the cooling tower in accordance with § 115.764(g)(2).</p> <p>Total Strippalbe VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a).</p> <p>On-Line Monitor = A continuous on-line monitor capable of providing total HRVOC and speciated HRVOCs in ppbw is being used.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			used.	
CWT8	30 TAC Chapter 115, HRVOC Cooling Towers	R5720-1	<p>Cooling Tower Heat Exchange System Exemptions = The stream directed to the cooling tower heat exchange system contains less than 5.0% by weight HRVOC.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p> <p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = NOT USING MINOR MODIFICATIONS TO THE MONITORING AND TESTING METHODS IN 30 TAC § 115.764.</p> <p>Flow Monitoring/Testing Method = Choosing to use a continuous flow monitor on each inlet of each cooling tower in accordance with § 115.764(a)(1), (b)(1), or (h)(1).</p> <p>Total Strippalbe VOC = Each individual heat exchanger in the cooling tower heat exchange system has less than 5.0% HRVOC in the process side and compliance with §115.764(d) is chosen.</p>	
CWT9	30 TAC Chapter 115, HRVOC Cooling Towers	R5720-1	<p>Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an exemption.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p> <p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = Minor modifications to the monitoring and testing methods approved by the executive director as allowed in § 115.764(f) are being used.</p> <p>Flow Monitoring/Testing Method = Choosing to monitor cooling water flow rate at a point representative of the flow of cooling water from only the HRVOC-containing units.</p> <p>Total Strippalbe VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a).</p> <p>On-Line Monitor = A continuous on-line monitor capable of providing total HRVOC and speciated HRVOCs in ppbw is being used.</p>	
GRPBENZSEP	40 CFR Part 61, Subpart FF	61FF-1	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = FLARE</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
GRPBENZSEP	40 CFR Part 63, Subpart G	63CC-1	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.148</p> <p>New Source = FACILITY IS A EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = NO BYPASS LINE</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = FLARE</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p>	
A1000-FL1	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A1000-FL2	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A1006-FL1	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
A1006-FL2	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A10823-FL1	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A10823-FL2	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A1284-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A1301-FL	30 TAC Chapter 115, Vent Gas	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Controls		<p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A1301-FL	40 CFR Part 63, Subpart CC	63MACTCC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Sampling is used to determine the total organic compound emission rate.</p>	
A140-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A1660B	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
A1746-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
A1746-FL	40 CFR Part 63, Subpart CC	63MACTCC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Sampling is used to determine the total organic compound emission rate.</p>	
A200-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A267-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A285-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A301-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A309-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A330-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
A350-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A380-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A422-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A422-FL	40 CFR Part 63, Subpart CC	63MACTCC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Sampling is used to determine the total organic compound emission rate.</p>	
A503-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A518-FL1	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A518-FL2	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A519-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A519-FL	40 CFR Part 63, Subpart CC	63MACTCC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Sampling is used to determine the total organic compound emission rate.</p>	
A9267-FL	30 TAC Chapter 115, Vent Gas	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Controls		<p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A9268-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A9268-FL	40 CFR Part 63, Subpart CC	63MACTCC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Sampling is used to determine the total organic compound emission rate.</p>	
A9315-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
A9315-FL	40 CFR Part 63, Subpart CC	63MACTCC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Engineering Assessment = Sampling is used to determine the total organic compound emission rate.	
AE2340	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
AE2636	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
AE2650	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
AE348	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
AE349	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.	
AE388	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
AE389	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
AE700	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
AE768	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
AR300-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.	
AR300-FL	40 CFR Part 63, Subpart CC	63MACTCC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Sampling is used to determine the total organic compound emission rate.</p>	
BWN VENT	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
BWN VENT	40 CFR Part 63, Subpart CC	63MACTCC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Divert Vent Stream = The miscellaneous process vent utilizes a vent system that contains no by-pass lines.</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 1 vent.</p> <p>Automated Data Compression Recording System = OWNER/OPERATOR DOES NOT USE AN AUTOMATED DATA COMPRESSION SYSTEM THAT RECORDS ALL VALUES THAT MEET SET CRITERIA FOR VARIATION FROM PREVIOUSLY RECORDED VALUES.</p> <p>Engineering Assessment = Sampling is used to determine the total organic compound emission rate.</p> <p>Continuous Operating Parameter Provisions = The owner or operator does not use an alternative to the continuous operating parameter monitoring and recordkeeping provisions of 40 CFR § 63.654(i).</p> <p>Control Device = Flare</p> <p>Additional Parameter Monitoring = Parameters specified in 40 CFR § 63.644(a) are being monitored.</p>	
C9150	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
C9151	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
C9152	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
C9153	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
CDUCT1	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
CDUCT2	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
DEG ACID	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
DEG ACID	40 CFR Part 63, Subpart CC	63MACTCC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Sampling is used to determine the total organic compound emission rate.</p>	
DEPNP COND	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
DEPNP COND	40 CFR Part 63,	63MACTCC-1	Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR §	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart CC		<p>63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Sampling is used to determine the total organic compound emission rate.</p>	
DHTVAC	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
H1000	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H1000	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H1010	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H1010	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H1011	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H1011	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H1100	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H1100	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H1170	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H1170	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H31001	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H31002	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H31003	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H3300	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H332V	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
H36100	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5100	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H5100	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5101	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.	
H5101	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5102	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H5102	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5103	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H5103	30 TAC Chapter	R5720-1	Alternative Monitoring = Not using alternative monitoring and testing methods.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	115, HRVOC Vent Gas		<p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5104	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5105	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5200	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H5200	30 TAC Chapter	R5720-1	Alternative Monitoring = Not using alternative monitoring and testing methods.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	115, HRVOC Vent Gas		<p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5301	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5302	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5303	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
H5304	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Testing Requirements = Meeting § 115.725(a).</p> <p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5305	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5350	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H53NN	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.	
H5400	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H5400	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5402	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H5402	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5403	30 TAC Chapter	R5720-1	Alternative Monitoring = Not using alternative monitoring and testing methods.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	115, HRVOC Vent Gas		<p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5404	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5500	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H5500A	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H5500B	30 TAC Chapter	R1111-01	Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	111, Visible Emissions		<p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H5500C	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H5600	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H5600	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H600	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = The executive director and Administrator have determined that 30 TAC § 111.111(a)(1)(F) may be used to comply with the appropriate opacity standard since the gas stream contains condensed water vapor which could interfere with proper CEMS operation.</p> <p>Total Feed Capacity = Total feed capacity is greater than 20,000 barrels per day.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	
H613	30 TAC Chapter 111, Visible Emissions	R1111-01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
H613	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H63000	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H70002	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
H7302	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Testing using the specified appropriate reference methods and procedures are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
HB00200	30 TAC Chapter 115, HRVOC Vent Gas	R5727	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate less than or equal to 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Exempt Date = The vent gas stream is not exempt.</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a control device other than a flare.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
HB00200	30 TAC Chapter 115, Vent Gas Controls	R5127	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is less than 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
IA88017-FL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
L2COMPVT	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
MRCM C4 VENT	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
MRCM C4 VENT1	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
MRCM C4 VENT2	30 TAC Chapter 115, Vent Gas	R5121-1	Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Controls		<p>establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is less than 408 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
MTBE DEGASSER	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
MTBE DEGASSER	40 CFR Part 63, Subpart CC	63CC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Sampling is used to determine the total organic compound emission rate.</p>	
V-1024	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V-1046	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V-1052	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V1074	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V1298	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V1299	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V31001	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V31002	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V31003	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V31004	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V54	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is less than 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
V5518	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is less than 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
V5527	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V5527	40 CFR Part 63, Subpart CC	63MACTCC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Sampling is used to determine the total organic compound emission rate.</p>	
V601	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V602	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
V9160	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
WW DEGASSER	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
WW DEGASSER	40 CFR Part 63, Subpart CC	63MACTCC-1	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Sampling is used to determine the total organic compound emission rate.</p>	
PAINTFE	30 TAC Chapter 115, Surface Coating Operations	R5421-1	<p>Alternate Requirements = No alternate requirement to 30 TAC §§ 115.421(a)(9) or 115.421(b)(8) has been approved or no alternate has been requested.</p> <p>Alternative Compliance Method = No alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria has been approved by the TCEQ Executive Director or no such alternate has been requested.</p> <p>Facility Operations = Other miscellaneous metal parts and products coating.</p> <p>Miscellaneous Coating Type = A coating that is low-bake, or utilizes air or forced air driers.</p> <p>VOC Emission Rate = Uncontrolled emission rates not qualifying for exemption from control.</p> <p>Vapor Recovery = No vapor recovery system is used to control emissions.</p>	
GRPBENZIGF	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPBENZSEP	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p> <p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
GRPBENZTK	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component with a vapor mounted primary seal.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
GRPBWNTK1	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted primary seal.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
GRPBWNTK2	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted primary seal.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPSEPARAT	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = A wastewater component that is exempted from the control requirements of 30 TAC § 115.142 because it handles only exempted wastewater streams under 30 TAC § 115.147(2).</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
GRPWWIFR	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component with a vapor mounted primary seal.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
GRPWWTK	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = A wastewater component that is exempted from the control requirements of 30 TAC § 115.142 because it handles only exempted wastewater streams under 30 TAC § 115.147(2).</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
S339	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted primary seal.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
T304	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted primary seal.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
X322	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component with a vapor mounted primary seal.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
X323	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted primary seal.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
X330	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is a petroleum refinery.</p> <p>Wastewater Component Type = A wastewater component that is exempted from the control requirements of 30 TAC § 115.142 because it handles only exempted wastewater streams under 30 TAC § 115.147(2).</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
CR3	40 CFR Part 63, Subpart UUU	63UUU	Alternate Method for Measuring Gas Flow Rate = Not using an alternate method for measuring gas flow rate as listed in §63.1573(a)(1).	The main standard, related standards, monitoring, testing, recordkeeping, and reporting rule citations were determined from an analysis of the rule text and the basis of determination.
FCCU	40 CFR Part 63, Subpart UUU	63UUU	Alternate Method for Measuring Gas Flow Rate = Not using an alternate method for measuring gas flow rate as listed in §63.1573(a)(1).	The main standard, related standards,

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
				monitoring, testing, recordkeeping, and reporting rule citations were determined from an analysis of the rule text and the basis of determination.
FLARECOKE	40 CFR Part 60, Subpart J	60J-1	Construction/Modification Date = After June 11, 1973 and on or before June 24, 2008.	
FLAREEP	40 CFR Part 60, Subpart J	60J-1	Construction/Modification Date = After June 11, 1973 and on or before June 24, 2008.	
FLAREGIRB	40 CFR Part 60, Subpart J	60J-1	Construction/Modification Date = After June 11, 1973 and on or before June 24, 2008.	
FLARENPN	40 CFR Part 60, Subpart J	60J-1	Construction/Modification Date = After June 11, 1973 and on or before June 24, 2008.	
FLAREWP	40 CFR Part 60, Subpart J	60J-1	Construction/Modification Date = After June 11, 1973 and on or before June 24, 2008.	
GRP-DUCT	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
GRP-FURN	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
GRPHTR2	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
GRPHTR3	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
GRPHTR4	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
GRPHTR6	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
GRPHTR7	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPSRU345	40 CFR Part 60, Subpart J	60J-1	Construction/Modification Date = After October 4, 1976 and on or before May 14, 2007.	
GRPSRU678	40 CFR Part 60, Subpart J	60J-1	Construction/Modification Date = After October 4, 1976 and on or before May 14, 2007.	
H1000	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H1001	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H1100	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H31003	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H3300	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H36100	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H5101	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H5102	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H5104	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H5105	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H5305	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
H5350	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H5403	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H5404	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H5500	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H600	40 CFR Part 60, Subpart J	60J-1	Facility Type = FCCU catalyst regenerator located at a petroleum refinery. Construction/Modification Date = After January 17, 1984 and on or before May 14, 2007. Discharged Gases = Gases discharged by the FCCU catalyst regenerator pass through an incinerator or waste heat boiler in which auxiliary or supplemental liquid or solid fossil fuel is burned.	
H613	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H63000	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H70002	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
H9150	40 CFR Part 60, Subpart J	60J-1	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.	
HB00200	40 CFR Part 60, Subpart Ja	60Ja-1	Facility Type = Process heater that is used for fuel gas combustion that meets requirements in § 60.107a(a)(3) [inherently low in sulfur content]. Heater Capacity = The process heater is rated equal to or greater than 100 MMBtu/hr. Low-NOx = The process heater has low-NO _x or ultra low-NO _x burners. Post Combustion = The unit has no post-combustion control device. Construction/Modification Date = After June 24, 2008 Sulfur Emission Limit = Owner or operator is choosing SO ₂ limit in terms of ppmv H ₂ S in fuel gas.	
PLAT2	40 CFR Part 63, Subpart UUU	63UUU	Alternate Method for Measuring Gas Flow Rate = Not using an alternate method for measuring gas flow rate as listed in §63.1573(a)(1).	The main standard, related standards, monitoring, testing,

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
				recordkeeping, and reporting rule citations were determined from an analysis of the rule text and the basis of determination.
SRU3/4	40 CFR Part 63, Subpart UUU	63UUU	Alternate Method for Measuring Gas Flow Rate = Not using an alternate method for measuring gas flow rate as listed in §63.1573(a)(1).	The main standard, related standards, monitoring, testing, recordkeeping, and reporting rule citations were determined from an analysis of the rule text and the basis of determination.
SRU5	40 CFR Part 63, Subpart UUU	63UUU	Alternate Method for Measuring Gas Flow Rate = Not using an alternate method for measuring gas flow rate as listed in §63.1573(a)(1).	The main standard, related standards, monitoring, testing, recordkeeping, and reporting rule citations were determined from an analysis of the rule text and the basis of determination.
SRU6	40 CFR Part 63, Subpart UUU	63UUU	Alternate Method for Measuring Gas Flow Rate = Not using an alternate method for measuring gas flow rate as listed in §63.1573(a)(1).	The main standard, related standards, monitoring, testing, recordkeeping, and reporting rule citations were determined from an analysis of the rule text and the basis of determination.
SRU7	40 CFR Part 63, Subpart UUU	63UUU	Alternate Method for Measuring Gas Flow Rate = Not using an alternate method for measuring gas flow rate as listed in §63.1573(a)(1).	The main standard, related standards, monitoring, testing, recordkeeping, and reporting rule citations were determined from an analysis of the rule text and the basis of determination.
SRU8	40 CFR Part 63, Subpart UUU	63UUU	Alternate Method for Measuring Gas Flow Rate = Not using an alternate method for measuring gas flow rate as listed in §63.1573(a)(1).	The main standard, related standards, monitoring, testing, recordkeeping, and reporting rule citations were determined from an analysis of the rule text and the basis of determination.

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
FLARECCU	40 CFR Part 63, Subpart G	63G-1	<p>Alternate Monitoring Parameters = Complying with the monitoring parameters specified in Subpart G.</p> <p>Unit Type = Any combination of waste management units, excluding containers and drains.</p> <p>Closed Vent System = Closed vent system is subject to and complying with 40 CFR § 63.172.</p> <p>By-pass Lines = No by-pass lines.</p> <p>Control Device Type = Flare.</p> <p>Monitoring Options = Control device is using an organic monitoring device as allowed under 40 CFR § 63.143(e)(2).</p>	
FLAREEP	40 CFR Part 61, Subpart FF	61FF-1	<p>Unit Type = Containers and individual drain systems</p> <p>CLOSED VENT SYSTEM AND CONTROL DEVICE AMOC = Complying with the requirements of § 61.349</p> <p>By-pass Line = System does not contain by-pass lines</p> <p>Control Device Type/Operation = Flare.</p>	
FLAREEP	40 CFR Part 63, Subpart G	63G-1	<p>Alternate Monitoring Parameters = Complying with the monitoring parameters specified in Subpart G.</p> <p>Unit Type = Any combination of waste management units, excluding containers and drains.</p> <p>Closed Vent System = Closed vent system is subject to and complying with 40 CFR § 63.172.</p> <p>By-pass Lines = No by-pass lines.</p> <p>Control Device Type = Flare.</p> <p>Monitoring Options = Control device is using an organic monitoring device as allowed under 40 CFR § 63.143(e)(2).</p>	
FLARESOUTH	40 CFR Part 63, Subpart G	63G-1	<p>Alternate Monitoring Parameters = Complying with the monitoring parameters specified in Subpart G.</p> <p>Unit Type = Any combination of waste management units, excluding containers and drains.</p> <p>Closed Vent System = Closed vent system is subject to and complying with 40 CFR § 63.172.</p> <p>By-pass Lines = No by-pass lines.</p> <p>Control Device Type = Flare.</p> <p>Monitoring Options = Control device is using an organic monitoring device as allowed under 40 CFR § 63.143(e)(2).</p>	
FLAREWP	40 CFR Part 61, Subpart FF	61FF-1	<p>Unit Type = Containers and individual drain systems</p> <p>By-pass Line = System does not contain by-pass lines</p> <p>Control Device Type/Operation = Flare.</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p>	
FLAREWP	40 CFR Part 63, Subpart G	63G-1	<p>Alternate Monitoring Parameters = Complying with the monitoring parameters specified in Subpart G.</p> <p>Unit Type = Any combination of waste management units, excluding containers and drains.</p> <p>Closed Vent System = Closed vent system is subject to and complying with 40 CFR § 63.172.</p> <p>By-pass Lines = No by-pass lines.</p> <p>Control Device Type = Flare.</p> <p>Monitoring Options = Control device is using an organic monitoring device as allowed under 40 CFR § 63.143(e)(2).</p>	
PROBWN	40 CFR Part 61, Subpart FF	61FF-1	<p>AMOC = An alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.348 for treatment processes is not used.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>By-Pass Line = The closed-vent system does not contain a by-pass line that could divert the vent stream away from the control device.</p> <p>Continuous Monitoring = The wastewater treatment system unit process parameters are continuously monitored to indicate proper system operation.</p> <p>Complying with § 61.342(e) = The facility is complying with 40 CFR § 61.342(e).</p> <p>Control Device Type/Operation = Flare.</p> <p>Openings = The treatment process or wastewater treatment system unit has no openings.</p> <p>Fuel Gas System = Not all gaseous vent streams from the treatment process or wastewater treatment system are routed to a fuel gas system.</p> <p>Benzene Removal = Benzene is removed from the waste stream to a level of less than 10 ppmw on a flow weighted annual average basis.</p> <p>Closed-Vent System and Control Device = A closed-vent system and control device is used.</p> <p>Process Or Stream Exemption = The treatment process or waste stream is not complying with 40 CFR §61.348(d).</p> <p>AMOC = No alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.349 for a closed-vent system and control device is used.</p> <p>Treatment Process Engineering Calculations = Engineering calculations show that the treatment process or wastewater treatment system unit is proven to achieve its emission limitation.</p>	

* - The "unit attributes" or operating conditions that determine what requirements apply

** - Notes changes made to the automated results from the DSS, and a brief explanation why

NSR Versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	Federal Operating Permit(FOP)
Issued Prior to new Construction or modification of an existing facility	For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation.
Authorizes air emissions	Codifies existing applicable requirements, does not authorize new emissions
Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented.	Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP.
Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations.	One public notice required. Opportunity for public comments. No contested case hearings.
Applies to all point source emissions in the state.	Applies to all major sources and some non-major sources identified by the EPA.
Applies to facilities: a portion of site or individual emission sources	One or multiple FOPs cover the entire site (consists of multiple facilities)
Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis.	Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site.
Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources.	Opportunity for EPA review, Affected states review, and a Public petition period for every FOP.
Permits have a table listing maximum emission limits for pollutants	Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements.
Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin.	Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated.
NSR permits are issued independent of FOP requirements.	FOP are independent of NSR permits, but contain a list of all NSR permits incorporated by reference

New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. The permit contains two attachments that list NSR Authorizations for the permitted area. These authorizations include major and minor new source review permits, standard permits and permits by rule. The “New Source Review Authorization References” attachment lists all NSR Authorizations for the permitted area, and the “New Source Review Authorization References by Emission Unit” attachment lists emission units in the permitted area and NSR authorizations for each. To address an objection to this permit granted by the EPA Administrator by order dated September 24, 2015, The attached tables have been revised to provide additional information on the PBRs claimed at this site. These NSR permits and registrations can be found in the main TCEQ file room, located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. The Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

The status of air permits and applications and a link to the Air Permits Remote Document Server is located at the following Web site:

www.tceq.texas.gov/permitting/air/nav/air_status_permits.html

Permits by Rule

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. The following table specifies the permits by rule that apply to the site. All current permits by rule are contained in Chapter 106. Outdated 30 TAC Chapter 106 permits by rule may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106list/index106.html

Outdated Standard Exemption lists may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html

Texas Commission on Environmental Quality (TCEQ) regulates facilities that release air contaminants, even in small amounts, under its air permit rules. Facilities with emissions that do not meet de minimis criteria but will not make a significant contribution of air contaminants to the atmosphere may be permitted by rule. Facilities authorized by PBR must be constructed and operated with certain restrictions.

A PBR may be claimed when both the following conditions are met: 1. The facility meets all applicable requirements of 30 TAC § 106.4. These requirements limit the amount of annual emissions to less than federal permit major source levels, and require compliance with all state and federal regulations; and 2. The facility meets all applicable conditions of one or more individual PBRs contained in 30 TAC Chapter 106. These requirements may specify design requirements for certain facilities, production or material use limits, and operational restrictions.

Certain PBRs require registration with TCEQ as stated in the specific PBR. Other PBRs are not required to be registered with TCEQ. In either case, the permit holder must maintain sufficient records to demonstrate compliance with the annual emissions limits specified in 30 TAC § 106 and maintain sufficient records to demonstrate compliance with the emission limits and specific conditions of the PBR.

Permit holders may also certify emissions in a PBR registration to establish federally enforceable emission limits below the emission limits of 30 TAC § 106.4 which establishes limits for production and planned MSS for each facility (piece of equipment) to 250 tons per year (tpy) Nitrogen Oxides (NO_x) and Carbon Monoxide (CO); 25 tpy Volatile Organic Compounds (VOC), Particulate Matter (PM), Sulfur Dioxide (SO₂), and any other contaminant (except water, nitrogen, ethane, hydrogen, oxygen, and greenhouse gases); 15 tpy of

particulate matter with diameters of 10 microns or less (PM₁₀); or 10 tpy of particulate matter with diameters of 2.5 microns or less (PM_{2.5}).

PBR registrations may be certified to demonstrate that emission allowables for each facility claimed under the PBR are less than the netting or major source trigger levels under the PSD and NNSR programs. Certifications are also required for sites subject to NOx cap and trade programs under 30 TAC Chapter 101 and for ensuring that any PBR claims do not exceed permitted flexible caps for facilities permitted under 30 TAC Chapter 116, Subchapter G.

For PBRs that are registered with TCEQ, copies of the registration letters may be viewed through the Remote Document Server (RDS) at <https://webmail.tceq.state.tx.us/gw/webpub>. PBRs registrations that are certified will have the specific maximum permitted allowables for each facility attached to the registration letter.

Incorporation of PBRs in NSR Permits

TCEQ’s Policy and Guidance Memo dated September 26, 2006

http://www.tceq.texas.gov/assets/public/permitting/air/memos/pbr_spc06.pdf defines the two different scenarios that will determine when and how a PBR or SP should be consolidated in the NSR permit for that facility when the NSR permit is amended or renewed: consolidation by reference and consolidation by incorporation.

Standard Permits and PBRs that directly affect the emissions of permitted facilities must, at a minimum, be consolidated by reference when the NSR permit is amended. If Standard Permits and PBRs occur at the NSR permitted site, but do not directly affect NSR permitted facilities, it is not required, but at the request of the NSR permit holder they may be consolidated by reference. Referencing will not require a best available control technology (BACT) review but may require an impacts review based on commission guidance.

Consolidation of all other PBRs and SPs by incorporation (rolled in) is voluntary. If the NSR permit holder requests incorporation (that is, reauthorization under the permit), PBRs and SPs may be incorporated but will undergo BACT and impacts review based on commission guidance. When incorporated into the NSR permit, the original authorization becomes void. The incorporation of PBRs and SPs requires an amendment, but no additional forms or fees are required if a complete renewal package with the above information is submitted

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: PSDTX815	Issuance Date: 01/13/2015
PSD Permit No.: PSDTX928	Issuance Date: 12/17/2014
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 21262	Issuance Date: 12/17/2014
Authorization No.: 22038	Issuance Date: 01/13/2015
Authorization No.: 3179	Issuance Date: 07/21/2011
Authorization No.: 3214	Issuance Date: 06/30/2008
Authorization No.: 77952	Issuance Date: 10/09/2015
Authorization No.: 81971	Issuance Date: 11/09/2009
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.261	Version No./Date: 09/04/2000

Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 03/14/1997
Number: 106.262	Version No./Date: 09/04/2000
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 09/04/2000
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.487	Version No./Date: 09/04/2000

Emission Units and Emission Points

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sandblasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the “Maximum Allowable Emission Rate Table”, or “MAERT” for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

Monitoring Sufficiency

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit’s compliance with the applicable emission limitation or standard. Subsection 70.6(c)(1) and 30 TAC § 122.142(b)(2)(B)(ii) also provides that all operating permits must contain monitoring requirements sufficient to assure compliance with the terms and conditions of the permit. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. Such monitoring requirements were developed through the NSR permitting process for permit specific emission limits and operating requirements, taking into consideration the specific types of equipment and processes, as well as the air contaminants emitted, authorized by the permit. More generally, monitoring, testing, recordkeeping, and reporting requirements are developed by TCEQ for, PM, SO₂, VOC and NO_x sources, and

these requirements can be found in 30 TAC Chapters 111, 112, 115 and 117, respectively. During the rulemaking process, the necessary monitoring, testing, recordkeeping, and reporting requirements are developed to ensure that applicable sources will be able to ensure that they are meeting the applicable rule requirements. EPA also develops necessary monitoring, testing, recordkeeping, and reporting requirements through federal rulemaking for applicable sources, under CAA sections 111 (NSPS) and 112 (NESHAP). If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

The rationale for the following units was prepared to address objections granted by the EPA Administrator on this permit in an order issued September 24, 2015.

Monitoring Rationale for Storage Tanks and Wastewater Treatment Facilities

The CEMSET calculations used in Shell's permit Applications follow the same treatment system emission methodology as is used in the EPA WATER series. The CEMSETS calculations contain additional treatment process emission modules, and have generally been tailored for the Shell Deer Park site's SET process. The EPA WATER9 and CEMSET models are based largely upon the calculation methodology available in the USEPA document Hazardous Waste Treatment, Storage, and Disposal Facilities (TSDF) - Air Emission Models (EPA-450/3-87-026, December 1987). However, the circular clarifier liquid phase mass transfer coefficient (KL) values calculated by WATER9 differ from the value calculated by CEMSETS and the TSDF calculations. The TSDF calculations agree with and support Shell's CEMSETS results. The apparent reason for the greater mass transfer in WATER9 is the assumed flow of water across the clarifier surface. In the CEMSETS and TSDF models, contaminants entering the clarifier undergo liquid-gas mass transfer from the quiescent surface and the weir. Samples of the inlet streams were taken over time to determine the average expected concentration of each pollutant. The flow of each inlet stream is monitored continuously, flow data is stored in Shell Deer Park's data management system. Concentration and flow data are input into the model to determine the mass emission rate of each pollutant. The data input into the model is performed annually.

Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected

Periodic Monitoring:

The Federal Clean Air Act requires that each federal operating permit include monitoring sufficient to assure compliance with the terms and conditions of the permit. Most of the emission limits and standards applicable to emission units at Title V sources include adequate monitoring to show that the units meet the limits and standards. For those requirements that do not include monitoring, or where the monitoring is not sufficient to assure compliance, the federal operating permit must include such monitoring for the emission units affected. The following emission units are subject to periodic monitoring requirements because the emission units are subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement that does not already require monitoring, or the monitoring for the applicable requirement is not sufficient to assure compliance:

Unit/Group/Process Information	
ID No.: A1660B	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: AE2340	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: AE2636	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: AE2650	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: AE348	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: AE349	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: AE388	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: AE389	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: AE700	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: AE768	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: DHTVAC	
Control Device ID No.: H1100	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Failure to monitor and record during periods of operation.	
<p>Basis of monitoring:</p> <p>A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: GRPMARLOAD	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-1
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: VOC Concentration	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to measure and record fugitive emissions from the vapor collection system in accordance with 40 CFR Part 60, Appendix A, Method 21.	
<p>Basis of monitoring: It is widely practiced and accepted to monitor the VOC concentration at the outlet of a control device by use of a portable analyzer with procedures such as EPA Test Method 25A or a VOC CEMS. The measured concentration along with stack flow rate or AP-42 factors and fuel consumption records may be used to demonstrate compliance with an underlying emission limit or standard. Outlet VOC concentration has been used as an indicator of VOC emissions in many federal rules including 40 CFR Part 60, Subpart III, 40 CFR Part 60, Subpart NNN, 40 CFR Part 60, Subpart RRR, 40 CFR Part 61, Subpart BB, 40 CFR Part 61, Subpart FF, 40 CFR Part 63, Subpart R, 40 CFR Part 63, Subpart DD, and 40 CFR Part 63, Subpart HH.</p>	

Unit/Group/Process Information	
ID No.: GRPMARLOAD	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-1
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	
<p>Basis of monitoring: It is widely practiced and accepted to use work practice as a monitoring option to demonstrate compliance. Preventive maintenance and visual inspections of control equipment, as recommended by the manufacturer, conducted by the owner or operator can ensure that the unit is operating properly. The work practice requirements prescribe that preventive maintenance and/or visual inspections be performed and a recorded in a log. This option assures that the owner or operator is adequately maintaining the control equipment.</p>	

Unit/Group/Process Information	
ID No.: GRPTKEFR2	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-2
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: GRPTKEFR3	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-2
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the “Periodic Monitoring Technical Reference Document” (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: GRPTKIFR10	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-1
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.	
<p>Basis of monitoring: The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: GRPTKIFR3	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-1
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.	
<p>Basis of monitoring: The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: H1000	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H1010	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H1011	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H1100	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H1170	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H5100	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H5101	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H5102	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H5103	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H5200	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H53NN	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H5400	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H5402	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H5500A	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H5500B	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H5500C	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H5600	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: H613	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Compliance History Review

1. In accordance with 30 TAC Chapter 60, the compliance history was reviewed on March 4, 2016.

Site rating: 10.26 / Satisfactory Company rating: 7.61 / Satisfactory

(High < 0.10; Satisfactory ≥ 0.10 and < 55; Unsatisfactory > 55)

2. Has the permit changed on the basis of the compliance history or site/company rating?No

Available Unit Attribute Forms

- OP-UA1 - Miscellaneous and Generic Unit Attributes
- OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes
- OP-UA3 - Storage Tank/Vessel Attributes
- OP-UA4 - Loading/Unloading Operations Attributes
- OP-UA5 - Process Heater/Furnace Attributes
- OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes
- OP-UA7 - Flare Attributes
- OP-UA8 - Coal Preparation Plant Attributes
- OP-UA9 - Nonmetallic Mineral Process Plant Attributes
- OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes
- OP-UA11 - Stationary Turbine Attributes
- OP-UA12 - Fugitive Emission Unit Attributes
- OP-UA13 - Industrial Process Cooling Tower Attributes
- OP-UA14 - Water Separator Attributes
- OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes
- OP-UA16 - Solvent Degreasing Machine Attributes
- OP-UA17 - Distillation Unit Attributes
- OP-UA18 - Surface Coating Operations Attributes
- OP-UA19 - Wastewater Unit Attributes
- OP-UA20 - Asphalt Operations Attributes
- OP-UA21 - Grain Elevator Attributes
- OP-UA22 - Printing Attributes
- OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes
- OP-UA25 - Synthetic Fiber Production Attributes
- OP-UA26 - Electroplating and Anodizing Unit Attributes
- OP-UA27 - Nitric Acid Manufacturing Attributes
- OP-UA28 - Polymer Manufacturing Attributes
- OP-UA29 - Glass Manufacturing Unit Attributes
- OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semichemical Pulp Mill Attributes
- OP-UA31 - Lead Smelting Attributes
- OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes
- OP-UA33 - Metallic Mineral Processing Plant Attributes
- OP-UA34 - Pharmaceutical Manufacturing
- OP-UA35 - Incinerator Attributes
- OP-UA36 - Steel Plant Unit Attributes
- OP-UA37 - Basic Oxygen Process Furnace Unit Attributes
- OP-UA38 - Lead-Acid Battery Manufacturing Plant Attributes
- OP-UA39 - Sterilization Source Attributes
- OP-UA40 - Ferrous Alloy Production Facility Attributes
- OP-UA41 - Dry Cleaning Facility Attributes
- OP-UA42 - Phosphate Fertilizer Manufacturing Attributes
- OP-UA43 - Sulfuric Acid Production Attributes
- OP-UA44 - Municipal Solid Waste Landfill/Waste Disposal Site Attributes
- OP-UA45 - Surface Impoundment Attributes
- OP-UA46 - Epoxy Resins and Non-Nylon Polyamides Production Attributes

OP-UA47 - Ship Building and Ship Repair Unit Attributes
OP-UA48 - Air Oxidation Unit Process Attributes
OP-UA49 - Vacuum-Producing System Attributes
OP-UA50 - Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes
OP-UA51 - Dryer/Kiln/Oven Attributes
OP-UA52 - Closed Vent Systems and Control Devices
OP-UA53 - Beryllium Processing Attributes
OP-UA54 - Mercury Chlor-Alkali Cell Attributes
OP-UA55 - Transfer System Attributes
OP-UA56 - Vinyl Chloride Process Attributes
OP-UA57 - Cleaning/Depainting Operation Attributes
OP-UA58 - Treatment Process Attributes
OP-UA59 - Coke By-Product Recovery Plant Attributes
OP-UA60 - Chemical Manufacturing Process Unit Attributes
OP-UA61 - Pulp, Paper, or Paperboard Producing Process Attributes
OP-UA62 - Glycol Dehydration Unit Attributes
OP-UA63 - Vegetable Oil Production Attributes