



DECISION DOCUMENT AMENDMENT

REYNOLDS METALS COMPANY STUDY AREA
MASSENA, NEW YORK

U.S. ENVIRONMENTAL PROTECTION AGENCY
REGION II
NEW YORK, NEW YORK

SEPTEMBER 1998

500443

**DECLARATION STATEMENT
DECISION DOCUMENT AMENDMENT**

SITE NAME AND LOCATION

Reynolds Metals Company Study Area
Massena, New York

STATEMENT OF BASIS AND PURPOSE

This decision document presents the United States Environmental Protection Agency's (EPA's) selection of a modification to the remedial action for the Reynolds Metals Company Study Area Site (the "Site"), in accordance with the requirements of the Comprehensive Environmental Response, Compensation and Liability Act of 1980, as amended (CERCLA), 42 U.S.C. §9601-9675, and to the extent practicable, the National Oil and Hazardous Substances Pollution Contingency Plan, 40 CFR Part 300. This decision document explains the factual and legal basis for selecting the remedy modification for the Site. The original remedial action was selected in the Decision Document issued by EPA on September 27, 1993.

The attached index (Appendix 1) identifies the items that comprise the Administrative Record upon which the selection of the remedial action is based.

ASSESSMENT OF THE SITE

Actual or threatened releases of hazardous substances from the Site, if not addressed by implementing the response actions selected in the September 27, 1993 Decision Document, as revised by this Decision Document Amendment, may present an imminent and substantial threat to the public health, welfare, or the environment.

DESCRIPTION OF MODIFICATION TO THE SELECTED REMEDY

The modification to the selected remedy addresses the disposal of contaminated sediments which will be dredged from the St. Lawrence River adjacent to the Reynolds Metals Company (Reynolds) aluminum production facility (Facility), located in Massena, New York.

The components of the modification to the selected remedy consist of the following:

- elimination of the on-site thermal desorption treatment component of the remedy;
- landfilling of all dredged and dewatered sediments with concentrations of polychlorinated biphenyls (PCBs) between 50 and 500 parts per million (ppm) at an approved off-site facility;
- treatment of all dredged and dewatered sediments with PCB concentrations exceeding 500 ppm at an approved off-site facility; and,
- consolidation of all dredged and dewatered sediments with PCB concentrations less than 50 ppm in the on-site Industrial Landfill, which will be covered with a multilayered cap in compliance with NYSDEC's 1992 Record of Decision (ROD) for the land-based portion of the cleanup at the Reynolds Facility. In order for the sediments to be disposed of on the Industrial Landfill, NYSDEC would first have to modify its land-based remedy to accommodate the additional volume of sediment from EPA's remedy. In the event that NYSDEC does not allow the placement of those sediments on the Landfill, they would be disposed of at another appropriate off-site facility.

All the other components of the original remedy as selected in the September 1993 Decision Document are NOT affected by this modification. These components are:

- dredging and/or excavation of sediment in the St. Lawrence River adjacent to the Reynolds Facility with PCB concentrations exceeding 1 ppm, polycyclic aromatic hydrocarbon (PAH) concentrations exceeding 10 ppm, and total dibenzofurans (TDBFs) concentrations exceeding 1 part per billion (ppb);
- decanting and dewatering of all dredged sediments, with the collected water being treated on site and discharged to the St. Lawrence River in compliance with the substantive requirements of the State Pollutant Discharge Elimination System (SPDES) program;
- monitoring of the St. Lawrence River water, sediments, and biota prior to, during, and after dredging operations.

EXPLANATION OF FUNDAMENTAL CHANGE

The September 1993 Decision Document called for the on-site treatment of dredged sediments with PCB concentrations exceeding 25 ppm utilizing thermal desorption technology and on-site landfilling of the treatment residuals and untreated sediments with PCB concentrations of 25 ppm or less in an unlined disposal pit at the Reynolds Facility, known as Black Mud Pond.

In 1995, Reynolds requested a modification of the original remedy based on new information regarding the cost for off-site disposal. A change in market conditions since 1993 had significantly reduced the cost of off-site landfilling as compared to on-site treatment. Additionally, the present-worth cost for the original remedy had increased to \$72,400,000, more than double the original cost estimate of \$35,100,000 (1993 dollars). This increase in cost was primarily due to an increase in the estimated volume of contaminated sediment which would be dredged from the St. Lawrence River, based partly on the results of additional sampling since 1993.


In light of these factors, Reynolds proposed to eliminate the on-site treatment component of the original remedy in favor of off-site landfilling at an approved disposal facility. Reynolds also proposed that sediments with PCB concentrations of 50 ppm and greater would be sent for off-site disposal, while sediments with PCB concentrations less than 50 ppm would be contained on site. Reynolds' proposed modification was consistent with NYSDEC's 1995 ROD Amendment for the disposition of contaminated soils and sediments generated by its land-based remedial program.

Therefore, as described in this Decision Document Amendment, all sediments removed from the St. Lawrence River having PCB concentrations greater than 50 ppm will be disposed at an approved off-site landfill or treatment facility, depending on the level of PCB contamination. All dredged sediments with PCB levels between 50 and 500 ppm will be landfilled off-site, while all sediments with PCB levels exceeding 500 ppm will be treated off-site. All dredged sediments with PCB concentrations less than 50 ppm will be consolidated into the Industrial Landfill located at the Reynolds Facility. Following dredging and dewatering of the sediments, verification sampling will be performed to delineate that portion of the dredged materials to be transported off-site for landfilling or treatment and that portion to be landfilled on-site.


The treatment of sediments having PCB levels exceeding 500 ppm is consistent with EPA's current policy regarding the remediation of PCB contamination under the Superfund program and the programs' expectations to utilize treatment to address principal threats at a site.

DECLARATION OF STATUTORY DETERMINATIONS

The original remedy, as revised by the selected modification, meets the requirements for remedial actions set forth in CERCLA §121, 42 U.S.C. §9621 in that it: (1) is protective of human health and the environment; (2) attains a level or standard of control of the hazardous substances, pollutants and contaminants, which at least attains the legally applicable or relevant and appropriate requirements under federal and state laws; (3) is cost-effective; (4) utilizes alternative treatment (or resource recovery) technologies to the maximum extent practicable; and (5) satisfies the statutory preference for remedies that employ treatment to reduce the toxicity, mobility, or volume of the hazardous substances, pollutants or contaminants at a site.



Jeanne M. Fox
Regional Administrator



Date

DECISION DOCUMENT AMENDMENT
REYNOLDS METALS COMPANY STUDY AREA
MASSENA, NEW YORK

U.S. ENVIRONMENTAL PROTECTION AGENCY
REGION II
NEW YORK, NEW YORK

SEPTEMBER 1998

500448

TABLE OF CONTENTS

DECISION SUMMARY

I.	INTRODUCTION	1
II.	REYNOLDS METALS COMPANY STUDY AREA	2
III.	HIGHLIGHTS OF COMMUNITY PARTICIPATION	3
IV.	REASONS FOR ISSUING THE DECISION DOCUMENT AMENDMENT .	4
V.	DESCRIPTION OF ALTERNATIVES	5
VI.	EVALUATION OF ALTERNATIVES	9
VII.	SELECTED REMEDY	15
VIII.	STATUTORY DETERMINATIONS	16
IX.	DOCUMENTATION OF SIGNIFICANT CHANGE	19

APPENDICES

1. INDEX FOR THE ADMINISTRATIVE RECORD
2. RESPONSIVENESS SUMMARY
3. 1993 DECISION DOCUMENT

500449

DECISION SUMMARY

DECISION DOCUMENT AMENDMENT Reynolds Metals Company Study Area Massena, New York

I. INTRODUCTION

The Reynolds Metals Company (Reynolds) Study Area Site (hereinafter the "Site"), consists of the river systems located adjacent to the Reynolds facility (Facility), an active aluminum production plant located on 1,600 acres off Route 37 near the Massena-Cornwall International Bridge in the Town of Massena, New York. The Site includes those portions of the St. Lawrence, Grasse, and Raquette Rivers, their tributaries, and any wetlands which are adjacent to the Reynolds Facility.

Located to the east and downriver of the Facility is the General Motors-Powertrain Division Plant, a federal National Priorities List site being remediated under the direct oversight of the United States Environmental Protection Agency (EPA), and the St. Regis Mohawk tribal lands, known as Akwesasne. An Aluminum Company of America (Alcoa) manufacturing facility is located eight (8) miles west and upriver of the Facility. See Location Map (Figure 1)

Reynolds has operated the plant for aluminum production since 1958. The aluminum is produced in metal pots lined with potliner, a material composed of carbon compounds, including coal tar pitch and coke. As a result of plant operations, various types of industrial waste, including hazardous substances, were generated and disposed of at the Facility. The major areas of contamination are the following: (1) *Black Mud Pond*, an unlined disposal pit used to hold settling carbon solids produced as a by-product of plant operations; (2) the *Industrial Landfill and Former Potliner Storage Area*, an 11.5-acre, unlined disposal area which received solid waste, industrial waste, construction and demolition debris, spent potlining waste, and polychlorinated biphenyl (PCB)-contaminated sewage sludge; (3) *Wetlands*, a tract of wetlands which received leachate, ground water and surface-water runoff from the Industrial Landfill and other areas of the Facility; and (4) the *North Yard*, an area where a heat transfer system (using PCB oils) was operated to maintain the temperature and fluidity of the coal tar pitch used in the aluminum production process. Other areas of contamination included the plant outfalls (open drainage ditches) which discharged wastewater and surface-water runoff from the Facility to the St. Lawrence River. See Site Map (Figure 2).

500450

II. REYNOLDS METALS COMPANY STUDY AREA

A field sampling program performed by Reynolds in 1988 confirmed the presence of PCBs in the St. Lawrence River sediments adjacent to the outfalls at the Reynolds Facility.

On September 28, 1989, the EPA issued a unilateral administrative order (the "Order") under Section 106(a) of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA), as amended, 42 U.S.C. §9606, to Reynolds for the performance of an investigation and remediation of the entire river system surrounding the Facility. The river system was designated the "Reynolds Study Area" (i.e., the Site), and included that portion of the St. Lawrence, Grasse, and Raquette Rivers, their tributaries, and any wetlands located adjacent to the Facility.

In accordance with the Order, Reynolds commenced an Additional River Sampling (ARS) program at the Site in 1991 to characterize further the nature and extent of contamination. The results of that study revealed the presence of several contaminants in the sediments of the St. Lawrence River, including PCBs, polycyclic aromatic hydrocarbons (PAHs), total dibenzofurans (TDBFs), fluoride, and cyanide. In light of those and past findings, the EPA concluded that the sources of the contamination at the Site were the uncontrolled surface-water runoff and wastewater discharges from the outfalls at the Reynolds Facility.

Using the data from Reynolds' ARS, the EPA performed baseline human health and ecological risk assessments to evaluate the potential health and environmental risks associated with the Site. The results of those assessments showed that the greatest risk was associated with the ingestion of PCB-contaminated fish caught in the St. Lawrence River by residents and fishermen. Other health threats were associated with the direct contact or ingestion of contaminated sediments.

Based on the findings of Reynolds' ARS and its subsequent Analysis of Alternatives, the EPA issued a Decision Document in September of 1993 which selected, as a remedy, the following: (1) the dredging and dewatering of all St. Lawrence River sediments with PCB levels exceeding 1 part per million (ppm), PAH levels exceeding 10 ppm, and TDBF levels exceeding 1 part per billion (ppb); (2) the on-site treatment of dredged sediments with PCB concentrations exceeding 25 ppm by thermal desorption technology; and (3) the on-site disposal of the treatment residuals, along with the untreated dredged sediments having PCB levels of 25 ppm or less, in Black Mud Pond.

At the time the Decision Document was issued, the EPA estimated the total volume of contaminated sediment requiring

dredging to be approximately 51,500 cubic yards (yds³). Of that volume, it was estimated that 37,000 yds³ of sediment contained PCB levels between 1 and 25 ppm and 14,500 yds³ of sediment contained PCB levels exceeding 25 ppm.

The Decision Document also called for the water which would be recovered from the decanting and dewatering of dredged sediments to be treated on site and discharged to the St. Lawrence River via a permitted outfall. Prior to dredging, additional sampling would be performed to delineate better the volume and areal extent of the river sediments requiring dredging.

Following the consolidation of the treatment residuals and dredged sediments into Black Mud Pond, it would be covered with a multilayered cap as part of the land-based cleanup.

The EPA's selected remedy did not address the contamination present on the land-based portion of the Facility. The land-based cleanup was performed by Reynolds under the direct oversight of the New York State Department of Environmental Conservation (NYSDEC).

It is noted that the component of the EPA's remedy for the disposition of contaminated sediments was, at that time, consistent with the ongoing land-based cleanup, which was selected by the NYSDEC in a 1992 record of decision (ROD). The land-based cleanup includes the on-site treatment of contaminated soil and sediment with PCB levels of 25 ppm or greater and the consolidation of the treatment residuals and materials with less than 25 ppm of PCBs in the Industrial Landfill at the Reynolds Facility.

III. HIGHLIGHTS OF COMMUNITY PARTICIPATION

The Post-Decision Proposed Plan (PDPP) for the Site was released to the public on July 30, 1998. The PDPP, along with other Site-related documents, are available to the public at both the administrative record and the information repository locations. A summary of the PDPP and a notice as to the availability of those documents and the administrative record was published in the *Courier-Observer* daily newspaper on July 30, 1998, and in the *Indian Times* and the *People's Voice* weekly newspapers on July 31, 1998. A copy of the public notice is included as an attachment to this Decision Document Amendment.

The public comment period began on July 30, 1998, and ended on August 28, 1998. A public meeting was held on August 12, 1998 at the Massena Public Library located at 41 Glenn Street, Massena, New York. An availability session was held on August 13, 1998 at the St. Regis Housing Authority Auditorium located in Hogansburg, New York. The purpose of the public meeting and availability session

was to discuss the proposed changes to the September 1993 Decision Document.

The responses to the comments received during the public comment period as well as those expressed orally at the public meeting, are stated in the Responsiveness Summary, which is an attachment to this decision document.

This Decision Document Amendment, presents the selected modification to the original remedial action for the disposition of the contaminated sediments found in the St. Lawrence River adjacent to the Reynolds Facility. The modification to the original remedial action is chosen in accordance with CERCLA and, to the extent practicable, the National Oil and Hazardous Substances Pollution Contingency Plan (NCP), 40 Code of Federal Regulation (CFR) Part 300. The decision as made for the Site, is based upon the administrative record. An index for the administrative record is included as an attachment to this document. This Decision Document Amendment will become a part of the administrative record file.

The administrative record file, containing the information upon which the modification to the original remedy is based, is available at the following locations:

U.S. Environmental Protection Agency
290 Broadway, 18th Floor
New York, New York 10007-1866
212-637-3000
Monday - Friday: 9:00 a.m. to 4:30 p.m.

Massena Public Library
41 Glenn Street
Massena, New York 13662
315-769-9914
Monday & Friday: 9:30 a.m. to 5:00 p.m.
Tuesday - Thursday: 9:30 a.m. to 9:00 p.m.

St. Regis Mohawk Tribe - Environmental Division
Health Services Building
Hogansburg, New York 13655
By Appointment: 518-358-3141

IV. REASONS FOR ISSUING THE DECISION DOCUMENT AMENDMENT

After the September 1993 Decision Document was issued by the EPA, Reynolds commenced the remedial design phase of the project.

In late 1995, Reynolds proposed modifying the remedy based on new information related to options for off-site sediment disposal. A change in market conditions since 1993 had significantly reduced the cost of off-site landfilling. Additionally, based on revised estimates of the volume of sediments to be dredged from the St. Lawrence River, which were made during the preliminary design, the cost of the existing remedy had increased significantly. In light of these factors, Reynolds proposed to eliminate the on-site treatment component of the remedy in favor of off-site landfilling.

Reynolds also proposed that sediments with PCB levels of 50 ppm and higher be sent off site for disposal, while sediments with less than 50 ppm be contained on site. This proposal, which represents an increase in the maximum PCB level to be landfilled on-site from 25 ppm to less than 50 ppm, is consistent with NYSDEC's land-based remedy, which had been modified in a June 1995 amendment to its 1992 ROD.

In 1996, Reynolds performed additional sampling in the St. Lawrence River to delineate better the areal extent and volume of the sediments to be dredged. The results of the additional sampling showed the volume of sediment requiring dredging to be significantly greater than originally estimated in 1993 (see Table 1). In 1993, the total volume of sediment was estimated to be approximately 51,500 yds³. The current sediment volume estimate is approximately 77,600 yds³. Of the 77,600 yds³, it is estimated that 39,700 yds³ contain PCBs at levels (greater than 25 ppm) which would have had to be treated under the original remedy. This volume is almost three times higher than the original estimate of 14,500 yds³.

Based on the additional costs associated with remediating a significantly larger volume of sediment, the estimated present-worth cost of the original remedy increased to \$72.4 million, more than double the original cost which, in 1993 dollars, was estimated to be \$35.1 million.

Because of the significant increase in volume, resulting in a significant increase in cost, the EPA decided to evaluate other less costly options which would maintain a comparable level of protection. The EPA decided to amend the September 1993 Decision Document to eliminate the on-site treatment component of the remedy in favor of off-site disposal and treatment alternatives.

V. DESCRIPTION OF ALTERNATIVES

The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) requires that each selected remedy be protective of human health and the environment, be cost-effective,

comply with other laws, and utilize permanent solutions and alternative treatment technologies and resource recovery alternatives to the maximum extent practicable. In addition, CERCLA includes a preference for treatment as a principle element for the reduction of toxicity, mobility, or volume of the hazardous substances.

The present-worth costs presented below for each alternative include capital costs and operation and maintenance (O&M) costs. The O&M costs are for post-remediation monitoring of the St. Lawrence River water, sediment and biota over a five-year period. The O&M costs associated with the Black Mud Pond or Industrial Landfill are considered to be part of the long-term management required under NYSDEC's land-based program and, therefore, are not included in the costs of the two alternatives.

ALTERNATIVE I. - EXISTING REMEDY AS SELECTED IN THE SEPTEMBER 1993 DECISION DOCUMENT

Dredging St. Lawrence River Sediments/ On-Site Treatment of Sediments with PCB Levels Exceeding 25 PPM/ On-Site Landfilling (in Black Mud Pond) of Treatment Residuals and Untreated Sediments with PCB Levels of 25 PPM or Less/ Monitoring of St. Lawrence River During and After Dredging

This alternative is defined as the selected remedy in the September 1993 Decision Document. It involves the dredging and/or excavation of approximately 77,600 yds³ (current volumetric estimate) of sediment with PCB concentrations exceeding 1 ppm, PAHs concentrations exceeding 10 ppm, and TDBF concentrations exceeding 1 ppb, from the St. Lawrence River adjacent to the Reynolds Facility. The dredged sediments would be decanted and dewatered, and the collected water would be treated on-site and discharged to the St. Lawrence River in compliance with the substantive State Pollutant Discharge Elimination System (SPDES) requirements.

After dewatering, those sediments having PCB levels which exceed 25 ppm, the volume of which is estimated to be approximately 39,700 yds³, would be treated in a thermal desorption unit to be constructed on-site. Thermal desorption is a process whereby contaminants are removed from the sediments through volatilization followed by condensation. The condensed PCB extract would subsequently be sent off-site for destruction by incineration.

The treated sediment residuals and approximately 38,700 yds³ of untreated sediment with PCB concentrations of 25 ppm or less would be consolidated in Black Mud Pond. Following the placement of the sediments into Black Mud Pond, it would have been capped

with a multilayered Resource Conservation and Recovery Act (RCRA) cap as part of the NYSDEC's land-based remedial program. Monitoring of the St. Lawrence River sediments, water, and biota prior to, during, and after dredging operations would be performed.

Capital Cost: \$34,700,000
(in 1993 dollars and based on original sediment volume estimates)

Capital Cost: \$72,000,000
(in 1997 dollars and based on revised sediment volume estimates)

O&M Cost: \$400,000
(post-remediation monitoring of St. Lawrence River over five-year period)

Present-Worth Cost: \$35,100,000
(in 1993 dollars and based on original sediment volume estimates)

Present-Worth Cost: \$72,400,000
(in 1997 dollars and based on revised sediment volume estimates)

Time to Implement: 4 years

ALTERNATIVE II. - MODIFIED REMEDY AS SELECTED IN THIS DECISION DOCUMENT AMENDMENT

Dredging St. Lawrence River Sediments/ Off-Site Landfilling of Sediments with PCB Levels Between 50 and 500 PPM/ Off-Site Treatment of Sediments with PCB Levels Exceeding 500 PPM/ On-Site Landfilling (in Industrial Landfill) of Sediments with PCB Levels Less Than 50 PPM/ Monitoring of St. Lawrence River During and After Dredging

This alternative is defined as the selected remedy in the Decision Document Amendment. It does not modify the remediation goals originally established by the EPA in the 1993 Decision Document for the St. Lawrence River sediments. As specified in that Decision Document, this alternative includes the dredging and/or excavation of St. Lawrence River sediments with PCB concentrations exceeding 1 ppm, PAH concentrations exceeding 10 ppm, and TDBF concentrations exceeding 1 ppb. The dredged sediments will be decanted and dewatered, with the collected water treated on-site and discharged to the St. Lawrence River in compliance with the substantive SPDES requirements.

This alternative eliminates the on-site thermal desorption treatment of sediments in favor of off-site disposal and treatment. Sediments with PCB concentrations between 50 and 500 ppm will be landfilled at an approved off-site facility. Sediments with PCB concentrations exceeding 500 ppm will be treated at an approved off-site facility. Sediments with PCB concentrations less than 50 ppm will be consolidated in the Industrial Landfill located at the Reynolds Facility, contingent upon NYSDEC's modification of its own Record of Decision (ROD) for the land-based cleanup. In the event that NYSDEC does not allow placement of the river sediments on the Landfill, those contaminated sediments would be disposed of at another appropriate off-site facility.

Following placement of the sediments into the Industrial Landfill, it will be capped and monitored in accordance with the NYSDEC's ROD for the land-based cleanup. The capping and monitoring requirements established by the NYSDEC for the Industrial Landfill will meet the relevant and appropriate requirements of a RCRA hazardous waste landfill. The cap to be placed atop the Landfill will be a multilayered RCRA cap. A leachate collection system is in place and long-term management controls, including ground-water monitoring, will be performed as part of the NYSDEC's land-based program. All monitoring data will be reviewed by the NYSDEC and the EPA to ensure that the integrity of the Landfill cap and leachate collection system are maintained over time.

Since Black Mud Pond was capped in 1996 as part of the NYSDEC's land-based program, it is not available for sediment disposal.

This alternative changes the maximum PCB level to be landfilled on-site from 25 ppm to less than 50 ppm. The 50 ppm PCB level established for off-site disposal is consistent with federal and New York State (NYS) laws for regulating PCBs. Under the Toxic Substances Control Act (TSCA), the federal law that regulates the treatment, storage, and disposal of PCBs, dredged materials with PCB levels of 50 ppm or greater must be disposed at a TSCA-approved chemical waste landfill, incinerated, or disposed of by another method approved by the EPA. Under the NYS hazardous waste program, the 50 ppm level is that which identifies PCBs as hazardous waste.

The 50 ppm PCB level is also consistent with the NYSDEC's 1995 ROD Amendment for the land-based portion of the cleanup. Under the NYSDEC's program, Reynolds has consolidated approximately 135,300 yds³ of soil with PCB levels less than 50 ppm into the Industrial Landfill. Under this alternative, it is estimated that an additional 43,400 yds³ of St. Lawrence River sediment will be consolidated therein.

This alternative, by treating sediments with PCB levels exceeding 500 ppm, is consistent with the EPA's "Guidance on Remedial Actions for Superfund Sites with PCB Contamination" (hereinafter, the "PCB Guidance") with respect to remediation of PCB "principal threats" at Superfund sites. Under the PCB Guidance, EPA favors the treatment of materials having PCB concentrations exceeding 500 ppm in an industrial setting.

The cost associated with the transportation and treatment of approximately 4,500 yds³ (7,200 tons) of sediment with PCB levels exceeding 500 ppm is estimated to be \$7,200,000 (\$1,000/ton). However, those costs will be significantly offset by the cost savings associated with off-site landfilling.

Capital Cost: \$62,800,000
(in 1997 dollars)

O&M Cost: \$400,000
(post-remediation monitoring of St.
Lawrence River over 5-year period)

Present-Worth Cost: \$63,200,000
(in 1997 dollars)

Time to Implement: 1-2 years

VI. EVALUATION OF ALTERNATIVES

In accordance with the NCP, this section presents a detailed analysis of the original remedy and the alternative remedy considered in the preceding section. The detailed analysis consists of an assessment of the two alternatives against each of the NCP's nine evaluation criteria and a comparative analysis focusing upon the relative performance of each alternative against those criteria.

The following "threshold" criteria must be satisfied by an alternative in order to be eligible for selection:

1. Overall protection of human health and the environment addresses whether or not a remedy provides adequate protection and describes how risks posed through each exposure pathway (based on a reasonable maximum exposure scenario) are eliminated, reduced, or controlled through treatment, engineering controls, or institutional controls; and,
2. Compliance with applicable or relevant and appropriate requirements (ARARs) addresses whether or not a remedy would meet all of the applicable or relevant and appropriate federal

and state environmental statutes and requirements (*i.e.*, those federal or state laws that specifically address a hazardous substance, pollutant or contaminant, remedial action or other circumstance found at a CERCLA site, or which address problems or situations sufficiently similar to those encountered at a site that their use is well suited to the site) or provide grounds for invoking a waiver.

The following "primary balancing" criteria are used to make comparisons and to identify the major trade-offs between alternatives:

3. *Long-term effectiveness and permanence* refers to the ability of a remedy to maintain reliable protection of human health and the environment over time, once cleanup goals have been met;
4. *Reduction of toxicity, mobility, or volume through treatment* refers to the degree to which remedial alternatives employ recycling or treatment that reduces the toxicity, mobility, or volume of hazardous substances at a site;
5. *Short-term effectiveness* addresses the period needed to achieve protection and any adverse impacts on human health and the environment that may be posed during the construction and implementation periods until cleanup goals are achieved;
6. *Implementability* refers to the technical and administrative feasibility of a remedy, including the availability of the materials and services needed; and,
7. *Cost* includes estimated capital and operation and maintenance costs, and the present-worth cost.

The following "modifying" criteria are considered fully after the formal public comment period on the Post-Decision Proposed Plan is completed:

8. *State acceptance* indicates whether, based on its review of the remedial investigation/feasibility study (RI/FS), and the proposed plan, the State supports, opposes, and/or has identified any reservations with the preferred alternative; and,
9. *Tribal/Community acceptance* refers to the public's general response to the alternatives described in the proposed plan and the RI/FS reports; factors of community acceptance to be discussed include support, reservation, and opposition by the tribe/community.

A comparative analysis of the alternatives based upon these evaluation criteria follows. The comparative analysis focuses upon the essential differences in the two alternatives: (1) on-site treatment versus off-site disposal/treatment of the more contaminated sediments; and (2) the increase in the maximum level of PCBs permitted to be placed in the Industrial Landfill from 25 ppm to less than 50 ppm.

1. Overall Protection of Human Health and the Environment

Both remedies (existing and modified) are considered to be protective of human health and the environment. Both remedies require the removal of contaminated sediments from the St. Lawrence River via dredging and/or excavation to cleanup levels established in the 1993 Decision Document. The existing remedy combines on-site treatment of the higher levels of contamination with on-site landfilling and capping of treatment residuals and lower levels of contamination. The modified remedy will combine off-site disposal with on-site landfilling and capping. The off-site disposal will consist of landfilling sediments having PCB concentrations between 50 and 500 ppm and treating sediments with PCB concentrations exceeding 500 ppm. The removal of contaminated sediments from the St. Lawrence River, along with the alternatives for landfilling and/or treatment of the dredged sediments, will minimize exposure to the PCBs and other contaminants and their availability to aquatic life.

The consolidation of sediments with PCB levels less than 50 ppm into the on-site Industrial Landfill, followed by the capping of the Landfill, will effectively isolate the sediments from the environment. Operation and maintenance of the leachate collection system and monitoring programs, including ground-water monitoring will be performed as part of the NYSDEC's land-based remedial program to ensure that the engineering controls continue to be effective in containing the contaminants in the landfill over time.

2. Compliance with Applicable, or Relevant and Appropriate Requirements (ARARs)

ARARs are those federal or state environmental and public health regulations that address a hazardous substance, pollutant, contaminant, remedial action, location, or other circumstance at a site. There are three classifications of ARARs: *chemical-specific*, which are health- or risk-based concentration limits of chemicals which may be found in, or discharged to, the ambient environment; *location-specific*, which are restrictions placed on the concentration of hazardous substances or the conduct of activities solely because of the specific locations in which they occur; and *action-specific*, which are usually technology- or activity-based

requirements or limitations on actions taken with respect to hazardous substances, pollutants, or contaminants.

The principal action-specific ARARs for the Site include the requirements of TSCA. Under TSCA, dredged materials that contain PCBs at concentrations greater than or equal to 50 ppm must be either incinerated, landfilled in a TSCA-approved chemical waste landfill, or disposed of by another method approved by the EPA. Both remedies would comply with all applicable TSCA requirements (40 CFR Parts 761.60 - 761.9). Landfilling or treatment of sediments with PCB concentrations of 50 ppm or greater would be performed in an off-site TSCA-approved landfill or treatment facility. All necessary approvals would be obtained prior to disposal to ensure sediments meet the facility's permit restrictions.

Both remedies would comply with all applicable or relevant and appropriate RCRA requirements and/or the corresponding NYS hazardous waste requirements for the identification, transportation, storage, treatment and disposal of hazardous waste (40 CFR Parts 261 through 264 and 268). Since materials with concentrations of PCBs that are greater than or equal to 50 ppm are regulated as hazardous wastes by NYS, its requirements for hazardous wastes are applicable and, therefore, would be met by the off-site disposal facility, if located in NYS.

The Clean Water Act (CWA) requirements for discharging directly to a surface-water body are also action-specific ARARs. Water collected from the dewatering of dredged river sediments or on-site thermal desorption would be treated and discharged into the St. Lawrence River via an outfall at the Reynolds Facility, which is permitted under the State Pollutant Discharge Elimination System (SPDES) program. Such discharge would meet all NYS requirements under the SPDES program (6 NYCRR Parts 750 through 757). Additionally, because NYS water quality criteria or standards are relevant and appropriate requirements, the treated water would meet such criteria or standards for the protection of human health through fish consumption and the protection of wildlife (6 NYCRR Parts 700 through 706). Other action-specific ARARs under the CWA would include the water monitoring and management requirements of 40 CFR Parts 122 through 136.

Since dredging operations will be performed in navigable waters of the United States, the dredging operations would comply with Section 10 of the Rivers and Harbors Act and U.S. Army Corps of Engineers regulations (33 USC Part 403 and 33 CFR Parts 320 through 330).

For air emissions associated with the operation of the on-site thermal desorption unit or other storage and handling activities,

the action-specific ARARs and guidance which would be met include 40 CFR Part 50; 6 NYCRR Parts 200, 201, 211, 212, 219 and 257; and NYS Air Guide 1.

Location-specific ARARs would include Executive Orders 11988 and 11990 for floodplain management and the protection of wetlands (40 CFR Part 6.302 and 40 CFR Part 6, Appendix A) for actions that may occur within a floodplain or wetland and the Fish and Wildlife Coordination Act (16 USC Part 661 et seq; 40 CFR Part 6.302) for actions affecting a river. Other location-specific ARARs may include the National Historic Preservation Act requirements for recovering and preserving artifacts and preserving historic properties (36 CFR Parts 65 and 800), the Wild and Scenic Rivers Act for protection of recreational rivers (40 CFR Part 6.302(e)) and the NYS Coastal Zone Management Program (1NYCRR Part 600).

NYSDEC's 1994 Technical Guidance for Screening Contaminated Sediments is a "To Be Considered" criterion.

3. Long-Term Effectiveness and Permanence

In general, landfilling remedies provide a lesser degree of permanence in remediating contamination at a site when compared with treatment alternatives that destroy contaminants. The original remedy would utilize thermal desorption, combined with off-site incineration of the contaminant extract, to permanently destroy the higher levels of contamination (*i.e.*, PCB levels exceeding 25 ppm). The modified remedy would utilize off-site incineration to destroy PCBs at concentrations exceeding 500 ppm.

Landfilling provides for long-term effectiveness by the management of contaminants in a secure, monitored location where adequate and reliable engineering controls are provided. For the original remedy, PCBs at levels of 25 ppm or less would have been landfilled in Black Mud Pond. For the modified remedy, a combination of off-site landfilling for PCB levels between 50 and 500 ppm and on-site landfilling for PCB levels between 1 and 50 ppm would reliably contain those contaminants over time. The long-term effectiveness of the Industrial Landfill as a containment system would be monitored by NYS to ensure the protection of ground water, surface water and the nearby wetlands at the Site and prevent future exposure by direct contact.

4. Reduction in Toxicity, Mobility, or Volume through Treatment

Both alternatives to some degree would reduce the toxicity, mobility, or volume of contaminants through treatment. The original remedy would utilize on-site thermal desorption, combined with off-site incineration of the contaminant extract, to reduce the toxicity and volume of the higher levels of contamination by

removal and ultimate destruction. The modified remedy would reduce the toxicity and volume of the high-level contamination (PCB levels exceeding 500 ppm) through off-site incineration.

Landfilling does not appreciably alter the toxicity or volume of the contaminants, but reduces their mobility through encapsulation.

5. Short-Term Effectiveness

For either remedy, there would be short-term impacts which have to be addressed when performing dredging and dewatering activities and the on-site landfilling of the lower levels of contamination. However, the potential short-term impacts of the modified remedy would be significantly lower than for the original remedy. The time necessary to implement the modified remedy (1-2 years) is anticipated to be considerably shorter than the time needed to procure, mobilize, and operate the thermal desorption unit (4 years) required by the original remedy. Although appropriate controls and safety measures would be applied to minimize potential exposure to site workers, fewer workers would be required to handle the sediments for off-site disposal as compared to on-site treatment, thereby reducing the overall exposure to field personnel. The potential for airborne particulates related to storage and handling of contaminated sediments would also be reduced as stockpiling, screening and thermal desorption unit feeding activities associated with the on-site treatment would be eliminated. Potential air impacts from the operation of the thermal desorption unit are also eliminated.

It is noted that, depending on the volume of sediment dredged and the number of vehicles available for each day of operation, temporary stockpiling of the sediments on-site may be necessary. In the event such stockpiling is required, the sediments would be managed in a manner to protect site workers and minimize the potential for contaminant migration.

There would be short-term risks associated with transporting PCB-contaminated sediments to an off-site landfill or treatment facility. However, these risks are estimated to be small due to the short duration of the off-site disposal activities.

All short-term risks to site workers would be addressed by compliance with a health and safety plan. An air monitoring plan would also be implemented for protection of workers and the community.

500463

6. Implementability

Both remedies may encounter some technical difficulties with regard to dredging the St. Lawrence River sediments to the established cleanup goals. To address such difficulties, the initial dredging operation will be performed in a manner which will identify site-specific conditions and operating parameters, such as dredging depths, effectiveness of using silt curtains and sheet pilings, and sediment suspension and settling characteristics. This information will be evaluated to improve the effectiveness of the dredging project. It is noted that Site surveys performed by Reynolds as part of the initial design work have shown areas of the riverbed to have irregular topographies, thick vegetation, and large cobbles and boulders. Those conditions may impact dredging operations and, ultimately, make it more difficult to achieve the cleanup goals.

The landfilling and treatment component of the two remedies are implementable from an engineering and technical standpoint. However, off-site disposal would be considerably easier to implement because the activities associated with the procurement, mobilization, and operation of the on-site treatment unit are avoided. Also, off-site landfill capacity is readily available. The dewatered sediments to be landfilled would be transported off-site by trucks. Depending on the volume of sediment dredged and the number of vehicles available for each day of operation, temporary stockpiling of the sediments on-site may be necessary.

7. Costs

The present-worth cost for the original remedy, in 1997 dollars and based on the revised estimates of sediment volumes to be dredged, is \$72.4 million.

The present-worth cost for the modified remedy, also in 1997 dollars and based on the revised estimates of sediment volumes, is \$63.2 million. This represents a cost savings of \$9.2 million.

The cost savings are attributable to the decrease in costs for off-site landfilling. Excess landfilling capacity, as well as the overall market conditions in the waste management industry, have helped reduce landfilling costs since 1993. The costs for thermal desorption, on the other hand, have not changed appreciably because they are more a function of technology, rather than treatment capacity.

8. State Acceptance

The State of New York concurred with EPA's Post-Decision Proposed Plan in August 1998. However, at the date that this

Decision Document Amendment is issued, it has not made a determination whether to concur on the selection of the modified remedy.

9. Tribal/Community Acceptance

The reaction to the modified remedy from the St. Regis Mohawk Tribe (Tribe) and the community, as received during the public comment period as well as at the public meeting and availability session, are contained in the Responsiveness Summary which is included as part of this decision document.

In general, the public appears to be receptive to the EPA's decision to modify the selected remedy. However, the Tribe, while generally supporting the EPA's preference for treatment and disposal of the more contaminated river sediments off-site, rather than on-site as originally decided, has a preference for the permanent treatment of hazardous substances present at the Reynolds Facility. The Tribe does not support a containment remedy as a permanent solution, but only as a temporary solution until a permanent treatment remedy is in place. Therefore, the Tribe has requested that new remedial treatment technologies be investigated on an annual basis until such time as a remedy is utilized to permanently destroy the contamination in the Industrial Landfill.

Additionally, industry has objected to the EPA's preference for the treatment of PCBs at concentrations exceeding 500 ppm. Although it is consistent with the current Superfund policy for the remediation of PCBs as a principal threat, it is not a requirement under current TSCA regulations.

VII. SELECTED REMEDY

Based on considerations of the requirements of CERCLA, the detailed analysis of the alternatives, and the comments received during the public comment period, the EPA has determined that Alternative II is the most appropriate remedy for the Site.

As described above, Alternative II, which is the remedy selected in this Decision Document Amendment, is consistent with the remediation goal set forth in the 1993 Decision Document for the Site, which is to remove sediments from the St. Lawrence River with PCB levels exceeding 1 ppm, PAH levels exceeding 10 ppm, and TDBF levels exceeding 1 ppb.

However, the on-site treatment component of the original remedy is eliminated. Rather, all dredged and dewatered sediments with PCB concentrations exceeding 500 ppm will be transported off-site for treatment at a TSCA-approved facility; all dredged and

dewatered sediments with PCB concentrations between 50 and 500 ppm will be transported off-site to a TSCA-approved landfill; and all dredged and dewatered sediments with PCB concentrations less than 50 ppm will be disposed of on the existing Industrial Landfill located at the Reynolds Facility. Following placement of the sediments on the Industrial Landfill, it will be capped in accordance with the NYSDEC's 1992 ROD (as amended in June 1995) for the land-based remedy.

It is noted that, in order for the river sediments to be disposed on the Landfill, NYSDEC would first have to modify its land-based remedy to accommodate the additional volume of sediment from EPA's remedy. In the event that NYSDEC does not allow the placement of those sediments on the Industrial Landfill, they would be disposed of at another appropriate off-site disposal facility.

Following the dredging and dewatering of the sediments, verification sampling will be performed to delineate which portion of the dredged materials will be sent off-site for landfilling or treatment and which portion will be landfilled on-site.

As discussed in this Decision Document Amendment, the technological limitations of dredging may preclude the attainment of the cleanup goals established for the St. Lawrence River sediments. If, after the implementation of the dredging project, the EPA determines that the cleanup goals cannot be achieved by existing dredging technologies, the EPA will make a determination at that time whether other remedial action(s) (e.g., capping the remaining contaminated sediments in place) will be performed. In the event the EPA makes such a determination, it will issue an explanation of significant difference to the selected remedy or propose an amendment to the Decision Document.

All other components of the original remedy will remain the same.

VIII. STATUTORY DETERMINATIONS

Under CERCLA and the NCP, the EPA's responsibility at Superfund sites is to undertake remedial actions that achieve adequate protection of human health and the environment. In addition, Section 121 of CERCLA establishes several other statutory requirements and preferences that the selected remedy must meet. Section 121 of CERCLA specifies that when complete, the selected remedial action for the Site must comply with ARARs established under federal and state environmental laws unless a statutory waiver is justified. The selected remedy, also, must be cost-effective and utilize permanent solutions and alternative treatment technologies or resource recovery technologies to the maximum

extent practicable. Finally, the statute includes a preference for remedies that employ treatment that permanently and significantly reduce the volume, toxicity, or mobility of hazardous wastes as their principle element. The following sections discuss how the selected remedy meets these statutory requirements.

1. Protection of Human Health and the Environment

The modified remedy maintains a comparable level of protection of human health and the environment as the original remedy set forth in the 1993 Decision Document. Dredging and/or excavation will be performed to remove sediments from the St. Lawrence River with PCB concentrations exceeding 1 ppm, PAH concentrations exceeding 10 ppm, and TDBF concentrations exceeding 1 ppb. The removal of the contaminants to the established cleanup goals will mitigate the health threats posed at the Site, primarily the ingestion of PCB-contaminated fish caught by local residents and fishermen, by minimizing exposure to the PCBs and other contaminants and their availability to aquatic life.

The modified remedy will result in the permanent destruction of high-level contamination through the treatment of dredged sediments with PCB concentrations exceeding 500 ppm at a TSCA-approved facility. The off-site landfilling of sediments with PCB concentrations between 50 and 500 ppm at an approved off-site facility where adequate engineering controls are provided will permanently remove those contaminants from the Site and encapsulate them in a secure and monitored containment system.

The dredged sediments with PCB levels less than 50 ppm will be contained in the Industrial Landfill located at the Reynolds Facility, with long-term management controls that include a landfill cap, leachate collection system, and monitoring programs, including ground-water monitoring. The capping and monitoring requirements have been established by the NYSDEC in its 1992 ROD (as amended in June 1995) and meet the relevant and appropriate requirements of a RCRA hazardous waste landfill. The cover to be placed atop the landfill will be a multilayered RCRA cap. The cap, leachate collection system, and long-term management controls will be operated and maintained as part of the NYSDEC's land-based remedial program for as long as the contaminants remain on-site. These on-site engineering controls and systems will provide adequate and reliable protection to human health and the environment over time.

2. Compliance with Applicable, or Relevant and Appropriate Requirements (ARARs)

The original analysis with respect to ARARs, as contained in the 1993 Decision Document, held that the original remedy did comply with all federal and state ARARs.

Since the modified remedy will not change the sediment dredging and dewatering components of the original remedy, there should be no substantive variation from the original analysis for compliance with ARARs as related to those actions.

The key elements which are changed in the modified remedy will also comply with federal and state ARARs. The 50-ppm level established for the off-site disposal of PCBs is consistent with federal and NYS laws for regulating PCBs. In compliance with TSCA regulations (40 CFR Parts 761.60 through 761.9), the dredged river sediments having PCB levels of 50 ppm and greater will be transported off-site and disposed of in a TSCA-approved chemical waste landfill or treatment facility, depending on the level of contamination. All necessary approvals will be obtained prior to disposal to ensure the dredged sediments meet the facilities' permit restrictions.

The modified remedy will comply with applicable or relevant and appropriate RCRA requirements and/or the corresponding NYS hazardous waste requirements for the identification, transportation, storage, treatment and disposal of hazardous waste (40 CFR Parts 261 through 264 and 268). In the event the selected off-site disposal facility is located in NYS, the NYS requirements for hazardous wastes are applicable and, therefore, will be met by the disposal facility.

The modified remedy is also consistent with the EPA's PCB Guidance. In accordance with the PCB Guidance for an industrial setting, the sediments with PCB levels less than 50 ppm will be contained on-site using long-term management controls, including a multilayered cap, leachate collection system, and ground-water monitoring. Also in accordance with the PCB Guidance, material contaminated with PCBs above 500 ppm will be treated.

3. Cost-Effectiveness

Cost-effectiveness is a critical component used in the balancing of the evaluation criteria. With the increase in the estimated volume of sediment to be dredged from the St. Lawrence River, the present-worth cost of the original remedy increased from \$35,100,000 (in 1993 dollars) to an estimated \$72,400,000 (in 1997 dollars). The cost savings associated with off-site disposal, rather than on-site treatment, was therefore a factor which

eventually led to the selection of the modifications as opposed to the original remedy.

The present-worth cost for the selected modifications, also in 1997 dollars and based on the revised sediment volume estimates, is \$63,200,000.

4. Utilization of Permanent Solutions and Alternative Treatment Technologies (or Resource Recovery Technologies) to the Maximum Extent Practicable

This statutory determination is satisfied by the original remedy and the selected modification.

The EPA believes that, when the Decision Document was issued in 1993, the original remedy, represented the maximum extent to which permanent solutions and treatment technologies could have been utilized in a cost-effective manner at the Site. We also believe that the modified remedy utilizes permanent solutions and alternative treatment technologies to the maximum extent practicable after consideration of the most recent volumetric and cost estimates.

5. Preference for Treatment as a Principal Element

This statutory determination is satisfied by the original remedy and the selected modification.

In the case of the original remedy, the preference for treatment is satisfied with higher levels of contamination (PCBs exceeding 25 ppm) being treated on-site through thermal desorption. For the modified remedy, the preference for treatment is still satisfied since the highest concentrations of contaminants, meaning PCB levels exceeding 500 ppm, will be treated at an off-site facility. The treatment of PCBs at levels exceeding 500 ppm is consistent with the EPA's PCB Guidance for treating principal threats at the Site.

IX. DOCUMENTATION OF SIGNIFICANT CHANGE

There are no significant changes from the preferred alternative, as presented in the Post-Decision Proposed Plan released to the public on July 30, 1998.

Site Location Map




FIGURE 1

Site Map




FIGURE 2

500471

TABLE 1

COMPARISON OF THE 1993 AND CURRENT ESTIMATES OF SEDIMENT VOLUMES
TO BE DREDGED FROM THE ST. LAWRENCE RIVER

<u>PCB Concentration Range (ppm)</u>	<u>1993 Volume Estimate (yds³)</u>	<u>Current Volume Estimate (yds³)</u>	
Between 1 and 25	37,000	38,700	
Greater than 25	14,500	38,900*	<u>38,900</u>
			4,700 (25 - <50 ppm)
			29,700 (50 - 500 ppm)
			4,500 (> 500 ppm)
Total	51,500	77,600	

* It is noted that the 38,900 yds³ is depicted in three separate volumes for PCB levels in the range of between 25 and 50 ppm, 50 to 500 ppm, and greater than 500 ppm.

500472

APPENDIX 1

INDEX FOR THE ADMINISTRATIVE RECORD

500473

REYNOLDS METALS COMPANY SITE
ADMINISTRATIVE RECORD SITE FILE UPDATE
INDEX OF DOCUMENTS

5.0 RECORD OF DECISION

5.1 Record of Decision

P. 500001- Record of Decision, Reynolds Metals Comany Site
500154 Study Area, Massena, St. Lawrence County, New
York, September 27, 1993.

REYNOLDS METALS COMPANY SITE
ADMINISTRATIVE RECORD FILE AMENDMENT
INDEX OF DOCUMENTS

5.0 RECORD OF DECISION

5.1 Record of Decision

- P. 500155- Record of Decision, Reynolds Metals Company, St.
500291 Lawrence Reduction Plant, Massena, N.Y., prepared
by the New York State Department of Environmental
Conservation(NYSDEC), Division of Hazardous Waste
Remediation, Region 6, Watertown, N.Y., January
1992.

5.2 Amendments to the Record of Decision

- P. 500292- Letter to Ms. Lisa Jackson, U.S. EPA, Region II,
500306 from Mr. Philip G. Waite, P.E., Project Manager,
Division of Hazardous Waste Remediation, Region 6,
NYSDEC, re: Reynolds Metals Company Site No. 6-45-
009, ROD Amendment, July 18, 1995. (Attachments:
(1) Amendment to the Record of Decision, Reynolds
Metals Company, St. Lawrence County, N.Y., June
1995; (2) Reynolds Metals Company Site,
Responsiveness Summary, Comments Generated on
Proposed Amendment to the Record of Decision, June
15, 1995.)
- P. 500307- Letter of transmittal to Ms. Anne Kelly, U.S. EPA,
500371 Region II, from Ms. Vicky L. Murphy, Reynolds
Metals Company, re: Attached River Sample Field
Logs, August 29, 1996.
- P. 500372- Report: Monthly Progress Report, Reynolds Metals
500386 Company, St. Lawrence Reduction Plant, River
Remediation Project, Massena, N.Y., September
1996.

- P. 500387- Letter to Mr. Rick Esterline, Remediation Project
500389 Director, Reynolds Metals Company, from Mr. Robert F. Vaughn, Chief, Special Projects Branch, U.S. EPA, Region II, re: Comments on the Reynolds Metals Company Sampling and Analysis Procedures, September 5, 1996.
- P. 500390- Letter to Ms. Anne Kelly, Project Coordinator,
500397 U.S. EPA, Region II, from Mr. A. Yazdi, Program Manager, Private Environmental Projects, Bechtel Environmental, Inc., re: Submittal of Monthly Progress Report, August 1996, Reynolds Metals Company River Remediation Project - Massena, N.Y., September 5, 1996.
- P. 500398- Facsimile re: letter to Mr. R.C. Esterline,
500398 Remediation Project Director, Reynolds Metals Company, from Mr. Philip G. Waite, P.E., Project Manager, Region 6, Division of Hazardous Waste Remediation, NYSDEC, re: Reynolds Metals Company Site, Sampling and Analytical Method Bias for Rocky Soils, September 14, 1993, September 6, 1996.
- P. 500399- Letter to Mr. Robert F. Vaughn, Chief, Special
500405 Projects Branch, U.S. EPA, Region II, from Mr. Rick Esterline, Project Director, Reynolds Metals Company, re: Responses to EPA areas of concern, September 11, 1996. (Attachment: Letter to Mr. Rick Esterline, Reynolds Metals Company, from Ms. Marijean B. Remington, Senior Vice President, Atlantic Testing Laboratories, Ltd., re: PCB Extraction Efficiency - Soil and River Bottom Sediment Samples, September 11, 1996.)
- P. 500406- Letter (via facsimile) to Ms. Anne Kelly,
500411 NY/Caribbean Branch, Emergency and Remedial Response Division, U.S. EPA, Region II, from Mr. George W. Heitzman, P.E., Senior Environmental Engineer, Division of Hazardous Waste Remediation, NYSDEC, re: St. Lawrence/Grasse River - Reynolds Study Area, September 13, 1996.

- P. 500412- Letter to Ms. Anne Kelly, Project Officer,
500414 Reynolds Metals Site, U.S. EPA, Region II, from
Mr. Rick Brooksbank, Data Management Supervisor,
Bechtel Environmental, Inc., re: Summary of
Immunoassay vs. 8080, Results on RMC River
Samples, September 16, 1996.
- P. 500415- Letter to Mr. Robert F. Vaughn, Chief, Special
500417 Projects Branch, U.S. EPA, Region II, from Mr.
Rick Esterline, Project Director, Reynolds Metals
Company, re: Administrative Order, Index No. II
CERCLA - 90230, letter dated September 18, 1996,
September 30, 1996.
- P. 500418- Facsimile to Ms. Anne Kelly, U.S. EPA, Region 2,
500420 from Mr. Philip G. Waite, NYSDEC, re: Reynolds
Metals Company Sampling Procedures, October 15,
1996. (Attachments: (1) Letter to Mr. R.C.
Esterline, Remediation Project Director, Reynolds
Metals Company, from Mr. Philip G. Waite, P.E.,
Project Manager, NYSDEC, re: Reynolds Metals
Company, Sampling Procedures, September 23, 1996,
(2) Memorandum to Mr. Philip Waite, Region 6,
NYSDEC, from Ms. Christine McGrath, QAU, ISS, BCS,
NYSDEC, re: Reynolds - Sampling, September 20,
1996.)
- P. 500421- Letter to Ms. Anne Kelly, U.S. EPA, Region II,
500422 from Mr. George W. Heitzman, P.E., Senior
Environmental Engineer, Division of Hazardous
Waste Remediation, NYSDEC, re: St. Lawrence/Grasse
River - Reynolds Study Area, November 18, 1996.
- P. 500423- Letter to Ms. Carole Petersen, Chief, NY/Caribbean
500440 Compliance Branch, U.S. EPA, Region II, from Mr.
Peter R. Jacobson, P.G., Senior Project Manager,
Woodward-Clyde Consultants, re: Additional
information for the EPA to modify the Decision
Document for the St. Lawrence River Sediments in
the Reynolds Study Area, October 22, 1997.
(Attachment: Revised Request for Modification of
Decision Document, St. Lawrence River Sediments,
prepared by Woodward-Clyde, prepared for Reynolds

Metals Company, St. Lawrence Reduction Plant,
October 22, 1997.)

P. 500441- Memorandum to Site File, from Mr. Mark Purcell,
500442 Remedial Project Manager, New York Remediation
Branch, Emergency and Remedial Response Division,
U.S. EPA, Region II, re: Unit Cost Estimate for
Off-Site Transportation and Incineration of PCB-
Contaminated Sediments, Reynolds Metals Company
Study Area Site, Massena, N.Y., June 19, 1998.

APPENDIX 2

RESPONSIVENESS SUMMARY

Reynolds Metals Company Study Area

Post-Decision Proposed Plan

500479

TABLE OF CONTENTS

RESPONSIVENESS SUMMARY

1.0	INTRODUCTION	1
2.0	SUMMARY OF COMMUNITY RELATIONS ACTIVITIES	1
3.0	SUMMARY OF COMMENTS RECEIVED DURING THE PUBLIC MEETING AND PUBLIC COMMENT PERIOD AND EPA'S RESPONSES	3
3.1	Post-Decision Proposed Plan	3
3.2	Industrial Landfill	5
3.3	Off-Site Treatment Threshold of 500 ppm for PCBS	12
3.4	Community Involvement and Information	16
3.5	Sediments and Dredging	18
3.6	Other	22

APPENDICES

- A. POST-DECISION PROPOSED PLAN
- B. PUBLIC NOTICE
- C. SIGN-IN SHEETS
- D. WRITTEN COMMENTS

**RESPONSIVENESS SUMMARY
REYNOLDS METALS COMPANY STUDY AREA
POST-DECISION PROPOSED PLAN**

1.0 INTRODUCTION

A responsiveness summary is required by the National Oil and Hazardous Substances Pollution Contingency Plan (NCP) at 40 CFR 300.430(f)(3)(F). It provides a summary of significant comments and questions received during the public comment period, and the United States Environmental Protection Agency's (EPA's) responses to those comments and questions. The responsiveness summary is appended to and is a part of the Decision Document, the document that describes the selected remedy for cleaning up a site. Comments summarized in this Responsiveness Summary have been considered in EPA's decision for selecting a modification to the original remedial action for the Reynolds Metals Company (Reynolds) Study Area site (hereinafter the "Site").

This Responsiveness Summary is organized into the following sections:

2.0 Summary of Community Relations Activities

This section summarizes EPA's community involvement activities relative to a Post-Decision Proposed Plan (hereinafter the "Plan") issued in July 1998.

3.0 Summary of Comments Received During the Public Comment Period and EPA's Responses

This section summarizes both oral and written significant comments submitted to EPA by interested citizens at the public meeting and during the public comment period and provides EPA's responses to these comments.

2.0 SUMMARY OF COMMUNITY RELATIONS ACTIVITIES

In July 1998, EPA released the Plan which described proposed changes to the remedy selected by EPA in its September 1993 Decision Document for the Site, located in Massena, New York. The Plan was developed by EPA in consultation with the New York State Department of Environmental Conservation (NYSDEC). The Plan is attached to this Responsiveness Summary as Appendix A.

The Plan, along with other technical supporting documents, was made available to the public at information repositories maintained at EPA Region II's office in New York City, at the Massena Public Library, and at the St. Regis Mohawk Tribe Health Services Building, located in Hogansburg, New York. The Plan also was mailed to approximately 400 citizens on EPA's mailing list for the Site.

EPA held a public comment period from July 30 through August 28, 1998, for interested citizens to comment on the Plan. A public notice announcing the public comment period, public meeting, and availability of the Plan was published in the Courier-Observer daily newspaper on July 30, 1998, and in the Indian Times and People's Voice weekly newspapers on July 31, 1998. A copy of the public notice is attached to this Responsiveness Summary as Appendix B. Also on July 30, EPA issued a press release to regional media in the United States and Canada.

EPA held a public meeting on Wednesday, August 12, 1998, at the Massena Public Library, 41 Glenn Street, in Massena, New York. Approximately 26 people attended. The sign-in sheets from the meeting are attached to this Responsiveness Summary as Appendix C. During the meeting, representatives from EPA, NYSDEC, and the New York State Department of Health (NYSDOH) answered questions and received comments on the Plan. The proceedings of the meeting were recorded in a transcript, which has been placed in the information repositories designated for the Site.

In addition, EPA held an informal public availability session on Thursday, August 13, 1998, at the St. Regis Housing Authority Auditorium, Route 37, Hogansburg, New York. Approximately 11 people attended. The sign-in sheets from the public availability session are attached to this Responsiveness Summary as Appendix C. During the session, representatives from EPA and NYSDEC held informal, one-on-one conversations about the Plan with residents of Akwesasne (St. Regis Mohawk Tribe).

Prior to the public meeting on August 12, representatives from EPA met with several Legislators from Akwesasne to brief them on the Plan. EPA invited the Legislators to the public meeting and public availability session.

In addition to comments received at the public meeting, EPA received written comments during the public comment period. EPA's responses to these comments are included in this Responsiveness Summary. Copies of the written comments are attached as Appendix D.

3.0 SUMMARY OF COMMENTS RECEIVED DURING THE PUBLIC MEETING AND PUBLIC COMMENT PERIOD AND EPA'S RESPONSES

All comments and questions submitted during the public meeting and public comment period are summarized below according to the following topics:

- 3.1 Post-Decision Proposed Plan
- 3.2 Industrial Landfill
- 3.3 Off-Site Treatment Threshold of 500 ppm for PCBs
- 3.4 Community Involvement and Information
- 3.5 Sediments and Dredging
- 3.6 Other

3.1 Post-Decision Proposed Plan

3.1.1 **Comment:** Representatives from the St. Regis Mohawk Tribe support treatment and disposal of polychlorinated biphenyl (PCB)-contaminated sediments off-site rather than treatment on-site as originally proposed. However, the Tribe prefers permanent treatment of the hazardous waste that will remain on-site. The Tribe has an obligation to look seven generations into the future during their decision-making process. Therefore, remedies that permanently solve the hazardous waste problem over the long term are the only acceptable options at the Site. Containment of any kind in an unlined landfill will serve to pass on the toxic waste problem to future generations. Containment is only acceptable as a temporary solution until a permanent treatment remedy that reduces the volume, mobility, and toxicity of contaminants is implemented.

EPA Response: The containment of lower levels of contamination (*i.e.*, PCB levels less than 50 parts per million (ppm)) in the existing on-site Industrial Landfill using appropriate engineering controls, including a leachate collection system and multilayered cap, will provide adequate protection of human health and the environment (see EPA Response to Comment No. 3.2.2, below). Long-term management controls will be implemented to assure that the Landfill's effectiveness and integrity as a containment system are maintained for as long as the contaminants remain on-site. In the event that Reynolds discontinues the operation at its aluminum production facility (hereinafter the "Facility") or conveys any interest in its Facility property to successors-in-title at some time in the future, such discontinuance or conveyance will not release or otherwise affect the liability of Reynolds to comply with all the provisions of the federal unilateral administrative orders and the state consent orders issued to Reynolds, or which Reynolds has entered

into, for investigating and remediating hazardous wastes at its Facility.

3.1.2 Comment: Representatives from the St. Regis Mohawk Tribe propose that EPA order Reynolds to investigate new remedial treatment technologies on an annual basis until a treatment remedy is found to permanently destroy the contamination in the Industrial Landfill. Such a permanent remedy would minimize Reynolds' continuing operation and maintenance obligations, thereby decreasing the financial cost of the remedy in the long term.

EPA Response: The remediation of the Reynolds Facility (land-based cleanup) is being overseen separately by NYSDEC. The long-term management of the Industrial Landfill as a containment system is part of that program, and is being addressed by Reynolds in compliance with NYSDEC's 1992 Record of Decision (ROD) and 1993 Consent Order. NYSDEC conducts annual reviews and inspections of the entire site-wide remediation. Any requirement for Reynolds to examine new treatment technologies for the Industrial Landfill on an annual basis would be established by NYSDEC.

Under CERCLA, EPA is required to perform a review every five years whenever the selected remedy will leave contamination on-site. However, since all sediments above the established cleanup goals would be removed from the St. Lawrence River and disposed of either off-site or at the Industrial Landfill (less than 50 ppm of PCBs), which is part of NYSDEC's remedial program, EPA would not perform those reviews at this Site.

In the event that NYSDEC does not allow the placement of river sediments containing PCBs at concentrations up to 50 ppm in the Industrial Landfill, those contaminated sediments would be disposed of at another appropriate off-site disposal facility.

3.1.3 Comment: A representative from the Canadian Review Panel¹ stated that the Plan generally meets with current Canadian policies on removal and containment of PCB-contaminated materials and is consistent with actions and decisions made at the Aluminum Company of America (Alcoa) and General Motors (GM) sites in Massena. There are no objections to the Plan in this regard.

EPA Response: No response is necessary.

¹ The Canadian Review Panel consists of representatives from Environment Canada - Ontario and Quebec Regions; the Ontario Ministry of the Environment; and the Quebec Ministère de l'Environnement et de la Faune.

3.2 Industrial Landfill

3.2.1 Comment: Representatives from the St. Regis Mohawk Tribe expressed concern about the total, long-term load of PCBs on the local environment. The 1993 remedy would have allowed on-site containment of 37,000 cubic yards (yds³) of sediments in the Black Mud Pond, none of which exceed 25 ppm of PCBs. In contrast, the current Plan would allow containment of 43,400 yds³ of sediments in the Industrial Landfill, with PCB concentrations up to 50 ppm. This is in addition to the 135,300 yds³ of PCB-contaminated soils at levels less than 50 ppm which have been placed in the Industrial Landfill as part of NYSDEC's land-based cleanup. Thus, the net load of contamination to be left on-site is significantly greater than proposed in 1993, and more toxic.

EPA Response: EPA does not consider the changes under this Plan with regard to deposition of sediments on the Industrial Landfill to significantly increase the volume or toxicity of the waste which would be contained on-site under the original remedy and NYSDEC's land-based cleanup. The volume of additional sediments (PCB levels between 25 and 50 ppm) which would be disposed of on the Landfill under this Plan is currently estimated to be 4,700 yds³. This represents less than three (3) percent of the total volume of 178,700 yds³ (135,300 yds³ of land-based soils and 43,400 yds³ of river sediments) which have been, or will be, placed therein.

Furthermore, although the PCB levels to be landfilled on-site would be increased under this Plan from 25 ppm to less than 50 ppm, EPA believes that the level of protection provided by the Industrial Landfill, with appropriate engineering controls, is comparable (see EPA Response to Comment No. 3.2.2, below). The wastes will be completely encapsulated within the Landfill once the cover system is installed, thereby eliminating their exposure to the environment.

The on-site containment of PCBs at concentrations less than 50 ppm is also consistent with EPA's "Guidance on Remedial Actions for Superfund Sites with PCB Contamination" (hereinafter the "PCB Guidance"). According to the PCB Guidance, for an industrial setting, low concentrations of PCBs (e.g., less than 50 ppm) may be effectively contained on-site in a secure, monitored location with appropriate long-term management controls, including a cover system and ground-water monitoring.

3.2.2 Comment: Representatives from the St. Regis Mohawk Tribe also stated that the Tribe never concurred with the state and federal proposals that the waste in the unlined Industrial Landfill remain in place permanently. They cited issues with the Landfill that make it unsuitable for containment, based on the

findings made in EPA's administrative record, including the following:

- ground water, and essentially headwaters of the wetland, intersect the PCB-contaminated waste mass in the Landfill and then discharges to the wetland;
- there is no record as to the concentrations of hazardous waste in the Landfill;
- there is no information as to the effectiveness of the leachate collection system that has been installed at the Landfill; and,
- the current ecological health of the impacted Wetlands (identified as Wetlands No. RR-6 by NYSDEC) or the extent to which they continue to suffer leaks from the Landfill have not been established.

EPA Response: With the use of appropriate engineering controls, as discussed in further detail below, the Industrial Landfill functions as an effective containment system. The operation of the leachate collection system since 1996 has effectively collected the shallow ground water (leachate) which is flowing from the Landfill southward toward the Wetlands. The collection of the leachate (approximately 1 million gallons per month) prevents the migration of PCBs and other contaminants through the overburden soils and waste materials to the Wetlands. Preliminary data from the initial round of ground-water sampling collected downgradient of the leachate collection system did not show the presence of PCBs. Further discussions of the ground-water monitoring results are also discussed below.

Surface-water controls installed at the Landfill also prevent contaminants from migrating to the Wetlands via uncontrolled surface-water runoff. The effectiveness of the Landfill will be enhanced further once the cap is installed and the infiltration of rainwater, which mixes with the wastes to form leachate, is eliminated.

Although there is no liner under the Industrial Landfill, it is sited directly atop a relatively impermeable clay layer which is present under the entire area of waste materials. The clay layer, which varies in thickness from a few feet to over 20 feet, impedes the movement of leachate downward from the Landfill into the underlying glacial till. The clay also acts as a confining layer (hydraulic barrier) between the shallow ground water within the overburden soils and the ground water in the underlying till. The shallow ground water (leachate) within the Landfill is constrained to flowing laterally southward, toward the adjacent

Wetlands. Ground water within the glacial till also flows in a southerly direction, but has an upward vertical component of flow which recharges the Wetlands and the waste materials within the Landfill. This upward component of ground-water flow into the Landfill, while helping to prevent the downward movement of contaminants, generates additional leachate.

Leachate Collection System: The leachate collection system was installed along the southern perimeter of the Landfill to intercept the leachate moving laterally through the overburden soils and waste materials to the Wetlands. The system consists of a two-foot wide trench filled with crushed stone. At the bottom of the trench is an eight-inch diameter, perforated collection pipe. Leachate flows into the more porous and permeable crushed stone and the collection pipe from the overburden soils and waste materials. The leachate is transported through the collection pipe to a pump and forcemain system which then carries it to the carbon treatment plant located at the North Yard for treatment. On the downgradient side (south side) and beneath the trench is the low-permeability clay, which prevents the leachate from passing beyond the crushed stone toward the Wetlands. The depth of the trench, which ranges from approximately five to seven feet, was established to intercept all of the waste materials and any thin silt or sand layers within the overburden soils. It was important that the leachate collection system intercepted those thin layers of silt and sand, since they have higher permeabilities than the underlying clay and could facilitate the migration of leachate laterally through the overburden soils.

The leachate collection system has been in operation for a few years. Since 1996, approximately one million gallons of leachate have been collected each month (12 million gallons per year). For the period between January and August of 1998, the leachate collection system has recovered approximately 8.6 million gallons of leachate.

Other Engineering Controls: Several other engineering controls have been installed at the Landfill. Surface-water controls and vegetative cover have been installed to control surface-water runoff. Monitoring wells have been installed around the perimeter of the Landfill for long-term monitoring of ground water quality. Following placement of the sediments into the Landfill, a multilayered cap, which will meet relevant and appropriate requirements of a Resource Conservation and Recovery Act (RCRA) hazardous waste landfill cap, will be installed to limit the infiltration of rainwater to the waste so as to minimize the volume of leachate generated. Once the cap is in place, the volume of leachate should decrease significantly.

Monitoring: The long-term management of the Industrial Landfill, which is being performed by Reynolds under the direct oversight of NYSDEC, includes the weekly monitoring of storm water levels, monthly monitoring of ground-water levels, and quarterly ground-water sampling and analyses.

Under NYSDEC's land-based cleanup, Reynolds is required to submit post-remediation reports for the entire site-wide remedial program to NYSDEC on a quarterly basis. The post-remediation reports, along with other related documents, are available for public review at NYSDEC repositories located at the Massena Public Library and NYSDEC Region 6 office, located in Watertown, New York. Copies of the monitoring reports prepared by Reynolds for the Industrial Landfill and Wetlands are currently provided to representatives of the Tribe's Environment Division.

NYSDEC has received the first set of preliminary data from the ground-water monitoring program, which began in late 1997/early 1998. PCBs were not detected in the ground-water samples analyzed. However, concentrations of cyanide and fluoride were detected. NYSDEC has indicated that it is too early in the monitoring program to determine the significance of those chemicals and it will continue to monitor the ground-water quality on a quarterly basis. Copies of those monitoring reports will be provided to EPA for review.

NYSDEC Inspections: Representatives of NYSDEC will conduct annual reviews and inspections of the Industrial Landfill and Wetlands. The St. Regis Mohawk Tribe is invited to participate in the annual inspections conducted by NYSDEC at the Reynolds Facility. It is EPA's understanding that NYSDEC and Reynolds have accommodated representatives of the Tribe's Environment Division in the past, when participation at inspections was requested. The Tribe's representatives were also permitted to collect samples for independent analyses during the remedial investigations performed at the Reynolds Facility.

Wetlands Remediation: In January 1998, NYSDEC approved Reynolds post-remediation report for the Wetlands entitled, "Area-Specific Completion Report for Remediation, Restoration, and Mitigation of Wetlands RR-6 at the Reynolds Metals Company St. Lawrence Reduction Plant, Massena, New York" (Wetlands Report). The Wetlands Report documents the remediation of the Wetlands between 1994 and 1997 and the attainment of the cleanup goals for PCBs (1 ppm) and other contaminants. It also documents the Wetlands restoration efforts and post-remediation monitoring which will be performed to assure that the Wetlands are not impacted by additional contamination from the site.

Water level monitoring will be performed at the Wetlands on a monthly basis. Monitoring will also include the continued sampling and analyses of surface-water discharges from the Wetlands via Outfalls 010 and 011, in accordance with applicable State Pollution Discharge Elimination System (SPDES) program requirements. Outfalls 010 and 011 flow from the Wetlands southward under Route 37 to the Raquette River.

3.2.3 Comment: The St. Regis Mohawk Tribe stated that since Reynolds is saving nearly \$10 million by this proposed change, a portion of the savings should be invested in more complete containment of the Industrial Landfill and ongoing evaluation of innovative in-situ treatment technologies for the permanent neutralization of Landfill wastes.

The Tribe suggested the following conditions for allowing the Landfill to remain in place: an endowment for the long-term operation, maintenance, and monitoring of the Landfill to assure its effectiveness forever or until a permanent remedy is implemented; a directive that Reynolds must regularly evaluate and report on the cost and effectiveness of in-situ treatment technologies which may result in a permanent remedy; and air monitoring and treatment of any volatile gases escaping from the Landfill air vents and through the composite cover.

EPA Response: In accordance with the provisions set forth in Section XII of NYSDEC's 1993 Consent Order for the land-based remediation, Reynolds was required to provide financial assurances of its ability to perform the cleanup, including the long-term operation, maintenance, and monitoring activities associated with the Industrial Landfill. Reynolds was also required to provide cost estimates of the operation and maintenance of the Landfill and other remedial systems installed as part of that remedial program

With regard to the periodic examination of new treatment technologies for the permanent destruction of the Landfill waste, please refer to EPA's Response to Comment No. 3.1.2, above. At this time, the engineering controls which are installed or planned for the Industrial Landfill are considered by EPA and NYSDEC to be effective in containing the waste within the Landfill. If it is determined by NYSDEC that additional engineering controls or other actions are necessary to assure the effectiveness of the Landfill as a containment system, NYSDEC may require Reynolds to undertake such action(s). Additional engineering controls are being considered by NYSDEC to minimize the large volume of shallow ground water which is believed to be flowing into the Landfill from the overburden soils to the north. This ground water mixes with the waste materials and creates leachate which, ultimately, must be collected by the leachate

collection system and treated. If the volume of leachate currently being collected - approximately 1.0 million gallons per month - does not significantly decrease after the cap is in place, NYSDEC may consider installing an upgradient ground-water cutoff wall to control the volume of ground water flowing into the Landfill.

NYSDEC has informed EPA that it agrees with the St. Regis Mohawk Tribe's comment about the need for an air monitoring program to detect any volatile gases which may escape from the Landfill vents and through the cap, once they are installed. There is no air monitoring program currently in place at the Landfill, which is covered with an interim soil layer and grass. NYSDEC plans on monitoring air emission levels initially to see if they exceed New York State air quality standards or guidelines. In the event such standards or guidelines are exceeded, NYSDEC would consider the treatment of the volatile gases to control emissions and the implementation of an air monitoring program for continual monitoring of the air quality at the Landfill.

3.2.4 Comment: The St. Regis Mohawk Tribal Council objects to the 50 ppm containment level and supports a 0 ppm level. They stated the area must be returned to the condition it was in when Reynolds first came to Massena, clean of contaminants.

EPA Response: EPA is charged with administering and enforcing existing environmental laws and regulations. The 50 ppm PCB level proposed in this Plan for off-site disposal is consistent with the Toxic Substances Control Act (TSCA), the federal law which regulates the treatment, storage, and disposal of PCBs based on their form and concentration. Under TSCA, dredged materials with PCBs at concentrations of 50 ppm or greater must be landfilled in a TSCA-approved chemical waste landfill, incinerated, or disposed of by another method approved by EPA. It is also consistent with NYSDEC's hazardous waste program, which identifies PCBs as hazardous wastes at the 50 ppm level.

Further, the 50 ppm level is consistent with EPA's current guidance for remediation of PCBs. For an industrial setting, materials with low concentrations of PCBs (e.g., less than 50 ppm) may be contained on-site with long-term management controls that include a cover system and ground-water monitoring.

3.2.5 Comment: A Research Scientist from the State University of New York (SUNY) at Oswego asked what type of monitoring has been conducted to ensure the integrity of the Industrial Landfill.

EPA Response: Please refer to EPA's Response to Comment No. 3.2.2, above.

3.2.6 Comment: A Research Scientist from SUNY-Oswego asked whether there was any contamination in the Wetlands next to the Industrial Landfill.

EPA Response: The Wetlands sediments were contaminated with several chemicals, including PCBs at levels as high as 14 ppm, fluoride (54,000 ppm) and cyanide (91 ppm). Surface water was also contaminated with PCBs at levels ranging up to 2.6 parts per billion (ppb), fluoride (96 ppm) and cyanide (1.3 ppm). The Wetlands were contaminated primarily from shallow ground water (leachate) flowing from the Industrial Landfill southward and discharging directly into the Wetlands. Additionally, small leachate seeps in the northwest corner of the Landfill periodically overflowed the containment berm and drained into the Wetlands via a small stream. During high rainfall events, the perimeter drainage ditches would overflow allowing surface-water runoff to flow directly to the Wetlands. The Wetlands also received contaminated sediments and surface water which drained from other areas of the Reynolds Facility.

The Wetlands were remediated between 1994 and 1997 as part of NYSDEC's land-based cleanup (see EPA Response to Comment No. 3.2.2, above).

3.2.7 Comment: A Research Scientist from SUNY-Oswego asked how much leachate from the leachate collection system is being produced on an annual basis.

EPA Response: Approximately 12 million gallons of leachate have been collected from the leachate collection system per year (1.0 million gallons per month) since 1996. Most of the water is believed to be from surface-water runoff. Surface water flows down the slopes of the Landfill and enters the leachate collection system by percolating downward from the ground surface through clay, rocks, and a geotextile fabric, which currently overlay the crushed stone within the trench. The final cap will cover the leachate collection system once it is installed. Infiltration of rainwater and ground-water flow from the upgradient areas of the Facility may also contribute significant volumes of leachate. Once the Landfill is capped and the leachate collection system no longer collects surface water, it is anticipated that the volume of leachate collected will decrease significantly (see EPA Response to Comment No. 3.2.3, above).

3.2.8 Comment: A Research Scientist from SUNY-Oswego asked whether there are materials within the Industrial Landfill with PCB concentrations greater than 50 ppm.

EPA Response: According to NYSDEC, previous investigations indicated that the bulk of the waste in the Industrial Landfill did not have PCB concentrations greater than 50 ppm. A small volume was found to exhibit PCBs at concentrations up to 690 ppm. During the land-based remediation, a very thorough sampling program was performed to ensure that materials with PCB concentrations of 50 ppm and greater were transported off-site for disposal and only materials with less than 50 ppm of PCBs were placed in the Landfill.

3.2.9 Comment: A representative from the Canadian Review Panel expressed concern regarding the lack of deep soil and ground-water monitoring in the Industrial Landfill. This gap in information presents some questions on whether the ground-water recovery and treatment systems will be fully effective.

EPA Response: As discussed in EPA's Response to Comment No. 3.2.2, above, the hydrogeologic conditions present beneath the Industrial Landfill impede the downward migration of contaminants from the Landfill into the underlying glacial till. The low-permeability clay beneath the waste materials and an upward hydraulic gradient from the underlying till into the overburden soils and waste materials prevent the shallow ground water from transporting contaminants downward through the clay layer. As a result, the shallow ground water is constrained to flow laterally southward, toward the leachate collection system, where it is captured and subsequently sent to the carbon treatment plant at the North Yard for treatment.

In light of these hydrogeologic conditions, EPA believes that it is unnecessary for the ground-water monitoring program to include wells for monitoring the deeper portions of the underlying till and ground water beneath the Landfill. Rather, the program consists of shallow ground-water monitoring wells located upgradient and downgradient of the Landfill. The downgradient monitoring wells, which are located south of the leachate collection system, will assess the effectiveness of that system in collecting all of the leachate flowing from the Landfill southward toward the Wetlands.

3.3 Off-Site Treatment Threshold of 500 ppm for PCBs

3.3.1 Comment: In an August 26, 1998 letter, Reynolds objected to EPA's requirement to treat dredged sediments greater than 500 ppm. In accordance with 40 CFR 761.61(b)(2), Reynolds is allowed to dispose of PCB remediation waste in a chemical waste landfill. As noted in the preamble to the final rule published in the Federal Register on June 29, 1998 for 40 CFR Parts 750 and 761, "dredged material falls within the definition

of PCB remediation waste, and as such, the other disposal options of 761.61(a), (b), and (c) are available for management and disposal of dredging material containing PCBs at any concentration..." In addition, disposal off-site would be equally protective and less costly, as EPA has affirmed in its "Comparison of Original Remedy and Proposed Changes" section of the Superfund Post-Decision Proposed Plan for the nearby GM Superfund site, August 1998.

Reynolds stated that treatment of PCB remediation waste is not required; it's an option. Reynolds has evaluated this option and believes that disposal of all sediments with PCB concentrations greater than 50 ppm at Chemical Waste Management's Model City facility is the most cost-effective and environmentally protective approach. Treatment of approximately 4,500 yds³ of sediment at a cost of \$7.2 million (\$5.8 million over landfill costs) is not a requirement Reynolds is willing to accept.

Reynolds cited past statements by EPA that, based on past experiences at the GM Superfund site, it is not expected that a significant quantity of the dredged sediment from the Site will be greater than 500 ppm. The Reynolds representative noted that GM's removal of sediment by hydraulic methods mixed high (greater than 500 ppm) contaminant level sediments with low contaminant level sediments resulting in sediments with an average PCB concentration of 200 ppm (per EPA's Superfund Post-Decision Proposed Plan, GM Superfund site, August 1998, page 7). However, Reynolds' proposed use of a closed clamshell bucket for dredging greatly increases the possibility of removing the sediments at higher in-situ concentrations. According to Reynolds, to imply the volumes will be much less is a \$5.6 million assumption that is difficult to justify.

Reynolds stated that EPA's preference to treat PCB sediments with concentrations greater than 500 ppm is not consistent with the land-based remediation project on the Reynolds Facility. The land-based remediation project landfilled soils off-site with PCB concentrations greater than 500 ppm.

Reynolds also stated that the requirement to incinerate the sediments is punitive and not consistent with other EPA river projects in the area. The "Alcoa Non-Time Critical Removal Action" had sediments with PCB concentrations that ranged from non-detect to 11,000 ppm. EPA allowed that sediment to be placed in Alcoa's on-site secure landfill with no restrictions on sediments with PCB concentrations greater than 500 ppm. Alcoa is a direct competitor in the aluminum market place and EPA's requirement for Reynolds to incinerate, while allowing Alcoa to landfill, forces Reynolds to spend an additional \$5.8 million and places Reynolds at a competitive disadvantage. Further, the GM

Post-Decision Proposed Plan, dated August 1998, does not require treatment of sediments and soils in the Raquette River previously identified as having PCB concentrations greater than 500 ppm. If Alcoa and GM are allowed to landfill sediments with PCB concentrations greater than 500 ppm and regulations allow it, then Reynolds is not prepared to spend an extra \$5.8 million to incinerate similarly contaminated sediments.

Reynolds cited several examples where sediments with PCB waste greater than 500 ppm have been landfilled (e.g., Facet Enterprises, Inc., New York; New York Cosden Chemical Coatings Corporation, New Jersey). A recent EPA publication, *Realizing Remediation: A Summary of Contaminated Sediment Remediation Activities in the Great Lakes Basin* (March 1998), discusses several sites with sediments or soils with PCB concentrations greater than 500 ppm that have been landfilled without thermal treatment at off-site facilities that meet requirements of the TSCA (e.g., Ottawa River Tributary, Ohio; Manistique River and Harbor, Michigan; Willow Run Creek, Michigan).

EPA Response: EPA acknowledges that federal TSCA regulations do not distinguish between dredged materials having PCB concentrations greater than 500 ppm and less than 500 ppm in specifying disposal requirements. This distinction is made by EPA, consistent with its Superfund program's expectation for using treatment to address the principal threats posed by a site, wherever practicable. Principal threats are generally characterized as waste that cannot be reliably controlled in place, such as liquids, highly mobile materials (e.g., solvents), and high concentrations of toxic compounds (e.g., several orders of magnitude above levels that allow unrestricted use and unlimited exposure). EPA's PCB guidance regarding the remediation of PCB contamination as a principle threat under the Superfund program favors the treatment of materials with PCB concentrations exceeding 500 ppm in an industrial setting.

Although EPA's program expectation is to use treatment to address principle threats, certain technological, economic and implementation factors may make treatment impracticable for certain types of site conditions. Treatment is less likely to be practicable when sites have large volumes of waste or when the waste is very difficult to handle and treat (e.g., mixed waste of widely varying composition). Other site-specific situations which may limit the use of treatment include: (1) the extraordinary size or complexity of a site makes treatment impracticable; (2) the use of treatment would result in greater overall risk to human health and the environment due to risks posed to workers or the surrounding community; and (3) treatment technologies are not technically feasible or are not available within a reasonable time frame.

In considering the Superfund program's expectation and EPA's PCB guidance, EPA has determined that treatment of the sediments with PCB levels exceeding 500 ppm can be practicably utilized with respect to the Site. Although the estimated cost for off-site incineration is high, there is an overall cost savings of \$9.2 million associated with this Plan.

EPA recognizes that its proposal is not consistent with the land-based remedy selected by NYSDEC at the Reynolds Facility, where excavated soils sent off-site for landfilling contained PCB levels an order of magnitude higher than the levels found in the river sediments. However, the preference for treatment is an EPA policy, not a federal or state regulation. NYSDEC, in selecting the land-based remedy, was only required to consider whether its preferred remedy met all federal and state ARARs.

EPA's preference for treatment is a statutory provision that applies to remedial actions selected by the Agency. However, the statutory preference for treatment does not apply to cleanups which occur under the EPA's removal program. Removal actions are conducted in an expedited manner (when compared to remedial actions) to mitigate or abate a release or threat of release; the time and resources associated with treatment may be incompatible with the expedited nature of a removal action. Of the specific examples cited by Reynolds, two were performed as removal actions: The Alcoa site in Massena and the Manistique River and Harbor site in Michigan. It also should be noted that the non-time critical removal action conducted at the Alcoa site was an early action conducted to address highly contaminated sediments in the vicinity of one of Alcoa's outfalls to the St. Lawrence River. The EPA has not yet selected a final remedial action for the Alcoa site.

Of the other examples cited by Reynolds, the Willow Run Creek site in Michigan was a state lead site and the Ottawa River Tributary site in Ohio was remediated through a voluntary partnership between the responsible party, the Ohio Environmental Protection Agency, the City of Toledo and the Great Lakes National Program Office (EPA), and therefore, is out of the realm of the Superfund program. The Cosden Chemical Coatings Corporation-site in New Jersey did not have PCB concentrations exceeding 500 ppm. The remedy selected for the Facet Enterprises, Inc., site in New York, although not specifically calling for the treatment of soils with PCB levels exceeding 500 ppm, included the off-site treatment of those soils by solidification prior to landfilling to address heavy metals in the soils which failed Toxic Characteristic Leaching Procedure (TCLP) testing for characteristics of a hazardous waste.

Regarding the August 1998 Post-Decision Proposed Plan for the GM Superfund site, EPA does not know whether the sediments and soils

to be sent off-site for disposal under that plan would exhibit PCB levels greater than 500 ppm. Post-dredging sampling and analyses of the St. Lawrence River sediments which are temporarily stockpiled at the GM plant, showed PCB levels to be lower than 500 ppm. Since EPA does not anticipate that the sediments or soils will contain PCB levels above 500 ppm, the determination whether or not treatment of those sediments and soils can be practicably utilized in a cost-effective manner will be made during construction, if the alternative preferred by EPA in the GM Post-Decision Proposed Plan is selected as the modified remedy.

3.3.2 Comment: A representative from Alcoa stated that TSCA mandates that dredged materials with PCB concentrations greater than 50 ppm must be either disposed of in a TSCA-approved landfill, incinerated, or disposed by alternative method approved by EPA. In this instance, the regulations do not identify the need for "special treatment" of sediment with PCB concentrations greater than 500 ppm. Hence, the need to manage and dispose of these materials in a manner that is different from those with PCB concentrations greater than 50 ppm and less than 500 ppm appears unwarranted. It would be equally protective to dispose of the materials with PCB concentrations greater than 500 ppm in a TSCA-approved landfill.

EPA Response: Please refer to EPA's Response to Comment 3.3.1., above.

3.4 Community Involvement and Information

3.4.1 Comment: Representatives from the St. Regis Mohawk Tribe stated that EPA's notice procedure was deficient. EPA released a 15-page, detailed Plan that was received by the Tribe on August 3, providing less than 10 days notice of a public meeting in Massena on August 12. This is inadequate notice in the Akwesasne Community.

The representatives from the St. Regis Mohawk Tribe referenced Executive Order No. 13084, issued May 14, 1998, which requires that agencies implement an effective process to permit Tribal governments to provide "meaningful and timely" input on matters that substantially affect Tribal communities. The natural resources which have been impacted by the Site are relied upon by the Akwesasne community. The community's strong interest in the Site and knowledge base will assist EPA in formulating an effective remedy. Therefore, a period of at least 45 days notice of public meetings regarding significant changes in remediation plans is necessary in order to provide for "meaningful and timely" public input from Akwesasne.

EPA Response: EPA regrets that the St. Regis Mohawk Tribe feels it was not given adequate advanced notice of the public meeting in Massena and the public availability session on Akwesasne. When EPA became aware of these concerns, it was already committed to the scheduled dates for the public meeting and availability session, since they were included in the public notice printed in the local newspapers and EPA's press release issued prior to the start of the public comment period. However, EPA did respond to the Tribe's concerns by modifying the project schedule for the subsequent Post-Decision Proposed Plan involving the GM Superfund site. That plan was issued on August 21, 1998, and announced a public meeting on September 17, 1998, providing almost a month's notice of the public meeting. In the future, EPA will consider these concerns when planning public involvement activities for the Site.

3.4.2 Comment: A representative from the Canadian Review Panel stated that Canada has an ongoing need to ensure that Canadian waters downstream are protected from transboundary movement of contaminants and toxicity. As such, he requested: regular contact with Site personnel; receipt of monitoring information; copies of the detailed work program; and copies of the dewatering, monitoring, health and safety, and contingency plans when they are available. He also requested additional information on the carbon treatment system at the North Yard and the location of the off-site disposal facility. He stated that Canadian agencies may conduct a water quality monitoring program on the St. Lawrence River during dredging.

EPA Response: EPA has, and will continue to have, ongoing contact with representatives from Environment Canada during developments at all three sites in Massena. EPA agrees to provide the requested information when it becomes available, as it has done in the past. In addition, EPA would welcome the opportunity to review plans and data from any water quality monitoring programs that Environment Canada or other Canadian agencies may conduct on the St. Lawrence River during dredging at the Site.

Further, once they have been completed, all technical reports, such as the dredging monitoring plan, will be available to the public at the information repositories. The information repositories are located in the Massena Public Library, the Tribe's Environment Division office in the Health Services Building on Akwesasne, and EPA's office in New York City.

3.4.3 Comment: A representative from Alcoa requested, when available, information on the monitoring and engineering controls proposed as part of the Site dredging project.

EPA Response: EPA agrees to provide the information related to the monitoring and engineering controls to Alcoa when the remedial design is finalized. Copies of the final remedial design report and supporting documentation will also be available to the public at the information repositories.

3.5 Sediments and Dredging

3.5.1 Comment: Noting there are potential problems with dredging in this part of the St. Lawrence River, a representative from Reynolds objected to EPA's assertion that it would make the determination for further dredging or capping of the sediments if the cleanup goals are not met. Reynolds asserts if a cap is believed to be necessary, it should be addressed prior to implementation of the Plan. Also, EPA has not addressed the higher costs involved with the combination of dredging and in-situ containment.

EPA Response: EPA selected dredging as a component of the original remedy called for in the 1993 Decision Document. This Plan does not change that component of the remedy. EPA is only acknowledging the technical limitations which are associated with dredging sediment in a riverine environment, as it did in its 1993 Decision Document. EPA has not determined that capping of sediments on the river bottom is a necessary alternative, and it will not make such determination until the designed dredging project, as approved by EPA, is performed to the satisfaction of EPA in attempting to achieve the cleanup goal of 1 ppm for PCBs (see EPA Response to Comment No. 3.5.2, below).

3.5.2 Comment: A representative from Alcoa stated that the Plan indicates that, should the cleanup goals not be attained, capping of residual sediments may become necessary. Since it is possible that elevated levels of chemical constituents will remain following dredging, EPA acknowledges that capping provides an acceptable level of chemical constituent isolation and risk reduction.

It would logically follow that capping, in-and-of-itself, would provide the same remedial benefits without first having to dredge. In essence, Alcoa believes that dredging (for mass removal) followed by capping, does not meet the cost-effectiveness "test," since capping alone can achieve the same endpoint more cost-effectively (i.e., without the added cost burden of dredging).

EPA Response: EPA has a statutory preference for technologies, such as dredging, that permanently remove the long-term risks from contaminated sediments. EPA has determined that dredging is

an effective way of reducing the volume of contaminated sediments in the river system based on limited previous experience at other Superfund sites and federal projects. EPA anticipates that if the cleanup goals are not met with dredging, then a cap may be needed. However, that cap would be containing a smaller volume of contaminated sediment.

In 1993, during preparation of its original Decision Document, EPA did consider containment instead of dredging. Although sediment containment with a graded cover would reduce the erosive force of the flowing river water and would limit movement of contaminants into the environment, its long-term effectiveness is dependent on the adequacy and reliability of the sediment cover. Long-term monitoring and maintenance of contained sediments would be difficult to achieve because the cover is located underwater. Because the sediments are submerged, the contained underwater sediments would require periodic inspections by divers. In addition, several rounds of sampling might be required to detect underwater containment cell leakage, since leaking contamination would be diluted. Further, if underwater monitoring revealed that cap repairs were necessary, such repairs could likely only be undertaken in late spring or in summer. Little information is available on the frequency with which maintenance would be needed or on the probability of cover failure. If the sediment cover fails, contaminated sediments would reenter the river system and become available for uptake by the biota and wildlife. Sediment dredging, on the other hand, would permanently remove the long-term risks associated with the contaminated sediments that are removed.

3.5.3 Comment: Representatives from the St. Regis Mohawk Tribe, noting that the remedy has not yet been designed, cautioned against handling or storage practices which threaten to suspend and volatilize PCB contaminants into the air. This is particularly so since Reynolds impacts Akwesasne's air resources.

EPA Response: An air monitoring program is being developed as part of the ongoing remedial design for the protection of Site workers and the community. Air monitoring will be performed during construction and include the real-time monitoring of contaminant levels and particulates in the breathing zone and work zone. Additionally, it will include monitoring downwind of the work zone and at the perimeter of the Site for the protection of the nearby community. Action levels for the monitored contaminants and particulates will be established. In the event that an established action level is exceeded, appropriate actions will be promptly taken to evaluate and mitigate the condition, as appropriate. Such actions may include the temporary stoppage of work and use of vapor suppressant controls.

3.5.4 Comment: A local reporter asked what steps will be taken during the dredging process to ensure contaminants do not move further downriver.

EPA Response: A number of techniques will be used to prevent the resuspension and transport of contaminants during dredging. First, the selection of the dredging technique (*i.e.*, environmental dredge bucket) was made with the goal of minimizing sediment resuspension. Unlike buckets used in navigational dredging, the bucket that will be used was designed specifically for environmental dredging projects, where turbidity is a concern.

In addition, the use of engineering controls such as steel sheet piling walls has been shown at other dredging projects to substantially reduce sediment resuspension. Steel sheet pilings will be driven into the riverbed, forming a wall around the dredging area to prevent any re-suspended sediments from moving outside the dredging area. The wall will also reduce the currents within the enclosure, making dredging easier. To prevent areas of higher contamination from affecting areas of lower contamination, silt curtains will be installed within the sheet piling wall to separate these areas.

EPA's selected remedy includes development of a dredging monitoring plan and sampling activities to measure the environmental impacts of dredging. This will include monitoring river water quality outside the sheet piling wall to detect contaminants moving beyond the wall during dredging. The selected remedy also includes a contingency plan, which will describe measures to control or minimize the impacts of dredging on the environment.

3.5.5 Comment: A Research Scientist from SUNY-Oswego asked whether the distribution of polycyclic aromatic hydrocarbons (PAHs) and total dibenzofurans (TDBFs) are consistent with the distribution of PCBs in the sediments.

EPA Response: Yes, the distribution of PAHs and TDBFs found in the St. Lawrence River sediments falls within the area containing PCBs. The higher concentrations of these chemicals were found, as were PCBs, closer to the shoreline and in proximity to several outfalls located at the Reynolds facility.

3.5.6 Comment: A representative from Alcoa agreed with EPA's conclusion that, given the technological limitations associated with today's dredging equipment, along with the site-specific conditions of the targeted river bottom, attainment of the proposed cleanup levels may not be possible. This position is based upon related experiences at other PCB-dredging sites

throughout the country. Data obtained from these sites have shown the inability of various dredging methods to meet low targeted cleanup levels on a consistent basis.

EPA Response: Please refer to EPA's Response to Comment No. 3.5.1, above.

3.5.7 Comment: Representatives of the St. Regis Mohawk Tribe stated that Footnote 2 on page 8 of the Plan leaves some ambiguity by suggesting that PCBs are somehow lost in the dredging process. This is not the case. Dredging is a very effective remedy and, when properly done, PCBs are not resuspended in the water column or air in such a manner that threatens downstream or downwind resources. Rather, the Tribe understands that the footnote suggests a certain kind of averaging or mixing may occur during the dredging process such that data gathered from the dredged materials tend to have lower values than hot spots which have already been identified in the in-situ sediment sampling.

EPA Response: Please refer to EPA's Response to Comment No. 3.5.4, above, which describes in further detail the mixing and resuspension of sediments during dredging operations.

3.5.8 Comment: The owner of a water distribution company who is a resident of Akwesasne stated that drinking water should be supplied to all residents of Akwesasne, both the U.S. and Canadian side, during dredging. The cost of this temporary distribution of water should be assumed by Reynolds. This program should be set up fairly through a bid process.

EPA Response: EPA does not believe that the dredging project will impact either the Canadian or Akwesasne drinking water supplies. The steel sheet piling wall which will be used during the dredging project should prevent any resuspended sediment from being transported downstream by currents. Additionally, the dredging monitoring plan and sampling activities which will be performed to monitor environmental impacts during dredging, will include the monitoring of river water quality on the outside of the sheet piling wall. The monitoring of water quality on the outside of the wall will determine the effectiveness of the wall in containing resuspended sediments.

Further, as a precautionary measure, additional water quality sampling and analyses will be performed at the St. Regis Mohawk Tribe's potable water treatment facility during dredging to verify that water treated at this facility is not adversely impacted during the dredging operation. The frequency of sampling, which will depend on the status of the dredging operation, the actions levels and responses will be specified in

the environmental monitoring plan which is currently being prepared. Additional water quality monitoring was performed at the St. Regis Mohawk Tribe's water treatment facility and a non-transient, noncommunity water supply facility located at the GM plant during the dredging operation conducted at the GM Superfund site.

3.6 Other

3.6.1 Comment: Representatives from the St. Regis Mohawk Tribe stated that the second column on page 6 of the Plan should be rewritten to reduce ambiguity and to describe the fate and treatment of the highly contaminated materials that were excavated from the North Yard area. Since these materials were perhaps the most toxic materials on the Reynolds site, it is very important to explain to the public what happened to them.

EPA Response: The Plan includes a brief summary of the North Yard area, the contamination found there during past investigations, and NYSDEC's selected remedy. The soils at the North Yard were found to contain the highest levels of PCBs (89,000 ppm) at the Reynolds Facility. The original remedy selected by NYSDEC in its 1992 ROD called for the excavation, treatment, and on-site disposal of all contaminated soil from the North Yard area with PCB levels exceeding 25 ppm. The remaining soils were covered with a multilayered asphalt cap.

NYSDEC modified its remedy in a 1995 ROD amendment. The modified remedy generally called for all excavated soils having PCB levels of 50 ppm and greater to be sent to an approved off-site facility for landfilling. The facility selected by Reynolds was the Chemical Waste Management's landfill in Model City, New York. The excavated soils having PCB levels between 25 and 50 ppm were consolidated in the on-site Industrial Landfill.

3.6.2 Comment: A Research Scientist from SUNY-Oswego asked whether there was a drainage ditch located just upriver from Reynold's outfalls.

EPA Response: Yes, there was a drainage ditch located on Reynold's facility, just upriver from the outfalls. Reynolds remediated the drainage ditch in the early 1990s as part of NYSDEC's land-based cleanup. The water that was running through the drainage ditch to the river has been rerouted back to the on-site carbon treatment plant where it is treated and then reused at the Reynolds Facility. Much of the effort in implementing the land-based cleanup focused on cleaning up surface-water discharges to the river, such as this one.

3.6.3 Comment: A resident noted, in the past, PCBs were added to hydraulic oil as a flame retardant. He asked what chemical is used today to create flame-retardant hydraulic oil and what are its toxic properties. He expressed concern that the chemical that is used today could create another "PCB situation" in the future.

EPA Response: Oils containing PCBs were used as cooling oils for transformers and other industrial purposes because PCBs are stable and fire-resistant. Due to their toxicity, tendency to bioaccumulate, and their persistence in the environment, EPA banned (with certain exceptions) the manufacturing, processing, and distribution of PCBs as of January 1, 1977. Today, mineral oils, organosilicate esters, and alkylated aromatics have replaced PCBs as cooling oils and fluids for transformers and industrial uses. Mineral oils are not chlorinated, halogenated, flammable, or classified as hazardous substances. The mineral oils used for transformers and other industrial purposes today are natural products that are not known carcinogens. Organosilicate esters and alkylated aromatics may also be used as heat transferring fluids. These compounds also are not classified as carcinogens and have very low toxicity. The alkylated aromatics are currently used at the Reynolds Facility.

3.6.4 Comment: A resident expressed concern that waste material from the Site will be taken to a dump in Buffalo where it will leak from the dump through rips in the landfill liner, flow through the shallow limestone, flow to Lake Ontario, and eventually flow back down the St. Lawrence River.

EPA Response: Under TSCA, dredged materials that contain PCBs at concentrations greater than or equal to 50 ppm must be landfilled in a TSCA-approved chemical waste landfill, incinerated, or disposed of by another method approved by EPA.

To comply with the TSCA regulations for the disposal of PCBs, Reynolds has proposed transporting the contaminated sediments off-site to the Chemical Waste Management's chemical waste landfill, located in Model City, New York. The Chemical Waste Management's landfill is a TSCA- and RCRA-permitted disposal facility where hazardous wastes are managed in a secure and monitored location. The landfill has a liner, engineering controls and monitoring wells to assure the long-term effectiveness of the landfill as a containment system. Once the off-site disposal facility is established, EPA would check the facility to ensure that it is in compliance with all applicable TSCA requirements. All necessary approvals would be obtained prior to disposal to ensure that the sediments meet the facility's permit restrictions.

A chemical waste landfill used for the disposal of PCBs must be approved by EPA and must meet the requirements specified in TSCA. The landfill must be located in thick, relatively impermeable geologic formations or the soil must have a high clay and silt content which meets specific requirements for parameters such as permeability, plasticity, and particle size. The bottom of the landfill must be above the historical high groundwater table and there must be no hydraulic connection between the landfill and standing or floating surface water. Monitoring wells and leachate collection systems are used to ensure that off-site releases do not occur. Flood protection or stormwater diversion systems also are required to protect the integrity of the landfill. In addition, PCBs and materials containing PCBs must be placed in the landfill in a manner that prevents damage to containers, and incompatible wastes must be segregated. All of these requirements are in place to prevent movement of leachate or materials from the landfill.

3.6.5 Comment: A local reporter asked about the schedule for implementing the Plan.

EPA Response: Dredging contaminated sediments from the St. Lawrence River is one aspect of the Plan that did not change. Therefore, although EPA waited until after the public comment period to select the disposal option outlined in the Plan, the design for the dredging program has been proceeding. Since the remedial design is nearing completion, EPA anticipates that the dredging program will commence in the Spring of 1999.

3.6.6 Comment: A representative from Alcoa quoted from the Plan that the mouth of the Grasse River at the confluence of the St. Lawrence River was originally identified as part of the Site. He requested rationale for the removal of this portion of the Site and its current inclusion as part of the Alcoa Study Area. He also requested that EPA explain the details surrounding this decision and to explain what portion of the Site was transferred.

EPA Response: EPA has not redefined the boundary of the Site to exclude the mouth of the Grasse River, even though it is located upstream of the Reynolds facility. However, the contaminants found there are similar to those detected in the lower reaches of the Grasse River that were attributable to the Alcoa facility. In light of those similarities, and because the mouth of the Grasse River is located downstream of the Alcoa facility, EPA will continue to examine the area as part of the ongoing investigation of the river system surrounding Alcoa.

APPENDIX A

POST-DECISION PROPOSED PLAN

July 1998

500505



Region 2

Reynolds Metals Superfund Site

Massena, St. Lawrence County, New York

July 1998

Mark Your Calendar

July 30, 1998 – August 28, 1998

Public comment period on the Post-Decision Proposed Plan for the Reynolds Study Area Site.

Wednesday, August 12, 1998

6:00 pm

Public Meeting at Massena Public Library, 41 Glenn St., Massena, NY

Thursday, August 13

5:00 – 7:00 pm

Availability session at St. Regis Housing Authority Auditorium, Hogansburg, NY

Community Role in the Selection Process

EPA relies on public input to ensure that the concerns of the community are considered in selecting an effective remedy for each site. This Plan is being distributed to solicit public comments regarding proposed changes to the remedy selected in EPA's 1993 Decision Document for the Site.

A public comment period will begin on July 30 and continue through August 28. A public meeting will be held during the public comment period at the Massena Public Library on Wednesday, August 12 at 6:00 pm to discuss the basis of the proposed changes. An availability session will be held on

PURPOSE OF POST-DECISION PROPOSED PLAN

This Post-Decision Proposed Plan (hereinafter the "Plan") describes proposed changes to the remedy selected by the U.S. Environmental Protection Agency (EPA) in its September 1993 Decision Document for the Reynolds Metals Company (Reynolds) Study Area Site (hereinafter the "Site"). This Plan was developed by EPA in consultation with the New York State Department of Environmental Conservation (NYSDEC).

The original remedy selected in 1993 addressed contaminated sediments in that portion of the St. Lawrence River located in the vicinity of the Reynolds facility (Facility). The major components of that remedy were: (1) dredging of river sediments contaminated with polychlorinated biphenyls (PCBs) and other chemicals; (2) on-site treatment of sediments with PCB concentrations greater than 25 parts per million (ppm); and (3) on-site disposal of treatment residuals and sediments having PCB levels less than or equal to 25 ppm in the Black Mud Pond (a former disposal pit at the Facility). The remedy did not address contamination present on the land-based portion of the Facility. The land-based cleanup was performed under the direct oversight of NYSDEC.

EPA is proposing changes to the original remedy which are equally protective of human health and the environment, but are significantly less expensive. Under this Plan, the more contaminated river sediments (PCB levels equal to 50 ppm or greater) would be disposed of at an approved off-site facility; sediments with PCB levels exceeding 500 ppm would be treated off site, while sediments with PCB levels between 50 and 500 ppm would be landfilled off site. The lower level contaminated sediments (less than 50 ppm of PCBs) would be disposed of at the Industrial Landfill, another disposal area located at the Facility. The cost savings are due to a change in market conditions which has significantly improved the cost-effectiveness of off-site disposal as compared to on-site treatment. Additionally, there has been an increase in the estimated volume of contaminated sediment which would require treatment.

The proposed changes would also be consistent with NYSDEC's land-based cleanup, where approximately 135,300 cubic yards (yd³) of soil with low levels of PCBs (less than 50 ppm) have been consolidated in the Industrial Landfill. If the actions described in this Plan are implemented, it is estimated that an additional 43,400 yd³ of sediment would be disposed therein. Following such disposal, the Industrial Landfill would be capped as part of NYSDEC's program.

Thursday, August 13 from 5:00 – 7:00 pm at the St. Regis Housing Authority Auditorium, Hogansburg, NY.

EPA will make a determination regarding the proposed changes to the remedy only after the public comment period has ended and the information submitted during this time has been reviewed and considered. In addition to oral comments, which may be submitted at the public meeting, written comments may be addressed to:

*Mark Purcell, Remedial Project Manager
U.S. Environmental Protection Agency
290 Broadway, 20th Floor
New York, NY 10007-1866*

The proposed changes summarized herein are described in Reynolds' October 22, 1997 document entitled "Request for Modification of Decision Document, St. Lawrence River Sediments," which should be consulted for a more detailed description. This document and others relating to the Site are available at the following locations:

*U.S. Environmental Protection Agency
290 Broadway, 18th Floor, New York, NY 10007-1866
By appt.: 212-637-3263*

*Massena Public Library
41 Glenn Street, Massena, NY 13662
Mon & Fri, 9:30 am – 5:00 pm;
Tues–Thur, 9:30 am – 9:00 pm; Sat & Sun, closed*

*St. Regis Mohawk Tribe - Environmental Division
Health Services Building, Hogansburg, NY 13655
By appt.: 518-358-3141*

EPA is issuing this Plan as part of its public participation responsibilities under Section 117(a) of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA), as amended, and Section 300.430(f) of the National Contingency Plan (NCP).

Background

The Reynolds Facility is an active aluminum production plant located on 1,600 acres in the Town of Massena, New York. It is bordered on the north by the Grasse and St. Lawrence Rivers, on the east by the New York Central Railroad, on the west by Haverstock Road (South Grasse River Road), and on the south by the Raquette River. The Facility is located off Route 37 near the Massena-Cornwall International Bridge, and directly

upriver of the General Motors-Powertrain Division Plant, a federal Superfund site being remediated under the direct oversight of EPA. St. Regis Mohawk tribal lands, known as Akwesasne, are within one-half mile of the Facility. The Aluminum Company of America (Alcoa) manufacturing facility is located eight (8) miles west and upriver of the Facility. EPA also oversees the cleanup of the river system surrounding the Alcoa facility (*see also Figure 1*).

The cleanup of the Reynolds Facility and surrounding areas is divided into two phases which are being overseen separately by state and federal regulatory authorities: NYSDEC oversees the land-based portion of the cleanup, and EPA oversees the cleanup of the river system adjacent to the Reynolds Facility, designated as the "Reynolds Study Area" (the Site). The Site includes those portions of the St. Lawrence, Grasse, and Raquette Rivers, their tributaries, and any wetlands which are adjacent to the Reynolds Facility¹.

Reynolds Facility

The Reynolds Facility was constructed in 1958 for the production of aluminum. The plant buildings occupy about seven percent or 112 acres of Reynolds' property. The remaining portion of the property consists primarily of forested areas and wetlands.

The aluminum is produced in individual metal pots which are lined with *potliner*, a material composed of a mixture of carbon compounds, including coal tar pitch and coke. As a result of plant operations, various types of industrial waste, including hazardous substances, were generated and disposed of at the Facility. Major areas of contamination include the Black Mud Pond, the Industrial Landfill, a Former Potliner Storage Area, a wetland, and the North Yard. Other areas of contamination include the plant outfalls (open drainage ditches), which discharge wastewater and surface-water runoff from the Facility to the St. Lawrence River (*see also Figure 2*). The Facility has been placed on NYSDEC's Registry of Inactive Hazardous Waste Sites.

In general, the topography of the area is characterized by low, elongated ridges of glacial till that generally trend northeast-southwest. Broad, flat valleys between the ridges contain marshy areas and meandering streams that drain to the St. Lawrence, Raquette, and Grasse rivers.


¹ The Site is part of the St. Lawrence/Grasse River Site (Site Code: 6-45-15) listed on the New York State Registry of Inactive Hazardous Waste Sites.

eneath the Facility is approximately 100 feet of overburden materials, consisting primarily of glacial till and clay, overlying fractured carbonate bedrock. Miscellaneous fill materials (reworked till) and a sand deposit are present above the till in several areas of the Facility. The sand deposit is encountered at a depth of approximately five to ten feet below the ground surface. Ground water within the overburden is present primarily in the more permeable sand deposits and fill materials. To a lesser degree, water is present in the underlying till. Ground-water flow at the Facility reflects the local topography, flowing toward both the St. Lawrence River to the north and the wetland and Raquette River to the south. A ridge of glacial till running through the area of Black Mud Pond forms the ground-water divide between the Raquette and St. Lawrence Rivers.

Black Mud Pond

Black Mud Pond was an unlined disposal pit constructed in 1973 along the western side of the Facility. Its purpose was to hold settling carbon solids produced as a by-product of plant operations. The Pond had a surface area of approximately six acres and a volume of approximately 20 million gallons prior to its closure by NYSDEC in 1996 (*see also NYSDEC's Land-Based Cleanup, below*). It is estimated that the Pond contained 165,000 yd³ of black mud, underlain by approximately 22,000 yd³ of contaminated soil. The waste materials consisted primarily of alumina (30–40 percent), carbon (35–45 percent) and fluoride (2–5 percent). Cyanide and PCBs were also present at concentrations up to 61 ppm and 8 ppm, respectively. The ground water beneath the Pond, which occurs at depths ranging from a few feet to 15 feet, contains elevated concentrations of several contaminants, including cyanide, fluoride, PCBs, phenols, and sulfate. The low permeabilities of the underlying till have prevented the ground-water contaminants from migrating from the Pond area.

Figure 1
Site Location Map




Industrial Landfill and Former Potliner Storage Area

The Industrial Landfill is an unlined landfill which covers an area of approximately 11.5 acres and is located near the southwest corner of the Reynolds Facility. Ground water is encountered in the fill materials directly

beneath the Landfill at depths between five and eight feet below the ground surface. The ground water generally flows to the south to discharge to the wetland. There is an upward vertical component of flow in the shallow ground-water zone. From 1957 to 1990, Reynolds disposed of solid waste, industrial debris, spent potlining waste, and PCB-contaminated sewage sludge at the Landfill.

Figure 2
PCB Contamination in the Reynolds Study Area



The Industrial Landfill and the adjacent Former Potliner Storage Area can be characterized as one contaminant source area, based on their proximity and similarity of contaminants. Waste materials at the Landfill and the underlying soil were contaminated with several chemicals, including cyanide (300 ppm), fluoride (8,500 ppm), aluminum (87,000 ppm), sulfate (13,000 ppm), polycyclic aromatic hydrocarbons (PAHs) (2,200 ppm), PCBs (690 ppm), and phenols (21 ppm).

Several contaminants were also detected in the shallow ground water at elevated concentrations, including cyanide, fluoride, PCBs, phenols, and sulfate.

Prior to 1984, most surface-water runoff discharged directly to a portion of the wetland. Leachate seeps which formed in the northwest corner of the Landfill frequently overflowed the containment berm and discharged to the wetland via a nearby small stream. In 1984, Reynolds installed a partial leachate collection system at the Industrial Landfill to collect and store leachate for treatment. Additional measures included the construction of surface-water controls and placement of vegetative cover on portions of the Landfill perimeter. A leachate collection underdrain was also installed to intercept the flow of contaminated ground water from the Landfill to the wetland. The leachate and ground water recovered by the collection system were initially sent through the Facility's existing treatment plant air scrubbers and subsequently discharged to the St. Lawrence River via a permitted outfall. After 1991, they were sent to the new carbon treatment plant located in the North Yard prior to discharging to the St. Lawrence River.

Wetland

A tract of regulated wetlands covering approximately 170 acres (identified as No. RR-6 by NYSDEC) occurs on the Reynolds property directly south of the Industrial Landfill. It is one of the three largest wetlands in the Town of Massena. The wetland is a ground-water discharge area for the southern portion of the property. Drainage from the wetland flows southward via two streams and discharges into the Raquette River. Prior to the construction of the partial surface-water runoff controls and leachate collection system for the Landfill area, the leachate, ground water, and surface water from the Landfill area discharged directly to the wetland. The wetland also received contaminated sediment and surface water which drained from other areas of the Facility.

Several contaminants were found in the wetland sediments at elevated concentrations, including aluminum, arsenic, cyanide, fluoride, sulfate and phenols. PCBs were also detected in the sediments at concentrations ranging up to 19 ppm. Contaminants found in surface-water samples collected from the wetland included PCBs, chrysene, fluoride and bis(2-ethylhexyl)phthalate.

North Yard

The North Yard is an area used to maintain the temperature and fluidity of the coal tar pitch used in the aluminum production process. In the past, Reynolds operated a heat transfer system which actively pumped a fluid containing PCBs from the Pitch Pump House to inside the plant. Through leaks and spills over the life of that system, high levels of PCBs accumulated in the soil in the North Yard area. The system was retrofitted with non-PCB oils in the early 1980's.

The North Yard is central to the majority of production activities. All of the raw materials and finished products enter and leave the Facility through this area. Other plant facilities at the North Yard include the unloading shed for receiving alumina, coke, soda ash and fluoride, the pitch storage tanks and the truck unloading dock.

Ground water is present in the fill materials (reworked till) beneath the North Yard area at depths ranging from 2 to 15 feet and flows northward into the St. Lawrence River. Man-made structures (*i.e.*, utility trenches and a drain collection system) in the southern part of the North Yard area act as preferential pathways for ground-water flow.

Past investigations in the North Yard area revealed the presence of several contaminants in the soil and ground water. PCBs, polychlorinated dibenzofurans (PCDFs), and polychlorinated dibenzo-p-dioxins (PCDDs) were detected in the soil. PCB levels were found as high as 89,000 ppm. PCDDs and PCDFs were detected in soils primarily near the pitch pump house at concentrations of 9.92 parts per billion (ppb) and 9.35 ppb, respectively. Aluminum, arsenic, cyanide, fluoride, phenols, and PCBs, among other contaminants, were detected in the ground water at elevated concentrations.

Due to the limited horizontal extent of the fill materials in the North Yard area and the very low permeabilities of the underlying till, the extent of the ground-water contamination is limited to the southern portion of the North Yard

area. No contaminants were found to have migrated into the St. Lawrence River from the ground water at the Facility.

Outfalls

There are four outfalls permitted under the State Pollution Discharge Elimination System (SPDES) program for discharging wastewater and surface-water runoff from the Facility to the St. Lawrence River.

Outfall 001 discharges wastewater from the carbon treatment plant located at the North Yard and surface-water runoff from the majority of the plant, including the North Yard area. Surface-water runoff and shallow ground water collected from the North Yard area is sent to the carbon treatment plant before discharging to the outfall. Surface water and leachate recovered from the collection system at the Industrial Landfill is also sent to the carbon treatment plant before reaching the outfall.

Outfall 002 discharges contact cooling water and storm-water runoff from the Facility. It carries the highest volume of water (averaging 2.5 million gallons per day) of the four outfalls. Prior to 1989, the discharge traveled down an open ditch at the Facility to enter the St. Lawrence River at the head of a small embayment. After 1989, this discharge was combined with that of Outfall 003. The outfall is currently designated as 005 by NYSDEC's Division of Water.

Outfall 003 discharges treated effluent from the sanitary treatment plant through an offshore, submerged pipe.

Outfall 004 is an open ditch which previously discharged intermittent runoff from diked areas in the northern portion of the Facility. The discharge is now diverted to the North Yard carbon treatment plant and subsequently used in production operations. This outfall is currently designated as 006 by NYSDEC's Division of Water.

NYSDEC's Land-Based Cleanup

In 1987, following the completion of several remedial investigations at the Facility, Reynolds entered into a Consent Order with NYSDEC to develop and implement a Facility-wide remedial program. Soon thereafter, Reynolds implemented several interim remedial measures (IRMs) at the Facility to minimize releases to the environ-

ment pending NYSDEC's selection of a final remedy. The IRMs included the cleanup of PCB-contaminated soil to levels of 10 ppm or less at Outfalls 002 and 006. A drain collection system was also installed in the southern portion of the North Yard area to collect contaminated ground water for treatment at the North Yard carbon plant.

NYSDEC issued a Record of Decision (ROD) in 1992 which outlined its selected remedy for the land-based portion of the Facility. The areas to be remediated included the Black Mud Pond, the Industrial Landfill and Former Potliner Storage Area, a portion of the wetland, and the North Yard area. The major components of the remedy included: (1) the dewatering and capping in-place of the waste materials and soils at Black Mud Pond with a Resource Conservation and Recovery Act (RCRA) cap; (2) the excavation, treatment and on-site disposal of all contaminated soil from the North Yard area with PCB levels greater than or equal to 25 ppm; (3) the capping of the remaining soil at the North Yard with a multilayered asphalt cap; (4) the excavation of soil and sediment with PCB concentrations greater than 1 ppm from the wetland and 10 ppm from other areas at the Facility for disposal in the Industrial Landfill and Former Potliner Waste Disposal Area; and (5) the installation of a new leachate collection system at the Industrial Landfill and capping of the Landfill and Former Potliner Waste Disposal Area with a RCRA cap. The ROD specified incineration as the chosen treatment technology but allowed Reynolds to evaluate other technologies, including solvent extraction and thermal desorption. In 1993, Reynolds and NYSDEC signed a Consent Order for Reynolds to implement the remedy.

NYSDEC's remedy did not address the contamination found in the sediments of the St. Lawrence River. That area of contamination is part of the Site and is being remediated through enforcement actions taken by EPA (see also Reynolds Study Area, below).

In January of 1995, Reynolds requested an amendment of NYSDEC's 1992 ROD for off-site disposal rather than on-site treatment, since a change in market conditions had significantly reduced the cost of off-site landfilling. In June of 1995, NYSDEC issued an *Amendment to the Record of Decision* to modify the selected remedy. The Amendment eliminated the requirement for on-site treatment and instead required off-site disposal of contaminated soil with PCB concentrations greater than or equal to 50 ppm. Excavated soils with less than 50 ppm of PCBs were to be consolidated in the on-site Industrial Landfill prior to capping.

To date, all land-based remedial work has been completed, with the exception of the capping of the Industrial Landfill. Approximately 135,300 yd³ of excavated soil with PCB concentrations of less than 50 ppm have been consolidated into the Industrial Landfill. Capping will be completed following placement into the Landfill of the additional sediments to be dredged from the St. Lawrence River as part of EPA's remedial efforts.

Reynolds Study Area

In 1988 and 1989, Reynolds performed an initial study of the sediments in the St. Lawrence River adjacent to its Facility. A total of 67 sediment samples were collected at 35 sampling locations along the riverbed. The analytical results showed PCBs were present in 17 sediment samples at concentrations ranging from 10 ppm to greater than 1,000 ppm. The highest concentrations were found in samples collected from within 250 feet of the Facility outfalls, primarily Outfall 001.

Based on the findings of Reynolds' riverbed study, EPA issued a Unilateral Administrative Order in 1989 requiring that Reynolds investigate and clean up contamination in the entire river system surrounding its Facility. The river system was designated the "Reynolds Study Area" (the Site) and included that portion of the St. Lawrence, Grasse, and Raquette Rivers, their tributaries, and any wetlands which were adjacent to the Facility.

It is noted that some areas of the Site are being addressed as part of other remedial programs. First, the mouth of the Grasse River at the confluence of the St. Lawrence River, which was originally identified as part of the Site, was found to contain contaminants similar to those detected in the lower reaches of the Grasse River that were attributable to the Alcoa facility. The area is being examined further as part of EPA's ongoing investigation of the river system surrounding Alcoa. Also, the wetland on the Reynolds property is part of the Site, but has been investigated and remediated as part of NYSDEC's land-based cleanup.

In 1991 and 1992, Reynolds performed an Additional River Sampling (ARS) program at the Site to characterize the nature and extent of contamination further. The results of that study revealed the presence of several contaminants at elevated concentrations in the sediments of the St. Lawrence River adjacent to the Facility. The primary

contaminants were PCBs, at a maximum concentration of 1,300 ppm. Other contaminants included PAHs (3,734 ppm), total dibenzofurans (TDBFs) (440 ppb), fluoride (1,040 ppm), and cyanide (37 ppm). The higher concentrations of these contaminants were found in sediment samples collected within 500 feet of the Reynolds outfalls, with the highest being in the immediate vicinity of Outfalls 001 and 006. Contaminant concentrations generally decreased in sediment samples which were collected further away from the shoreline.

PCBs were not detected in the water samples taken by Reynolds from the St. Lawrence River. However, NYSDEC has detected PCBs in surface water at concentrations up to 54 parts per trillion using more sensitive analytical techniques. PAHs were found in only one water sample at concentrations up to 11 ppb. Several metals were also detected in water samples from both the St. Lawrence and Raquette Rivers at concentrations above background levels, including aluminum (0.74 ppm).

In light of these findings, it was concluded that the sources of the contaminants at the Site were the uncontrolled surface-water runoff and wastewater discharges from the outfalls at the Reynolds Facility into the St. Lawrence River.

Using the data from Reynolds' ARS, EPA performed baseline human health and ecological risk assessments to evaluate the potential risks to human health and the environment associated with the Site. The results of those assessments showed that the contaminated sediments at the Site posed a threat to human health and the environment. The greatest health risk was associated with the ingestion of PCB-contaminated fish caught in the St. Lawrence River by residents and fishermen. Other health threats were associated with the direct contact or ingestion of contaminated sediments.

Based on the findings of Reynolds' ARS, its subsequent Analysis of Alternatives, and EPA's consideration of public comments and community concerns, EPA issued a Decision Document in September of 1993 for the cleanup of contamination in the St. Lawrence River sediments adjacent to the Reynolds Facility. The major components of the remedy included: (1) the dredging of all sediments with PCB levels exceeding 1 ppm, PAH levels exceeding 10 ppm, and TDBF levels exceeding 1 ppb; (2) the on-site treatment of sediments with PCB concentrations greater than 25 ppm by thermal desorption, with the contaminants that are condensed in the treatment process

being sent off site for incineration; and (3) the consolidation of the treatment residuals, along with the untreated sediments having PCB levels of 25 ppm or less, in Black Mud Pond. The Pond would subsequently be capped as part of NYSDEC's land-based remedial program. The water recovered during the dewatering of dredged sediments would also be treated on site and discharged to the St. Lawrence River via a permitted outfall. Prior to dredging, additional sediment and surface-water sampling in the St. Lawrence River would be performed to delineate the extent of the area to be dredged. It was estimated that the remedy would be completed in 4 years following the start of construction.

In 1994, Reynolds began design of the remedy. Sediment and surface-water sampling were performed in the St. Lawrence River to delineate the extent and volume of the sediments to be dredged. The results of the additional sampling showed the volume of contaminated sediment to be significantly greater than originally estimated (*see also Table 1*). For sediments having PCB levels between 1 and 25 ppm, the current estimate of 38,700 yd³ was only slightly higher than the original estimate of 37,000 yd³. However, for sediments having PCB levels exceeding 25 ppm, the current estimate of 38,900 yd³ was almost three times greater than the original estimate of 14,500 yd³. Table 1 depicts the 38,900 yd³ as three separate volume estimates for PCB levels in the range of between 25 and 50 ppm (4,700 yd³), 50–500 ppm (29,700 yd³), and greater than 500 ppm (4,500 yd³).

Table 1

Comparison of the 1993 & Current Estimates of Sediment Volumes To Be Dredged from the St. Lawrence River

PCB Concentration Range (ppm)	1993 Volume Estimate (yd ³)	Current Volume Estimate (yd ³)
Between 1 and 25	37,000	38,700
Greater than 25	14,500	
Between 25 and 50		4,700 ²
50 to 500		29,700
Greater than 500		4,500
Total	51,500	77,600

²It is noted that the 4,700 yd³ combined with the 38,700 yd³ having PCB levels between 1 and 25 ppm results in a total of 43,400 yd³ of sediment with PCB levels of less than 500 ppm which would be landfilled on site under this Plan.

The results of the additional sampling also supported Reynolds' earlier findings that the higher concentrations of these contaminants are present closer to the shoreline. The 4,500 yd³ of sediment with PCB levels exceeding 500 ppm are located near the 001 and 006 Outfalls.

In 1995, Reynolds requested a modification of the remedy based on new information regarding the options for sediment disposal. A change in market conditions since 1993 had significantly reduced the cost of off-site disposal as compared to on-site treatment. Additionally, the present-worth cost for on-site treatment had increased to \$72.4 million, more than double the original cost estimate of \$35.1 million (*see also Table 2*).

In light of these factors, Reynolds proposed to eliminate the on-site treatment component of the remedy in favor of off-site disposal. Reynolds also proposed that sediments with PCB levels of greater than or equal to 50 ppm would be sent off-site for disposal, while sediments with less than 50 ppm of PCBs would be disposed of at the Reynolds Facility. The proposed increase in the PCB level from 25 to 50 ppm for on-site landfilling is consistent with NYSDEC's 1995 ROD Amendment for the land-based cleanup.

Scope and Role of Action

This Plan will modify two key elements of the original remedy selected by EPA in its 1993 Decision Document to address contaminated sediment in the St. Lawrence River; one concerning the use of treatment and the other concerning the allowable level of PCBs to be disposed of on site. Specifically, EPA is proposing the disposal of all dredged sediments with PCB concentrations greater than or equal to 50 ppm at an approved off-site landfill or treatment facility, depending on the level of PCB contamination, and the consolidation of all dredged sediments with PCB concentrations less than 50 ppm in the Industrial Landfill located at the Reynolds Facility. Sediments with PCB levels exceeding 500 ppm would be treated off site, while sediments with PCB levels between 50 and 500 ppm would be landfilled off site².

²A small percentage (6%) of the total volume of sediment to be dredged from the St. Lawrence River is estimated to contain PCBs at levels exceeding 500 ppm. While PCB levels as high as 1,300 ppm were detected, based on past experiences with dredging operations in riverine systems (e.g., the adjacent General Motors plant site), EPA expects that the range of PCB levels in the sediments after dredging will be significantly lower than currently identified due to the dredging process.

Table 2

Costs Associated with 1993 Remedy

Capital Cost:	\$72 million (originally estimated to be \$34.7 million based on 1993 volume estimates)
O & M Cost:	\$400,000 for post-remediation monitoring over a 5-year period (does not include O&M costs for long-term management of Black Mud Pond, which would be conducted under NYSDEC's land-based remedial program)
Present-Worth Cost:	\$72.4 million (originally estimated to be \$35.1 million based on 1993 volume estimates)
Time to Implement:	Approximately 4 years

The 50-ppm PCB level established for off-site disposal is consistent with federal and New York State (NYS) laws for regulating PCBs. Under the Toxic Substances Control Act (TSCA), dredged materials with PCB levels of 50 ppm or greater must be disposed in a TSCA-approved chemical waste landfill, incinerated, or disposed of by another method approved by EPA. Under the NYS hazardous waste program, the 50-ppm level is that which identifies PCBs as hazardous waste.

This Plan is also consistent with EPA's "Guidance for Remedial Actions for Superfund Sites with PCB Contamination" (also referred to as the "PCB Guidance"). According to such guidance for an industrial setting, materials with PCB levels in the 10–25 ppm range may be contained on site with minimal long-term management controls, while materials with higher PCB concentrations (*e.g.*, 25–50 ppm) may be contained on site with long-term management controls that include a cap and ground-water monitoring. The capping and monitoring requirements established by NYSDEC in its 1992 ROD for the on-site Industrial Landfill would meet the relevant and appropriate requirements of a RCRA hazardous waste landfill. The cover to be placed atop the Landfill would be a multilayered RCRA cap. A leachate collection system is in place and long-term management controls, including ground-water monitoring, would be performed as part of NYSDEC's land-based program. All monitoring data would be reviewed by NYSDEC and EPA to ensure that the integrity of the landfill cap and leachate collection system are maintained over time.

Finally, the 50-ppm PCB level is also consistent with NYSDEC's 1995 ROD Amendment for the land-based portion of the cleanup. Under NYSDEC's program, Reynolds has consolidated approximately 135,300 yd³ of soil with PCB levels less than 50 ppm into the on-site Industrial Landfill. An additional 43,400 yd³ of St. Lawrence River sediment with PCB levels of less than 50 ppm will also be consolidated therein.

EPA is *not* proposing to change the cleanup goals established for the Site. The goal of the remedial action is to remove sediments from the St. Lawrence River with PCB concentrations exceeding 1 ppm, total PAH concentrations exceeding 10 ppm, and TDBF concentrations exceeding 1 ppb. It is noted, however, that due to the technological limitations associated with dredging sediments from a riverine environment, those cleanup goals may be difficult to achieve.

EPA intends to remove contaminated sediments from the St. Lawrence River by dredging to predetermined limits which would be defined during the remedial design. Post-dredging sampling would then be performed to determine if the cleanup goal of 1 ppm of PCBs has been achieved. If such a goal is not achieved, then EPA would make a determination at that time whether further dredging and/or capping of the sediments is necessary.

Summary of Original Remedy and Proposed Changes

CERCLA requires that each selected site remedy be protective of human health and the environment, be cost-effective, comply with applicable or relevant and appropriate requirements (ARARs) or justify a waiver from those requirements, and utilize permanent solutions and alternative treatment technologies and resource recovery alternatives to the maximum extent practicable. In addition, the statute includes a preference for treatment as a principal element for the reduction of toxicity, mobility, or volume of the hazardous substances.

A comparison of the original remedy and the proposed changes to that remedy is presented below. The costs presented for each remedy include capital costs and net present-worth costs. Costs associated with post-remediation monitoring of the St. Lawrence River are also presented as operation and maintenance (O&M) costs. O&M costs for the Industrial Landfill are considered to

500514

part of the long-term management required under NYSDEC's land-based program and, therefore, are not included in this Plan. The time to implement reflects the total time required for construction of the remedy. This time frame does not include the time required to design the remedy.

Original Remedy Selected in 1993

The major components of the original remedy as specified in EPA's 1993 Decision Document include:

- dredging and/or excavation of approximately 51,500 yd³ of sediment with PCB concentrations exceeding 1 ppm, total PAH concentrations exceeding 10 ppm, and TDBF concentrations exceeding 1 ppb, from the St. Lawrence River adjacent to the Reynolds Facility;
- decanting and dewatering all dredged sediments, with the collected water being treated on site and discharged to the St. Lawrence River in compliance with the substantive SPDES requirements;
- treatment of approximately 14,500 yd³ of dredged and dewatered sediments with PCB concentrations exceeding 25 ppm by on-site thermal desorption, a process for removing contaminants through volatilization followed by condensation, and subsequent off-site incineration of the condensed PCB extract;
- disposal of the treated sediment residuals and approximately 37,000 yd³ of untreated sediment with low levels of PCBs (less than or equal to 25 ppm) in Black Mud Pond, which would be capped with a multilayered RCRA cap as part of NYSDEC's land-based program; and,
- monitoring of the St. Lawrence River sediments, water, and biota prior to, during, and after dredging operations.

The net present-worth of the original remedy, based on dredging 51,500 yd³ of sediment, was estimated to be approximately \$35.1 million. However, the estimated volume of contaminated sediment to be dredged from the St. Lawrence River has increased to 77,600 yd³, based on the results of additional sampling by Reynolds during performance of the remedial design. Subsequently, the estimated volume of the sediments requiring treatment (i.e., exceeding 25 ppm) has also increased from 14,500 yd³ to 38,900 yd³. Accounting for these differences, the net present-worth of the original remedy is now estimated at \$72.4 million (*see also* Table 2). The present-worth

value includes an estimated cost of \$400,000 to perform post-remediation monitoring, including ecological monitoring, in the St. Lawrence River over a five-year period. Since the long-term management of Black Mud Pond would have been performed under NYSDEC's land-based cleanup, there were no O&M costs associated with such efforts. The time estimated to implement the original remedy following completion of design work was 4 years.

Proposed Changes to the 1993 Remedy

The proposed changes to the 1993 remedy are as follows:

- eliminate the on-site thermal desorption treatment component of the remedy;
- landfill all dredged and dewatered sediments with PCB levels between 50 and 500 ppm (approximately 29,700 yd³) at an approved off-site facility;
- treat all dredged and dewatered sediments with PCB levels exceeding 500 ppm (approximately 4,500 yd³) at an approved off-site facility; and,
- consolidate all dredged and dewatered sediments with less than 50 ppm of PCBs (approximately 43,400 yd³) in the on-site Industrial Landfill, which will be capped in compliance with NYSDEC's 1992 ROD and 1993 Consent Order for the land-based cleanup; Black Mud Pond was capped in 1996 as part of NYSDEC's cleanup and, therefore, is not available for sediment disposal.

The 43,400 yd³ of sediment to be landfilled on site consists of 38,700 yd³ with PCB levels less than 25 ppm and 4,700 yd³ with PCB levels between 25 and 50 ppm (*see also* Table 1).

The present-worth cost of the remedy with the changes described above is estimated to be \$63.2 million (*see also* Table 3). This estimate includes a capital cost of approximately \$5.2 million for on-site landfilling of the 43,400 yd³ of sediment with PCB levels less than 50 ppm, \$9.5 million for off-site landfilling of the 29,700 yd³ of sediment with PCB levels between 50 and 500 ppm, and \$7.2 million for transporting and incinerating the 4,500 yd³ of sediment with PCB levels exceeding 500 ppm³.

³ For the reasons stated in the previous footnote, EPA considers that the volume of 4,500 yd³ of material greater than 500 ppm and associated treatment cost of \$7.2 million are conservative values, and the actual volume and associated cost may be significantly less.

Table 3

Costs Associated with Proposed Changes

Capital Cost:	\$62.8 million
O & M Cost:	\$400,000 for post-remediation monitoring over a 5-year period (does not include O&M costs for long-term management of the Industrial Landfill, which would be conducted under NYSDEC's land-based remedial program)
Present-Worth Cost:	\$63.2 million
Time to Implement:	Approximately 1-2 years

The other capital costs are primarily associated with the dredging program. The time estimated to implement the remedy following design completion is 1 to 2 years. Table 4 presents a comparison of the original remedy and the proposed changes.

Comparison of Original Remedy and the Proposed Changes

During the detailed evaluation of remedial alternatives, each alternative is assessed against nine evaluation criteria, namely, overall protection of human health and the environment; compliance with ARARs; long-term effectiveness and permanence; reduction of toxicity, mobility, or volume through treatment; short-term effectiveness; implementability; cost; and state and community acceptance. The evaluation criteria are described in Table 5.

A comparative analysis of the original remedy and the proposed changes to that remedy, based upon the nine evaluation criteria, follows.

Overall Protection of Human Health & the Environment

Both remedies (original and modified) are considered to be protective of human health and the environment. Both remedies would require the removal of contaminated sediments from the St. Lawrence River to cleanup levels established by EPA in its 1993 Decision Document. The original remedy would combine on-site treatment of the higher levels of contamination with on-site landfilling and

Table 4

Comparison of Proposed Changes to 1993 Remedy

1993 Remedy	Proposed Changes
Dredge the St. Lawrence River	No change
Treat dredged sediments with PCB levels > 25 ppm	Dispose of dredged sediments with PCB levels between 50 and 500 ppm in an off-site landfill; treat dredged sediments with PCB levels > 500 ppm at an off-site facility
Contain sediments with PCB levels ≤ 25 ppm on site in the Black Mud Pond	Contain sediment with PCBs < 50 ppm on site in the industrial landfill
Black Mud Pond will be capped as part of NYSDEC's land-based cleanup	Industrial landfill will be capped as part of NYSDEC's land-based cleanup
Monitor St. Lawrence River	No change
Present-Worth Cost: \$72.4 million (current estimate)	Present-Worth Cost: \$63.2 million

capping of treatment residuals and lower levels of contamination. The modified remedy would combine off-site disposal with on-site landfilling and capping. The off-site disposal would consist of landfilling sediments having PCB levels between 50 and 500 ppm and treating sediments with PCB levels exceeding 500 ppm. The removal of contaminated sediments from the St. Lawrence River, along with the alternatives for landfilling and/or treating the sediments, would minimize exposure to the PCBs and other contaminants and their availability to aquatic life.

Compliance with ARARs

ARARs are those federal and state environmental and public health regulations that specifically address a hazardous substance, pollutant, contaminant, remedial action, location, or other circumstance at a site. There are three classifications of ARARs: *chemical-specific*, which are health- or risk-based concentration limits of chemicals which may be found in, or discharged to, the ambient environment; *location-specific*, which are restrictions placed on the concentration of hazardous

substances or the conduct of activities solely because of the specific locations in which they occur; and *action-specific*, which are usually technology- or activity-based requirements or limitations on actions taken with respect to hazardous wastes.

The principle action-specific ARARs for the Site include the requirements of TSCA, the federal law that regulates the treatment, storage and disposal of PCBs based on their form and concentration. Under TSCA, dredged materials that contain PCBs at concentrations greater than or equal to 50 ppm must either be incinerated, landfilled in a TSCA-approved chemical waste landfill, or disposed of by another method approved by EPA. Both remedies would comply with all applicable TSCA requirements (40 CFR Parts 761.60-761.9). Landfilling or treatment of sediments with PCB concentrations of 50 ppm or greater would be performed in an off-site TSCA-approved landfill or treatment facility. All necessary approvals would be obtained prior to disposal to ensure sediments meet the facility's permit restrictions.

Both remedies would comply with all applicable or relevant and appropriate RCRA requirements and/or the corresponding NYS hazardous waste requirements for the identification, transportation, storage, treatment and disposal of hazardous waste (40 CFR Parts 261 through 264 and 268). Since materials with concentrations of PCBs that are greater than or equal to 50 ppm are regulated as hazardous wastes by NYS, its requirements for hazardous wastes are applicable and, therefore, would be met by the off-site disposal facility, if located in NYS.

The Clean Water Act (CWA) requirements for discharging directly to a surface-water body are also action-specific ARARs. Water collected from the dewatering of dredged river sediments or on-site thermal desorption would be treated and discharged into the St. Lawrence River via an outfall at the Reynolds Facility, which is permitted under the SPDES program. Such discharge would meet all NYS requirements under the SPDES program (6 NYCRR Parts 750 through 757). Additionally, because NYS water quality criteria or standards are relevant and appropriate requirements, the treated water would meet such criteria or standards for the protection of human health through fish consumption and the protection of wildlife (6 NYCRR Parts 700 through 706). Other action-specific ARARs under the CWA would include the water monitoring and management requirements of 40 CFR Parts 122 through 136.

Since dredging operations will be performed in navigable waters of the United States, the dredging operations would comply with Section 10 of the Rivers and Harbors Act and U.S. Army Corps of Engineers regulations (33 USC Part 403 and 33 CFR Parts 320-330).

For the operation of the thermal desorption unit under the original remedy, action-specific federal and NYS requirements and guidance for air emissions would be met (40 CFR Part 50; 6 NYCRR Parts 200, 201, 211, 212, 219 and 257; NYS Air Guide-1).

Location-specific ARARs would include Executive Orders 11988 and 11990 for floodplain management and the protection of wetlands (40 CFR Part 6.302 and 40 CFR Part 6, Appendix A) for actions that may occur within a floodplain or wetland and the Fish and Wildlife Coordination Act (16 USC Part 661 et seq; 40 CFR Part 6.302) for actions affecting a river. Other location-specific ARARs may include the National Historic Preservation Act requirements for recovering and preserving artifacts and preserving historic properties (36 CFR Parts 65 and 800), the Wild and Scenic Rivers Act for protection of recreational rivers (40 CFR Part 6.302(e)) and the NYS Coastal Zone Management Program (1 NYCRR Part 600).

There are no chemical-specific ARARs for sediments. NYSDEC's 1994 Technical Guidance for Screening Contaminated Sediments is a "To Be Considered" criterion.

Long-Term Effectiveness and Permanence

In general, landfilling remedies provide a lesser degree of permanence in remediating contamination at a site when compared with treatment alternatives that destroy contaminants. Incineration and thermal desorption would result in the destruction of PCBs and other contaminants. Landfilling provides for long-term effectiveness by the permanent management of the contaminants in a secure, monitored location where adequate and reliable engineering controls are provided. The original remedy would utilize thermal desorption, combined with off-site incineration of the condensed PCB extract, to destroy the higher levels of contamination. The modified remedy would utilize off-site incineration to destroy PCBs at levels exceeding 500 ppm. A combination of off-site and on-site landfilling would reliably contain the remaining contaminants over time. The long-term effectiveness of the Industrial Landfill as a containment system will be monitored to ensure the protection of ground water, surface

500517

Table 5
Evaluation Criteria

- **Overall Protection of Human Health and the Environment** addresses whether or not a remedy provides adequate protection and describes how risks are eliminated, reduced, or controlled through treatment, engineering controls, or institutional controls.
- **Compliance with ARARs** addresses whether or not a remedy will meet all of the applicable or relevant and appropriate requirements of other environmental statutes and requirements or provide grounds for invoking a waiver.
- **Long-Term Effectiveness** refers to the ability of a remedy to maintain protection of human health and the environment once cleanup goals have been met.
- **Reduction of Toxicity, Mobility, or Volume through Treatment** is the anticipated performance of the treatment technologies a remedy may employ.
- **Short-Term Effectiveness** addresses the period of time needed to achieve protection and any adverse impacts on human health and the environment that may be posed during the construction and implementation period until cleanup goals are achieved.
- **Implementability** is the technical and administrative feasibility of a remedy, including the availability of materials and services needed to implement a particular option.
- **Cost** includes estimated capital and operation and maintenance costs, and net present-worth costs.
- **State Acceptance** indicates whether, based on its review of this Plan, the state concurs, opposes, or has no comment on the preferred alternative.
- **Community Acceptance** will be assessed in the ROD Amendment following a review of the public comments received on this Plan.

water and wetlands at the Site and eliminate direct contact exposure. Such monitoring will be performed as part of NYSDEC's land-based remedial program.

Reduction in Toxicity, Mobility, or Volume through Treatment

Both remedies would reduce the toxicity, mobility, or volume of contaminants through treatment. The original remedy would utilize thermal desorption, combined with off-site incineration of the condensed PCB extract, to reduce the toxicity and volume of the higher levels of contamination by removal and ultimate destruction. The modified remedy would reduce the toxicity and volume of the high-level contamination (PCB levels exceeding 500 ppm) through treatment. Landfilling does not appreciably alter the toxicity or volume of the contaminants, but reduces their mobility through encapsulation.

Short-Term Effectiveness

For either remedy, there will be short-term impacts which have to be addressed when performing dredging and dewatering activities and the on-site landfilling of the lower levels of contamination. However, the potential short-term impacts of the modified remedy would be

significantly lower than for the original remedy. The time necessary to complete the off-site disposal alternative (1 to 2 years) is anticipated to be considerably shorter than that time estimated for procurement, mobilization, and operation of the thermal desorber (4 years). Although appropriate controls would be applied to minimize potential exposures to site workers, fewer workers would be required for the off-site disposal alternative, thereby reducing the overall exposure by field personnel. Further, potential risks to on-site workers will be lessened by reducing the material's handling requirements needed for on-site treatment. The potential for airborne particulates related to storage and handling of contaminated sediments would also be reduced as on-site stockpiling, screening and thermal desorption unit feeding activities associated with the treatment alternative would be eliminated. It is noted that, depending on the volume of sediment dredged and the number of vehicles available for each day of operation, temporary stockpiling of the sediments on site may be necessary. In the event such stockpiling is required, the sediments would be managed in a manner to protect site workers and minimize the potential for contaminant migration. Potential air impacts from the operation of the thermal desorber are also eliminated. There will be short-term risks associated with transporting PCB-contaminated sediments to an off-site landfill or treatment

500518

facility. However, these risks are estimated to be small due to the short duration of the off-site disposal activities. All short-term risks to site workers will be addressed by compliance with a health and safety plan. An air monitoring plan will also be implemented for protection of workers and the community.

Implementability

The initial dredging program will be performed in a manner which will identify site-specific conditions and operating parameters, such as dredging depths, effectiveness of using silt curtains and sheet pilings, and sediment suspension and settling characteristics. This information will be evaluated to improve the effectiveness of the removal program. Site surveys performed by Reynolds as part of the initial design work have shown areas of the riverbed to have irregular topographies, thick vegetation, and large cobbles and boulders. Such conditions may impact dredging operations and, ultimately, make it more difficult to achieve the cleanup goals.

The landfilling and treatment components of the two remedies are implementable from an engineering and technical standpoint. However, off-site landfilling and treatment would be considerably easier to implement because the activities associated with procuring, mobilizing, and operating the on-site treatment unit are avoided. Also, off-site landfill capacity is readily available. The dewatered sediments to be landfilled would be transported off site by trucks. Depending on the volume of sediment dredged and the number of vehicles available for each day of operation, temporary stockpiling of the sediments on site may be necessary.

Cost

The capital, present-worth, and O&M costs of the two remedies are summarized in Tables 2 and 3. The net present-worth of the original 1993 remedy, based on revised estimates of sediment volumes (77,600 yd³), is \$72.4 million. The net present-worth of the proposed modified remedy is \$63.2 million. This represents a decrease of \$9.2 million.

The significant cost savings are attributable to the decrease in costs for off-site landfilling. Excess landfilling capacity, as well as the overall market conditions in the waste management industry, have helped reduce such costs since

1993. The costs for thermal desorption, on the other hand, have not changed appreciably because they are more a function of technology, rather than treatment capacity.

State Acceptance

The State of New York concurs on the proposed remedy modifications.

Tribal / Community Acceptance

Community acceptance for the proposed remedy will be assessed in the amended Decision Document following the review of public comments received on this Plan.

The St. Regis Mohawk Tribe has expressed a preference for the treatment of all material with greater than 50 ppm of PCBs and off-site disposal or treatment of all material with PCB concentrations between 25 and 50 ppm.

Proposed Remedy Modification

Based upon an evaluation of the remedy selected by the EPA in its 1993 Decision Document and the changes proposed in this Plan, EPA recommends that the original remedy be modified to incorporate a combination of off-site and on-site disposal for the contaminated sediments to be dredged from the St. Lawrence River. As originally specified in the 1993 Decision Document, the goal of the remedial action is to remove sediments from the St. Lawrence River with PCB levels exceeding 1 ppm, PAH levels exceeding 10 ppm, and TDBF levels exceeding 1 ppb. All dredged sediments with PCB concentrations exceeding 500 ppm would be transported off site for treatment at a TSCA-approved facility. All dredged sediments with PCB concentrations between 50 and 500 ppm would be transported off site to a TSCA-approved landfill. The dredged sediments with less than 50 ppm of PCBs would be disposed of in the existing Industrial Landfill located at the Reynolds Facility and capped in accordance with NYSDEC's 1992 ROD and 1993 Consent Order for the land-based cleanup.

As discussed in this Plan, the technological limitations of dredging may preclude the attainment of the cleanup goals established for the St. Lawrence River sediments. If, after the implementation of the dredging program, EPA deter-

500519

ines that such goals cannot be achieved by existing dredging technologies, then EPA would make a determination at that time whether capping the remaining contaminated sediments in place is necessary.

Current EPA policy regarding the remediation of PCB contamination under the Superfund program favors treatment of materials with PCB concentrations above 500 ppm at an industrial site. Therefore, in accordance with that policy, all sediments removed from the St. Lawrence River having PCB concentrations greater than 500 ppm would be transported off site for treatment by incineration. As stated previously, EPA believes that the current estimate of approximately 4,500 yd³ (7,200 tons) of sediment with concentrations greater than 500 ppm is a conservative value. Following the dredging and dewatering of the sediments, verification sampling would be performed to delineate which portion of the dredged materials would be sent off site for landfilling or treatment and which portion would be landfilled on site.

The Post-Decision preferred alternative provides the best balance of trade-offs among the alternatives with respect to the evaluating criteria. EPA believes that the preferred alternative will be protective of human health and the environment, comply with ARARs, be cost-effective, and utilize permanent solutions and alternative treatment technologies or resource recovery technologies to the maximum extent practicable. The preferred alternative also will meet the statutory preference for the use of treatment as a principal element.

Next Steps

EPA will present the proposed remedy modification at the public meeting in Massena, New York on August 12, 1998. Questions and comments received at the public meeting and during the public comment period will be addressed in a Responsiveness Summary. The Responsiveness Summary will be appended to a Decision Document Amendment for the Site, which will reflect EPA's final decision in modifying any components of the original remedy. 6

500520

Mailing List Additions

If you know of someone you would like to be placed on the Reynolds Study Area Site mailing list, please fill out this form and mail to:

Mark Purcell
Remedial Project Manager
U.S. Environmental Protection Agency
290 Broadway, 20th Floor
New York, NY 10007-1866

Name _____

Address _____

Telephone _____

Affiliation _____



APPENDIX B
PUBLIC NOTICE

500522



THE UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
INVITES PUBLIC COMMENT ON THE
POST-DECISION PROPOSED PLAN FOR THE CLEANUP OF THE REYNOLDS METALS
COMPANY SUPERFUND SITE, MASSENA, ST. LAWRENCE COUNTY, NEW YORK

The U.S. Environmental Protection Agency (EPA) invites public comment on its proposed changes to the remedy selected by EPA in its 1993 Decision Document for the Reynolds Metals Company (Reynolds) Superfund Site (hereinafter the "Site") in Massena, New York. EPA will accept comments during a public comment period which begins on July 30, 1998 and ends on August 28, 1998. Written comments may be submitted to the following address:

Mark Purcell, Remedial Project Manager, U.S. Environmental Protection Agency
290 Broadway, 20th Floor, New York, NY 10007-1866

EPA's Current Selected Remedy

In September 1993, EPA selected a remedy to address contaminated sediments located in the portion of the St. Lawrence River in the vicinity of the Reynolds aluminum production facility (Facility). The major components of that remedy were: 1) dredging of river sediments containing polychlorinated biphenyls (PCBs) at concentrations greater than 1 part per million (ppm) and other contaminants; 2) on-site treatment, by thermal desorption, of dredged sediments having PCB concentrations greater than 25 ppm; and 3) on-site disposal of treatment residuals and sediments having PCB concentrations less than or equal to 25 ppm in the Black Mud Pond (a former disposal pit at the Facility), which would then be capped as part of the New York State Department of Environmental Conservation's (NYSDEC's) land-based cleanup. The remedy did not address contamination present on the land-based portion of the Facility. NYSDEC selected and oversaw a separate cleanup program for such contamination.

Proposed Changes to the Selected Remedy

EPA is proposing to revise the remedy selected in 1993 and would like the public to consider and comment on the changes presented below. These changes are equally protective of human health and the environment, but are significantly less expensive.

EPA is proposing to eliminate on-site thermal desorption treatment as a component of the remedy. This treatment method would be replaced as follows: 1) all dredged sediments containing PCB concentrations greater than 500 ppm would be treated at an approved off-site facility; 2) all dredged sediments containing PCBs at concentrations between 50 and 500 ppm would be landfilled at an approved off-site facility; and 3) all dredged sediments with PCB concentrations less than 50 ppm would be consolidated in an Industrial Landfill located at the Facility. The Industrial Landfill will be capped as part of NYSDEC's land-based cleanup program. The Black Mud Pond, originally intended to receive treated and low-level PCB sediments, was capped in 1996 as part of NYSDEC's cleanup, and is no longer available for sediment disposal.

EPA is not proposing changes to the cleanup goals established for the Site. The goals include the removal of sediments from the St. Lawrence River with PCB levels exceeding 1 ppm.

The results of additional sampling since 1993 have shown that the volume of sediment requiring dredging is much larger than originally estimated. With this increase in sediment volume, the cost of the original remedy has more than doubled. The cost savings associated with the proposed changes result from a change in market conditions which has significantly improved the cost-effectiveness of off-site disposal as compared to on-site treatment.


For More Information

Detailed information on the proposed changes to the remedy for the Site are available in *Reynolds Metals' Request for Modification of Decision Document*, dated October 22, 1997, and EPA's *Superfund Post-Decision Proposed Plan*, dated July 1998. This and related technical documents can be reviewed at the following locations:

U.S. Environmental Protection Agency
290 Broadway, 18th Floor, New York, NY 10007-1866
By appt.: 212-637-3263

Massena Public Library, 41 Glenn Street, Massena, NY 13662
Mon & Fri, 9:30 am - 5:00 pm; Tues-Thur, 9:30 am - 9:00 pm;
Sat & Sun, Closed

St. Regis Mohawk Tribe - Environmental Division
Health Services Building, Hogansburg, NY 13655
By appt.: 518-358-3141



Mark Your Calendar

Public Meeting
Wednesday, August 12, 1998

6:00 pm
Massena Public Library

Availability Session
Thursday, August 13, 1998

5:00 - 7:00 pm
St. Regis Housing
Authority Auditorium

500523

Appendix D

Written Comments Received During the

Public Comment Period

(Organized by the date each letter was prepared)

APPENDIX D

WRITTEN COMMENTS RECEIVED DURING THE

PUBLIC COMMENT PERIOD

(Organized by the date each letter was prepared)

500545

TEIONONWATHE

DISTRIBUTOR

140 K SAINT REGIS ROAD
HOGANSBURG, NEW YORK 13655

P. O. BOX 308
SAINT REGIS, QUEBEC HOM 1A0

Phone: 518-358-9844

Fax: 518-358-4592

HAND-DELIVERED

August 13, 1998

Mr. Mark Purcell
Project Manager
Environmental Protection Agency

Dear Mr. Purcell


As a resident of the Akwesasne Reserve and as Past Chief, I have been following very closely the clean up and proposed clean up of the Reynolds site. Because of recent events and activities in regards to dredging of the PCB site that is due to begin in 1999, I would like to submit the following proposal on both a personal and business basis.

On the issue of the dredging operation, I feel that drinking water should be supplied to all residents of the Akwesasne Reserve; both on the Canadian and American side. The cost of this distribution of water on a temporary basis should be assumed by the Reynolds Metal Company. As a resident of Akwesasne I intend to pursue this matter to that end. On the business side, particularly as the owner of a water distributing company, I feel that this could be done fairly through a bid process.

I would like to offer my services and the services of my company to the Reynolds Metal Company to have this program initiated well in advance of the dredging operation.

In closing I wish to add that Teiononwathe Distributor is a 100% Mohawk owned company based on the Akwesasne Reserve. Should you have any further questions or concerns, please do not hesitate to contact me.

Sincerely,


Mike Thomas
President

cc: Reynolds Metal Company
Mr. Ed Smoke, CEO, Mohawk Tribal Council
Mr. Mike Mitchell, Grand Chief, Mohawk Council of Akwesasne

500546



St. Regis Mohawk Tribe

Rt. 37 Box 8A
Hogansburg, New York 13655
Tel. 518-358-2272
Fax 518-358-3203

Chief Executive Officer
Edward D. Smoke
Vice-Chief
John Bigtree Jr.

Tribal Clerk
Carol T. Herne

Tribal Council
Hilda E. Smoke
Bryan J. Garrow
Barbara A. Lazore

Alma C. Ransom
Paul O. Thompson

Mark Purcell, Remedial Project Manager
U. S. Environmental Protection Agency
290 Broadway, 20th Floor
New York, New York 10007-1866

RE: Comments of the St. Regis Mohawk Tribe on the
Superfund Post-Decision Proposed Plan for the
Reynolds Metals Company Site, Massena, New York

Dear Mr. Purcell:

The St. Regis Mohawk Tribe has reviewed the Environmental Protection Agency's Superfund Post-Decision Proposed Plan ("Plan") for the Reynolds Metal Superfund Site in Massena, New York dated July, 1998, and hereby submits the following comments.

Generally, the Tribe supports the central thrust of the Plan, which involves treatment and disposal of PCB-contaminated river sediments offsite rather than treatment onsite as originally proposed. However, the Tribe has a distinct preference for permanent treatment of the hazardous wastes present at the Site. Containment of any kind in an unlined landfill will only serve to pass-on the toxic waste problem to our future generations. We cannot, as representatives of the St. Regis Mohawk Tribe support a containment remedy as a permanent solution. It is the position of the Tribe that containment is only acceptable as a temporary solution until a permanent treatment remedy is in place. The Tribe directs and reminds EPA of its focus on remedies that are permanent, and that reduce the volume, mobility and toxicity of the contaminants present at the Reynolds Site.

The Tribe proposes that EPA order Reynolds to investigate new remedial treatment technologies on an annual basis until a treatment remedy is found to permanently destroy the contamination in the industrial dump. The benefit of such a permanent remedy, whether in situ or offsite, will be to minimize Reynolds continuing operation and maintenance obligations. This will decrease the financial cost of the remedy over the long-term.

We have an obligation to our people to look seven generations

500547

into the future during our decision-making process. Therefore, remedies that permanently solve the hazardous waste problem over the long-term are the only acceptable options at the Reynolds Site.

Community Role in the Selection Process.

Although EPA maintains that public input is important in selecting effective remedies at hazardous waste sites such as Reynolds, the notice procedure in this case was deficient. EPA released a 15-page, detailed proposed plan that was received by the Community no earlier than August 3, providing less than 10 days notice of a public meeting in Massena on August 12. This is simply inadequate notice in the Akwesasne Community.

Executive Order No. 13084, issued May 14, 1998, requires that agencies implement an effective process to permit Tribal governments to provide "meaningful and timely" input on matters that substantially affect Tribal communities. The natural resources which have been impacted by Reynolds' hazardous waste are relied upon by the Akwesasne Community. There are many interested members of the public, and also professionals within the Akwesasne Community who maintain vital concern regarding the impact of the Reynolds Metals hazardous waste site on the local environment. This local interest and knowledge can and will assist EPA in formulating an effective remedy for the Reynolds site. Therefore, EPA must be keenly attentive to providing a full and fair opportunity for input. A period of at least 45 days notice of public meetings regarding significant changes in remediation plans, such as the July proposed Plan, is necessary in order to provide for "meaningful and timely" public input from Akwesasne.

Onsite Disposal.

The Tribe remains concerned about the total, long-term load of PCBs on the local environment. Although the exportation of hazardous waste as announced in the proposed Plan is favorable, the net result of the amendment is a greater load of PCBs on the local environment. That is, the 1993 plan provided for the treatment of sediments with PCBs concentrations > 25 ppm and the onsite disposal of treatment residuals and sediments having PCB levels \leq 25 ppm. The net result of the 1993 proposed original remedy was to contain 37,000 cubic yards of contaminated soil or sediment in the Black Mud Pond, none of which exceeded 25 ppm of PCBs. In contrast, if the actions described in the July, 1998 proposed Plan are implemented, it is estimated that an additional 6,400 cubic yards of PCB contaminated sediment would be contained in the Industrial Landfill, for a total of 43,400 cubic yards of contaminated sediment, with levels of PCBs up to 50 ppm. This is in addition to the 135,300 cubic yards of PCB contaminated soils at levels \leq 50 ppm

placed in the Industrial Landfill as part of NYSDEC's land-based cleanup. Thus, the net load of contamination to be left on site is significantly greater than proposed in 1993, and more toxic.

As discussed below, since Reynolds is saving nearly \$10 million dollars by this proposed change, a material portion of the savings should be invested in more complete containment in the Industrial dump immediately and ongoing evaluation of innovative *in situ* treatment technologies for the permanent neutralization of dump wastes.

The St. Regis Mohawk Tribal Council must insist that the level of 50 ppm is ludicrous and we will not tolerate it any longer. We insist on 0 ppm as the treatment level. The area must be returned to the condition it was in when Reynolds first came to this area, clean of contaminants.

The Industrial Waste Dump.

The St. Regis Mohawk Tribe does not concur in the State and Federal remedial plan of leaving the unlined industrial landfill in place as a permanent remedy. Reynolds should not now benefit from its improper use of this unlined industrial dump over a term of more than 30 years. The Tribe has never provided concurrence to the State and Federal suggestion that the waste in the industrial dump remain in place permanently. This is particularly so because of the findings that have been made in this administrative record which include:

- The industrial landfill contains hazardous waste levels of PCBs;

- There is no record as to the circumstances or the extent of the hazardous waste levels in the industrial landfill;

- There is no discussion in the administrative record as to the effectiveness of the leachate collection underdrain system that has been installed at the industrial landfill;

- The original "leachate controls" were suggested only as interim remedial measures to protect the wetland that had been impacted by the hazardous waste;

- The groundwater, and essentially the headwaters of the wetland, intersect the PCB-contaminated waste mass in the landfill;

- The administrative record documents that the groundwater which intersects the waste mass discharges to the wetland; and

- There is nothing in the record which establishes the current ecological health of the impacted wetland or the extent to which it continues to suffer leakage from the industrial landfill.

For these reasons, the St. Regis Mohawk Tribe does not concur in the proposed addition of PCB-contaminated waste materials to the industrial dump. In addition the following conditions must be met to allow the existing industrial dump to remain in place :

- The endowment for the long term operation, maintenance and monitoring of the industrial dump be adequate to assure its effectiveness forever, or until a permanent remedy is implemented; and

- During the monitoring of the industrial dump, Reynolds is placed under a directive to regularly evaluate and report on the cost and the effectiveness of instituting in situ treatment technologies which may result in a permanent remedy.

- Air monitoring and treatment of any volatile gases escaping from the dump air vents and through the composite cover.

Design concerns.

Recent studies establish that dredged materials are capable of volatilizing PCB contaminants into the ambient air during the remedial and treatment process. Although the Tribe understands that the remedy for the PCB contaminated river sediments has not yet been designed, we believe it is not too early to caution against handling or storage practices which threaten to suspend and volatilize PCB contaminants into the air. This is particularly so because the Tribe has already established in other proceedings that Reynolds impacts Mohawk's air resources.

Other comments.

The second column on Page 6 of the proposed plan should be rewritten more carefully to relieve ambiguity and to describe the fate and treatment of the highly contaminated materials that were excavated from the North Yard area. Since these materials were perhaps the most toxic materials on the Reynolds site, it is very important to explain to the public what happened to them.


500550

Mark Purcell, Remedial Project Manager
August 17, 1998
Page 5

Footnote 2 on Page 8 leaves some ambiguity by suggesting that PCBs are somehow lost in the dredging process. This is not the case. Dredging is a very effective remedy and, when properly done, PCBs are not re-suspended in the water column or the air in such a manner that threatens downstream or downwind resources. Rather, we understand the thrust of Footnote 2 to suggest that a certain kind of averaging or mixing may occur in the dredging process such that data that is gathered from the dredged materials tends to have lower values than hot spots which have already been identified in the in situ sediment sampling.

Thank you for the opportunity to provide these comments. We are available to meet with you if you have any questions.


Sincerely,



Edward D. Smoke,
Chief Executive Officer



John Bigtree Jr.,
Vice Chief Executive Officer



Barbara A. Lazore,
Legislative Councilor

Alma C. Ransom
Legislative Councilor



Hilda E. Smoke,
Legislative Councilor



Paul O. Thompson,
Legislative Councilor



Bryan Garrow,
Legislative Councilor

cc: Darrell Sweredowski, DEC
Mike O'Toole, DEC
Anne Kelly, EPA
Mel Hauptman, EPA

500551



REYNOLDS METALS COMPANY

Primary Metals Division
P. O. Box 500 • Massena, New York 13662-0500 • (315) 764-6000

Remediation Project Offices (315) 764-1996
• FAX # (315) 764-9394 •

August 26, 1998

Emergency and Remedial Response Division
U.S. Environmental Protection Agency
290 Broadway, 20th Floor
New York, NY 10007-1866

Attn: Reynolds Metals Site
Remedial Project Manager
Mark Purcell

Re: Administrative Order
Index No. II CERCLA-90230

Dear Mr. Purcell:

Reynolds has reviewed EPA's Post-Decision Proposed Plan describing the proposed changes to the remedy selected by USEPA in its September 1993 Decision Document for the RMC Study Area Site under authority of the above referenced Order, and submits this letter as an initial response.

Reynolds would like to reaffirm its commitment to work with the EPA and to move forward in satisfaction of the Order. We appreciate EPA's consideration of Reynolds' comments on the proposed remedial action plan.

However, as you know, Reynolds has concerns and reservations in connection with USEPA's requirement, or rather preference, to treat sediments with PCB levels exceeding 500 ppm offsite by incineration.

Reynolds objects to EPA's requirement to treat dredged sediments greater than 500 ppm. In accordance with 40 CFR 761.61(b)(2), RMC is allowed to dispose of PCB remediation waste in a chemical waste landfill. As noted in the preamble to the final rule published in the Federal Register on June 29, 1998 for 40 CFR Parts 750 and 761, "dredged material falls within the definition of PCB remediation waste, and as such, the other disposal options of 761.61(a), (b), and © are available for management and disposal of dredged material containing PCB's at any concentration . . ." Treatment of PCB remediation waste is not required, but is instead, an option for disposal. RMC has evaluated this option and firmly believes that disposal of all sediments greater than 50 ppm at Chemical Waste Management's Model City facility is the most cost effective and environmentally protective approach. Treatment of approximately 4,500 cubic yards of sediment at a cost of \$7.2 million (\$5.8 million over landfill costs) is not a requirement RMC is willing to accept.

500552

Reynolds proposes to dispose of these sediments at a TSCA-approved offsite facility. Disposal offsite would be equally protective and less costly, as EPA has reaffirmed in its Comparison of Original Remedy and Proposed Changes section of the Superfund Post-Decision Proposed Plan for General Motors Superfund Site, August 1998. TSCA and its regulations require that dredged sediments with concentrations of PCB's greater than 50 ppm be *either* incinerated, landfilled in a TSCA-approved chemical waste landfill, or disposed of by another method approved by EPA (40 CFR parts 761.60-761.9). The requirement in the proposed change to thermally destroy the sediments with PCB levels exceeding 500 ppm appears to only be a preference in this instance.

EPA has indicated that based on past experiences at the General Motors facility, it is not expected that a significant quantity of the dredged sediment will be greater than 500 ppm. However, RMC's proposed use of a closed clamshell bucket for dredging, greatly increases the possibility of removing the sediments at in-situ concentrations. By comparison, GM's removal of sediment by hydraulic methods mixed high contaminant level sediments with low contaminant level sediments resulting in sediments with an average PCB concentration of 200 ppm (per EPA's Superfund Post-Decision Proposed Plan, General Motors Superfund Site, August 1998, p.7). To imply the volumes will be much less is a \$5.8 million assumption by EPA that is difficult to justify and a matter which RMC is not willing to gamble with.

The EPA's preference to treat PCBs sediments with concentrations greater than 500 ppm, unnecessarily increases the project costs by approximately \$5.8 million. The landbased remediation project landfilled soils with PCB concentrations greater than 500 ppm in complete compliance with all laws and regulations. The requirement to incinerate the river sediments is punitive and not consistent with landbased work or other EPA river projects in the area.

The "ALCOA Non-Time Critical Removal Action" had sediments with PCB concentrations that ranged from non-detect to 11,000 ppm. EPA allowed that sediment to be placed in ALCOA's on-site secure landfill with no restrictions on greater than 500 ppm sediments (Superfund Program Update for the Alcoa Study Area, August 1995). Alcoa is a direct competitor in the aluminum market place and EPA's requirement for RMC to incinerate, while allowing Alcoa to landfill, forces Reynolds Metals Company to spend an additional \$5.8 million and places RMC at a competitive disadvantage.

The General Motors Post-Decision Proposed Plan, August 1998, that is now in public comment period, does not require treatment of sediments/soils in the Raquette River previously identified as greater than 500 ppm PCBs.

We ask that EPA be consistent and follow regulations concerning the disposal of greater than 500 ppm PCB material. If Alcoa and General Motors are allowed to landfill greater than 500 ppm PCB material and the regulations allow it, then Reynolds is not prepared to spend an extra \$5.8 million to incinerate like sediments.

A review of the ROD's for EPA Region 2 and 5 has identified several examples where sediments with PCB waste have been landfilled (e.g., Facet Interprises, Inc., New York; Cosden Chemical Coatings Corp., New Jersey). A recent EPA publication in March 1998 "Realizing Remediation: A Summary of Contaminated Sediment Remediation Activities in the Great Lakes Basin", includes discussions of several sites with sediments and/or soils contaminated with PCB levels exceeding 500 ppm that have been landfilled without thermal treatment at TSCA-approved offsite facilities (e.g., Ottawa River Tributary, Ohio; Manistique River and Harbor, Michigan; Willow Run Creek, Michigan).

Also, since there are potential problems with dredging in this area of the St. Lawrence River, and since EPA would make the determination for further dredging and/or capping of the sediments (per EPA's Superfund Post-Decision Proposed Plan, July 1998, p.9), RMC would like to communicate their opposition to the concept of further dredging vs. capping. If a cap is believed to be necessary, it should be addressed prior to implementation of the proposed plan. Also, the higher costs involved with the combination of dredging and in-situ containment have not been addressed.

Reynolds is looking forward to working with the EPA in resolving this and any design issues remaining with respect to the remediation. We are confident that by maintaining a good working relationship we can best ensure that this remediation is conducted in a safe, efficient, timely and cost-effective manner.

Sincerely,



Richard C. Esterline
Project Coordinator

cc: 1 copy:

Chief, New York/Caribbean Compliance Branch
Emergency and Remedial Response Division
U.S. Environmental Protection Agency
290 Broadway
New York, NY 10007-1866

Attn: Reynolds Metals Site Attorney

1 copy:

Anne Kelly
Emergency and Remedial Response Division
Remedial Project Manager
U.S. Environmental Protection Agency
290 Broadway, 20th Floor
New York, NY 10007-1866

3 copies:

George Heitzman
Division of Construction Management
New York State Department of
Environmental Conservation
50 Wolf Road
Albany, NY 12233

3 copies:

St. Regis Mohawk Indian Tribe
Environmental Health Services
St. Regis Mohawk Indian Reservation
Community Building
Hogansburg, NY 13655

bcc:

Fred Swafford
Jim Brown
Jim McKinnon
Bob Lenney
Vicky Murphy
Kevin Shaw
Ali Yazdi
Peter Jacobson
Darrell Nicholas

LAEPARODMODCOM.DOC

August 27, 1998

Mr. Mark Purcell
Remedial Project Manager
U.S. Environmental Protection Agency
290 Broadway, 20th Floor
New York, NY 10007-1866

**Re: Comments to USEPA's Superfund Post-Decision Proposed Plan for
Reynolds Metals Superfund Site**

Dear Mark:

1. The rationale for requiring Reynolds to incinerate sediment containing >500 ppm PCBs is unclear. As stated in the Post-Decision Proposed Plan, the Toxic Substances Control Act (TSCA) mandates that dredged materials with PCB concentrations >50 ppm must be either disposed in a TSCA-approved landfill, incinerated, or disposed by alternate method approved by USEPA. In this instance, the regulations do not identify the need for "special treatment" of sediment containing >500 ppm PCBs. Hence, the need to manage and dispose of these materials in a manner that is different from those containing >50 ppm and <500 ppm appears unwarranted. It would be equally protective to dispose of the >500 ppm materials in a TSCA-approved landfill.
2. The Post-Decision Proposed Plan indicates that "the mouth of the Grasse River at the confluence of the St. Lawrence River was originally identified as part of the [Reynolds Metals] Superfund Site, . . ." Alcoa is requesting rationale/justification for the removal of this portion of the Site and its current inclusion as part of the Grasse River site. Alcoa requests that EPA explain the details surrounding the decision to include this area, which was originally part of the Reynolds Metals Site, in the Grasse River Site. What portion of the Reynolds Metals Site was transferred?
3. Alcoa concurs with EPA's general conclusion that, given the technological limitations associated with today's dredging equipment, along with the site-specific conditions of the targeted River bottom, attainment of the proposed cleanup levels may not be possible. This concurrence is based upon related experiences at other PCB dredging sites throughout the country. Data obtained from these sites have shown the inability of various dredging methods to meet low targeted cleanup levels on a consistent basis.

500557

4. The Post-Decision Proposed Plan indicates that, should the specified cleanup goals not be attained, capping of residual sediments may become necessary. Since it is possible that elevated levels of chemical constituents will remain following dredging (see Comment 3), the Agencies acknowledge that capping provides an acceptable level of chemical constituent isolation and risk reduction.

It would logically follow that capping, in-and-of-itself, would provide the same remedial benefits without first having to dredge. In essence, Alcoa believes that dredging (for mass removal) followed by capping, does not meet the cost effectiveness "test," since capping alone can achieve the same endpoint more cost effectively (i.e., without the added cost burden of dredging).

5. Alcoa requests from EPA, when it becomes available, information on the monitoring and engineering controls proposed as part of the River dredging project.

Sincerely,



Patrick Dargan
Location Remediation Manager
Alcoa Massena Operations

KLM/ipc
USEPA8-27-98.doc

500558

Environment
CanadaEnvironnement
CanadaOntario Region
4905 Dufferin Street
Downsview, Ontario
M3H 5T4Région de l'Ontario
4905, rue Dufferin
Downsview, Ontario
M3H 5T4

For *John*
Huszyński
cc: Caspe

August 28, 1998

Ms. Jeanne Fox
Regional Administrator
US EPA
Region 2
290 Broadway
New York, N.Y. 10007-1866

1998 AUG 31 PM 3:15
DIRECTOR'S OFFICE

US E.P.A. REGION II
RECEIVED
AUG 31 1998

Dear Ms. Fox:

In response to the public comment period on the Post Decision Proposed Plan for the Reynolds Study Area Site, the following agencies have provided comments through the Canadian Review Panel for Massena sites: Environment Canada - Ontario and Quebec Regions, the Ontario Ministry of the Environment and the Quebec Ministère de l'Environnement et de la Faune. Comments are based on the July 98 proposed plan as well as previous reviews of site characterizations, studies and proposals including: "Overview and Update on Massena Waste Site Cleanups" (Intera Consultants, March 1997).

The proposal generally meets with current Canadian policies on removal and containment of PCB contaminated material and is consistent with actions and decisions made at the ALCOA and GM sites in Massena. There are no objections to the proposed plan in this regard. We do have a concern regarding the lack of deep soil and groundwater monitoring at the Reynolds site under the landfill which is proposed to accept the waste less than 50 ppm PCBs. This gap in information causes some questions on whether the groundwater recovery and treatment system will be fully effective.

Some recent sediment toxicity information from Canadian research studies near Reynolds is enclosed. The full reports have previously been made available to Reynolds and are being provided to Mark Purcell (EPA project manager) in a separate mailing. As with the 1995 General Motors river remediation project, Canada has an ongoing need to ensure that Canadian waters downstream are protected from transboundary movement of contaminants and toxicity. We will therefore be requesting regular contact with site personnel and receipt of monitoring information as the project gets underway. Based on the dredging, containment and monitoring program, Canadian agencies may also plan a near-

10:11 PM 16 AUG 98

US EPA


500559

Canada

site and time-integrated water quality monitoring program on the St. Lawrence River.

We appreciate the ongoing contact with EPA project personnel on the developments at all 3 Massena Superfund sites and request copies of the detailed work program, dewatering, monitoring, health and safety and contingency plans when they are available. Additionally, further information on the water treatment system and location of the off-site disposal facility is requested.

Sincerely,



J. Mills
Regional Director General
Ontario Region

cc: Marie Adam
Foreign Affairs and International Trade

Mark Purcell
Remedial Project Manager
US EPA

500560

TOXICITY OF SEDIMENTS NEAR AN ALUMINUM PRODUCTION PLANT
ON THE ST. LAWRENCE RIVER TO FRESHWATER ORGANISMS, WITH
EMPHASIS ON FLUORIDE, PART I

National Water Research Institute - Contribution No. 96-162

MANAGEMENT PERSPECTIVE

J.L. Metcalfe-Smith,
G.R. Sirota, K.E. Hotze
and J.J. Reid

Fluoride was recently declared "toxic" under the Canadian Environmental Protection Act, based on its potential to cause long-term harmful effects to biota in aquatic and terrestrial ecosystems. However, information on the toxicity of sediment-associated fluoride to benthic organisms was considered incomplete. The impetus behind our study was to address this knowledge gap. Aluminum smelting is one of the major sources of fluoride to the Canadian environment. The Reynolds Metals Company aluminum production plant in Massena NY was chosen for study because it discharges into the St. Lawrence River Area of Concern and is one of three Superfund sites in the AOC undergoing remediation. Approximately 51,500 cu yds of sediment contaminated with PCBs, PAHs, cyanide, fluoride, aluminum and dibenzofurans are scheduled to be dredged from the Reynolds Metals Study Area (RMSA) in 1996. Earlier work by consultants to Reynolds Metals showed that several of these contaminants have the potential to be remobilized into the water column during dredging and possibly harm indigenous biota. This is of concern to the Canadian Review Panel for Massena Superfund Sites, who are responsible for assessing the risk of Superfund activities to the Canadian environment. The objectives of this study were, therefore, to determine: the toxicity of sediments from the RMSA prior to remediation; the toxicity of elutriates, to assess the potential impact of dredging activities; the probable toxic agent(s), using the Toxicity Identification Evaluation (TIE) approach; and the contribution of fluoride to the observed toxicity.

Sediment was collected from seven sites in the RMSA in the fall of 1993, analyzed for contaminants of concern, and bioassayed. Sediment from the most contaminated site caused mortality of fathead minnows (*Pimephales promelas*) and mayflies (*Hexagenia limbata*). Based on figures provided by the U.S. EPA, approximately 8300 cu yds of sediment are contaminated to this degree. Sediment from the next two most contaminated sites represented an additional 11,400 cu yds of sediment and affected the growth of both organisms. It was therefore estimated that nearly 40% of the sediment to be dredged was either acutely or chronically toxic to freshwater organisms. Elutriate from the most contaminated site was acutely toxic to fathead minnows and *Coriodelphax dubia*, and elutriate from one other site affected the growth of fathead

500561

minnows, thus indicating that the toxic agent could readily desorb from disturbed sediments. Results of the Phase I TIE suggested an organic contaminant as the probable toxic agent. Fluoride did not appear to contribute to the toxicity of either elutriates or sediments. Results of this study showed that the removal of contaminated sediment from the RMSA should make a significant contribution to the restoration of a healthy ecosystem in the St. Lawrence River Area of Concern, but also showed that dredging operations may themselves pose a threat to the aquatic environment. It was recommended that further work be conducted to address the following objectives: (i) a Phase II TIE should be conducted to more specifically identify the toxic agent(s) in sediments; (ii) dredging conditions should be simulated in the laboratory to determine the effects on survival, growth and induction of mixed function oxygenases in fish; (iii) definitive bioassays should be conducted to determine the levels of sediment-associated fluoride that are toxic to standard benthic test organisms.

500562

APPENDIX 3

1993 DECISION DOCUMENT

500563

Declaration for the Decision Document

Site Name and Location

Reynolds Metals Company Site Study Area
Massena, St. Lawrence County, New York

Statement of Basis and Purpose

This decision document presents the selected remedial action for the Reynolds Metals Company Site Study Area, in Massena, New York, which was chosen in accordance with the requirements of the Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA), as amended by the Superfund Amendments and Reauthorization Act of 1986 (SARA) and, to the extent practicable, the National Oil and Hazardous Substances Pollution Contingency Plan (NCP). This decision document explains the factual and legal basis for selecting the remedy for this Site.

The New York State Department of Environmental Conservation (NYSDEC) strongly supports the proposed dredging of contaminated sediments from the river, agrees with EPA's cleanup levels for the Site, and agrees with and supports the concept of using the Black Mud Pond for the disposal of untreated sediments and treatment residuals. However, while the NYSDEC agrees with the cleanup numbers for the Site, they do not agree with the process by which they were obtained. In addition, the NYSDEC would encourage the use of lower treatment levels if it could be demonstrated that doing so would not add unreasonable costs to the project. Their letter is attached as Appendix 3.

The information supporting this remedial action decision is contained in the administrative record for this Site, the index of which is also attached to this document as Appendix 4.

Assessment of the Site

Actual or threatened releases of hazardous substances from this Site, if not addressed by implementing the response action selected in this Decision Document, may present an imminent and substantial threat to public health, welfare, or the environment.

Description of the Selected Remedy

This action or "operable unit" is the first and only operable unit planned by the U. S. Environmental Protection Agency for the Reynolds Metals Company Site Study Area and addresses the principal threat posed by contaminated sediments in this Area by utilizing a mixed treatment/containment remedy for these contaminated sediments.


The major components of the selected remedy include the following:

- Dredging and/or excavation of approximately 51,500 cubic yards of sediments with polychlorinated biphenyl (PCB) concentrations above 1 part per million (ppm), total polyaromatic hydrocarbon (PAH) concentrations above 10 ppm, and total dibenzofuran (TDBF) concentrations above 1 part per billion (ppb) from contaminated areas in the St. Lawrence River and from the associated riverbank;
- Treatment of approximately 14,500 cubic yards of dredged/excavated material with PCB concentrations above 25 ppm by thermal desorption. Untreated sediments (with PCB concentrations between 1 ppm and 25 ppm) and treatment residuals (which are expected to be non-hazardous and to have PCB concentrations below 10 ppm) will be disposed on-site, in the Black Mud Pond, and covered. The Black Mud Pond will be capped in conformance with the requirements of the January 22, 1992 New York State Record of Decision for the state lead Reynolds Metals Site, which encompasses the entire Reynolds facility. Contaminants condensed in the thermal desorption process will be transported off-site and burned at a commercial incinerator.

Declaration of Statutory Determinations

The selected remedy is protective of human health and the environment, complies with Federal and State requirements that are legally applicable or relevant and appropriate to the remedial action, and is cost-effective. This remedy utilizes permanent solutions and alternative treatment (or resource recovery) technologies to the maximum extent practicable, and it satisfies the statutory preference for remedies that employ treatment that reduces toxicity, mobility, or volume as their principal element.

Because this remedy will result in hazardous substances remaining on site above health-based levels, a review will be conducted within five years, and every five years thereafter, after commencement of remedial action to ensure that the remedy continues to provide adequate protection of human health and the environment.



William J. Muszynski, P.E.
Acting Regional Administrator
U. S. Environmental Protection Agency

Date

9/27/93

DECISION SUMMARY
REYNOLDS METALS COMPANY SITE STUDY AREA
MASSENA, NEW YORK

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
REGION II
NEW YORK

TABLE OF CONTENTS

I.	Site Name, Location, and Description	1
II.	Site History and Enforcement Activities	2
III.	Highlights of Community Participation	4
IV.	Scope and Role of Operable Unit or Response Action Within Site Strategy	5
V.	Summary of Site Characteristics	5
VI.	Summary of Site Risks	6
VII.	Description of Alternatives	11
VIII.	Summary of Comparative Analysis of Alternatives	20
IX.	Selected Remedy	27
X.	Statutory Determinations	29
XI.	Documentation of Significant Changes	30

Attachments

APPENDIX 1 - FIGURES
APPENDIX 2 - TABLES
APPENDIX 3 - STATE LETTER OF CONCURRENCE
APPENDIX 4 - ADMINISTRATIVE RECORD INDEX
APPENDIX 5 - RESPONSIVENESS SUMMARY

Decision Summary for the Decision Document

I. Site Name, Location, and Description

The Reynolds Metals Company (RMC) facility is an active aluminum production plant located on 1600 acres in the town of Massena in St. Lawrence County, New York. The RMC facility is bordered on the north by the Grasse and St. Lawrence Rivers, on the east by the New York Central Railroad, on the west by Haverstock Road (South Grasse River Road), and on the south by the Raquette River. The plant is located off Route 37 near the Massena-Cornwall International Bridge, directly upriver of the General Motors - Powertrain Division Plant (see Figure 1).

The Reynolds Metals Company Study Area Site ("the Site") includes that portion of the St. Lawrence, Grasse, and Raquette Rivers, any tributaries of those rivers and any wetlands which are between the International Bridge and the confluence of the Grasse and St. Lawrence Rivers and that portion of the Raquette River which is south of the confluence of the Grasse and St. Lawrence Rivers and south of the International Bridge. The Reynolds Study Area Site is depicted in Figure 1. In general, the Reynolds Study Area Site encompasses those surface waters, sediments, and wetlands which are adjacent to the Reynolds Metals Company facility in Massena, New York. The Reynolds Study Area is part of the St. Lawrence/Grasse River Site (site code 6-45-15) which was added to the New York State Registry of Inactive Hazardous Waste Sites on April 14, 1987. This Site was listed as a result of environmental impacts which occurred to the river system at and in the vicinity of the Aluminum Company of America (ALCOA), Reynolds Metals, and General Motors facilities.

Land use in the area surrounding the Site consists of mixed residential and industrial uses. The St. Regis Mohawk Indian Reservation, Akwesasne, is located within 0.5 miles of the RMC facility. Approximately 3,500 individuals live on the St. Regis Indian Reservation. The downtown area of Massena is located approximately eight miles west and upriver of the RMC facility. The 1980 population estimate for Massena was 14,856. In addition, the St. Lawrence River forms the border between the U.S. and Canada in this area.

Due to past contamination of the General Motors facility and in the surrounding river system, the General Motors-Powertrain Division plant has been designated as a federal Superfund Site. EPA is overseeing cleanup of the General Motors facility and surrounding river system. EPA is also overseeing the cleanup of the river system surrounding the ALCOA facility, which is approximately eight miles upriver from the RMC Site.

Major areas of contamination on the RMC facility include an unlined pit used for the disposal of carbon solids known as the Black Mud

Pond, a landfill, and the plant's North Yard. The New York State Department of Environmental Conservation (NYSDEC) is overseeing the cleanup of contamination on the RMC and ALCOA facilities.

The St. Lawrence River flows are partially controlled by the Moses-Saunders Power Dam, located approximately four miles upstream of the Site on the St. Lawrence River. In the vicinity of the Site, the St. Lawrence River is greater than 0.5 miles in width with depths exceeding 30 feet in some portions of the River. The section of the St. Lawrence River adjacent to the RMC facility is part of the St. Lawrence Seaway. In general, the Reynolds Study Area is comprised of a shallow shelf containing slow currents, fine-grained sediments, and dense beds of submergent aquatic vegetation. The shallow shelf was created in the late 1950s by dredge spoil from the south Cornwall Navigation Channel that is located 300 to 800 feet offshore from the RMC facility. No dredge spoil has been deposited in this section of the river since the initial dredging.

Local water bodies are used recreationally for swimming, wading, fishing, boating, camping, and picnicking. Two general groups, the Mohawk native population and recreational fisherman, fish in the vicinity of the Reynolds Study Area. However, direct land access to the Reynolds Study Area is limited by the steep nature of the shoreline.

A tract of regulated water wetlands (identified as No. RR-6 by NYSDEC) occur on the Reynolds' property. The wetland is approximately 170 acres in size and is a Class 2 wetland. It is one of the three largest wetlands in the town of Massena. NYSDEC is also overseeing the cleanup of contamination in these wetlands.

II. Site History and Enforcement Activities

The RMC plant was constructed in 1958 for the production of aluminum from alumina (aluminum oxide). The main components of the plant include the reduction plant and supporting structures and facilities encompassing about 20.5 acres, the solid waste landfill (11.5 acres), and the Black Mud Pond (approximately 6 acres).

Aluminum is produced in individual pots lined with "potliner," which is composed of a mixture of carbon compounds and which acts as the cathode of the electrolytic cell. Potliner is fabricated in the carbon plant section of the plant where coal tar pitch, coke and other materials are blended and shaped to fit the pots. A heat transfer medium (HTM) system is used to maintain the pitch in a flowable and pumpable form. The HTM system no longer uses a polychlorinated biphenyl (PCB) oil.

As a result of production activities and years of continuous operations and expansion, various types of industrial waste, including hazardous waste, were generated, disposed of, and spread throughout the facility. Contaminated areas on the facility property are being investigated and remediated by RMC under the authority of Consent Orders with NYSDEC. Several areas on the

facility serve as potential sources of contamination to the Reynolds Study Area. These areas are described briefly below and are depicted in Figure 2.

Wastes from the plant's potliner recovery system were disposed of in the Black Mud Pond. The Black Mud Pond contains waste primarily composed of alumina (30-40%) and carbon (35-45%) with fluoride at 2-5%, cyanide at 61 parts per million (ppm), and PCBs at 3.4-8.1 ppm. These contaminants have been detected in groundwater near the pond. However, groundwater contamination appears to be confined to a limited area downgradient of the pond. Shallow contaminated groundwater may be discharging to surface water pathways to the south and east of the pond.

The plant's Solid Waste Landfill and former Potliner Storage Area can be characterized as one contaminant source area, based on their proximity and similarity of contaminants and receptor zone of contaminants migrating from the area. The contamination detected in the waste, groundwater, leachate and surface water is characterized by elevated concentrations of cyanides (up to 300 ppm), fluorides (up to 8500 ppm), sulfates (up to 13,000 ppm), aluminum (up to 87,000 ppm) and polyaromatic hydrocarbons (PAHs) (up to 2,200 ppm). PCBs are also detected in both areas at concentrations as high as 690 ppm. Groundwater from these areas drains to wetlands RR-6, south of the Landfill area. A leachate collection system on the Landfill intercepts some, but not all, of the contaminated groundwater from the Landfill to the wetlands. Remediation of this wetland is being overseen by NYSDEC.

PCBs, polychlorinated dibenzofurans (PCDFs), and polychlorinated dibenzo-p-dioxins (PCDDs) are distributed in North Yard surficial soils. PCBs have been found in this area at concentrations as high as 89,000 ppm. PCDDs and PCDFs have been detected at levels of 9.92 parts per billion (ppb) and 9.35 ppb, respectively. PCBs, PCDFs, and PCDDs originate from the plant HTM system. North Yard groundwater contamination is characterized by local areas of elevated concentrations of aluminum, arsenic, cyanide, PCBs, and fluoride.

In addition to contamination throughout the facility, RMC also discharged contaminants to the St. Lawrence River through four outfalls - known as Outfalls 001, 002, 003, and 004. Three of these outfalls - Outfalls 001 and a combined Outfall 002 and 003 - are still in use. These outfalls are depicted in Figure 3 and served as the primary sources of contamination to the Site.

Discharges from Outfall 001 include water from the facility's waste water treatment system. Outfall 002 discharges contact cooling water and stormwater runoff from the facility. It carries the highest volume of water (averaging 2.5 million gallons per day) of all four of the outfalls. Prior to November 1989, the discharge from Outfall 002 traveled down an open ditch on the RMC property to enter the St. Lawrence River. After November 1989, this discharge was combined with that of Outfall 003. Outfall 003 carries treated

discharge from the facility sanitary treatment plant. Outfall 003 discharges to the St. Lawrence River through a submerged pipe located approximately 100 feet from the shore. Prior to June 1988, Outfall 004 carried intermittent runoff from northern areas of the plant. The runoff formerly discharged at Outfall 004 is now treated and used in plant operations.

The RMC facility and upland areas are listed on the NYSDEC Registry of Inactive Hazardous Waste Sites. In September 1987, RMC and NYSDEC signed a Consent Order, pursuant to which RMC agreed to investigate contamination at the RMC facility. However, this Order did not include an investigation of contamination in the river system surrounding the facility. In January 1992, NYSDEC issued a Record of Decision (ROD) which outlined its selected remedy for the RMC facility, excluding the river system. NYSDEC's selected remedy included a combination of excavation and treatment of areas highly contaminated with PCBs and other contaminants and consolidation and containment of other contaminated areas on the facility. In March, 1993, RMC and NYSDEC signed a Consent Order which required RMC to implement the remedy in the January 1992 ROD.

In January 1989, RMC completed an initial study of sediment contamination in the St. Lawrence River adjacent to its plant. In September 1989, EPA issued a Unilateral Administrative Order (EPA Index No. II CERCLA-90230), requiring that RMC investigate and clean up contamination in the river system surrounding the RMC facility. The river system has been termed the "Reynolds Study Area." In August 1991, RMC submitted a revised Additional River Sampling (ARS) Report which further characterized the nature and extent of contamination in the Reynolds Study Area. In March 1992, RMC submitted a draft Analysis of Alternatives (AA) Report which evaluated options for remediating contaminated sediments at the Site. In January 1993, RMC submitted a revised draft AA Report for the Reynolds Study Area.

III. Highlights of Community Participation

The ARS and AA Reports and the Proposed Plan for the Reynolds Study Area Site were released to the public for comment on February 19, 1993. These documents were made available to the public in both the administrative record and in information repositories maintained at the EPA Docket Room in Region II, at the St. Regis Mohawk Tribal Offices, and at the Massena Public Library. The notice of availability for these two documents was published in the Massena Courier-Observer on February 19, 1993, in the People's Voice on February 22, 1993, and in the Indian Times on February 19, 1993. A public comment period on the documents was held from February 19, 1993 through April 21, 1993. The public comment period was extended once upon the request of officials from Environment Canada.

EPA held a public meeting regarding the Reynolds Study Area Site on March 9, 1993 at the Massena Town Hall. At this meeting, representatives from EPA answered questions about problems at the Site and the remedial alternatives under consideration. A response

to the comments received during this period is included in the Responsiveness Summary, which is part of this Decision Document. The Responsiveness Summary and Decision Document, along with the administrative record for the Reynolds Study Area Site, are available at the information repositories referenced above.

IV. Scope and Role of Operable Unit or Response Action Within Site Strategy

This Decision Document addresses the first and only planned remedial action for the Reynolds Study Area Site. This action is intended to address the principal threats to human health and the environment posed by the contaminated sediments in the Reynolds Study Area. Remediation of the contaminated upland areas on the RMC facility is being overseen by NYSDEC.

V. Summary of Site Characteristics

Hydrodynamic Conditions

Prior to completion of the ARS, RMC conducted a study of flow conditions in the St. Lawrence River adjacent to its facility. The flow study, conducted in November 1989, supplemented previous flow studies done by RMC and its consultants. The flow study yielded the following general conclusions about the Reynolds Study Area Site which are depicted graphically in Figure 3. The main river current which enters the area adjacent to the RMC facility from Polly's Gut has velocities of 8 feet per second or greater. This flow is deflected to the east by training dikes which protect the Seaway channel. There are a series of clockwise and counterclockwise eddies as the main current exits the training dikes. These eddies are characterized by low velocity flow and migrate toward the shore in both upstream and downstream directions. There is an area in the vicinity of Outfalls 001 and 004 which exhibits some flow separation with predominantly upstream flow to the west of the outfalls and predominantly downstream flow to the east of the outfalls.

The overall result of these flow patterns is that water generally stagnates along the shoreline in the vicinity of Outfall 001. Because of this stagnation, sediments and particulate materials discharged into the River through the four outfalls generally remain close to shore. This pattern would be enhanced in summer months by extensive vegetation growth that would act to further slow currents in the shallow water near the shore.

Contaminant Characteristics

As part of the ARS, sediment samples were collected from 47 locations in the St. Lawrence River and 17 locations in the Raquette River adjacent to the RMC facility. A total of 127 sediment samples were collected, 20 in the Raquette River and 107 in the St. Lawrence River. The results of the ARS sampling were generally consistent with the results from 67 sediment samples taken in 1988 by RMC

although the levels of contamination detected during the ARS were higher than those found in the 1988 study.

Based on sampling and analyses conducted during the ARS, there are several contaminants in Reynolds Study Area sediments including PCBs, PAHs, total dibenzofurans (TDBFs), fluoride, and cyanide. PCBs are the primary contaminant found in sediment samples in the Reynolds Study Area. Contaminants other than PCBs are generally found in a pattern similar to that of PCBs and will be remediated along with PCBs.

PCBs were found in 72 of the sediment samples taken from the St. Lawrence River. However no PCBs were found in background samples or in sediment samples from the Raquette River. Figures 4 - 6 show an approximation of the general distribution of PCBs at various depths in the Reynolds Study Area. Figures 7 - 10 show the distribution of PAHs, cyanides, fluorides, and TDBFs in the Reynolds Study Area. EPA estimates that there are approximately 51,500 cubic yards of sediment with PCB concentrations above 1 ppm, PAH concentrations above 10 ppm, and TDBF concentrations above 1 ppb.

The highest concentration of PCBs detected in sediments in the Reynolds Study Area was 1300 parts per million (ppm). All samples with PCB concentrations above 100 ppm are located within 500 feet of the RMC outfalls. Concentrations decrease away from the shoreline. PCBs were detected in some samples at a depth of 24 inches into the sediments and may extend below that depth at some locations. Sediment depths range from one foot to over 5 feet. PCBs were not detected in water samples taken by RMC from the St. Lawrence River. However, NYSDEC, using a more sensitive analytical technique than the one used by RMC, detected PCBs in surface water at levels up to 54 parts per trillion (ppt).

PCBs and other contaminants which are present in Reynolds Study Area sediments may migrate downstream or dissolve slowly into the River. In addition, PCBs in contaminated sediments can serve as a source of contamination for aquatic organisms and begin to bioaccumulate within the food chain. Therefore, one potential pathway of human exposure is human consumption of PCBs in the fatty tissue of fish and wildlife, as explained below.

VI. Summary of Site Risks

Human Health Risks

Contaminant Identification and Exposure Assessment

EPA conducted a baseline risk assessment to evaluate the potential risks to human health and the environment associated with the Site in its current state. The baseline risk assessment focused on the chemicals in Reynolds Study Area sediments which are likely to pose the most significant risks to human health and the environment. These "contaminants of concern" for the Reynolds Metals Company Study Area Site are listed in Table 1.

500573

EPA's Baseline Risk Assessment identified several potential exposure pathways by which the public may be exposed to contaminant releases. The potential exposure routes which were identified in the baseline risk assessment for St. Lawrence River and Raquette River sediments include:

- dermal contact with contaminated sediments;
- ingestion of contaminated sediments;
- ingestion of fish caught from the St. Lawrence River;
- ingestion of surface water from the St. Lawrence River;
- inhalation of contaminants volatilized from surface water; and
- dermal contact with surface water during swimming.

Of these potential pathways of exposure, ingestion of surface water, inhalation of volatilized contaminants, and dermal contact with surface water were not evaluated quantitatively in the baseline risk assessment because available data indicated that the risks associated with these exposure pathways would be relatively minor compared to the other routes of exposure considered.

The baseline risk assessment evaluated both present and possible future exposures for recreational users and for subsistence fishermen. Potentially exposed populations include area residents and residents of the St. Regis Mohawk Reservation and Canadians who are downriver of the Site. Risks were calculated for small children and for adults. Exposure assumptions were based on reasonable maximum exposure scenarios. Tables 2 - 4 present the exposure assumptions used by EPA in its Baseline Risk Assessment.

Toxicity Assessment

Under current EPA guidelines, the likelihood of carcinogenic (cancer causing) and noncarcinogenic effects due to exposure to Site chemicals are considered separately. It was assumed that the toxic effects of the site-related chemicals would be additive. Thus, carcinogenic and noncarcinogenic risks associated with exposures to individual contaminants were summed separately to indicate the potential risks associated with mixtures of potential carcinogens and noncarcinogens, respectively.

Potential carcinogenic risks were evaluated using the cancer slope factors developed by EPA for the contaminants of concern. Cancer slope factors (SFs) have been developed by EPA's Carcinogenic Risk Assessment Verification Endeavor (CRAVE) for estimating excess lifetime cancer risks associated with exposure to potentially carcinogenic chemicals. SFs, which are expressed in units of $(\text{mg/kg-day})^{-1}$, are multiplied by the estimated intake of a potential carcinogen, in mg/kg-day , to provide an upper-bound estimate of the excess lifetime cancer risk associated with exposure at that intake level. The term "upper bound" reflects the conservative estimate of the risks calculated from the SF. Use of this approach makes underestimation of the actual cancer risk highly unlikely. Cancer

slope factors are derived from the results of human epidemiological studies or chronic animal bioassays to which animal-to-human extrapolation and uncertainty factors have been applied. SF values for Reynolds Study Area contaminants of concern are given in Table 5.

Noncarcinogenic risks were assessed using a hazard index (HI) approach, based on a comparison of expected contaminant intakes and safe levels of intake (Reference Doses). Reference doses (RfDs) have been developed by EPA for indicating the potential for adverse health effects from exposure to chemicals exhibiting noncarcinogenic effects. RfDs, which are expressed in units of milligrams/kilogram-day (mg/kg-day), are estimates of daily exposure levels for humans which are thought to be safe over a lifetime (including sensitive individuals). Estimated intakes of chemicals from environmental media (e.g., the amount of a chemical ingested from contaminated drinking water) can be compared to the RfD. RfDs are derived from human epidemiological studies or animal studies to which uncertainty factors have been applied (e.g., to account for the use of animal data to predict effects on humans). These uncertainty factors help ensure that the RfDs will not underestimate the potential for adverse noncarcinogenic effects to occur. RfDs for Reynolds Study Area contaminants of concern are given in Table 5.

Human Health Risk Characterization

Excess lifetime cancer risks for the Reynolds Study Area were determined by multiplying the intake levels with the SF (see Table 5) for each contaminant of concern. These risks are probabilities that are expressed in scientific notation (e.g., 1×10^{-6}). An excess lifetime cancer risk of 1×10^{-6} indicates that as a plausible upper bound, an individual has an additional one in one million chance of developing cancer as a result of site-related exposure to contaminants over a 70-year lifetime under the specific exposure conditions presented in the Reynolds Study Area. Table 6 presents a summary of the carcinogenic risks posed by each exposure pathway developed for the Reynolds Study Area. The greatest carcinogenic risk values calculated for the Site are associated with the ingestion of fish caught in the St. Lawrence River. The only contaminants contributing to this value were PCBs.

For known or suspected carcinogens, EPA considers excess upper bound individual lifetime cancer risks of between 10^{-4} to 10^{-6} to be acceptable. This level indicates that an individual has not greater than a one in ten thousand to one in a million chance of developing cancer as a result of site-related exposure to a carcinogen over a 70-year period under specific exposure conditions at the Site. As illustrated in Table 6, the risks associated with all exposure pathways associated with the St. Lawrence River are outside the range considered acceptable by EPA. The risks associated with ingestion of fish from the Raguette River were calculated and were found to be unacceptable. However, these calculations were based on fish caught near the mouth of the Raguette River, not in the

immediate vicinity of the Reynolds facility. These risks are assumed to be attributable to sources other than the Reynolds Study Area Site due to the low levels of contaminants detected in Raquette River sediments (< 1 ppm PCBs) and surface water (< 65 ppt PCBs) in the vicinity of the Reynolds facility.

The potential risks of noncarcinogenic effects of contaminants in a single medium are expressed as the hazard index (or the ratio of the intake level for a given medium to the RfD), given in Table 5, for each contaminant of concern. Table 7 presents a summary of the HIs posed by each exposure pathway. Again, the noncarcinogenic effects associated with ingestion of fish are generally greater than those associated with other exposure pathways.

A hazard index greater than 1 indicates that potential exists for noncarcinogenic health effects to occur as a result of site-related exposures. The HI provides a useful reference point for gauging the potential significance of multiple contaminant exposures within a single medium or across media. As illustrated in Table 7, the noncarcinogenic effects associated with all exposure pathways associated with the St. Lawrence River are above 1. The noncarcinogenic effects associated with Raquette River pathways were below 1 due to the low levels of contaminants detected in Raquette River sediments and surface water.

It can be seen from Table 7 that the HI for noncarcinogenic effects from ingestion of fish from the St. Lawrence and Raquette Rivers is 70. Therefore, noncarcinogenic effects may occur from the exposure routes evaluated in the Risk Assessment. The noncarcinogenic risk was attributable to PCBs.

Uncertainties

The procedures and inputs used to assess risks in this evaluation, as in all such assessments, are subject to a wide variety of uncertainties. In general, the main sources of uncertainty include:

- environmental chemistry sampling and analysis;
- environmental parameter measurement;
- fate and transport modeling;
- exposure parameter estimation; and
- toxicological data.

Uncertainty in environmental sampling arises in part from the potentially uneven distribution of chemicals in the media sampled. Consequently, there is significant uncertainty as to the actual levels present. Environmental chemistry analysis error can stem from several sources including the errors inherent in the analytical methods and characteristics of the matrix being sampled. Uncertainty in the exposure assessment is related to the presence of potentially sensitive populations (fishermen and residents) in very close proximity to the Site. Additional uncertainties arise from estimates of how often an individual would actually come in contact with the chemicals of concern, the period of time over which such

exposure would occur, and in the models used to estimate the concentrations of the chemicals of concern at the point of exposure.

Uncertainties in toxicological data occur in extrapolating both from animals to humans and from high to low doses of exposure, as well as from the difficulties in assessing the toxicity of a mixture of chemicals. These uncertainties are addressed by making conservative assumptions concerning risk and exposure parameters throughout the assessment. As a result, the baseline risk assessment provides upper bound estimates of the risks to populations near the Site.

Potential site-specific sources of uncertainty for the Reynolds Study Area Site include the inherent variability associated with environmental sampling of biota, especially fish. For example, fish contaminant concentrations may vary depending on species, mobility, fat content, age, and feeding habits. The significant total number of samples in the Reynolds Study Area serves to reduce this source of uncertainty.

Environmental Risks

An ecological risk assessment was performed to determine the actual and/or potential effects of contaminants of concern on fish and other primarily aquatic wildlife in the Reynolds Study Area. A four-step process was utilized for assessing site-related ecological risks for a reasonable maximum exposure scenario: **Problem Formulation and Hazard Identification** - development of information characterizing habitats and potentially exposed species found in the Reynolds Study Area and identification of contaminants of concern and exposure pathways and receptors; **Exposure Assessment** - involves the estimation of actual and potential exposure point concentrations for selected indicator species; **Ecological Effects Assessment** - literature reviews, field studies, and toxicity tests linking contaminant concentrations to effects on indicator species; and **Risk Characterization** - measurement or estimation of both current and future adverse effects from exposure to contaminants in the Reynolds Study Area.

EPA identified several contaminants which were of concern from an ecological risk perspective and their respective animal receptors including PCBs, PAHs, aluminum, fluoride, and cyanide in aquatic macroinvertebrates, yellow perch, white sucker, least bittern, belted kingfisher, little brown bat, and mink. PCBs have been shown to have adverse effects on these receptors including reproductive impairment in certain birds and reproductive failure in mink.

Aquatic macroinvertebrates may take up contaminants from water which has contacted contaminated sediments. Aquatic macroinvertebrates are then consumed by fish, birds, and small mammals. Because PCBs remain in the fat cells of these animals, the concentrations of PCBs in these small animals increase over time. These small animals with increasingly higher PCB concentrations may then be eaten by larger animals.

The results of the ecological risk assessment indicate that the contaminated sediment and water in the St. Lawrence River in the Reynolds Study Area pose unacceptable risks to several species. These risks include reproductive effects to animals which bioaccumulate PCBs in their tissues. In addition, the concentrations of several contaminants, including aluminum and PAHs, are several times higher than federal and State ambient water quality criteria and federal sediment quality criteria and National Oceanic and Atmospheric Administration sediment guidelines which are based on protection of wildlife.

Risk Summary

Actual or threatened releases of hazardous substances from the Site, if not addressed by the preferred alternative or one of the other active measures considered, may present an imminent and substantial threat to public health, welfare or the environment.

VII. Description of Alternatives

Sediment Cleanup Levels

Based on the results of its risk assessment, EPA established cleanup levels for contaminated sediment in the Reynolds Study Area which are protective of human health and the environment. The cleanup levels are: PCBs - 1 ppm; PAHs - 10 ppm; TDBF - 1 ppb. Cleanup levels are the concentration of contaminants in sediment above which some remedial action will be taken (*i.e.*, treatment or containment). These cleanup levels were based on ingestion of fish by local residents and represent sediment contaminant concentrations which would be associated with carcinogenic risks on the order of 10^{-4} .

Cleanup to these levels will also remove the threat from other contaminants such as fluoride and cyanide. The 1 ppm PCB cleanup level is identical to that selected by EPA for contaminated sediment associated with the General Motors Site which is immediately downstream of the RMC facility. For the G.M. Site, EPA estimated that a 1 ppm PCB cleanup level in sediments is associated with a 10^{-4} (1 in 10,000) excess cancer risk to humans. For the RMC Study Area Site, EPA estimates that a 1 ppm PCB cleanup level in sediments is associated with an excess cancer risk to humans on the order of 10^{-4} (1 in 10,000). There is a variation in estimated residual cancer risks between the G.M. and RMC Study Area Sites due to uncertainties associated with estimating the effect of varying sediment PCB concentrations on area fish.

A rough approximation of the area which must be addressed to meet Site cleanup levels is given in Figure 11. There are approximately 51,500 cubic yards of sediment over a 27- acre area with PCB concentrations above 1 ppm, PAHs above 10 ppm, and TDBFs above 1 ppb. EPA considers such sediments to pose a principal threat to human health and the environment.

It should be noted that federal and New York State sediment quality criteria guidance indicate that PCB cleanup levels well below 1 ppm are required to achieve protection of the environment since PCBs pose a significant ecological risk. While EPA would prefer a lower cleanup level which would be associated with a 10^{-6} cancer risk, EPA has significant concerns as to the technical practicability of achieving a PCB cleanup level below 1 ppm in this area of the St. Lawrence River. In selecting the 1 ppm cleanup goal, EPA has balanced its desire for a very low cleanup level which will minimize residual risk with the constraints posed by the limitations of dredging as a means of removing sediment with the further intent of selecting treatment as a principal element over containment. EPA believes that a 1 ppm cleanup goal in the St. Lawrence River provides an acceptable measure of protection of human health.

Description of Alternatives

The AA Report evaluated in detail several alternatives for addressing the contamination in the St. Lawrence River in the Reynolds Study Area. These alternatives are described below. Construction times given include the time necessary to construct and implement the remedy but do not include the time required for design or contract award.

The remedial alternatives developed for the Site are consistent with EPA's 1990 "Guidance for Remedial Actions for Superfund Sites with PCB Contamination" (also referred to as the "PCB Guidance"). For instance, according to this guidance, soils with PCB concentrations in the 10 - 25 ppm range may be disposed on an industrial facility with minimal long-term management controls. Accordingly, EPA has evaluated an alternative for the RMC Site which includes disposal of sediments with PCB concentrations between 10 and 25 ppm in the Black Mud Pond, rather than in an engineered landfill (see Alternative G below). The PCB Guidance also recommends that soils with higher concentrations of PCBs be disposed on an industrial facility in an engineered containment system which may include a cover and liner system. Accordingly, EPA has evaluated alternatives which include disposal of untreated sediments (see Alternative D below) or treated sediments with PCB concentrations between 50 and 500 ppm in an engineered landfill (see Alternative I below). In addition, several of the other alternatives evaluated below (including Alternatives E, F, and J) include options for disposal in the Black Mud Pond or in an engineered landfill depending on whether the material is a hazardous waste. The alternatives are described in detail below.

Alternative A: No Action

Capital Cost: \$ 0
O&M Cost: \$ 0/year
Present Worth Cost: \$ 0
Construction Time: None

The Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) requires that the "no action" alternative be considered as a baseline for comparison with other alternatives. This action consists of allowing the 51,500 cubic yards of contaminated sediments with concentrations above the cleanup levels to remain in their present state. No actions would be taken to remove or contain contaminated sediments which currently pose a threat to human health and the environment.

Because this alternative would result in contaminants remaining on-site above health-based levels, CERCLA requires that the Site be reviewed at least once every five years. If justified by the review, remedial actions may be implemented to remove or treat the wastes.

Alternative B: In-Situ Capping of Sediments

Capital Cost: \$ 13.3 million
O&M Cost: \$ 190,000/year
Present Worth Cost: \$ 16.6 million
Construction Time: 3 years

This alternative involves leaving the 51,500 cubic yards of contaminated sediments in place and placing a multilayer cap consisting of fine-grained clean sand and a woven geotextile fabric over the sediments. The portion of the Site adjacent to the shoreline would then be armored to minimize erosion (see Figure 12). This alternative is designed to isolate and limit the transport of river sediments and is based on methods commonly used to reduce shoreline erosion.

Prior to construction, the Reynolds Study Area bathymetry would be refined and remapped. In addition, areas of dense vegetation and any areas containing boulders or debris would be identified and mapped. The geotextile fabric would be pieced together from sections delivered to the shoreline and each geofabric piece transported on a barge out to each area defined for sediment capping. Once lowered from the barge, the geotextile would be anchored with sand bags. The placement of the geotextile would be carefully controlled to minimize mudwaves and turbidity. Clean sand would then be spread in an approximate 1.5 foot layer over the geotextile using a diffuser.

Armoring material would then be placed in the shallow area adjacent to the shoreline which is exposed to wave action and boat wakes. The armoring system would be concrete revetment which consists of a water permeable fabric casing, which has been woven from high-

strength synthetic fibers and which would be laid by laborers and then filled with concrete. The total area of the cap would extend 10 to 20 percent beyond the contaminated area to maximize isolation of the contaminated sediment from the aquatic environment. Inspections and monitoring including depth sounding and water quality monitoring would be conducted during construction. After construction, a long-term physical, chemical, and biological performance monitoring program would be instituted to determine the cover's effectiveness in containing contaminated sediments. This alternative also provides for periodic maintenance of the cover and posting warning signs and restricting access from both on and offshore.

Because this alternative would result in contaminants remaining on-site above health-based levels, CERCLA requires that the Site be reviewed at least once every five years. If justified by the review, remedial actions may be implemented to remove or treat the wastes.

Alternative D: Sediment Removal/Landfilling

Capital Cost: \$ 33.4 million
O&M Cost: \$ 28,000/year
Present Worth Cost: \$ 33.9 million
Construction Time: 4 years

This alternative involves dredging sediment which is above Reynolds Study Area cleanup levels (approximately 51,500 cubic yards) from the St. Lawrence River adjacent to the RMC facility. The dredged sediment would then be pretreated and placed in an engineered landfill on the RMC facility.

Prior to dredging, silt curtains would be installed to minimize transport of contaminated sediment which may be suspended during the dredging process. Hydraulic dredges would be used to remove sediments. Oversized materials would be screened from the dredged sediments as the sediments are offloaded into scows and transported to the shoreline. Sediments would then be decanted and dewatered and placed, along with the previously screened oversized debris, into an on-site engineered landfill. Water removed from the sediments would be treated using methods including flocculation and chemical precipitation to remove solids, and sand bed filtration and activated carbon adsorption. All water that is removed from sediments would be discharged to the St. Lawrence River in compliance with the substantive requirements of the New York State Pollutant Discharge Elimination System (SPDES) which regulates surface water discharges in New York State.

Following completion of sediment placement in the landfill, the on-site landfill would be closed. Leachate from the landfill would be collected, treated, and discharged to the St. Lawrence River. Groundwater downgradient of the landfill would be monitored.

500581

The major ARARs associated with this alternative include the applicable federal Toxic Substances Control Act (TSCA) and the relevant and appropriate federal and State Resource Conservation and Recovery Act (RCRA) regulations which govern the construction, closure, and monitoring of the on-site landfill. In addition, all discharges to the St. Lawrence River would be subject to applicable substantive SPDES requirements and all operations would be subject to New York State air quality standards.

Because this alternative would result in contaminants remaining on-site above health-based levels, CERCLA requires that the Site be reviewed at least once every five years. If justified by the five year review, remedial actions may be implemented to remove or treat the wastes.

Alternative E: Sediment Removal/Incineration/On-site Disposal in the Black Mud Pond or Landfilling

Capital Cost: \$ 52.8 million (with Black Mud Pond disposal)
 \$ 55.3 million (with landfill construction)
O&M Cost: \$ 28,000/year
Present Worth Cost: \$ 53.3 million (with Black Mud Pond disposal)
 \$ 55.8 million (with landfill construction)
Construction Time: 4 years

This alternative involves dredging sediments which are above Reynolds Study Area cleanup levels (approximately 51,500 cubic yards) from the St. Lawrence River adjacent to the RMC facility. The dredged sediment would then be pretreated to remove water, incinerated to destroy organic contaminants, and disposed of on-site in the Black Mud Pond.

Prior to dredging, silt curtains would be installed to minimize transport of contaminated sediment which may be resuspended during the dredging process. Hydraulic dredges would be used to remove sediments. Oversized materials would be screened from the dredged sediments as the sediments are offloaded into scows and transported to the shoreline. Sediments would then be decanted, dewatered, and incinerated on-site. The incinerator ash would have PCB levels at or below 2 ppm.

The ash would be tested using the RCRA Toxicity Characteristic Leaching Procedure (TCLP) test to determine if it is a RCRA hazardous waste. EPA has tested the sediments and does not expect that the ash from the incinerator would be a RCRA hazardous waste. If the ash was not a RCRA hazardous waste, it would be disposed of on-site in the Black Mud Pond along with the previously screened debris. If the ash was found to be a RCRA hazardous waste, it would either be treated to render it non-hazardous or it would be disposed, along with the previously screened oversized debris, in an engineered on-site landfill. Therefore, the costs of this alternative may vary, depending on whether construction of an engineered landfill is necessary.

Water removed from the sediments would be treated using methods including flocculation and chemical precipitation to remove solids, and sand bed filtration and activated carbon adsorption. All water that is removed from sediments or generated during the treatment process would be discharged to the St. Lawrence River in compliance with substantive SPDES requirements.

The major ARARs associated with this alternative include the applicable federal TSCA and the relevant and appropriate federal and State RCRA regulations which govern the operation and monitoring of the on-site incinerator and the construction, closure, and monitoring of the on-site landfill. In addition, air emissions from the incinerator would be monitored to ensure compliance with federal Clean Air Act regulations and New York State air quality standards and air emissions regulations. Discharges to the St. Lawrence River would be subject to applicable substantive SPDES requirements.

Alternative F: Sediment Removal/Thermal Desorption/On-site Disposal in the Black Mud Pond or Landfilling

Capital Cost: \$ 43.7 million (with Black Mud Pond disposal)
 \$ 46.2 million (with landfill construction)
O&M Cost: \$ 28,000/year
Present Worth Cost: \$ 44.2 million (with Black Mud Pond disposal)
 \$ 46.7 million (with landfill construction)
Construction Time: 4 years

This alternative involves dredging sediments which are above Reynolds Study Area cleanup levels (approximately 51,500 cubic yards) from the St. Lawrence River adjacent to the RMC facility. The dredged sediment would then be pretreated to remove water, treated by thermal desorption to remove organic contaminants, and disposed of on-site.

Prior to dredging, silt curtains would be installed to minimize transport of contaminated sediment which may be suspended during the dredging process. Hydraulic dredges would be used to remove sediments. Oversized materials would be screened from the dredged sediments as the sediments are offloaded into scows and transported to the shoreline. Sediments would then be decanted, dewatered, and treated on-site. The sediment treatment process would consist of thermal desorption, an innovative technology which thermally extracts organic contaminants and subsequently condenses and recovers the distilled contaminants. The recovered contaminants would then be sent to an off-site location for incineration at a permitted commercial incinerator.

Based on the results of treatability testing, treated sediments would have PCB concentrations below 10 ppm. The treated sediments would be tested using the RCRA TCLP test to determine if they are a RCRA hazardous waste. EPA has tested the sediments and does not expect that the treated sediments would be a RCRA hazardous waste. If the treated sediments were not a RCRA hazardous waste, they would be disposed of on-site in the Black Mud Pond along with the

previously screened debris. If the treated sediments were found to be a RCRA hazardous waste, they would either be treated to render them non-hazardous or they would be disposed, along with the previously screened oversized debris, in an engineered on-site landfill. Therefore, the costs of this alternative may vary, depending on whether construction of an engineered landfill is necessary.

Water removed from the sediments would be treated using methods including flocculation and chemical precipitation to remove solids, and sand bed filtration and activated carbon adsorption. All water that is removed from sediments or generated during the treatment process would be discharged to the St. Lawrence River in compliance with substantive SPDES requirements.

The major ARARs associated with this alternative include the applicable federal TSCA and the relevant and appropriate federal and State RCRA regulations which govern the construction, closure, and monitoring of the on-site landfill. In addition, air emissions from the thermal desorption process would be monitored to ensure compliance with federal Clean Air Act regulations and New York State air quality standards and air emissions regulations. Discharges to the St. Lawrence River would be subject to applicable substantive SPDES requirements.

Alternative G: Sediment Removal/Partial Thermal Desorption/Disposal in the Black Mud Pond

Alternative G(A) - 25 ppm treatment level
Capital Cost: \$ 34.8 million
O&M Cost: \$ 28,000/year
Present Worth Cost: \$ 35.1 million
Construction Time: 4 years

Alternative G(B) - 10 ppm treatment level
Capital Cost: \$ 36.4 million
O&M Cost: \$ 28,000/year
Present Worth Cost: \$ 36.7 million
Construction Time: 4 years

This alternative is very similar to Alternative F above. However, under this alternative, only those more highly contaminated sediments would be treated by thermal desorption. As in Alternatives D - F, this alternative involves dredging sediments which are above Reynolds Study Area cleanup levels (approximately 51,500 cubic yards) from the St. Lawrence River adjacent to the RMC facility. The dredged sediment would then be pretreated to remove water. Sediment with PCB concentrations above the treatment level would be treated by thermal desorption to remove organic contaminants. Treated sediment and untreated sediment would then be disposed of on-site in the Black Mud Pond.

Under this alternative, EPA has evaluated two different treatment levels. Under Alternative G(A), only those sediments with PCB

concentrations above 25 ppm (approximately 14,500 cubic yards) would be treated by thermal desorption. The remaining 37,000 cubic yards of sediment with PCB concentrations at or below 25 ppm would be disposed of on-site without prior treatment. Under Alternative G(B), only those sediments with PCB concentrations above 10 ppm (approximately 19,700 cubic yards) would be treated by thermal desorption. The remaining 31,800 cubic yards of sediment would be disposed of on-site without prior treatment. The 10 ppm and 25 ppm PCB treatment levels evaluated represent levels which EPA generally considers acceptable for on-site disposal in an industrial area (see discussion on page 12). Per the EPA PCB Guidance, material with PCB concentrations in the 10 - 25 ppm range may generally be disposed of on an industrial facility with minimal long-term management.

Prior to dredging, silt curtains would be installed to minimize transport of contaminated sediment which may be suspended during the dredging process. Hydraulic dredges would be used to remove sediments. Oversized materials would be screened from the dredged sediments as the sediments are offloaded into scows and transported to the shoreline. Sediments would then be decanted, dewatered, and, for those sediments with PCB concentrations above the treatment level, treated on-site by thermal desorption. Condensed contaminants recovered during treatment would then be sent to an off-site location for incineration at a permitted commercial incinerator.

Based on the results of treatability testing, treated sediments would have PCB concentrations below 10 ppm. Treated and untreated sediments would be tested to ensure that they cannot be classified as a RCRA hazardous waste using the RCRA TCLP test. Treated sediments, along with untreated dewatered sediments, would be disposed of on-site in the Black Mud Pond and capped in conformance with the requirements of the January 22, 1992 New York State Record of Decision for the state lead Reynolds Metals Site.

Water removed from the sediments would be treated using methods including flocculation and chemical precipitation to remove solids, and sand bed filtration and activated carbon adsorption. All water that is removed from sediments or generated during the treatment process would be discharged to the St. Lawrence River in compliance with substantive SPDES requirements.

The major ARARs associated with this alternative include the applicable federal TSCA and the relevant and appropriate federal and State RCRA regulations which govern the disposal and monitoring of the sediments. In addition, air emissions from the thermal desorption process would be monitored to ensure compliance with federal Clean Air Act regulations and New York State air quality standards and air emissions regulations. Discharges to the St. Lawrence River would be subject to applicable substantive SPDES regulations.

Because this alternative would result in contaminants remaining on-site above health-based levels, CERCLA requires that the Site be

reviewed at least once every five years. If justified by the five year review, remedial actions may be implemented to remove or treat the wastes.

Alternative I: Sediment Removal/Partial Thermal Desorption/Landfilling

Alternative I(A) - 500 ppm treatment level
Capital Cost: \$ 35.3 million
O&M Cost: \$ 28,000/year
Present Worth Cost: \$ 35.8 million
Construction Time: 4 years

Alternative I(B) - 50 ppm treatment level
Capital Cost: \$ 37.4 million
O&M Cost: \$ 28,000/year
Present Worth Cost: \$ 37.9 million
Construction Time: 4 years

This alternative is very similar to Alternative G above. However, under this alternative, only the most highly contaminated sediments would be treated by thermal desorption. As in Alternatives F and G, this alternative involves dredging sediments which are above Reynolds Study Area cleanup levels (approximately 51,500 cubic yards) from the St. Lawrence River adjacent to the RMC facility. The dredged sediment would then be pretreated to remove water and sediment with PCB concentrations above the treatment level would be treated by thermal desorption to remove organic contaminants. Treated sediment and untreated sediment would then be disposed of on-site.

Under this alternative, EPA has evaluated two different treatment levels. Under Alternative I(A), only those sediments with PCB concentrations above 500 ppm (approximately 2,300 cubic yards) would be treated by thermal desorption. The remaining 49,200 cubic yards of sediment with PCB concentrations below 500 ppm would be disposed of in an on-site landfill without prior treatment. Under Alternative I(B), only those sediments with PCB concentrations above 50 ppm (approximately 11,300 cubic yards) would be treated by thermal desorption. The remaining 39,700 cubic yards of sediment would be disposed of on-site without prior treatment. The 500 ppm and 50 ppm PCB treatment levels evaluated represent levels which EPA generally considers acceptable for on-site disposal in an industrial area (see discussion on page 12). Per the EPA PCB Guidance, material with PCB concentrations in the 50 - 500 ppm range may generally be disposed of on an industrial facility in an engineered containment system.

Prior to dredging, silt curtains would be installed to minimize transport of contaminated sediment which may be suspended during the dredging process. Hydraulic dredges would be used to remove sediments. Oversized materials would be screened from the dredged sediments as the sediments are offloaded into scows and transported to the shoreline. Sediments would then be decanted, dewatered, and,

for those sediments with PCB concentrations above the treatment level, treated on-site by thermal desorption. Condensed contaminants recovered during treatment would then be sent to an off-site location for incineration at a permitted commercial incinerator.

Based on the results of treatability testing, treated sediments would have PCB concentrations below 10 ppm. Treated and untreated sediments would be placed, along with the previously screened oversized debris and untreated sediments, into an on-site landfill.

Water removed from the sediments would be treated using methods including flocculation and chemical precipitation to remove solids, and sand bed filtration and activated carbon adsorption. All water that is removed from sediments or generated during the treatment process would be discharged to the St. Lawrence River in compliance with substantive SPDES requirements.

The major ARARs associated with this alternative include the applicable federal TSCA and the relevant and appropriate federal and State RCRA regulations which govern the construction, closure, and monitoring of the on-site landfill. In addition, air emissions from the thermal desorption process would be monitored to ensure compliance with federal Clean Air Act regulations and New York State air quality standards and air emissions regulations. Discharges to the St. Lawrence River would be subject to applicable substantive SPDES regulations.

Because this alternative would result in contaminants remaining on-site above health-based levels, CERCLA requires that the Site be reviewed at least once every five years. If justified by the five year review, remedial actions may be implemented to remove or treat the wastes.

Alternative J: Partial Sediment Removal/Thermal Desorption/On-site Disposal in the Black Mud Pond or Landfilling/In-Situ Capping

Capital Cost: \$ 17.1 million (with Black Mud Pond disposal)
 \$ 19.6 million (with landfill construction)
O&M Cost: \$ 28,000/year
Present Worth Cost: \$ 17.6 million (with Black Mud Pond disposal)
 \$ 23.2 million (with landfill construction)
Construction Time: 3 years

This alternative includes dredging approximately 2,300 cubic yards of contaminated sediment with PCB concentrations above 500 ppm from the St. Lawrence River adjacent to the RMC facility. The dredged sediment would then be pretreated to remove water and treated by thermal desorption to remove organic contaminants. Treated sediment would then be disposed of on-site. The remaining 49,200 cubic yards of contaminated sediment would be left in place and covered in the river with a multilayer cap.

Prior to dredging, silt curtains would be installed to minimize transport of contaminated sediment which may be resuspended during the dredging process. Hydraulic dredges would be used to remove sediments. Oversized materials would be screened from the dredged sediments as the sediments are offloaded into scows and transported to the shoreline. Sediments would then be decanted, dewatered, and treated on-site by thermal desorption. Condensed contaminants recovered during treatment would then be sent to an off-site location for incineration at a permitted commercial incinerator. Water removed from the sediments would be treated using methods including flocculation and chemical precipitation to remove solids, and sand bed filtration and activated carbon adsorption. All water that is removed from sediments or generated during the treatment process would be discharged to the St. Lawrence River in compliance with substantive SPDES requirements.

Based on the results of treatability testing, treated sediments would have PCB concentrations below 10 ppm. The treated sediments would be tested using the RCRA TCLP test to determine if they are a RCRA hazardous waste. EPA has tested the sediments and does not expect that the treated sediments will be a RCRA hazardous waste. If the treated sediments are not a RCRA hazardous waste, they will be disposed of on-site in the Black Mud Pond along with the previously screened debris. If the treated sediments are found to be a RCRA hazardous waste, they will either be treated to render them non-hazardous or they will be disposed, along with the previously screened oversized debris, in an engineered on-site landfill. Therefore, the costs of this alternative may vary, depending on whether construction of an engineered landfill is necessary.

As in Alternative B, the remaining 49,200 cubic yards of sediment would be left in place and a multilayer cap consisting of fine-grained clean sand and a woven geotextile fabric would be placed over the sediments. The capping system design, construction, and monitoring would be identical to that described in Alternative B. This alternative also provides for periodic maintenance of the cover and posting warning signs and restricting access from both on and offshore.

The major ARARs associated with this alternative include the applicable federal TSCA and the relevant and appropriate federal and State RCRA regulations which govern the construction, closure, and monitoring of the on-site landfill. In addition, air emissions from the thermal desorption process would be monitored to ensure compliance with federal Clean Air Act regulations and New York State air quality standards and air emissions regulations. Discharges to the St. Lawrence River would be subject to applicable substantive SPDES regulations.

Because this alternative would result in contaminants remaining on-site above health-based levels, CERCLA requires that the Site be reviewed at least once every five years. If justified by the five

year review, remedial actions may be implemented to remove or treat the wastes.

VIII. Summary of Comparative Analysis of Alternatives

In accordance with the National Contingency Plan (NCP), a detailed analysis of each alternative was performed. The purpose of the detailed analysis was to objectively assess the alternatives with respect to nine evaluation criteria that encompass statutory requirements and include other gauges of the overall feasibility and acceptability of remedial alternatives. The analysis was comprised of an individual assessment of the alternatives against each criterion and a comparative analysis designed to determine the relative performance of the alternatives and identify major trade-offs, that is, relative advantages and disadvantages, among them.

The nine evaluation criteria against which the alternatives were evaluated are as follows:

Threshold Criteria - The first two criteria must be satisfied in order for an alternative to be eligible for selection.

1. Overall Protection of Human Health and the Environment addresses whether a remedy provides adequate protection and describes how risks posed through each pathway are eliminated, reduced, or controlled through treatment, engineering controls, or institutional controls.
2. Compliance with Applicable, or Relevant and Appropriate Requirements (ARARs) is used to determine whether each alternative will meet all of its federal and state ARARs. When an ARAR is not met, the detailed analysis should discuss whether one of the six statutory waivers is appropriate.

Primary Balancing Criteria - The next five "primary balancing criteria" are to be used to weigh major trade-offs among the different hazardous waste management strategies.

3. Long-term Effectiveness and Permanence focuses on any residual risk remaining at the Site after the completion of the remedial action. This analysis includes consideration of the degree of threat posed by the hazardous substances remaining at the Site and the adequacy of any controls (for example, engineering and institutional) used to manage the hazardous substances remaining at the Site.
4. Reduction of Toxicity, Mobility, or Volume Through Treatment is the anticipated performance of the treatment technologies a particular remedy may employ.

5. **Short-term Effectiveness** addresses the effects of the alternative during the construction and implementation phase until the remedial response objectives are met.
6. **Implementability** addresses the technical and administrative feasibility of implementing an alternative and the availability of various services and materials required during its implementation.
7. **Cost** includes estimated capital, and operation and maintenance costs, both translated to a present worth basis. The detailed analysis evaluates and compares the cost of the respective alternatives, but draws no conclusions as to the cost effectiveness of the alternatives. Cost effectiveness is determined in the remedy selection phase, when cost is considered along with the other balancing criteria.

Modifying Criteria - The final two criteria are regarded as "modifying criteria," and are to be taken into account after the above criteria have been evaluated. They are generally to be focused upon after public comment is received.

8. **State Acceptance** reflects the statutory requirement to provide for substantial and meaningful State and Tribal involvement.
9. **Community Acceptance** refers to the St. Regis Mohawk Tribe's and the community's comments on the remedial alternatives under consideration, along with the Proposed Plan. Comments received during the public comment period, and the EPA's responses to those comments, are summarized in the Responsiveness Summary which is attached to this ROD.

The following is a summary of the comparison of each alternative's strengths and weaknesses with respect to the nine evaluation criteria.

Overall Protection of Human Health and the Environment

With the exception of Alternative A, no action, each of the alternatives, if properly implemented, operated, and maintained, protects human health and the environment. Although the alternatives differ in the degree of protection they afford, all reduce excess carcinogenic health risks to humans to levels within the acceptable EPA range of 10^{-4} to 10^{-6} . Each of the alternatives also differs in how they provide protection, either through treatment of contaminated sediments, containment of sediments, or a combination of both.

Since Alternative A, the no action alternative, is not protective, it will not be considered in the remainder of this analysis.

Compliance with ARARs

All action alternatives comply with ARARs. As noted in the section above, the major federal and State ARARs include portions of TSCA and RCRA and State solid and hazardous waste disposal regulations. In addition, State SPDES provisions and federal Clean Air Act regulations are also ARARs for several of the alternatives. There are no chemical-specific ARARs for sediments.

Any thermal desorber will involve the release of an air stream from which PCBs have been removed. Such an air stream must represent an acceptable risk for PCBs and products of incomplete combustion, if any combustion occurs in the thermal desorption process. Evaluation of risk and of the TSCA requirements for a 99.9999% mass emissions factor will be included in determining the operation of the thermal desorber. In addition, emissions from the desorber must meet federal and State ARARs.

Long-Term Effectiveness and Permanence

In general, the containment and capping alternatives (Alternatives B and D) provide a lesser degree of permanence in remediating contamination than treatment alternatives (Alternatives E, F, G, I, and J) which destroy contamination. Alternative B which allows contamination to remain in the river system is less permanent than Alternative D. Alternatives E and F, which include treatment of all contaminated sediment, best meet this criterion. The mixed treatment/containment alternatives (Alternatives G, I, and J) provide a higher degree of permanence than the containment alternatives (Alternatives B and D) through permanent destruction of contaminants in highly contaminated sediments.

Of the alternatives which include treatment of contaminated sediments (Alternatives E, F, G, I, and J), long-term effectiveness varies depending on the extent to which contaminants are permanently destroyed. Accordingly, Alternatives E and F which include treatment and destruction of contaminants in all dredged sediments are more effective than Alternatives G, I, and J which include partial treatment of contaminants in dredged sediments. Similarly, Alternative G which includes treatment of sediments with PCB concentrations above 25 ppm (Alternative G(A)) or 10 ppm (Alternative G(B)) is more effective than Alternatives I and J which include treatment of sediments with PCB concentrations above 500 ppm (Alternative I(A) and Alternative J) or 50 ppm (Alternative I(B)).

The proper implementation of all alternatives would result in acceptable residual cancer risks and noncarcinogenic effects, i.e., cancer risks between 10^{-4} and 10^{-6} , and hazard indices below 1. However, the effectiveness of certain alternatives is dependent on specific technical constraints. For example, the long-term effectiveness of Alternative B (in-situ capping) depends on the success of efforts to accurately place the sediment cap and to repair or replace the cap if monitoring indicates that it is failing

to adequately isolate the sediments. Similarly, the effectiveness of Alternatives D, E, F, G, and I will depend on whether it is technically possible to dredge contaminated sediments completely such that all sediment cleanup levels are met.

Alternatives B and J, which include in-situ capping, would require the greatest degree of long-term monitoring and operation and maintenance. This is because, contrary to the other alternatives where contaminated sediments are removed from the river system, the contaminated sediments would be left in-place in the river system under Alternatives B and J. Monitoring and maintenance of contained underwater sediments is technically more difficult than monitoring treated or untreated sediments which are placed in an upland landfill. Because the sediments are submerged, the contained underwater sediments would require periodic inspections by divers. In addition, several rounds of sampling might be required to detect underwater containment cell leakage, since any leaking contamination would be diluted. Further, if underwater monitoring revealed that cap repairs were necessary, such repairs could likely only be undertaken in late spring or in summer.

In addition, the operation and maintenance requirements for Alternatives B and J pose the greatest uncertainties and technical difficulties. For example, the risk to human health and the environment is greatest if Alternatives B and J fail since contaminated sediments would reenter the river system and be available to contaminate fish and wildlife. Sediments contained in a landfill are more secure since a leak in the landfill cap or liner does not automatically result in sediments reentering the river system and contaminating fish and wildlife.

Reduction of Toxicity, Mobility, or Volume through Treatment

In general, all of the alternatives which include dredging and treatment best meet this criterion. Alternatives E and F, which include treatment of all 51,500 cubic yards of contaminated sediments with PCB concentrations above 1 ppm, would result in the greatest reduction of toxicity, mobility, and volume of all the alternatives. Alternative G which includes treatment of sediments with PCB concentrations above 25 ppm (Alternative G(A)) or 10 ppm (Alternative G(B)) is more effective in reducing contaminant toxicity, mobility, and volume than Alternatives I and J which includes treatment of sediments with PCB concentrations above 500 ppm (Alternative I(A) and Alternative J) or 50 ppm (Alternative I(B)).

Although capping and containment alternatives (Alternatives B and D) would reduce the mobility of contaminated material in sediment, no treatment would be performed. Incineration or thermal desorption of sediments (as in Alternatives E, F, G, I, and J) would reduce the mobility, toxicity, and volume of the contaminated material. Incineration produces an ash which must be disposed. Thermal desorption would produce a toxic extract which would be shipped off-site for incineration. Both thermal desorption and incineration

would result in the production of treated sediment residuals or ash which EPA does not anticipate will be hazardous.

Short-Term Effectiveness

In general, effective alternatives which can be implemented quickly with little risk to human health and the environment are favored under this criterion. Of the action alternatives evaluated, Alternative B (in-situ capping) would have the fewest short-term effects because sediment suspension would be minimized. Sediment suspension is a concern because any suspended contaminated sediment could redeposit in downstream areas. Alternatives which involve sediment dredging (Alternatives D, E, F, G, I, and J) include the use of extensive controls such as silt curtains to minimize sediment suspension and deposition in the River.

Sediment treatment alternatives (Alternatives E, F, G, I, and J) would reduce the potential for direct contact with contaminated sediment by permanently removing the source of contamination. Community and worker exposure would be minimized by the use of construction methods that minimize air emissions from treatment processes; also, protective equipment that minimizes workers' contact with the contaminated materials would be utilized. Air quality would be monitored during remediation.

Completion of remedial design for any selected remedy would take up to two years. The time required to implement each alternative is: 3 years for Alternative B; 4 years for Alternatives D, E, F, G, and I; and 3 years for Alternative J.

Implementability

All of the alternatives are implementable from an engineering standpoint. However, there are some inherent difficulties which make some alternatives more difficult to implement than others.

While the technology associated with Alternatives B and J (in-situ capping) has been generally used in lakes and harbors, the technical feasibility of ensuring the integrity of the cap, given the currents in the area adjacent to the RMC facility, remains questionable. If the integrity of the cap cannot be maintained in the future, additional cleanup activities, such as sediment dredging, would be required. In addition, because sediments would remain underwater, it may be technically difficult to monitor the effectiveness of the cap. If a cap failure went undetected, fish and wildlife would again be exposed to PCBs and other contaminants.

The greatest potential technical difficulty associated with the sediment removal alternatives (Alternatives D, E, F, G, I, and J) is the technical feasibility of dredging sediments sufficiently to achieve the cleanup goals for the Site. With the exception of the G.M. Site, to date, no environmental dredging program has had as its goal the removal of sediments to levels of 1 ppm PCBs. If dredging cannot achieve the 1 ppm PCB level, additional cleanup activities,

which could include sediment containment, would be required. For example, Alternative J includes a combination of dredging to remove some highly contaminated sediment and containment of the remaining sediment which is not dredged.

Incineration, a component of Alternative E, is the most proven and widely available technology for treating many contaminants. However, test burns would be required prior to implementation of incineration. Thermal desorption processes, included in Alternatives F, G, I, and J, while not as widely applied as incineration, have been used in full-scale sediment remediation. Landfilling is also a widely used, easily implementable, relatively easily monitored technology. Coordination with several agencies, including the St. Lawrence Seaway Development Corporation and the U.S. Corps of Engineers would be required prior to implementation of any alternative.

Cost

The costs associated with each alternative are presented in the descriptions of the alternatives given above. These costs are estimates and may change as a result of modifications made during design and/or construction.

The least expensive action alternative is Alternative B with a present worth cost of \$ 16.6 million. Alternative J is the next least expensive with present worth costs ranging from \$ 17.6 million to \$ 23.2 million. Alternatives D, G and I have present worth costs which range from \$ 33.9 million to \$ 37.9 million. Alternative F has present worth costs which range from \$ 44.2 million to \$ 46.7 million. Alternative E is the most expensive alternative with present worth costs ranging from \$ 53.3 million to \$ 55.8 million.

State Acceptance

The NYSDEC strongly supports the proposed dredging of contaminated sediments from the river, agrees with EPA's cleanup levels for the Site, and agrees with and supports the concept of using the Black Mud Pond for the disposal of untreated sediments and treatment residuals. However, while the NYSDEC agrees with the cleanup numbers for the Site, they do not agree with the process by which they were obtained. In addition, the NYSDEC would encourage the use of lower treatment levels if it could be demonstrated that doing so would not add unreasonable costs to the project.

Community Acceptance

Comments from the community submitted during the public comment period indicate that the community has varying opinions regarding remediation of the Reynolds Study Area. The St. Regis Mohawk Tribe expressed a desire for a cleanup plan which takes the contaminants out of the river system and permanently disposes of them. They prefer a 0.1 ppm PCB cleanup level for contaminated sediments and called for additional sampling in the Raquette River.

Comments received from the general public indicated that a majority supported Alternative G(B) with one modification: that sediments and treated residuals be disposed in an engineered landfill, rather than disposed of on-site with a soil cover. Comments from the Canadian government indicated that they believed a pilot-scale dredging study was essential prior to full-scale remedy implementation and requested that EPA consider additional containment measures other than a soil cover for sediments. However, comments received from area industries, including Reynolds, General Motors, and ALCOA, and from the Massena Industrial Development Corporation supported the increased use of in-place containment of sediments as part of EPA's selected remedy and questioned whether a 1 ppm PCB cleanup level is technically achievable. Comments are responded to in detail in the Responsiveness Summary which is an appendix to this document.

IX. Selected Remedy

Based upon an evaluation of the various alternatives and comments received from the public, EPA has selected Alternative G(A), Sediment Removal/Partial Thermal Desorption/Disposal in the Black Mud Pond for remediation of the Reynolds Study Area Site. The major components of the selected remedy include:

- Dredging/Excavation of Contaminated Sediments

Sediments in the St. Lawrence River with PCB levels above 1 ppm, PAH levels above 10 ppm, and TDBF levels above 1 ppb will be dredged and/or excavated. The approximate area to be dredged is shown in Figure 11. EPA estimates that approximately 51,500 cubic yards of sediment will be removed from the Reynolds Study Area though the actual volume of sediment which exceeds the above criteria may prove to exceed or be less than that amount. All contaminated sediments in the area to be dredged will be removed given the technological limitations associated with dredging. In selecting the 1 ppm cleanup goal, EPA has balanced its desire for a very low cleanup level which will minimize residual risk with the constraints posed by dredging as a means of removing sediment from a riverine environment.

Prior to dredging, additional sediment and surface water sampling will be conducted to better delineate the extent of the area to be dredged and to serve as baseline monitoring data. The area to be sampled will include the upriver portion of the Reynolds Study Area and the area near the mouth of the Grasse River. Bathymetry in the Reynolds Study Area will be refined and remapped. In addition, areas of dense vegetation and any areas containing boulders or debris will be identified and mapped. The initial dredging program will be conducted in a manner which will identify site-specific information and operating parameters such as dredging rates and depths, sediment removal efficiencies, silt curtains and sheet piling effectiveness, sediment dewatering methods, and sediment suspension and settling characteristics. This information will be evaluated and used as appropriate in modifying operating procedures to improve the effectiveness of the removal program.

Silt curtains and, if deemed necessary during design, sheet piling will be installed on the river side of the areas to be dredged to provide a stilling basin for dredging operations and to minimize transport of contaminated sediment which may be resuspended during the dredging process. Sediments will generally be removed using hydraulic dredges but mechanical dredges may also be used when appropriate. Sediments near the shoreline may also be excavated using conventional excavation equipment. During dredging, sediments and surface water will be monitored to ensure that downstream transport of contaminated sediment is minimized. A contingency plan will be developed which describes measures to control and/or minimize the impacts of dredging. Measures to control the impacts of dredging could include, if approved by EPA, modification and/or suspension of dredging activities. Oversized materials will be screened from the dredged sediments as the sediments are transported to the shoreline. Dredged/excavated areas will be restored to their original grade either through the use of fill or, if determined to be appropriate by EPA during design, through natural sediment deposition.

- Partial Thermal Desorption of Sediments

Removed sediments will then be decanted and dewatered. Those sediments with PCB concentrations above 25 ppm (approximately 14,500 cubic yards) will then be treated on-site by thermal desorption. Based on the results of treatability testing, treated sediments will have PCB concentrations below 10 ppm. Condensed contaminants recovered during thermal desorption will be sent to an off-site location for incineration at a permitted commercial incinerator. Water removed from the sediments will be treated using methods including flocculation and chemical precipitation to remove solids, and sand bed filtration and activated carbon adsorption. All water that is removed from sediments or generated during the treatment process will be discharged to the St. Lawrence River in compliance with substantive SPDES requirements.

Emissions from the thermal desorption system will be controlled using venturi scrubbers and scrubber towers. Emissions will be monitored to ensure compliance with federal and State air quality and emissions requirements.

- Sediment On-site Disposal in the Black Mud Pond

Sediments will be tested using the RCRA TCLP to ensure that they cannot be classified as RCRA hazardous waste. If they are RCRA hazardous waste, additional treatment, such as solidification, may be required to render them non-hazardous. Treated sediments, along with approximately 37,000 cubic yards of untreated dewatered sediments with PCB concentrations between 1 and 25 ppm, and rinsed oversized material will be disposed of on-site in the Black Mud Pond. The Black Mud Pond will be capped, in compliance with the requirements of the New York State-Reynolds Consent Order, with a multilayer cap and monitored and maintained to ensure the integrity of the cap.

Prior to remediation, a floodplains assessment will be performed and a determination will be made as to the consistency of the remedial action with the New York State Coastal Zone Management Program. Some changes may be made to the remedy as a result of the remedial design and construction processes. If the changes are significant, for purposes of Section 300.435(c)(2) of the National Contingency Plan, then EPA will follow the appropriate procedures set forth in that regulatory provision. Monitoring of the St. Lawrence River sediments, water, and biota will be performed prior to, during, and after dredging operations.

The capital cost of the selected remedy is \$ 34.8 million. Annual operation and maintenance costs are \$ 28,000/year. The total present worth cost of the selected remedy is \$ 35.1 million. A more detailed breakdown of estimated costs associated with the selected remedy is presented in Table 8.

X. Statutory Determinations

Protection of Human Health and the Environment

The selected remedy protects human health and the environment through the removal of contaminated sediments from the river system and the subsequent permanent treatment of highly contaminated sediments. Treated sediments and untreated sediments with low level contamination will be disposed of on-site. Cleaned oversized items which cannot be treated will also be disposed of on-site. Following implementation of the selected remedy, the excess cancer risk to adults will be on the order of 10^{-4} , within the range considered acceptable by EPA. In addition, following implementation, hazard indices for non-carcinogens will be less than one.

Compliance with Applicable or Relevant and Appropriate Requirements

A list of ARARs for the selected remedy is presented in Table 9. The selected remedy complies with these ARARs.

TSCA is the primary federal law which regulates the disposal of PCBs. A special allowance is made under 40 CFR §761.60(a)(5)(iii) of the TSCA regulations for dredged material disposal. For the reasons described in this document (see the discussions in Part VIII entitled "Long-term Effectiveness and Permanence", "Reduction of Toxicity, Mobility, or Volume through Treatment", and "Cost" and the discussion in the following section), EPA believes that the remedy selected herein is consistent with the TSCA requirements at 40 CFR §761.60(a)(5)(iii).

Cost-Effectiveness

The selected remedy is cost-effective because it has been demonstrated to provide overall effectiveness proportional to its

costs. The present worth cost of the selected alternative, Alternative G(A), which includes a 25 ppm treatment threshold, is \$ 35.1 million. The present worth cost of Alternative G(B), which includes a 10 ppm treatment threshold, is \$ 36.7 million. The present worth cost of Alternative I(A), which incorporates a 500 ppm treatment threshold, is \$ 35.8 million. The present worth cost of Alternative I(B), which incorporates a 50 ppm treatment threshold, is \$ 37.9 million. Thus, EPA has selected the least expensive alternative which provides for permanent removal and treatment of the majority of the principal threat posed by contaminated sediments. In addition, a comparison of the costs of Alternatives G(A), I(A), and I(B) demonstrates that it is more expensive to construct a landfill for disposal of sediments with PCB concentrations between 25 and 500 ppm than it is to treat such sediments. Therefore, Alternative G(A) is more cost-effective than Alternative I.

The use of thermal desorption, rather than incineration, minimizes the cost of treatment. The 25 ppm treatment threshold results in permanent treatment of the majority of the PCB mass within the contaminated sediments and is consistent with EPA guidance and the State's cleanup plans for the upland portion of the Reynolds facility, while at the same time being less expensive than Alternative G(B), which includes a treatment level of 10 ppm. EPA's preference for use of the Black Mud Pond for disposal is also cost-effective since it will minimize the amount of fill needed in this area and it will consolidate material in one management area.

Utilization of Permanent Solutions and Alternative Treatment
(or resource recovery) Technologies to the Maximum Extent
Practicable (MEP)

The selected remedy utilizes permanent solutions and treatment technologies to the maximum extent practicable. The selected remedy represents the best balance of tradeoffs in terms of long-term effectiveness and permanence, reduction in toxicity, mobility, or volume through treatment, short-term effectiveness, implementability, and cost while also considering the statutory preference for treatment as a principal element and considering State, Tribe, and community acceptance.

The selected remedy offers a higher degree of permanence than in-situ containment alternatives.. Because PCBs, PAHs, and TDBFs are highly persistent in the environment, removal and treatment provide the most effective way of assuring long-term protection. In addition, the treatment of the most highly contaminated sediments combined with on-site containment of untreated sediments and treatment residuals significantly reduces the total concentration of PCBs in the material which must be managed over the long-term. The use of thermal desorption combined with incineration of the condensed extract from the thermal desorption process will reduce the toxicity and mobility of contaminants. Although there are short-term impacts associated with the selected remedy, these will

be mitigated through the use of controls such as silt curtains and, if necessary, sheet piles.

EPA realizes that the implementability of the selected remedy has not been fully established. Therefore, the initial dredging program will be conducted in a manner which will identify site-specific information and operating parameters such as dredging rates and depths, sediment removal efficiencies, silt curtains and sheet piling effectiveness, sediment dewatering methods, and sediment suspension and settling characteristics. This information will be evaluated and used as appropriate in modifying operating procedures to improve the effectiveness of the removal program. Among the alternatives considered for the Site, the major tradeoffs that provided the basis for EPA's remedy selection were the fact that the selected remedy provides long-term effectiveness and permanence and reduces the toxicity of the principal threat material at the lowest cost while being consistent with the State's selected remedy for the upland portion of the Reynolds facility.

Preference for Treatment as a Principal Element

By removing and treating the contaminated sediments with PCB concentrations above 25 ppm, the selected remedy satisfies the statutory preference for remedies that employ treatment as a principal element. The selected remedy is consistent with Superfund program expectations that indicate that highly toxic, persistent wastes are a priority for treatment.

XI. Documentation of Significant Changes

After reviewing comments received from the New York State Department of Environmental Conservation, EPA has determined that the Black Mud Pond would be a suitable location for disposal of treatment residuals and untreated sediment. Utilization of the Black Mud Pond as a disposal area would consolidate contaminants in one management unit while realizing cost savings due to eliminating construction, maintenance, and monitoring of a new disposal cell and substantially reducing the volume of fill needed for the Black Mud Pond before capping.


Originally, EPA, in its Proposed Plan, preferred Alternative G(B), sediment removal/partial thermal desorption/disposal with soil cover which incorporated a 10 ppm PCB treatment level. However, EPA has determined that a 25 ppm PCB treatment level is consistent with New York State's plans for remediating on-site contamination and that this change will lower remedial costs. However, although the treatment level is consistent, the process by which the number was obtained is not consistent with the State's process by which they obtained their cleanup and treatment numbers for the on-site contamination. This treatment level is consistent with EPA guidance which recommends a 10 - 25 ppm soil cleanup level for industrial sites as generally protective of human health and the environment.


In addition, material with PCB concentrations below 25 ppm could be placed in the Black Mud Pond since it would not contain concentrations significantly above material currently found in the Black Mud Pond. Accordingly, EPA has selected Alternative G(A), which incorporates a 25 ppm PCB treatment level and disposal in the Black Mud Pond, for remediation of the Reynolds Study Area sediments.

APPENDIX 1



FIGURES


500602






LEGEND:

-  ST. LAWRENCE RIVER DRAINAGE
-  RAQUETTE RIVER DRAINAGE

SITE DRAINAGE AREAS ST. LAWRENCE REDUCTION PLANT REYNOLDS METALS COMPANY MASSENA, NEW YORK		
Woodward-Clyde Consultants Consulting Engineers, Geologists and Environmental Scientists		
Job No. 88C20188-3	Drawing No. 88180372	Date: 07/12/91
Drawn by J.E.	Checked by	
Scale		FIGURE 2
		

500603



LEGEND:

1988 STUDY

- ⊙ OUTFALL LOCATION
- WATER DEPTH, 6 FEET
- WATER DEPTH, 12 FEET
- WATER DEPTH, 18 FEET
- ① MAIN RIVER FLOW—CORE CURRENT
- ② ZONE OF TURBULENCE
- ③ REVERSE FLOW—COUNTER CURRENT
- ④ ZONE OF LOW-VELOCITY TURBULENCE
- ✕ CURRENT METER AND DROGUE TRANSECTS
- DT 1989 DIVING TRANSECTS

REYNOLDS
PLANT

SKETCH OF MAJOR FLOW ZONES
AND CIRCULATION PATTERNS
REYNOLDS METALS COMPANY
MASSENA, NEW YORK



Woodward-Clyde Consultants


Consulting Engineers, Geologists and Environmental Scientists


Job No. 99C2515B-3	Drawing No. 95150240	Date: 01/08/1993
Drawn by: TP	Checked by:	
Scale:		


NTS

FIGURE 3

500604










LEGEND	
1988 SAMPLING	1990 SAMPLING
● CORE SAMPLES	□ SEDIMENT SAMPLING LOCATIONS
■ GRAB SAMPLES	⊕ SEDIMENT SAMPLES TO INCLUDE ELUTRIATE TESTING
○ OUTFALL	⊗ SURVEYED SHORE LOCATION MARKER
ND NOT DETECTED	X WATER SAMPLING LOCATIONS
— BOUNDARY OF STUDY AREAS	

S. CORNWALL CHANNEL - ST. LAWRENCE RIVER





LEGEND:

- | | | | |
|--|---|---|---|
| | 1-2 ppm (OUTER BOUNDARY INCLUDES PPMs GREATER THAN 10ppm) | | RIVER FLOW DIRECTION |
| | 2-8 ppm | • | INDIVIDUAL SAMPLE LOCATIONS, CONCENTRATIONS IN ppm, J-ESTIMATED CONCENTRATION |
| | >8 ppm | X | OUTFALL LOCATION |

500612

ST. LAWRENCE RIVER
DISTRIBUTION OF PCB SEDIMENT CONCENTRATIONS
REYNOLDS METALS COMPANY
MASSENA, NEW YORK



Woodward-Clyde Consultants


Consulting Engineers, Geologists and Environmental Scientists

Job No: 88C2515F-1 Drawing No: 83159540 Date: 01/18/1993


Drawn by: TP Checked by:

Scale: 0 800'

FIGURE 11



CROSS-SECTION



PLAN VIEW

LEGEND:

- BOUNDARY OF CONTAMINATED SEDIMENT
- 5 TYPICAL EXISTING BATHYMETRY CONTOURS
- GEOTEXTILE
- CLEAN SAND CAP
- ARMORING (REVTMENT MAT)

IN-SITU CAP SCHEMATIC
REYNOLDS METALS COMPANY
MASSENA, NEW YORK



Woodward-Clyde Consultants

Consulting Engineers, Geologists and Environmental Scientists

Job No.: 89C2515F-1 Drawing No. 95159360 Date: 01/08/1993
Drawn by: DEG Checked by:
Scale: NOT TO SCALE

FIGURE 12

Rev. No.	Date	Type of Revision	Checked by:

500613

APPENDIX 2

TABLES

TABLE 1. REYNOLDS METAL STUDY AREA: CONTAMINANTS OF CONCERN

Contaminants	Sediments		Fish	
	St. Lawrence	Raquette	St. Lawrence	Raquette
SEMI-VOLATILES				
Acenaphthene	X			
Acenaphthylene	X			
Anthracene	X			
Benzo(a)anthracene	X			
Benzo(a)pyrene	X			
Benzo(b)fluoranthene	X			
Benzo(h)fluoranthene	X			
Benzo(g,h,i)perylene	X			
Chrysene	X			
Dibenzo(a,h)anthracene	X			
Dibenzofurans	X			
Fluoranthene	X			
Fluorene	X		X	
Phenanthrene	X			
Pyrene	X			
CDDs/CDFs	X		X	X
METALS				
Aluminum	X	X		
Fluoride	X	X	X	
Lead	X	X		
Cyanide	X	X	X	
Mercury	X	X	X	X
PESTICIDES/PCBs*				
Aroclor 1016	X		X	X
Aroclor 1221	X		X	
Aroclor 1248	X		X	
Aroclor 1254	X		X	X
Aroclor 1260	X		X	
Dieldrin			X	X
DDE			X	X

*Risk Assessment evaluates total PCBs.

500615

TABLE 2

EXPOSURE PATHWAY: INGESTION OF FISH BY MOHAWK NATION RESIDENTS FOR PRESENT AND FUTURE SCENARIOS

Variable	Range	Midpoint	Value Used	Rationale	Reference
<i>Receptor Population</i>				Mohawk Nation Residents	
<i>Body Weight (kg)</i> Resident	-	-	70	Per EPA guidance	EPA, 1989d EPA, 1989a
<i>Duration of Exposure (Years)</i> Resident	1 - 70	35	70	Based on known residence time of Mohawk Nation members	Jock, 1991
<i>Exposure Frequency (Days/Year)</i>	1-365	183	350	Value used is specified in supplemental EPA guidance	EPA, 1991a
<i>Ingestion Rate (g/Day)</i> Resident	-	-	132	Per EPA guidance	EPA, 1989a
<i>Averaging Time (Days)</i> noncarcinogenic carcinogenic	365 - 25550	12775	25550	Range, midpoint and value used are based on exposure duration for noncarcinogens and lifetime for carcinogens	EPA, 1989a

EPA, 1989a. Risk Assessment Guidance for Superfund, Volume I, EPA 540/1-89/002. Office of Emergency and Remedial Response. December 1989.

EPA, 1989d. Exposure Factors Handbook, EPA 600/8-89/043. Exposure Assessment Group, Office of Health and Environmental Assessment. 1989.

EPA, 1991a. Human Health Evaluation Manual, Supplemental Guidance: "Standard Default Exposure Factors". OSWER Directive 9285.6-03. March 25, 1991.

Jock, 1991. St. Regis Mohawk Tribe Environmental Program, Personal communication with Naida Gavrelis, TRC Environmental Corporation.

TABLE 3

EXPOSURE PATHWAY: DERMAL CONTACT WITH RIVER SEDIMENTS BY LOCAL RESIDENTS AND FISHERMEN FOR PRESENT AND FUTURE SCENARIOS

Variable	Range	Midpoint	Value Used	Rationale	Reference
<i>Receptor Population</i>				Local Residents	
<i>Body Weight (Kg)</i>					
Small Child (Age 1-6)	-	-	15	As specified in supplemental guidance	EPA, 1991a
Adult	-	-	70		
<i>Duration of Exposure (Years)</i>					
Small Child	1 - 6	3	6	Based on known residence time of Mohawk Nation members	Jock, 1991
Adult/Fisherman	1 - 70	35	64		
<i>Exposure Frequency (Days/Year)</i>					
Small Child	1 - 365	183	143	Assume child spends 5 d/wk outdoors during summer and 3 d/wk during spring and fall (39 weeks total)	
Adult	1 - 365	183	78	Assume adult spends 2 d/wk outdoors during spring, summer, and fall (39 weeks total)	
Fisherman	1 - 365	183	350	Assumes fishing occurs daily year round.	Jock, 1992 EPA, 1991a
<i>Skin Surface Area Contacted (sq.cm)</i>					
<u>Small Child</u>					
Arms	-	-	960	50th percentile values; assume ave. is represented by values for ages 3-4	EPA, 1989a
Hands	-	-	400		EPA, 1989d
Legs	-	-	1800		
Feet	-	-	520		
Total Area of These Limbs	-	-	3680		
<u>Adult/Fisherman</u>					
Arms	-	-	2300	Values used are presented in RAGS, except for feet (EFH)	EPA, 1989a
Hands	-	-	820		EPA, 1989d
Total Area of These Limbs	-	-	3120		
<i>Soil Skin Adherence Factor (mg/sq. cm)</i>					
	0.2 - 1.0	0.6	0.6	Value used is midpoint of range	EPA, 1992b

500617

TABLE 3

EXPOSURE PATHWAY: DERMAL CONTACT WITH RIVER SEDIMENTS BY LOCAL RESIDENTS AND FISHERMEN FOR PRESENT AND FUTURE SCENARIOS (continued)

Variable	Range	Midpoint	Value Used	Rationale	Reference
<i>Absorption Factor (Percent)</i>					
PCBs (Aroclor 1254)	0.006 - 0.06	0.03	0.03	Value used is midpoint of range given by EPA	EPA, 1992b
CDD/CDFs	0.001 - 0.03	0.02	0.02		
<i>Averaging Time (Days)</i>					
<u>Small Child</u>					
noncarcinogenic	365 - 2190	1095	2190	Range, midpoint, and value used are based on exposure duration for noncarcinogens and lifetime for carcinogens	EPA, 1989a
carcinogenic			25550		
<u>Adult/Fisherman</u>					
noncarcinogens	365 - 25550	12775	23360		
carcinogens			25550		

EPA, 1989a. Risk Assessment Guidance for Superfund, Volume I, EPA 540/1-89/002. Office of Emergency and Remedial Response. December 1989.

EPA, 1989d. Exposure Factors Handbook, EPA 600/8-89/043. Exposure Assessment Group, Office of Health and Environmental Assessment. 1989.

EPA, 1991a. Human Health Evaluation Manual, Supplemental Guidance: "Standard Default Exposure Factors". OSWER Directive 9285.6-03. March 25, 1991.

EPA, 1992b. Dermal Exposure Assessment: Principles and Applications. Interim Report, EPA/600/8-91/011B. Office of Research and Development. January 1992.

Jock, 1991 and 1992. St. Regis Mohawk Tribe Environmental Programs. Personal communication with Naida Gavrelis and Scott Heim, TRC Environmental Corporation.

TABLE 4

EXPOSURE PATHWAY: INGESTION OF SEDIMENTS FROM THE RIVER BANKS BY LOCAL RESIDENTS AND FISHERMEN FOR PRESENT AND FUTURE SCENARIOS

Variable	Range	Midpoint	Value Used	Rationale	Reference
<i>Receptor Population</i>				Local Residents	
<i>Body Weight (kg)</i>					
Small Child (Age 1-6)	-	-	15	As specified in supplemental guidance	EPA, 1991a
Adult	-	-	70		
<i>Duration of Exposure (Years)</i>					
Small Child	1 - 6	3	6	Total duration equals 70 year residence time	EPA, 1991a
Adult/Fisherman	1 - 70	35	64		
<i>Exposure Frequency (Days/Year)</i>					
Small Child	1 - 365	183	143	Assumes 5 d/wk outdoors during summer and 3 d/wk during spring and fall (39 weeks total)	
Adult	1 - 365	183	78	Assume 2 d/wk outdoors during spring, summer, and fall (39 weeks total)	
Fisherman	1 - 365	183	350	Assumes fishing occurs daily year round	Jock, 1992 EPA, 1991a
<i>Ingestion Rate (mg/Day)</i>					
Child	-	-	200	Value used is specified in RAGS	EPA, 1989a
Adult	-	-	100		
<i>Fraction Ingested from Contaminated Source (Unitless)</i>					
	-	-	1	Assume that all soil contacted is contaminated	EPA, 1989a
<i>Averaging Time (Days)</i>					
<u>Child</u>					
noncarcinogens	365 - 2190	1095	2190	Range, midpoint, and value used are based on exposure duration for noncarcinogens and lifetime for carcinogens	EPA, 1989a
carcinogens			25550		
<u>Adult/Fisherman</u>					
noncarcinogens	365 - 25550	12775	23360		
carcinogens			25550		

EPA, 1989a. Risk Assessment Guidance for Superfund, Volume I, EPA 540/1-89/002. Office of Emergency and Remedial Response. December 1989.

EPA, 1991a. Human Health Evaluation Manual, Supplemental Guidance: "Standard Default Exposure Factors". OSWER Directive 9285.6-03. March 25, 1991.

Jock, 1992. St. Regis Mohawk Tribe Environmental Programs. Personal Communication with Scott Heim, TRC Environmental Corporation.

TABLE 5 TOXICITY VALUES FOR THE REYNOLDS SITE CONTAMINANTS

Chemical	CARCINOGENIC				CHRONIC	
	Weight of Evidence Classification		Oral Slope Factor (mg/kg/day)-1		Chronic Oral RfD (mg/kg/day)	
Acenaphthene	--	a			6.00E-02	a
Acenaphthylene	D	a				
Anthracene	D	a			3.00E-01	a
Benzo(a)anthracene	B2	a	7.30E-01	d		
Benzo(a)pyrene	B2	a	7.30E+00	a		
Benzo(b)fluoranthene	B2	a	7.30E-01	d		
Benzo(g,h,i)perylene	D	a				
Benzo(k)fluoranthene	B2	a	7.30E-01	d		
Chrysene	B2	a	7.30E-02	d		
Dibenzofuran	D	a			4.00E-03	c
Dibenz(a,b)anthracene	B2	a	7.30E+00	d		
Fluoranthene	D	a			4.00E-02	a
Fluorene	D	a			4.00E-02	a
2,3,7,8-Heptachlorodibenzodioxin	B2	b	1.60E+03	e		
2,3,7,8-Heptachlorodibenzofuran	B2	b	1.60E+03	e		
2,3,7,8-Hexachlorodibenzodioxin	B2	b	1.60E+04	e		
2,3,7,8-Hexachlorodibenzofuran	B2	b	1.60E+04	e		
Octochlorodibenzodioxin	B2	b	1.60E+02	e		
Octochlorodibenzofuran	B2	b	1.60E+02	e		
2,3,7,8-Pentachlorodibenzodioxin	B2	b	8.00E+04	e		
1,2,3,7,8-Pentachlorodibenzofuran	B2	b	8.00E+03	e		
2,3,4,7,8-Pentachlorodibenzofuran	B2	b	8.00E+04	e		
Phenanthrene	D	a				
Pyrene	D	a			3.00E-02	a
2,3,7,8-Tetrachlorodibenzodioxin	B2	b	1.60E+05	b		
2,3,7,8-Tetrachlorodibenzofuran	B2	b	1.60E+04	e		

500620

TABLE 5 (CONTINUED)						
Chemical	CARCINOGENIC				CHRONIC	
	Weight of Evidence Classification		Oral Slope Factor (mg/kg/day)-1		Chronic Oral RfD (mg/kg/day)	
Aroclor - 1260	B2	a	7.70E+00	a		
Aroclor - 1016					7.00E - 05	c
Aluminum	D	d			1.00E+00	c
Cyanide	D	a			2.00E-02	a
Fluoride	--	a			6.00E-02	a
Lead	B2	a				
Mercury	D	a			3.00E-04	b

- a. U.S. EPA, Integrated Risk Information System (IRIS), September 1, 1992.
- b. U.S. EPA, Health Effects Assessment Summary Tables (HEAST), FY 1992.
- c. Interim value from ECAO (see text for specific references).
- d. Oral slope factor for B(a)P used for PAHs classified as B2 carcinogens with the following TEFs applied:

Benzo(a)anthracene	0.1
Benzo(a)fluoranthene	0.1
Benzo(k)fluoranthene	0.1
Chrysene	0.01
Dibenz(a,h)anthracene	1.0
- e. Oral slope factor for 2,3,7,8-TCDD was used for other chlorinated dioxins/dibenzofurans with the following TEFs (EPA, 1989e) applied:

2,3,7,8-PeCDDs	0.5
2,3,7,8-HxCDDs	0.1
2,3,7,8-HpCDDs	0.01
OCDDs	0.001
2,3,7,8-TCDFs	0.1
2,3,7,8-PeCDFs	0.5
1,2,3,7,8-PeCDFs	0.05
2,3,7,8-HxCDFs	0.1
2,3,7,8-HpCDFs	0.01
OCDFs	0.001

TABLE 6. SUMMARY OF CARCINOGENIC RISK ESTIMATED FOR THE REYNOLDS SITE

Scenario	Receptor	Present/Future	Total Risk
FISH INGESTION			
St. Lawrence River at RMC	Resident	P/F	4×10^{-2} *
St. Lawrence River - RMC Vicinity	Resident	P/F	6×10^{-2} *
Raquette River	Resident	P/F	4×10^{-2} *
SEDIMENT			
Ingestion - St. Lawrence River	Fisherman	P/F	6×10^{-3} *
Dermal Contact - St. Lawrence River	Fisherman	P/F	3×10^{-3} *
Ingestion - Raquette River	Fisherman	P/F	N/A
Ingestion - St. Lawrence River	Resident	P/F	3×10^{-3} *
Dermal Contact - St. Lawrence River	Resident	P/F	1×10^{-3} *
Ingestion - Raquette River	Resident	P/F	N/A

*Exceeds 10^{-4} risk

N/A - Not applicable, no carcinogens detected

TABLE . 7 SUMMARY OF NONCARCINOGENIC HAZARD INDICES (HI)
ESTIMATED FOR THE REYNOLDS SITE

Scenario	Receptor	Present/Future	Total Risk
FISH INGESTION			
St. Lawrence River at RMC	Resident	P/F	$7 \times 10^{+1*}$
St. Lawrence River - RMC Vicinity	Resident	P/F	$1 \times 10^{+2*}$
Raquette River	Resident	P/F	$7 \times 10^{+1*}$
SEDIMENT			
Ingestion - St. Lawrence River	Fisherman	P/F	$5 \times 10^0*$
Dermal Contact - St. Lawrence River	Fisherman	P/F	$3 \times 10^0*$
Ingestion - Raquette River	Fisherman	P/F	2×10^{-2}
Ingestion - St. Lawrence River	Resident	P/F	$2 \times 10^{+1*}$
Dermal Contact - St. Lawrence River	Resident	P/F	$9 \times 10^0*$
Ingestion - Raquette River	Resident	P/F	9×10^{-2}

*HI exceeds one (1)

500623

TABLE 8
SUMMARY OF COSTS OF SELECTED REMEDY

<u>Component of Selected Remedy</u>	<u>Cost</u>
Sampling	\$ 200,000
Mobilization/Demobilization	\$ 1,200,000
Site Preparation	\$ 2,100,000
Dredging/Dewatering/On-shore Loading	\$ 15,900,000
ATP Treatment	\$ 2,900,000
DIRECT COSTS	\$ 22,300,000
INDIRECT COSTS (30% of direct costs)	\$ 6,700,000
SUBTOTAL	\$ 29,000,000
CONTINGENCY (20% of subtotal)	\$ 5,800,000
TOTAL CAPITAL COSTS OF REMEDY	\$ 34.8 million
O&M COSTS*	\$ 28,000/year
O&M 30 YEAR PRESENT WORTH**	\$ 250,000
TOTAL PRESENT WORTH COSTS OF REMEDY	\$ 35.1 million

* O&M begins after completion of construction.

** Based on an assumed discount rate of 5%.

TABLE 9

**MAJOR APPLICABLE OR RELEVANT AND APPROPRIATE REQUIREMENTS,
AMONG OTHERS, ASSOCIATED WITH THE SELECTED REMEDY**

Chemical-Specific ARARs

- **Clean Air Act**
 - National Primary and Secondary Ambient Air Quality Standards at 40 CFR Part 50
- **New York State Requirements**
 - Air quality standards at 6 NYCRR Part 257
 - Air emission regulations at 6 NYCRR Part 211
 - Water quality regulations for surface waters and groundwaters at 6 NYCRR Parts 700 - 705

Action-Specific ARARs

- **Toxic Substances Control Act**
 - PCB disposal requirements for disposal of dredged material generally found at 40 CFR 761.60(a)(5)
- **Resource Conservation and Recovery Act**
 - Capping and monitoring requirements generally found at 40 CFR 264.303 and 264.310
 - Groundwater monitoring requirements at 40 CFR 264 Subpart F
 - Generator requirements at 40 CFR 262
 - Transporter requirements at 40 CFR 263
- **Clean Water Act**
 - Best available technology and monitoring requirements at 40 CFR 122.44
 - Best management practices program at 40 CFR 125.100, 40 CFR 125.104, 40 CFR 136.1-136.4
- **River and Harbors Act**
 - Dredging requirements at 33 CFR 320-330

TABLE 9 (cont.)

MAJOR APPLICABLE OR RELEVANT AND APPROPRIATE REQUIREMENTS, AMONG OTHERS, ASSOCIATED WITH THE SELECTED REMEDY

- **New York State Requirements**

- Solid waste management facility regulations at 6 NYCRR Part 360
- Final status standards for hazardous waste facilities at 6 NYCRR Part 373, including standards for incinerators at 373-3.15 and standards for thermal treatment at 373-3.16
- Implementation of National Permit Discharge Elimination System at 6 NYCRR 750-757
- Process exhaust and/or ventilation system requirements at 6 NYCRR Part 212

Location-Specific ARARs

- **Executive Orders 11988 and 11990**
 - Floodplains management and protection of wetlands at 40 CFR 6.302 and 40 CFR 6, Appendix A
- **Fish and Wildlife Coordination Act**
 - Protection of endangered species and wildlife at 33 CFR Parts 320-330 and 40 CFR 6.302
- **National Wildlife Historical Preservation Act**
 - Preservation of historic properties at 36 CFR 65 and 36 CFR 800
- **Endangered Species Act**
 - Protection of endangered species at 50 CFR 200, 50 CFR 402
- **Clean Water Act**
 - Section 404 requirements for dredge spoil discharge at 40 CFR 230 and 33 CFR Parts 320-330
- **Wild and Scenic Act**
 - Protection of recreational river at 40 CFR 6.302(e)
- **Coastal Zone Management Act**

TABLE 9 (cont.)

**MAJOR APPLICABLE OR RELEVANT AND APPROPRIATE REQUIREMENTS,
AMONG OTHERS, ASSOCIATED WITH THE SELECTED REMEDY**

- New York State Requirements
 - Endangered species requirements at 6 NYCRR 182
 - Coastal zone management policies at 1 NYCRR Part 600


"To Be Considered" Requirements

- St. Regis Mohawk Tribe Requirements
 - 0.1 ppm PCB sediment level
 - 5 ng/m³ PCB air level
- Clean Water Act interim sediment quality criteria
- New York State sediment quality criteria
- Acceptable ambient levels of volatile organics in emissions from all sources in NYS Air Guide I

APPENDIX 3
STATE LETTER OF CONCURRENCE

-7010

SEP 27 1993



Thomas C. Jerling
Commissioner

Ms. Kathleen C. Callahan
Acting Deputy Regional Administrator
U.S. Environmental Protection Agency
Region II
26 Federal Plaza
New York, New York 10278

Dear Ms. Callahan:

The New York State Department of Environmental Conservation has reviewed the United States Environmental Protection Agency (USEPA) Draft Record of Decision (ROD) for the Reynolds Study Area for which Reynolds Metals is responsible for investigating and remediating, pursuant to the September 1989 USEPA Unilateral Administrative Order.

We strongly support the proposed dredging of contaminated sediments from the river and can agree with USEPA's cleanup levels for this site. We also agree with and support the concept of using the Black Mud Pond for the disposal of untreated sediments and treatment residuals.


Regarding the document's reference to the on-site PCB treatment levels required by the New York State ROD, we believe that it is inappropriate to state that the 25 parts per million (ppm) level being considered by USEPA is consistent with that level required by New York State. While the numbers are the same, the processes followed to arrive at those values are not. The 25 ppm PCB soil treatment level selected by New York State was based on a cost analysis which compared projected remedial costs to the mass of PCBs which would be treated through the use of different treatment levels. USEPA does not appear to have conducted an analysis similar to the above. Therefore, the ROD language should be duly modified. As the Department has previously indicated, we do not accept USEPA's PCB Guidance Document since it is inconsistent with our approach to PCB remediation and, as indicated in the document, the guidance is optional for USEPA to follow. In accordance with the State's approach, we recommend that USEPA require Reynolds Metals to evaluate remedial design sampling results to determine the feasibility of treating sediments with PCB concentrations below 25 ppm. Based on the results of the evaluation, we would encourage the use of lower treatment levels if it could be demonstrated that doing so would not add unreasonable costs to the project.

While the Department can agree with USEPA's cleanup levels for this site, we strongly encourage Reynolds Metals to eliminate as much of the contamination as possible, while it is in the process of remediating the environs of this site and to pursue the lowest possible cleanup level that is feasible under existing conditions.

The USEPA should ensure that pilot testing of the thermal desorption unit is performed during remedial design to verify that the emissions from the treatment unit are acceptable.

Thank you for the opportunity to review this document.

Sincerely,


Ann Hill DeBarbieri
Deputy Commissioner
Office of Environmental Remediation

500630

APPENDIX 4
ADMINISTRATIVE RECORD INDEX

Document Number: REY-001-0001 To 0084

Date: / /

Title: (Letter containing the Reynolds Metals site monthly reports for November 1989, - September 1990, November 1990, - May 1991, and July 1991, - June 1992)

Type: CORRESPONDENCE

Category: 2.0.0.0.0 Removal Response

Author: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Lenney, Robert J.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Visnic, Christine: US EPA

Document Number: REY-001-0519 To 0526

Parent: REY-001-0517

Date: / /

Title: Additional River Sampling Report Response to Comments

Type: OTHER

Category: 3.1.0.0.0 Sampling and Analysis Plan (SAP)

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-001-0897 To 0971

Parent: REY-001-0896

Date: / /

Title: APPENDIX C, Reynolds River Program Sediment Samples, APPENDIX D, Reynolds River Program Water Samples, APPENDIX E, Reynolds River Program Elutriate Samples (collected on various days during September 1990)

Type: DATA

Category: 3.2.0.0.0 Sampling and Analysis Data/Chain of Custody Forms

Author: none: none

Recipient: none: none

Document Number: REY-001-0975 To 1005

Parent: REY-001-0972

Date: / /

Title: St. Lawrence River Ecological Data Collection Plan - Reynolds Metals Co. Massena, New York

Type: PLAN

Category: 3.2.0.0.0 Sampling and Analysis Data/Chain of Custody Forms

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

500632

Document Number: REY-002-0431 To 0440

Parent: REY-002-0429

Date: / /

Title: Enclosure #1 Sampling, Analysis and Monitoring Plan (SAMP) General Comments

Type: PLAN

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: none: US EPA

Recipient: none: none

Document Number: REY-002-0557 To 0615

Date: / / Confidential

Title: (Field Work Notebook for Reynolds Metals Company)

Type: FINANCIAL/TECHNICAL

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Dunn, Maria C.: Alliance Technologies Corporation

Recipient: none: none

Document Number: REY-002-0643 To 0646

Parent: REY-002-0642

Date: / /

Title: NYSDEC Review Comments on Draft Additional River Sampling Report, St. Lawrence River System
dated January 24, 1991, Prepared for Reynolds Metals Company, Prepared by Woodward-Clyde Consultants

Type: PLAN

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: none: NY Dept of Environmental Conservation

Recipient: none: none

Document Number: REY-002-0647 To 0651

Parent: REY-002-0642

Date: / /

Title: NYSDEC Review Comments on Technical Memorandum Preliminary Analysis of Alternatives St. Lawrence
River System dated January 24, 1991, Prepared for Reynolds Metals Company, Prepared by Woodward-Clyde
Consultants

Type: PLAN

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: none: NY Dept of Environmental Conservation

Recipient: none: none

500633

Document Number: REY-002-0654 To 0744

Parent: REY-002-0652

Date: / /

Title: Attachment A (Summary data packages for seventeen split samples collected in the St. Lawrence and Raquette Rivers)

Type: FINANCIAL/TECHNICAL

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: none: Versar

Recipient: none: none

Document Number: REY-002-0745 To 0758

Parent: REY-002-0652

Date: / /

Title: Comparison of NYSDEC Sample Splits - Sampling, Analysis & Monitoring Plan, St. Lawrence - Grasse River Site, Site Code 6-45-015 Reynolds Metals 106 Order

Type: OTHER

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: none: none

Recipient: none: none

Document Number: REY-002-0789 To 0796

Parent: REY-002-0784

Date: / /

Title: Enclosure #1 Draft Additional River Sampling Report (ARS Report) General Comments

Type: PLAN

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Condition: DRAFT

Author: none: US EPA

Recipient: none: none

Document Number: REY-002-0797 To 0806

Parent: REY-002-0784

Date: / /

Title: Enclosure #2, Technical Memorandum, Preliminary Analysis of Alternatives - General Comments

Type: PLAN

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: none: US EPA

Recipient: none: none

500634

Document Number: REY-002-0824 To 0830

Parent: REY-002-0822

Date: / /

Title: Enclosure Draft Ecological Data Collection Plan - General Comments

Type: OTHER

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: none: US EPA

Recipient: none: none

Document Number: REY-002-0881 To 0881

Date: / /

Title: St. Regis Mohawk Tribe PCB ARARs (Applicable or Relevant and Appropriate Requirements)

Type: OTHER

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: none: none

Recipient: none: none

Document Number: REY-002-1009 To 1032

Parent: REY-002-1007

Date: / /

Title: Draft Treatability Study Work Plan, General Comments

Type: PLAN

Category: 4.5.0.0.0 Feasibility Study Correspondence

Author: none: US EPA

Recipient: none: none

Document Number: REY-001-1139 To 1144

Parent: REY-001-1137

Date: / /

Title: Summary of Responses to Comments, Analysis of Alternatives Work Plan

Type: PLAN

Category: 3.3.0.0.0 Work Plan

Author: none: Woodward-Clyde Consultants

Recipient: none: none

Document Number: REY-002-0416 To 0416

Parent: REY-002-0411

Date: 03/17/89

Title: (Letter requesting a map delineating Reynolds Metals property lines and a drainage pattern map for the eastern side of the Reynolds Metals plant)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Jock, Ken: St. Regis Mohawk Tribe

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0441 To 0477

Parent: REY-002-0429

Date: 04/06/89

Title: Enclosure #4, SOP No. HW-6, Revision #6, CLP Organics Data Review and Preliminary Review

Type: PLAN

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Bevilacqua, Louis: none

Recipient: none: none

Document Number: REY-002-0478 To 0493

Parent: REY-002-0429

Date: 07/10/89

Title: Enclosure #5, CLP (2,3,7,8 TCDD) Data Review, Revision 4

Type: PLAN

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Gerazounis, Stelios: none

Recipient: none: none

Document Number: REY-002-1039 To 1068

Date: 09/28/89

Title: Administrative Order In the Matter of Reynolds Metals Company - Respondent

Type: LEGAL DOCUMENT

Category: 7.3.0.0.0 Administrative Orders

Author: Muszynski, William J.: US EPA

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Attached: REY-002-1069

500636

1/18/93

Index Chronological Order
REYNOLDS METAL CO. Documents

Page: 6

Document Number: REY-002-1089 To 1089

Parent: REY-002-1087

Date: 10/26/89

Title: (Attendance sheet of the October 26, 1989, Technical Meeting)

Type: OTHER

Category: 10.5.0.0.0 Documentation of Other Public Meetings

Author: various: various

Recipient: none: none

Document Number: REY-002-1069 To 1079

Parent: REY-002-1039

Date: 10/31/89

Title: (Letter expressing concern about the broad scope and clarity of the Administrative Order issued to Reynolds Metals Company)

Type: CORRESPONDENCE

Category: 7.3.0.0.0 Administrative Orders

Author: McKinnon, James E.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Corman, Bernice I.: US EPA

Document Number: REY-002-1087 To 1088

Date: 11/01/89

Title: (Letter summarizing an October 26, 1989, meeting, and forwarding the enclosed attendance sheet)

Type: CORRESPONDENCE

Category: 10.5.0.0.0 Documentation of Other Public Meetings

Author: Petersen, Carole: US EPA

Recipient: Delisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Attached: REY-002-1089

Document Number: REY-001-1122 To 1124

Date: 11/02/89

Title: (Letter forwarding the enclosed Work Plan for collection of additional hydrodynamic data in the St. Lawrence and Raquette Rivers)

Type: CORRESPONDENCE

Category: 3.3.0.0.0 Work Plan

Author: Jacobson, Peter R.: Woodward-Clyde Consultants

Owens, Edward H.: Woodward-Clyde Consultants

Recipient: Delisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Attached: REY-001-1125

500637

Document Number: REY-001-1125 To 1136

Parent: REY-001-1122

Date: 11/02/89

Title: Work Plan, River Hydrodynamic Data Collection, St. Lawrence River System

Type: PLAN

Category: 3.3.0.0.0 Work Plan

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0402 To 0403

Date: 11/02/89

Title: (Letter responding to a November 1989, letter and serving to clarify agreements made in a joint meeting on October 26, 1989)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Petersen, Carole: US EPA

Document Number: REY-002-0404 To 0406

Date: 11/09/89

Title: (Letter commenting on the River Hydrodynamic Data Collection Work Plan and listing what is to be addressed during the implementation of the Work Plan)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Petersen, Carole: US EPA

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0407 To 0408

Date: 11/09/89

Title: (Letter commenting on the River Hydrodynamic Data Collection Work Plan, St. Lawrence River System)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Visnic, Christine: US EPA

500638

Document Number: REY-002-0409 To 0410

Date: 11/21/89

Title: (Letter responding to a November 2, 1989, letter regarding the proposed flow study for the Reynolds study area)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Petersen, Carole: US EPA

Recipient: Delisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0418 To 0428

Parent: REY-002-0417

Date: 12/01/89

Title: NYSDEC Review Comments on the Sampling, Analysis & Monitoring Plan, Additional River Sampling - St. Lawrence River System for Reynolds Metals Company - Massena, NY, dated December 1989

Type: OTHER

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: none: NY Dept of Environmental Conservation

Recipient: none: none

Document Number: REY-002-0411 To 0415

Date: 01/04/90

Title: (Letter commenting on "Reynolds Metals Company's Sampling, Analysis and Monitoring Plan for Additional River Studies, St. Lawrence River System, December, 1989")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Jock, Ken: St. Regis Mohawk Tribe

Recipient: Visnic, Christine: US EPA

Attached: REY-002-0416

Document Number: REY-002-0417 To 0417

Date: 01/17/90

Title: (Letter forwarding the enclosed comments on the Sampling, Analysis and Monitoring Plan for Additional River Sampling at the St. Lawrence River System for Reynolds Metals Company - Massena, New York)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Visnic, Christine: US EPA

Attached: REY-002-0418

500639

Document Number: REY-002-0494 To 0529

Parent: REY-002-0429

Date: 02/16/90

Title: Enclosure #6, SOP No. MW-2, Evaluation of Metals Data for the Contract Laboratory Program
(CLP)

Type: PLAN

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Sheikh, Hanif: none

Recipient: none: none

Document Number: REY-001-1277 To 1431

Parent: REY-001-1275

Date: 03/01/90

Title: Volume I, Final Remedial Investigation Report, St. Lawrence Reduction Plant

Type: REPORT

Category: 3.4.0.0.0 RI Reports

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0884 To 1006

Parent: REY-002-0882

Date: 03/01/90

Title: Preliminary Feasibility Study Report - St. Lawrence Reduction Plant

Type: REPORT

Category: 4.2.0.0.0 FS Reports

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-001-1275 To 1276

Date: 03/30/90

Title: (Letter forwarding the enclosed "Final Remedial Investigation Report," of tasks conducted
at the St. Lawrence Reduction Plant)

Type: CORRESPONDENCE

Category: 3.4.0.0.0 RI Reports

Author: Crouse, George W.: Woodward-Clyde Consultants

Jacobson, Peter R.: Woodward-Clyde Consultants

Kramer, Mark M.: Woodward-Clyde Consultants

Recipient: Sweredoski, Derrell: NY Dept of Environmental Conservation

Attached: REY-001-1277

500640

Document Number: REY-001-1432 To 1549

Date: 03/30/90

Title: Volume II, Final Remedial Investigation Report, St. Lawrence Reduction Plant, Appendices A through E

Type: REPORT

Category: 3.4.0.0.0 RI Reports

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-001-1550 To 1933

Date: 03/30/90

Title: Volume III, Final Remediation Investigation Report, St. Lawrence Reduction Plant, Appendix F

Type: REPORT

Category: 3.4.0.0.0 RI Reports

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0882 To 0883

Date: 03/30/90

Title: (Letter forwarding the enclosed "Preliminary Feasibility Study Report - St. Lawrence Reduction Plant")

Type: CORRESPONDENCE

Category: 4.2.0.0.0 FS Reports

Author: Crouse, George W.: Woodward-Clyde Consultants

Jacobson, Peter R.: Woodward-Clyde Consultants

Recipient: Sweredoski, Darrell: Reynolds Aluminum/Reynolds Metal Company

Attached: REY-002-0884

Document Number: REY-002-0429 To 0430

Date: 04/20/90

Title: (Letter forwarding the enclosed comments on the "Sampling, Analysis and Monitoring Plan for Additional River Sampling at the Reynolds Metals Company Site")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Pavlou, George: US EPA

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Attached: REY-002-0431 REY-002-0441 REY-002-0478 REY-002-0494

500641

Document Number: REY-001-0085 To 0498

Date: 05/01/90

Title: Sampling, Analysis, and Monitoring Plan for Additional River Studies, St. Lawrence River System

Type: PLAN

Category: 3.1.0.0.0 Sampling and Analysis Plan (SAP)

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0530 To 0530

Date: 06/06/90

Title: (Letter authorizing the Reynolds Metals Company to proceed with an analysis of alternatives for the site and stating that a detailed work plan for conduct of an analysis of remedial alternatives will be submitted)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Pavlou, George: US EPA

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0531 To 0534

Date: 06/15/90

Title: (Letter commenting on the "Sampling, Analysis and Monitoring Plan for Additional River Studies - St. Lawrence River System")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-0543 To 0544

Parent: REY-002-0540

Date: 06/18/90

Title: (Letter forwarding the enclosed insurance certificate covering Woodward-Clyde Consultants for any site work at Reynolds' Massena facility)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Jacobson, Peter R.: Woodward-Clyde Consultants

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

500642

Document Number: REY-001-0502 To 0516

Parent: REY-001-0499

Date: 07/01/90

Title: Summary of On-Site Environment Conditions, St. Lawrence Reduction Plant

Type: PLAN

Category: 3.1.0.0.0 Sampling and Analysis Plan (SAP)

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0535 To 0538

Date: 07/26/90

Title: (Letter forwarding the enclosed additional comments on Reynolds Metals Company's proposed Sampling, Analysis and Monitoring Plan)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Pavlou, George: US EPA

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-001-0499 To 0501

Date: 07/27/90

Title: (Letter forwarding the enclosed "Summary of On-Site Environmental Conditions at the St. Lawrence Reduction Plant," which is a supplement to the May 23, 1990, revision)

Type: CORRESPONDENCE

Category: 3.1.0.0.0 Sampling and Analysis Plan (SAP)

Author: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Attached: REY-001-0502

Document Number: REY-002-0545 To 0548

Parent: REY-002-0540

Date: 08/02/90

Title: (Letter stating that Frank S. Waller, P.E., will be supervising and directing Woodward-Clyde Consultants on Reynolds' behalf for the St. Lawrence River Program and forwarding Mr. Waller's resume)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Jacobson, Peter R.: Woodward-Clyde Consultants

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

500643

7/18/93

Index Chronological Order
REYNOLDS METAL CO. Documents

Page: 13

Document Number: REY-002-0549 To 0554

Parent: REY-002-0540

Date: 08/02/90

Title: (Letter forwarding the enclosed laboratory data to supplement the organic data for the distilled water used at Reynolds Metals Company's Laboratory)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Jacobson, Peter R.: Woodward-Clyde Consultants

Kramer, Mark M.: Woodward-Clyde Consultants

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0539 To 0539

Date: 08/10/90

Title: (Letter commenting on Reynolds Metals Company's supplement to their revised Sampling, Analysis and Monitoring Plan dated July 27, 1990)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Jock, Ken: St. Regis Mohawk Tribe

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-0540 To 0542

Date: 08/17/90

Title: (Letter acknowledging the receipt of approval of "Reynolds Metals Company's Sampling, Analysis and Monitoring Plan," notification of the anticipated start of field work, and also forwarding three letters)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Attached: REY-002-0543 REY-002-0545 REY-002-0549

Document Number: REY-002-0555 To 0556

Date: 08/17/90

Title: (Letter conditionally approving the revised "Sampling, Analysis and Monitoring Plan - Additional River Sampling" and the supplement dated July 1990, and listing provisions)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Pavlou, George: US EPA

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

500644

Document Number: REY-002-0616 To 0616

Date: 09/07/90

Title: (Letter requesting additional information on the analytical methods presented in the revised
"Sampling, Analysis and Monitoring Plan - Additional River Sampling," dated May 1990)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Carson, Lisa P.: US EPA

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0617 To 0619

Date: 09/07/90

Title: (Letter commenting on the July 1990, "Work Plan for Analysis of Remedial Alternatives - St.
Lawrence River System")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-0621 To 0623

Parent: REY-002-0620

Date: 09/10/90

Title: (Letter forwarding the enclosed data from the MDL study performed for PCB analyses by EPA
Method 608)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Flynn, Dennis W.: ENSECO

Recipient: Buetikofer, Clifford A.: Woodward-Clyde Consultants

Document Number: REY-002-0620 To 0620

Date: 09/11/90

Title: (Letter forwarding the enclosed summary of the ENSECO MDL study of Method 608)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Attached: REY-002-0621

500645

Document Number: REY-002-0624 To 0624

Date: 09/26/90

Title: (Letter commenting on the "Reynolds Metals Company Analysis of Alternatives Work Plan")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Jock, Ken: St. Regis Mohawk Tribe

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-001-1934 To 2057

Date: 10/25/90

Title: Field Oversight Summary Report, Part I, Additional River Sampling, Reynolds Metals Company,
Massena, New York

Type: REPORT

Category: 3.4.0.0.0 RI Reports

Author: Sullivan, Douglas: Alliance Technologies Corporation

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-001-1145 To 1205

Parent: REY-001-1137

Date: 11/01/90

Title: Work Plan for Analysis of Remedial Alternatives, St. Lawrence River System

Type: PLAN

Category: 3.3.0.0.0 Work Plan

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0625 To 0626

Date: 11/07/90

Title: (Letter confirming a discussion regarding the deadline for Reynolds Metals Company's submission
of the "Draft Additional River Sampling Report" and the "Technical Memorandum on Alternatives
Screening")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Pavlou, George: US EPA

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

500646

Document Number: REY-002-0627 To 0634

Date: 11/16/90

Title: (Letter forwarding the enclosed comments on the "Work Plan for Analysis of Remedial Alternatives
- St. Lawrence River System for the Reynolds Metals Company Site")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Pavlou, George: US EPA

Recipient: Delisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-001-1137 To 1138

Date: 12/03/90

Title: (Letter forwarding the enclosed "Work Plan for Analysis of Remedial Alternatives, St. Lawrence
River System")

Type: CORRESPONDENCE

Category: 3.3.0.0.0 Work Plan

Author: Delisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Attached: REY-001-1139 REY-001-1145

Document Number: REY-002-0635 To 0638

Date: 12/18/90

Title: (Letter commenting on the November 1990, "Work Plan for Analysis of Remedial Alternatives
- St. Lawrence River System")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-001-0896 To 0896

Date: 12/21/90

Title: (Letter forwarding the enclosed validated data from the river program for the Reynolds Metals
Company)

Type: CORRESPONDENCE

Category: 3.2.0.0.0 Sampling and Analysis Data/Chain of Custody Forms

Author: Buetikofer, Clifford A.: Woodward-Clyde Consultants

Recipient: Delisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Attached: REY-001-0897

500647

Document Number: REY-002-0639 To 0641

Date: 03/11/91

Title: (Letter discussing the ecological data collection activities required by EPA regarding the Reynolds Metals Company site)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Pavlou, George: US EPA

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0642 To 0642

Date: 03/12/91

Title: (Letter forwarding the enclosed comments on the "Draft Additional River Sampling Report and the Technical Memorandum - St. Lawrence River System")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Carson, Lisa P.: US EPA

Attached: REY-002-0643 REY-002-0647

Document Number: REY-002-0759 To 0760

Date: 03/28/91

Title: (Letter discussing a March 11, 1991, letter requesting that a work plan for the collection of data, which will support an ecological risk assessment, be developed)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-0652 To 0653

Date: 04/02/91

Title: (Letter forwarding the enclosed summary data packages for seventeen split samples obtained and analyzed as part of the "Sampling, Analysis and Monitoring Plan Field Investigation Program in the St. Lawrence and Raquette Rivers")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Momberger, George: NY Dept of Environmental Conservation

Recipient: Carson, Lisa P.: US EPA

Reagan, Jim: US EPA

Attached: REY-002-0654 REY-002-0745

500648

Document Number: REY-002-0761 To 0762

Date: 04/23/91

Title: (Letter forwarding the enclosed "Fish Data Analysis Interim Report")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Feinberg, Charles: Alliance Technologies Corporation

Recipient: Moyik, Cathy: US EPA

Attached: REY-002-0763

Document Number: REY-002-0763 To 0776

Parent: REY-002-0761

Date: 04/23/91

Title: Fish Data Analysis Interim Report, Reynolds Metal Company, Massena, New York, Risk Assessment

Type: REPORT

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Gavrellis, Naida: Alliance Technologies Corporation

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-0777 To 0778

Date: 06/03/91

Title: (Letter commenting on the "Ecological Data Collection Plan - St. Lawrence River - Reynolds Metals Plant - Massena, New York" and stating that it is inadequate for the purpose of collection of data for a human health Risk Assessment)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Laccetti, Geoff: NY Dept of Health

Recipient: Daigle, William: NY Dept of Environmental Conservation

Document Number: REY-002-0779 To 0783

Date: 06/04/91

Title: (Letter commenting on the "Ecological Data Collection Plan - St. Lawrence River - Reynolds Metals Plant - Massena, New York")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Carson, Lisa P.: US EPA

500649

Document Number: REY-002-0784 To 0785

Date: 06/07/91

Title: (Letter conditionally approving the revised "Work Plan for Analysis of Remedial Alternatives," dated November 1990)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Pavlou, George: US EPA

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Attached: REY-002-0786 REY-002-0789 REY-002-0797

Document Number: REY-002-0786 To 0788

Parent: REY-002-0784

Date: 06/07/91

Title: (Letter forwarding the enclosed comments on the "Draft Additional River Sampling Report" and the "Technical Memorandum, Preliminary Analysis of Alternatives")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Pavlou, George: US EPA

Document Number: REY-002-0807 To 0810

Date: 06/25/91

Title: (Letter commenting on the "Ecological Data Collection Plan for the St. Lawrence River," dated April 1991)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Csulak, Frank G.: US Dept of Commerce

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-0812 To 0815

Parent: REY-002-0811

Date: 06/27/91

Title: (Letter discussing the sampling and analysis of fish in the St. Lawrence River)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Stone, Ward B.: NY Dept of Environmental Conservation

Recipient: Jock, Ken: St. Regis Mohawk Tribe

500650

Document Number: REY-002-0811 To 0811

Date: 07/03/91

Title: (Cover sheet forwarding a letter which underscores the need for sampling/analyses of fish
in the Reynolds' 106 order study area near the shore along the St. Lawrence River)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: various: none

Attached: REY-002-0812

Document Number: REY-002-0816 To 0817

Date: 07/09/91

Title: (Letter commenting on the "Ecological Data Collection Plan - St. Lawrence River - Reynolds
Metals Plant - Massena, NY, April 26, 1991")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Kadlec, Michael: St. Regis Mohawk Tribe

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-0818 To 0819

Date: 07/18/91

Title: (Letter identifying preliminary polychlorinated biphenyl (PCB) sediment cleanup and treatment
goals for the Reynolds Metals Company site)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: McCabe, William: US EPA

Recipient: Delisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0820 To 0821

Date: 07/25/91

Title: (Letter acknowledging receipt of a June 18, 1991, letter containing preliminary sediment clean-up
goals and an agreement to the schedule of submittals)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Condition: MISSING ATTACHMENT

Author: Delisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-0822 To 0823

Date: 08/02/91

Title: (Letter forwarding the enclosed comments on the April 26, 1991, "Draft Ecological Data Collection Plan, St. Lawrence River, Reynolds Metals Plant, Massena, New York")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: McCabe, William: US EPA

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Attached: REY-002-0824

Document Number: REY-001-0527 To 0895

Parent: REY-001-0517

Date: 08/13/91

Title: Revised Additional River Sampling Report, St. Lawrence Reduction Plant

Type: REPORT

Category: 3.1.0.0.0 Sampling and Analysis Plan (SAP)

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-001-0517 To 0518

Date: 08/14/91

Title: (Letter forwarding the enclosed "Revised Additional River Sampling Report, St. Lawrence Reduction Plant" and the "Additional River Sampling Report Response to Comments")

Type: CORRESPONDENCE

Category: 3.1.0.0.0 Sampling and Analysis Plan (SAP)

Author: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Attached: REY-001-0519 REY-001-0527

Document Number: REY-002-0831 To 0832

Date: 08/16/91

Title: (Letter responding to an August 2, 1991, letter commenting on the "Ecological Data Collection Plan, St. Lawrence River, Reynolds Metals Plant, Massena, New York")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

500652

1/18/93

Index Chronological Order
REYNOLDS METAL CO. Documents

Page: 22

Document Number: REY-002-0833 To 0834

Date: 08/20/91

Title: (Memo commenting on the "RMC 106 Order - Treatability Study Workplan for PCBs in River Sediments")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Kolak, Nick: NY Dept of Environmental Conservation

Recipient: Daigle, William: NY Dept of Environmental Conservation

Document Number: REY-002-0835 To 0836

Date: 08/20/91

Title: (Memo discussing an August 20, 1991, telephone conversation with Mr. DeLisle of Reynolds Metals Company regarding an August 16, 1991, letter, which discussed the "Draft Ecological Data Collection Plan")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Carson, Lisa P.: US EPA

Recipient: file: US EPA

Document Number: REY-002-0837 To 0839

Date: 08/27/91

Title: (Letter commenting on the August 7, 1991, "Workplan - Treatability Study - St. Lawrence River Sediments")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-0840 To 0841

Date: 08/27/91

Title: (Letter commenting on Reynolds Metals' August 16, 1991, response to an EPA letter regarding the April 26, 1991, "Draft Ecological Data Collection Plan")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Carson, Lisa P.: US EPA

500653

Document Number: REY-002-0842 To 0842

Date: 09/03/91

Title: (Memo discussing a September 3, 1991, telephone conversation with Reynolds Metals Company concerning the "Ecological Data Collection Plan" and its revision)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Carson, Lisa P.: US EPA

Recipient: file: US EPA

Document Number: REY-002-0843 To 0843

Date: 09/04/91

Title: (Letter forwarding the enclosed "Interim Report 02" regarding the preliminary PCB cleanup levels in sediment for the Reynolds Metals site)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Feinberg, Charles: Alliance Technologies Corporation

Recipient: Moyik, Cathy: US EPA

Attached: REY-002-0844

Document Number: REY-002-0844 To 0861

Parent: REY-002-0843

Date: 09/04/91

Title: Interim Cleanup Levels, Interim Report 02 Risk Assessment Reynolds Metal Company

Type: REPORT

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Gavrelis, Maide: Alliance Technologies Corporation

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-1082 To 1082

Parent: REY-002-1080

Date: 10/01/91

Title: Summary of Biological Tissue Collections, St. Lawrence and Acquatto Rivers, Reynolds Metals Company, October 1991

Type: FINANCIAL/TECHNICAL

Category: 7.8.0.0.0 Enforcement Correspondence

Author: none: Woodward-Clyde Consultants

Recipient: none: US EPA

500654

Document Number: REY-002-0862 To 0863

Date: 10/02/91

Title: (Letter commenting on the "St. Lawrence River Ecological Data Collection Plan - Reynolds Metal Co., Massena, NY")

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Jock, Ken: St. Regis Mohawk Tribe

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-0864 To 0865

Date: 10/10/91

Title: (Letter commenting on the "St. Lawrence River Ecological Data Collection Plan - Reynolds Metals Company - Massena, New York," dated September 1991)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-0866 To 0868

Date: 10/10/91

Title: (Letter conditionally approving the revised "St. Lawrence River Ecological Data Collection Plan," dated September 1991, and listing modifications which are to be made to the Plan)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: McCabe, William: US EPA

Recipient: Delisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-001-0972 To 0974

Date: 10/11/91

Title: (Letter forwarding the enclosed revised "Ecological Data Collection Plan for the St. Lawrence and Raquette Rivers")

Type: CORRESPONDENCE

Category: 3.2.0.0.0 Sampling and Analysis Data/Chain of Custody Forms

Author: Delisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Attached: REY-001-0975

Document Number: REY-002-1007 To 1008

Date: 10/11/91

Title: (Letter forwarding the enclosed comments on the August 7, 1991, "Draft Treatability Study, St. Lawrence River Sediments")

Type: CORRESPONDENCE

Category: 4.5.0.0.0 Feasibility Study Correspondence

Author: Petersen, Carole: US EPA

Recipient: Delisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Attached: REY-002-1009

Document Number: REY-001-1206 To 1207

Date: 10/17/91

Title: (Letter forwarding the enclosed revised "Treatability Study Work Plan for St. Lawrence River Sediments")

Type: CORRESPONDENCE

Category: 3.3.0.0.0 Work Plan

Author: Delisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Attached: REY-001-1208

Document Number: REY-001-1208 To 1274

Parent: REY-001-1206

Date: 10/18/91

Title: Final Work Plan, Treatability Study, St. Lawrence River Sediment

Type: PLAN

Category: 3.3.0.0.0 Work Plan

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-1083 To 1084

Date: 10/21/91

Title: (Letter forwarding the enclosed revised Table 1 from the "St. Lawrence River Ecological Data Collection Plan for Reynolds Metals Company")

Type: CORRESPONDENCE

Category: 7.8.0.0.0 Enforcement Correspondence

Author: Jacobson, Peter R.: Woodward-Clyde Consultants

Mancini, Ceil: Woodward-Clyde Consultants

Recipient: Carson, Lisa P.: US EPA

Attached: REY-002-1085

Document Number: REY-002-1085 To 1086

Parent: REY-002-1083

Date: 10/21/91

Title: Table 1 Field Sampling Plan, Ecological Data Collection Plan, Reynolds Metals Company, Massena,
New York

Type: PLAN

Category: 7.8.0.0.0 Enforcement Correspondence

Author: none: Woodward-Clyde Consultants

Recipient: none: none

Document Number: REY-002-1080 To 1081

Date: 11/01/91

Title: (Letter forwarding the enclosed summary table of the results of biological tissue collections
performed in the St. Lawrence and Raquette Rivers from October 21, to November 1, 1991)

Type: CORRESPONDENCE

Category: 7.8.0.0.0 Enforcement Correspondence

Author: Jacobson, Peter R.: Woodward-Clyde Consultants

Mancini, Ceil: Woodward-Clyde Consultants

Recipient: Carson, Lisa P.: US EPA

Attached: REY-002-1082

Document Number: REY-002-1033 To 1037

Date: 11/12/91

Title: (Letter commenting on the October 18, 1991, "Final Work Plan - Treatability Study - St. Lawrence
River Sediment")

Type: CORRESPONDENCE

Category: 4.5.0.0.0 Feasibility Study Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-1038 To 1038

Date: 11/12/91

Title: (Letter approving the revised "Final Work Plan, Treatability Study, St. Lawrence River Sediments,"
dated October 18, 1991, and stating that it must be submitted to EPA by January 31, 1992)

Type: CORRESPONDENCE

Category: 4.5.0.0.0 Feasibility Study Correspondence

Author: Petersen, Carole: US EPA

Recipient: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

500657

Document Number: REY-001-1006 To 1007

Date: 02/07/92

Title: (Letter forwarding the enclosed "St. Lawrence and Raquette River Technical Data Summary Report")

Type: CORRESPONDENCE

Category: 3.2.0.0.0 Sampling and Analysis Data/Chain of Custody Forms

Author: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Attached: REY-001-1008

Document Number: REY-001-1008 To 1121

Parent: REY-001-1006

Date: 02/07/92

Title: St. Lawrence River and Raquette River Technical Data Summary Report, Reynolds Metals Company,
Massena, New York

Type: REPORT

Category: 3.2.0.0.0 Sampling and Analysis Data/Chain of Custody Forms

Author: none: Woodward-Clyde Consultants

Recipient: none: US EPA

none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0869 To 0869

Date: 02/07/92

Title: (Letter stating that effective March 1, 1992, the new Project Coordinator will be Robert J.
Lenney)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: DeLisle, Dale A.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Document Number: REY-002-0871 To 0875

Parent: REY-002-0870

Date: 04/02/92

Title: (Letter discussing contaminated soils in the vicinity of the proposed 006 outfall ditch between
Haverstock Road and the St. Lawrence River and forwarding the attached sample results)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Bence, David F.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Waite, Philip G.: NY Dept of Environmental Conservation

500658

Document Number: REY-002-0870 To 0870

Date: 05/11/92

Title: (Letter forwarding the enclosed April 2, 1992, letter which indicates that soils in the vicinity of the Reynolds Metals site are contaminated with PCBs)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Carson, Lisa P.: US EPA

Attached: REY-002-0871

Document Number: REY-002-0877 To 0880

Parent: REY-002-0876

Date: 05/19/92

Title: Telecopier Information (Cover sheet forwarding sample results from the 006 outfall construction area in the vicinity of the Reynolds Metals Company's shoreline)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Rence, Dave: Reynolds Aluminum/Reynolds Metal Company

Recipient: Waite, Philip G.: NY Dept of Environmental Conservation

Document Number: REY-002-0876 To 0876

Date: 05/26/92

Title: (Transmittal slip forwarding the additional sample data from the Reynolds Metals Company's shoreline area)

Type: CORRESPONDENCE

Category: 3.5.0.0.0 Remedial Investigation Correspondence

Author: Daigle, William: NY Dept of Environmental Conservation

Recipient: Carson, Lisa P.: US EPA

Attached: REY-002-0877

Document Number: REY-002-0001 To 0001

Date: 01/18/93

Title: (Letter forwarding the enclosed revised report on the Analysis of Alternatives for the St. Lawrence Plant River Sediments regarding the Reynolds Metals site)

Type: CORRESPONDENCE

Category: 3.4.0.0.0 RI Reports

Author: Lennay, Robert J.: Reynolds Aluminum/Reynolds Metal Company

Recipient: Carson, Lisa P.: US EPA

Attached: REY-002-0002 REY-002-0003

500659

Document Number: REY-002-0003 To 0401

Parent: REY-002-0001

Date: 01/22/93

Title: Final Report - Analysis of Alternatives, St. Lawrence River System

Type: REPORT

Category: 3.4.0.0.0 RI Reports

Author: none: Woodward-Clyde Consultants

Recipient: none: Reynolds Aluminum/Reynolds Metal Company

Document Number: REY-002-0002 To 0002

Parent: REY-002-0001

Date: 01/22/93

Title: (Letter forwarding the enclosed revised report on the Analysis of Alternatives for the St.
Lawrence River sediments regarding the Reynolds Metals site)

Type: CORRESPONDENCE

Category: 3.4.0.0.0 RI Reports

Author: Coad, Richard M.: Woodward-Clyde Consultants

Jacobson, Peter R.: Woodward-Clyde Consultants

Recipient: Lenney, Robert J.: Reynolds Aluminum/Reynolds Metal Company

500660

APPENDIX 5
RESPONSIVENESS SUMMARY

**ARCS II EPA CONTRACT NO. 68-W8-0124
EPA WORK ASSIGNMENT NO. 023-2P4D
ICF TECHNOLOGY INCORPORATED**

FINAL

**RESPONSIVENESS SUMMARY
REYNOLDS METALS COMPANY SITE STUDY AREA
MASSENA, ST. LAWRENCE COUNTY, NEW YORK**

SEPTEMBER 1993

NOTICE

The preparation of this document has been funded by the United States Environmental Protection Agency (EPA) under the Alternative Remedial Contracting Strategy (ARCS) II Contract Number 68-W8-0124 to ICF Technology Incorporated (ICF).

500662

TABLE OF CONTENTS

1.0	INTRODUCTION	1
2.0	RESPONSIVENESS SUMMARY OVERVIEW	3
2.1	Site Description	3
2.2	Summary of Remedial Alternatives Presented in the Proposed Plan	4
2.3	Summary of EPA's Selected Remedial Alternative	5
3.0	BACKGROUND ON COMMUNITY INVOLVEMENT AND CONCERNS	6
4.0	SUMMARY OF MAJOR QUESTIONS AND COMMENTS RECEIVED FROM THE LOCAL COMMUNITY AND EPA's RESPONSES TO THESE COMMENTS	8
4.1	Remedial Alternative Preferences	8
4.2	Risk Assessment	13
4.3	Cleanup Levels	14
4.4	Cost	15
4.5	Decision Process	15
4.6	Other	16
5.0	COMPREHENSIVE SUMMARY OF SIGNIFICANT LEGAL AND TECHNICAL COMMENTS AND EPA's RESPONSES TO THESE COMMENTS	18
5.1	Petition	18
5.2	Reynolds Metals Company (RMC)	19
5.3	St. Regis Mohawk Tribe	33
5.4	New York State Department of Environmental Conservation (NYSDEC) ...	35
5.5	Canadian Review Panel	37
5.6	Cornwall Environmental Resource Center (CERC)	41
5.7	Massena Industrial Development Corporation (MIDC)	44
5.8	Aluminum Company of America (ALCOA)	47
5.9	General Motors (G.M.)	53

APPENDICES

APPENDIX A: Proposed Plan

APPENDIX B: Public Notices that were printed in the Courier-Observer, Indian Times and People's Voice newspapers to announce the Proposed Plan and public meeting, and to announce extension of the public comment period.

APPENDIX C: Sign-in sheets of participants at the March 9, 1993 public meeting.

APPENDIX D: Written comments received by EPA during the public comment period and summarized in Sections 4.0 and 5.0 of this Responsiveness Summary. EPA's responses to the written comments are also included in Sections 4.0 and 5.0 of this Responsiveness Summary.

1.0 INTRODUCTION

As part of its public participation responsibilities, the U.S. Environmental Protection Agency (EPA) held a public comment period from February 19 through April 21, 1993 for interested citizens to comment on EPA's Proposed Plan for the Reynolds Metals Company Site Study Area (also referenced in this document as the Site) in Massena, St. Lawrence County, New York. Although originally scheduled to end on March 22, EPA extended the public comment period an additional 30 days to April 21 at the request of several citizens.

The Reynolds Study Area and EPA's Proposed Plan focus on contamination in the river system surrounding the Reynolds Metals Company (RMC) facility. The Proposed Plan did not address the cleanup plan for the RMC facility and upland areas, which is being administered by the New York State Department of Environmental Conservation (NYSDEC). The Proposed Plan identified EPA's preferred alternative for remediating contaminated sediments in the river system surrounding the RMC facility.

EPA held a public meeting on March 9, 1993, at the Massena Town Hall in Massena, New York. During the meeting, representatives from EPA answered questions and received verbal and written comments on EPA's Proposed Plan and the other remedial alternatives under consideration.

In addition to comments received at the public meeting, EPA received written comments throughout the public comment period regarding its Proposed Plan. EPA's responses to significant comments received during the public comment period are included in this Responsiveness Summary which is appended to, and a part of, the decision document for the Site. All comments summarized in this document were factored into EPA's final determination of a remedial alternative for cleaning up the Site. EPA's selected remedy for the Site is described in the summary of the decision document.

This Responsiveness Summary is organized into the following sections.

2.0 RESPONSIVENESS SUMMARY OVERVIEW. This section briefly describes the RMC Site and activities conducted to date by EPA and RMC relative to the Superfund process, and outlines EPA's selected remedial alternative.

3.0 BACKGROUND ON COMMUNITY INVOLVEMENT AND CONCERNS. This section provides a brief history of community interest and concerns regarding the Site.

4.0 SUMMARY OF MAJOR QUESTIONS AND COMMENTS RECEIVED FROM THE LOCAL COMMUNITY AND EPA'S RESPONSES TO THESE COMMENTS. This section summarizes both verbal and written comments submitted to EPA by the local community during the public comment period and provides EPA's responses to these comments. "Local community" means those individuals who have identified themselves as living in the immediate vicinity of the Site and are potentially threatened from a health or environmental standpoint.

5.0 COMPREHENSIVE SUMMARY OF SIGNIFICANT LEGAL AND TECHNICAL COMMENTS AND EPA'S RESPONSES TO THESE COMMENTS. This section summarizes other verbal and written comments submitted to EPA during the public comment period and provides EPA's responses to these comments. It is comprised of specific legal and technical questions and, where necessary, elaborates with technical detail on answers covered in Section 4.0.

APPENDICES

There are four appendices attached to this document. They are as follows:

APPENDIX A: Proposed Plan

APPENDIX B: Public Notices that were printed in the Courier-Observer, Indian Times, and People's Voice newspapers to announce the public meeting and extension of the public comment period.

APPENDIX C: Sign-in sheets of participants at the March 9, 1993 public meeting.

APPENDIX D: Written comments received by EPA during the public comment period and summarized in Sections 4.0 and 5.0 of this Responsiveness Summary. EPA's responses to the written comments are also included in Sections 4.0 and 5.0 of this Responsiveness Summary.

2.0 RESPONSIVENESS SUMMARY OVERVIEW

2.1 Site Description

The RMC facility is an active aluminum production plant located on 1600 acres in Massena, St. Lawrence County, New York. The facility is located off Route 37, near the Massena-Cornwall International Bridge, directly upriver of the General Motors (G.M.)-Powertrain Division plant. The St. Regis Mohawk Indian Reservation, *Akwesasne*, is located about two miles downstream of the RMC facility. (Please refer to the Proposed Plan, Page 3, Figure 1, which is attached as Appendix A).

The RMC plant was constructed in 1958 for the production of aluminum from alumina. As a result of production activities and years of continuous operations and expansion, various types of industrial wastes including hazardous waste were generated, disposed, and spread throughout the facility. Major areas of contamination on the facility include an unlined pit known as the Black Mud Pond which was used for the disposal of carbon solids, a landfill, and the plant's North Yard. The RMC facility and upland areas are on the NYSDEC Registry of Class 2 Inactive Hazardous Waste Sites. In January 1992, NYSDEC issued a Record of Decision which outlined its cleanup plans for the RMC facility. NYSDEC's selected remedy included a combination of excavation and treatment of areas highly contaminated with polychlorinated biphenyls (PCBs)¹, and consolidation and containment of other contaminated areas on the facility. NYSDEC is overseeing the cleanup of contamination on the RMC facility, including contamination associated with the aluminum production facility. EPA's Proposed Plan and subsequent decision document do not focus on the cleanup plan for the RMC facility and upland areas.

In addition to contamination throughout the facility, RMC also discharged contaminants to the St. Lawrence River through four permitted outfalls. The outfalls discharged treated wastewater, contact cooling water, and stormwater runoff. As a result of these outfalls, contamination is also found in the river system surrounding the RMC facility. EPA is the lead agency for overseeing the cleanup of contamination in the river system surrounding the RMC facility.

The river system surrounding the RMC facility has been termed the "Reynolds Study Area" and includes that portion of the St. Lawrence, Grasse and Raquette Rivers, any tributaries of those rivers, and any wetlands which are between the International Bridge and the confluence of the Grasse and St. Lawrence Rivers. It also includes the portion of the Raquette River which is south of the confluence of the Grasse and St. Lawrence Rivers and south of the International Bridge.

¹PCBs are a group of toxic chemicals used for a variety of purposes including electrical applications, adhesives, hydraulic fluids and caulking compounds. PCBs are persistent in the environment because they are very stable, non-reactive and highly heat resistant. Chronic exposure to PCBs is believed to cause liver damage. It is also known to bioaccumulate in fatty tissues. PCB use and sale was banned in 1976 with the passage of the Toxic Substances Control Act.

PCBs were the primary contaminant found in sediment samples in the Reynolds Study Area. PCB oils were used by RMC as a heat transfer medium; RMC no longer uses PCB oils in its heat transfer medium system. Other contaminants detected in the St. Lawrence River sediments adjacent to the RMC facility include: polyaromatic hydrocarbons (PAHs), total dibenzofurans (TDBFs), aluminum, cyanide, and fluoride. EPA estimates that there are roughly 51,500 cubic yards of sediment with PCB concentrations above 1 part per million (ppm), PAH concentrations above 10 ppm, and TDBFs above 1 part per billion (ppb).

2.2 Summary of Remedial Alternatives Presented in the Proposed Plan

Based on the results of its risk assessment, EPA established cleanup levels for contaminated sediment in the Reynolds Study Area which are protective of human health and the environment. The cleanup levels are: PCBs - 1 ppm; PAHs - 10 ppm; and TDBF - 1 ppb. Cleanup to these levels will also remove the threat from other contaminants such as aluminum, cyanide and fluoride. It is EPA's intention that all three cleanup levels be met unless they are shown to be technically impracticable to achieve.

The following is a list of the remedial alternatives evaluated within the AA report and Proposed Plan. The alternative which was identified as EPA's preferred alternative in the February 1993 Proposed Plan is highlighted. Additional information on these alternatives can be found in the Proposed Plan, attached as Appendix A.

Alternative A: No Action

Alternative B: In-situ capping of sediments

Alternative D: Sediment removal and disposal in an on-site landfill

Alternative E: Sediment removal, on-site incineration, and disposal in an on-site landfill

Alternative F: Sediment removal, thermal desorption treatment, and disposal in an on-site landfill

Alternative G: Sediment removal, thermal desorption treatment of the majority of the contaminated sediment, and on-site disposal with cover

Option A: Thermal desorption treatment of material above 25 ppm

Option B: Thermal desorption treatment of material above 10 ppm

Alternative I: Sediment removal, thermal desorption treatment of the most contaminated sediments, and on-site landfilling of the less contaminated sediments and treated material

Option A: Thermal desorption treatment of material above 500 ppm

Option B: Thermal desorption treatment of material above 50 ppm

Alternative J: Partial removal of the most contaminated sediments, thermal desorption treatment, on-site landfilling of treated material, and in-situ capping of remaining sediment

2.3 Summary of EPA's Selected Remedial Alternative

The major components of EPA's selected remedy include:

- Dredging and/or excavation of approximately 51,500 cubic yards of sediments and sediments near the shoreline with PCB concentrations above 1 ppm, total PAH concentrations above 10 ppm, and total TDBF concentrations above 1 ppb from contaminated areas in the St. Lawrence River and from the associated riverbank;
- Treatment of approximately 14,500 cubic yards of dredged/excavated material with PCB concentrations above 25 ppm by thermal desorption. Untreated sediments (with PCB concentrations between 1 ppm and 25 ppm) and treatment residuals (which are expected to be non-hazardous and to have PCB concentrations below 10 ppm) will be disposed on-site, in the Black Mud Pond, and covered. The Black Mud Pond will be capped in conformance with the requirements of the January 22, 1992 New York State Record of Decision for the state lead Reynolds Metals Site, which encompasses the entire RMC facility. Contaminants condensed in the thermal desorption process will be transported off-site and burned at a commercial incinerator.

For more information regarding the EPA's selected remedy or the thermal desorption technology, please see EPA's decision document for the Reynolds Metals Study Area.

3.0 BACKGROUND ON COMMUNITY INVOLVEMENT AND CONCERNS

Historically, there has been a high level of community interest in all three Massena area sites--ALCOA, G.M., and RMC--and in contamination of the St. Lawrence River. The public first became aware of contamination in the St. Lawrence River in the early 1970s, when tests conducted by the Canadian government revealed measurable levels of PCBs in fish taken from the river. A number of supplemental studies have been conducted by various United States and Canadian regulatory agencies to determine the nature and extent of contamination and their points of origin.

In addition to ALCOA, G.M., RMC, and the state and local governments, at least four major interest groups have been involved in the Superfund cleanup process for these sites. These organizations include the St. Regis Mohawk Tribe, located directly downriver from the plants; regional environmentalists; groups in the Massena area concerned with maintaining a viable local economy; and Canadian agencies and citizens. The community most directly affected by contamination on and around the plants and in the St. Lawrence River is the St. Regis Mohawk Tribe Reservation, *Akwesasne*. The St. Regis Mohawk Tribe Reservation is adjacent to the G.M. Site and downriver from the ALCOA and RMC facilities. Reservation lands are located on both the United States and Canadian sides of the St. Lawrence River. There are approximately 3,500 residents on the United States side of the Reservation, and approximately 4,000 residents on the Canadian side of the Reservation. Concern for the health of their environment is very keen among the Mohawk people, whose lifestyle relies heavily on farming, fishing, hunting and trapping.

Because of the high level of interest in these sites, EPA has been conducting an ongoing community relations program in the Massena, New York area during investigation of the sites, and will continue the community relations program during cleanup of the sites. The program includes both formal and informal meetings with local officials, members of the St. Regis Mohawk Tribe, New York State representatives, Canadian officials and citizens, community and environmental groups, and other interested citizens. EPA has also provided a Technical Assistance Grant (TAG) to the Akwesasne Task Force on the Environment (members of the St. Regis Mohawk Tribe) to assist them in their efforts to fully participate in the Superfund decision-making process.

As part of its community relations program, in November 1988, EPA conducted a workshop in the Massena area on the various technologies available to remediate PCB-contaminated soils, sludges, and groundwater. EPA also prepared and distributed 11 fact sheets to describe the various alternatives that could be considered to remediate PCB-contaminated media at the sites.

Recently, EPA conducted site-specific community relations activities for the Reynolds Study Area. Following completion of the ARS and AA Reports, EPA, in February 1993, released its Proposed Plan for cleaning up contamination of the river system surrounding the RMC facility. This document, along with the ARS and AA Reports, were made available to the public through the information repositories maintained at EPA Region II's office in New York City, at the Massena Public Library, and at the St. Regis Mohawk Tribe Health Services Building. The Proposed Plan was also mailed to approximately 250 citizens on the Massena Area Mailing List.

The notice of availability of these documents was published in the Courier-Observer and Indian Times newspapers on February 19, 1993, and in the People's Voice² newspaper on February 22, 1993. A public comment period was held from February 19 through April 21, 1993. Although originally scheduled to end on March 22, EPA extended the public comment period an additional 30 days to April 21 at the request of several interested citizens. A second public notice announcing extension of the public comment period was published in the Courier-Observer and Indian Times newspapers on March 5, 1993, and in the People's Voice newspaper on March 8, 1993. Copies of the public notices are attached as Appendix B.

A public meeting was held on March 9, 1993. During the meeting, representatives from EPA answered questions and received comments on EPA's Proposed Plan and the other remedial alternatives under consideration. A transcript of the public meeting is available in the information repositories referenced above. The sign-in sheets from the public meeting are attached as Appendix C.

Copies of the written comment received during the public comment period are attached as Appendix D. Responses to comments received during the public comment period are included in this Responsiveness Summary, which is part of EPA's decision document. The Responsiveness Summary and decision document, along with the Administrative Record for the Site, are available at the information repositories referenced above.

² Indian Times and People's Voice are weekly newspapers affiliated with the St. Regis Mohawk Tribe.

4.0 SUMMARY OF MAJOR QUESTIONS AND COMMENTS RECEIVED FROM THE LOCAL COMMUNITY AND EPA's RESPONSES TO THESE COMMENTS

The public comment period on the Proposed Plan for the RMC Site was held from February 19 to April 21, 1993. Questions and comments received during this time are summarized below. Section 4.0 summarizes both verbal and written comments submitted to EPA by the local community during the public comment period and provides EPA's responses to these comments. Section 5.0 is comprised of specific legal and technical questions submitted to EPA during the public comment period and, where necessary, elaborates with technical detail on answers covered in Section 4.0. All written comments received during the public comment period and summarized in Section 4.0 and 5.0 of this Responsiveness Summary are attached as Appendix D.

Comments in Section 4.0 are organized into the following relevant topics:

- 4.1 Remedial Alternative Preferences
- 4.2 Risk Assessment
- 4.3 Cleanup Levels
- 4.4 Cost
- 4.5 Decision Process
- 4.6 Other

4.1 Remedial Alternative Preferences

4.1.1 Comment: A representative from St. Lawrence County asked if thermal desorption would volatilize contaminants other than PCBs, such as aluminum, cyanide and fluoride.

Response: Thermal desorption will remove organic compounds, such as PCBs, PAHs and TDBFs, from the sediments, but will not remove the inorganic compounds, such as aluminum, cyanide and fluoride. However, the levels of inorganic contaminants detected in sediments are not high enough to require separate treatment. EPA's baseline risk assessment determined that the levels of aluminum, cyanide and fluoride did not pose a significant threat to human health when compared to the risks posed by PCBs, PAHs, and TDBFs. Treated sediment and the remaining untreated material will be disposed on-site in the Black Mud Pond.

4.1.2 Comment: Representatives from the Akwesasne Task Force on the Environment, St. Regis Mohawk Tribe, several interested citizens, and Dr. Ward Stone, NYSDEC Wildlife Pathologist, support EPA's proposal to dredge contaminated sediments from the St. Lawrence River and treat them using thermal desorption.

Response: No response necessary.

4.1.3 Comment: Representatives from the Akwesasne Task Force on the Environment, the St. Regis Mohawk Tribe, Dr. Stone and an interested citizen recommend that EPA select

Alternative F, which involves sediment removal, thermal desorption treatment of contaminated material, and disposal in an on-site landfill. Thermal desorption will not treat the inorganic materials such as cyanide and fluoride; therefore, the material stored on the RMC facility would only be partially treated. Since the partially treated material would still contain potentially hazardous inorganic compounds, they recommend that it be stored in a lined landfill on the RMC facility. They referenced the need for a long-term, more permanent remedy.

Response: In response to a suggestion by NYSDEC, EPA is now requiring that untreated sediments (with PCB concentrations between 1 ppm and 25 ppm) and treatment residuals (which are expected to be non-hazardous and to have PCB concentrations below 10 ppm) will be disposed on-site, in the Black Mud Pond, and covered. NYSDEC's Record of Decision for the RMC facility calls for capping and groundwater monitoring of the Black Mud Pond. The inorganic contaminants found in the St. Lawrence River sediments are similar to those in the Black Mud Pond. Utilizing the Black Mud Pond will consolidate similar contaminants into one area while realizing cost savings related to eliminating construction, maintenance and monitoring of a new disposal area, and substantially reducing the volume of fill material needed for the Black Mud Pond.

The treated sediments will be tested using the Resource Conservation and Recovery Act (RCRA) Toxicity Characteristic Leachate Procedure (TCLP) test to determine if they are a RCRA hazardous waste. EPA has tested the sediments and does not expect that the treated sediments will be a RCRA hazardous waste. If the treated sediments are not a RCRA hazardous waste, they will be disposed on-site in the Black Mud Pond along with the previously screened debris. If the treated sediments are found to be a RCRA hazardous waste, they will either be treated to render them non-hazardous or they will be disposed, along with the previously screened oversized debris, in an engineered on-site landfill.

4.1.4 Comment: Representatives from RMC and Dr. Stone recommend that EPA's comprehensive plan to clean up contamination in the St. Lawrence River system attributable to the three major industrial facilities located in Massena, New York, begin at the most upstream facility and proceed downstream. This will prevent any potential for upstream contaminants to recontaminate cleaned areas.

Response: EPA agrees in principle and notes that the cleanup of the ALCOA facility is currently proceeding under the authority of a federal Unilateral Administrative Order and a State Consent Order, while the cleanup of the G.M. facility is proceeding under the authority of two federal Unilateral Administrative Orders. Currently, investigation of the river system and adjacent wetlands surrounding the ALCOA facility is being conducted to determine the appropriate remediation plans for that facility. Remedial alternatives have been selected for the G.M. Site, which is currently in the remedial design phase of cleanup. EPA's objective is to coordinate the cleanup efforts at the RMC Site with the cleanup of the other Massena area facilities to the extent possible. To that end, EPA will utilize a phased approach that will begin with dredging PCB hotspots, or areas with the highest PCB contamination, at each facility. At present, EPA plans that first phase dredging activities will commence at all three facilities in summer 1994.

4.1.5 Comment: An interested citizen commented that incineration should not be used to treat the contaminated sediments. Rather, the contaminated sediments should be stored in a cement "mausoleum" on the RMC property and monitored regularly.

Response: EPA believes that high level contamination in the St. Lawrence River should be treated to reduce PCB concentrations, rather than contained on the RMC facility without prior treatment because this material represents the principal threat at the Site. However, EPA recognizes that there may be impacts associated with on-site incineration and that the public is very concerned about the use of on-site incineration. EPA has chosen thermal desorption treatment, not on-site incineration, to treat all sediments with PCB concentrations above 25 ppm (approximately 14,500 cubic yards). Untreated sediments (with PCB concentrations between 1 ppm and 25 ppm) and treatment residuals (which are expected to be non-hazardous and to have PCB concentrations below 10 ppm) will be disposed on-site, in the Black Mud Pond, and covered. The selected remedy will result in permanent removal of contaminated sediment from the St. Lawrence River system and provide for treatment of the majority of the PCB mass in the contaminated sediments.

4.1.6 Comment: An interested citizen asked how EPA will control the river flow during dredging, and whether or not EPA will monitor the river after dredging to see if any of the contaminated sediments migrated downriver.

Response: EPA will not control the flow of the river during dredging. Rather, EPA will use available technologies to control the sediments in the vicinity of the dredging and to prevent migration of sediments during dredging. EPA's selected remedy includes development of a dredging monitoring plan that will include sampling activities to measure the environmental impacts of dredging. It will also include a contingency plan which will describe measures to control and/or minimize the impacts of dredging on the environment.

During dredging, EPA will monitor the river using techniques as turbidity analysis to determine if there is any increase of sediment suspension during dredging. If monitoring shows a significant increase in sediment suspension, then EPA will discontinue dredging and reevaluate that option. In addition, in the event that monitoring indicates that there are any downstream depositional areas which collect resuspended sediment, those areas can be dredged to remove the resuspended sediments. The iterative process of sampling, excavating, and re-sampling is contemplated as an integral part of the remedial action.

4.1.7 Comment: An interested citizen asked whether, if RMC builds the thermal desorption plant, G.M. and ALCOA would also be able to use it for their cleanup programs.

Response: The three industries have been and will continue to work together on cleaning up the contamination problems to the greatest extent possible. However, cleanup of contamination will depend on the specific characteristics of each site. For example, RMC has already conducted small scale pilot tests on the thermal desorption technology ATP and has had positive results. G.M. will be pilot testing technologies other than ATP at its site. The investigation of the ALCOA site has not reached the stage where a remedial technology has been selected. EPA will not require that the companies use identical technologies.

4.1.8 Comment: Mr. Stone stated that some areas of contamination outlined by EPA in its Proposed Plan may not be accurate. He stated that the area in the vicinity of Discharge 002 may have much higher PCB levels than reported by EPA, requiring much more sediment to be removed than proposed by EPA.

Response: EPA's Proposed Plan provided a rough approximation of the area which must be addressed to meet Site cleanup levels. Prior to dredging, additional sediment and surface water sampling will be conducted to better delineate the extent of the area to be dredged and to serve as baseline monitoring data. Sediments with PCB concentrations above 1 ppm, total PAH concentrations above 10 ppm, and total TDBF concentrations above 1 ppb will be dredged unless it proves technically impracticable to do so.

4.1.9 Comment: An interested citizen asked if EPA used a safety factor to determine the cleanup areas for PCBs, PAHs and TDBFs.

Response: EPA did not use a safety factor. Rather, EPA mapped the areas where PCBs, PAHs and TDBFs were found in order to determine the area of contamination to be removed.

4.1.10 Comment: Representatives from RMC stated that site-specific issues need to be considered in evaluating the appropriate remedial alternative for the Reynolds Study Area. The technologies that are appropriate for the Reynolds Study Area may be different than for other areas along the river due to the characteristics of the river bottom and the hydrodynamics of the St. Lawrence River in the vicinity of the RMC facility.

Response: After careful consideration of RMC's site-specific characteristics, EPA evaluated and balanced each remedial alternative according to the nine criteria set forth in the National Oil and Hazardous Substances Pollution Contingency Plan (NCP) (300.430 {e}{9}{iii}). In addition, EPA also evaluated its selected remedy for consistency with EPA's 1990 "Guidance for Remedial Actions for Superfund Sites with PCB Contamination" (also referred to as the "PCB Guidance"). EPA recognizes that every Superfund site is different (different physical characteristics, contaminants, pathways of exposure, media); thus, EPA evaluates and selects an appropriate remedial alternative for each site on a site-by-site basis in light of available guidance and regulations.

4.1.11 Comment: A representative from RMC expressed concern with EPA's selection of a remedy that has a low possibility of success, is extremely expensive, and has the highest short-term risks associated with any of the alternatives.

Response: EPA does not agree that its selected remedy has a low possibility of success. Treatability studies indicate that thermal desorption will effectively treat contaminated sediments from the Reynolds Study Area. EPA's selected remedy is implementable from an engineering standpoint.

EPA acknowledges that the greatest potential difficulty associated with its selected remedy is the technical feasibility of dredging sediments sufficiently to achieve the cleanup goals for the

Site. However, dredging has been used effectively at another Superfund site in New Bedford Harbor, Massachusetts, to remove PCB-contaminated sediments from an estuary.

There are several factors which EPA believes will contribute to the effectiveness of dredging as a means of removing sediment from the St. Lawrence River. First, the area to be dredged is fairly shallow and is located adjacent to the shore of the St. Lawrence River. Second, the use of engineering controls such as sheet pile walls has been shown to substantially reduce sediment suspension. Third, the selection of the dredging technique (e.g., a hydraulic dredge), can be made with the goal of minimizing sediment suspension. Fourth, the public health and environmental impacts resulting from sediment dredging (which are of relatively short duration) are lower than the current long-term risks posed by the contaminated sediment. Finally, in the event that monitoring indicates that there are any downstream depositional areas which collect resuspended sediments, they can be dredged to remove those resuspended sediments. The iterative process of sampling, excavating and re-sampling is contemplated as an integral part of the remedial action.

The selected remedy is cost-effective because it has been demonstrated to provide overall effectiveness proportional to its costs. The present worth cost of the selected alternative, Alternative G(A), which includes a 25 ppm treatment threshold, is \$ 35.1 million. The present worth cost of Alternative G(B), which includes a 10 ppm treatment threshold, is \$ 36.7 million. The present worth cost of Alternative I(A), which incorporates a 500 ppm treatment threshold, is \$ 35.8 million. The present worth cost of Alternative I(B), which incorporates a 50 ppm treatment threshold, is \$ 37.9 million. Thus, EPA has selected the least expensive alternative which provides for permanent removal and treatment of the majority of the principal threat posed by contaminated sediments. In addition, a comparison of the costs of Alternatives G(A), I(A), and I(B) demonstrates that it is more expensive to construct a landfill for disposal of sediments with PCB concentrations between 25 and 500 ppm than it is to treat such sediments. Therefore, Alternative G(A) is more cost-effective than Alternative I.

The use of thermal desorption, rather than incineration, minimizes the cost of treatment. The 25 ppm treatment threshold results in permanent treatment of the majority of the PCB mass within the contaminated sediments and is consistent with EPA guidance and New York State's cleanup plans for the upland portion of the RMC facility, while at the same time being less expensive than Alternative G(B), which includes a treatment level of 10 ppm. EPA's preference for use of the Black Mud Pond for disposal is also cost-effective since it will minimize the amount of fill needed in this area and it will consolidate material in one management area.

Finally, EPA believes that none of the remedial alternatives considered in the Analysis of Alternatives (AA) report, including EPA's selected remedial alternative, pose unacceptable short-term risks to human health. All remedial alternatives, with the exception of the No Action alternative, involve some short-term suspension of contaminated sediments. The selected remedy includes the use of extensive controls such as silt curtains to minimize sediment suspension and migration. The selected remedy involves sediment treatment to reduce the potential for direct contact with contaminated sediment by permanently removing the source of contamination. Community and worker exposure will be minimized by the use of construction methods that minimize workers' contact with the contaminated materials. Air quality will be monitored during remediation.

4.1.12 Comment: A representative from RMC stated that EPA has underestimated the positive attributes of armoring (in-situ containment or cap) and RMC's ability to monitor the cap for its long term performance.

Response: In-situ containment was considered by EPA. However, after carefully balancing the specific characteristics of the Site against the nine criteria as outlined in the NCP, EPA has determined that the long-term effectiveness and permanence afforded by the selected alternative offset any short-term risks posed by the selected alternative and the higher costs of the selected alternative. Although containment of contamination is less difficult than excavation or dredging and treatment of contamination, EPA prefers technologies in which treatment that permanently and significantly reduces the volume, toxicity or mobility of the PCBs is a principal element.

EPA has determined that dredging is an effective way of removing the volume of contaminated sediments in the river system based on limited previous experience at other Superfund sites and federal projects. In addition, although sediment containment with a graded cover would reduce the erosive force of the flowing river water and would limit movement of contaminants into the environment, its long-term effectiveness is dependent upon the adequacy and reliability of the sediment cover. Long-term monitoring and maintenance of contained sediments would be difficult to achieve because the cover is located underwater. Because the sediments are submerged, the contained underwater sediments would require periodic inspections by divers. In addition, several rounds of sampling might be required to detect underwater containment cell leakage, since any leaking contamination would be diluted. Further, if underwater monitoring revealed that cap repairs were necessary, such repairs could likely only be undertaken in late spring or in summer. Little information is available on the frequency with which maintenance would be needed or on the probability of cover failure. If the sediment cover fails, cancer risks on the order of 10^{-2} would be present immediately since contaminated sediments would reenter the river system, and be available to contaminate fish and wildlife. Sediment dredging, on the other hand, would permanently remove the long-term risks from contaminated sediments.

4.2 Risk Assessment

4.2.1 Comment: An interested citizen asked if EPA had developed a risk assessment for the combination of PCBs, PAHs, TDBFs, aluminum, and cyanide.

Response: EPA's risk assessment provides both chemical-specific and combined risks associated with these chemicals.

4.2.2 Comment: Representatives from RMC stated that site-specific issues need to be considered in evaluating appropriate cleanup levels for the Reynolds Study Area. Since the cleanup levels are to be risk-driven, the risk assessment should be specific to the RMC Site and not based on regional data.

Response: Where possible, site-specific assumptions were used in the evaluation of cleanup levels. Sediment concentrations evaluated were those in the Reynolds Study Area.

4.2.3 Comment: A representative from RMC stated that it is premature for EPA to propose a remedy before the risk assessment has been completed. In its draft form, the risk assessment has serious flaws in the assumptions used, the methods employed, and the conclusions reached.

Response: Generally, EPA issues all risk assessments, Additional River Study (ARS) reports, AA reports, and other investigative reports in draft form during the public comment period to allow for public comment on those documents as well as on the Proposed Plan. Although in draft form, the risk assessment was complete, and EPA did not anticipate any major changes. After reviewing comments made by RMC and the public which are summarized in this responsiveness summary, EPA has revised and finalized the draft risk assessment. The revisions to the risk assessment were minor.

4.3 Cleanup Levels

4.3.1 Comment: Representatives from the Akwesasne Task Force on the Environment, St. Regis Mohawk Tribe, Dr. Stone, and an interested citizen stated that EPA's cleanup level should be 0.1 ppm. They expressed the need to protect the food chain, particularly for the Mohawk community whose culture relies heavily on fishing and hunting. They also cited recent research that has revealed new information on the negative, non-carcinogenic health effects of PCBs; and the potential, cumulative health effects of exposure to multiple contaminants via multiple pathways of contamination.

Response: Based on the results of its risk assessment, EPA established cleanup levels for contaminated sediment in the Reynolds Study Area which are protective of human health and the environment. The cleanup levels are: PCBs - 1 ppm; PAHs - 10 ppm; and TDBF - 1 ppb. Cleanup levels are the concentration of contaminants in sediment above which some remedial action will be taken (i.e., treatment or containment). These cleanup levels were based on ingestion of fish by local residents and represent sediment contaminant concentrations which would be associated with carcinogenic risks on the order of 10^{-4} .

Cleanup to these levels will also remove the threat from other contaminants such as fluoride and cyanide. The 1 ppm PCB cleanup level is identical to that selected by EPA for contaminated sediment associated with the G.M. Site which is immediately downstream of the RMC facility. For the G.M. Site, EPA estimated that a 1 ppm PCB cleanup level in sediments is associated with a 10^{-4} (1 in 10,000) excess cancer risk to humans. For the RMC Study Area Site, EPA estimates that a 1 ppm PCB cleanup level in sediments is associated with an excess cancer risk to humans on the order of 10^{-4} (1 in 10,000). There is a variation in estimated residual cancer risks between the G.M. and RMC Study Area Sites due to uncertainties associated with estimating the effect of varying sediment PCB concentrations on area fish.

A rough approximation of the area which must be addressed to meet Site cleanup levels is given in Figure 11 of the decision document. There are approximately 51,500 cubic yards of sediment over a 27-acre area with PCB concentrations above 1 ppm, PAHs above 10 ppm, and TDBFs above 1 ppb. EPA considers such sediments to pose a principal threat to human health and the environment.

It should be noted that federal and New York State sediment quality criteria guidance indicate that PCB cleanup levels well below 1 ppm are required to achieve protection of the environment since PCBs pose a significant ecological risk. While EPA would prefer a lower cleanup level which would be associated with a 10^{-6} cancer risk, EPA has significant concerns as to the technical practicability of achieving a PCB cleanup level below 1 ppm in this area of the St. Lawrence River. In selecting the 1 ppm cleanup goal, EPA has balanced its desire for a very low cleanup level which will minimize residual risk with the constraints posed by the limitations of dredging as a means of removing sediment with the further intent of selecting treatment as a principal element over containment. EPA believes that a 1 ppm cleanup goal in the St. Lawrence River provides an acceptable measure of protection of human health.

4.4 Cost

4.4.1 Comment: Representatives from RMC stated that EPA has not adequately balanced risk with cost as required by the NCP. Specifically, EPA has essentially doubled the cleanup cost by using a cleanup level that is based on a more stringent risk level than required by the NCP. In addition, EPA's recommended alternative is \$ 13.5 million more expensive than the RMC option with little added benefit. Representatives from RMC cited EPA's Proposed Plan, which they believe indicates that EPA's proposed approach may require in-situ containment of the entire area after dredging, thereby duplicating remediation and increasing costs.

Response: Please see EPA's response to comment 4.1.11.

EPA is sensitive to RMC's concerns regarding duplication of remediation and increasing costs. Therefore, an initial dredging program will be conducted in a manner which will identify site-specific information and operating parameters such as dredging rates and depths, sediment removal efficiencies, silt curtains and sheet piling effectiveness, sediment dewatering methods, and sediment suspension and settling characteristics. This information will be evaluated and used as appropriate in modifying operating procedures to improve the effectiveness of the removal program.

4.5 Decision Process

4.5.1 Comment: An interested citizen commented that the cleanup decision should be made by the people most affected by the contamination.

Response: After consideration of all public comments received during the public comment period, EPA, in consultation with NYSDEC and the St. Regis Mohawk Tribe, made the final decision regarding the remedial alternative to be implemented at the Site. All public comments received during the public comment period were factored into EPA's final determination of the selected remedial alternative. EPA intends to continue its ongoing public involvement activities to solicit suggestions and comments throughout the remedial design and implementation.

4.5.2 Comment: An interested citizen stated that there should be methods for adjusting the selected remedy in the future if it proves faulty or if there are unforeseen risks to human health and the environment years from now.

Response: Because EPA's selected remedial alternative would result in contaminants remaining on-site above health-based levels, the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) as amended, requires that the Site be reviewed at least once every five years. If justified by the review, additional response actions may be implemented to remove or treat the wastes, if necessary, to protect human health and the environment.

4.5.3 Comment: An interested citizen asked if EPA and NYSDEC will coordinate and agree upon cleanup standards and procedures before ordering RMC to do the cleanup work.

Response: EPA has coordinated with NYSDEC on the cleanup goals for the RMC facility, upland areas, and adjacent river sediments. EPA's 1989 Order to RMC includes performance of the cleanup alternative selected by EPA.

4.6 Other

4.6.1 Comment: A representative from the St. Regis Mohawk Tribe and several interested citizens stated that RMC, along with the other industries in the area, have contributed to the destruction of the Mohawk lifestyle and negative impacts on the Mohawk economy and health. The Mohawk community has gone from a diet of fish, wildlife and game to a supermarket-type diet, which has resulted in an increase in diabetes in their community. The Mohawk economy has changed from physical occupations such as fishing and agriculture, to inactive occupations such as retail and gambling. The decrease in activity may be contributing to the rising diabetes level in the community as well. The negative impacts on the Mohawk community and increasing diabetes levels need to be evaluated.

Response: EPA notes the concerns about recent changes in the diet and economy of the Mohawk people. At present, due to contamination, there are fishing advisories in effect for the St. Lawrence River in the Massena area. While the Superfund law does not directly address these issues, it does so indirectly by requiring remediation of contaminated areas. The goal of EPA's remedial efforts in the Massena area is to restore contaminated sediment hotspots and, thus, to ultimately restore the river environment to allow unrestricted fishing in the St. Lawrence River.

4.6.2 Comment: An interested citizen asked whether tests were conducted for dioxin, given the presence of TDBFs at the Site.

Response: Tests were conducted for dioxin in sediments in the Reynolds Study Area. Investigations conducted at the Site included analyses of eight sediment samples from the St. Lawrence River. Dioxin was not detected in any of the samples.

4.6.3 Comment: A representative from Save Our River stated that if the Bombay-Brasher-Helena area is allowed to be strip-mined of clay for the Superfund site landfills and the St. Lawrence County landfills, it will destroy the groundwater table for the St. Regis and St. Lawrence Rivers.

Response: EPA is not requiring that a clay-lined landfill be constructed as part of its remedy for the Reynolds Study Area.

4.6.4 Comment: Mr. Stone stated that if the Mohawks are truly a sovereign nation, then they should have control over their waters and the St. Lawrence River, and their Applicable or Relevant and Appropriate Requirements (ARARs) should be followed.

Response: The St. Regis Mohawk Tribe has identified cleanup standards which are applicable to remedial actions which will be conducted on the St. Regis Mohawk Reservation as part of the G.M. Site remediation. Since contaminants found within the RMC Site do not fall within the boundaries of the St. Regis Mohawk Reservation, the Tribal cleanup standards do not apply. At the RMC Site, the Tribal cleanup standards are "To Be Considered" Requirements (see Table 9 of the decision document). However, the St. Regis Mohawk Tribe was consulted during development of EPA's Proposed Plan and selected remedy, and will continue to play a meaningful role during all phases of the decision-making process at the RMC Site.

4.6.5 Comment: Several interested citizens commented on the negative health and environmental impacts of PCBs.

Response: EPA's awareness of the negative health and environmental impacts of PCBs has led it to select an aggressive remedial approach and cleanup goal that will be protective of human health and the environment.

5.0 COMPREHENSIVE SUMMARY OF SIGNIFICANT LEGAL AND TECHNICAL COMMENTS AND EPA'S RESPONSES TO THESE COMMENTS

As mentioned earlier, Section 5.0 is comprised of specific legal and technical questions submitted to EPA during the public comment period and, where necessary, elaborates with technical detail on answers covered in Section 4.0. All written comments received during the public comment period and summarized here are attached as Appendix D.

Comments from the following citizens and/organizations are summarized below:

- 5.1 Public Petition
- 5.2 Reynolds Metals Company
- 5.3 St. Regis Mohawk Tribe
- 5.4 New York State Department of Environmental Conservation
- 5.5 Canadian Review Panel
- 5.6 Cornwall Environmental Resource Center
- 5.7 Massena Industrial Development Corporation
- 5.8 Aluminum Company of America
- 5.9 General Motors Corporation

5.1 Petition

One hundred and thirty five (135) citizens mailed EPA the following petition: "As a resident of the St. Lawrence River Valley, I endorse the EPA's proposed plan for the remediation of the Reynolds Metals Study Area. I urge the implementation of Alternative G(B): the removal of all sediments with PCB contamination over 1 ppm; the use of thermal extraction rather than incineration; and the treatment level of 10 ppm rather than 25, 50 or 500 ppm. The only change I would support would be the use of a lined, rather than unlined, landfill to prevent any contamination of surrounding surface or ground waters from untreated sediments or treated residuals."

Response: Please see EPA's response to comment 4.1.3.

5.2 Reynolds Metals Company (RMC)

The comments summarized in this section were received from RMC.

5.2.1 Comment: RMC states that EPA has not chosen a defined remedial alternative in its Proposed Plan. It appears that EPA is proposing to dredge to the extent feasible and then implement some other remedial alternative. The criteria for EPA's preferred alternative have not been defined, and EPA's preferred alternative may actually be comprised of two separate remediations (Alternative G(B) plus in-situ containment). Not only is this questionable engineering judgement, but it also represents a risk management decision that is contrary to EPA's mandate to reduce environmental and human health risks.

Moreover, only when pilot scale dredging is performed can EPA determine how much, if any, dredging is consistent with the requirements of CERCLA. The technology would need to be demonstrated as feasible prior to initiating any plans for full scale implementation.

Therefore, RMC recommends Alternative J: Partial Sediment Removal/Thermal Desorption/Landfilling/In-Situ Capping, an approach that requires the methods to be demonstrated as feasible prior to initiating the remediation.

Response: EPA has selected a carefully defined remedial alternative for the Site. EPA's selected alternative involves dredging and treatment of dredged/excavated material with PCB concentrations above 25 ppm by thermal desorption. Untreated sediments (with PCB concentrations between 1 ppm and 25 ppm) and treatment residuals (which are expected to be non-hazardous and to have PCB concentrations below 10 ppm) will be disposed on-site, in the Black Mud Pond, and covered.

There are several factors which EPA believes will contribute to the effectiveness of dredging as a means of removing sediment from the St. Lawrence River. First, the area to be dredged is fairly shallow and is located adjacent to the shore of the St. Lawrence River. Second, the use of engineering controls such as sheet pile walls has been shown to substantially reduce sediment suspension. Third, the selection of the dredging technique (e.g., a hydraulic dredge), can be made with the goal of minimizing sediment suspension. Fourth, the public health and environmental impacts resulting from sediment dredging (which are of relatively short duration) are lower than the current long-term risks posed by the contaminated sediment. Finally, in the event that monitoring indicates that there are any downstream depositional areas which collect resuspended sediments, they can be dredged to remove those resuspended sediments. The iterative process of sampling, excavating and re-sampling is contemplated as an integral part of the remedial action.

Dredging has been used effectively at another Superfund site in New Bedford Harbor, Massachusetts, to remove PCB-contaminated sediments from an estuary. EPA is sensitive to RMC's concerns regarding duplication of remediation and increasing costs. Therefore, an initial dredging program will be conducted in a manner which will identify site-specific information and operating parameters such as dredging rates and depths, sediment removal efficiencies, silt curtains and sheet piling effectiveness, sediment dewatering methods, and sediment suspension and settling characteristics. This information will be evaluated and used

as appropriate in modifying operating procedures to improve the effectiveness of the removal program.

5.2.2 Comment: RMC believes that EPA has issued its Proposed Plan prematurely, without the benefit of a finalized Risk Assessment. The draft risk assessment is inconsistent with the risk assessment prepared for the adjacent G.M. Site.

Response: Please see EPA's response to comment 4.2.3.

EPA has compared the approach used to prepare the draft risk assessments for the G.M. and RMC Sites. In general, the approaches are comparable. However, both rely on site-specific information.

5.2.3 Comment: RMC's primary concern with the Human Health Assessment (HHA) portion of the draft risk assessment is the reasonableness of assumptions and information used in estimating exposures. First, the report states that NYSDEC fish sampling data was used in the risk assessment even though the data were not validated. Second, many of the highly conservative assumptions used in the HHA are attributed to a personal communication-K. Jock (1991). There is no way to verify the context, understanding, accuracy or appropriateness of the communicated information because this information is not contained in publicly-available documents.

Third, the toxicity assessment portion of the HHA was essentially nonexistent which is inconsistent with EPA Guidance. Furthermore, EPA improperly characterized risks and selected inappropriate cleanup levels by using highly conservative toxicity values based on outdated EPA Guidance. The HHA uses the Aroclor 1260 carcinogenic slope factor for all PCB mixtures, when there is considerable evidence that the lower chlorinated mixtures exhibit much lower carcinogenic potential, if they are carcinogenic at all.

Fourth, the exposure assessment overstates the risks. The HHA suggests with no justification that "sediments may become more exposed" in the future. Office of Solid Waste and Emergency Response (OSWER) directives for risk assessment indicate that future uses or risks should only be evaluated if there is a reasonable likelihood they will occur. The assumptions used for sediment exposure in children, adults, and fishermen are very extreme and unjustified.

Response: The two most common results of the data validation process are the rejection of certain non-detects and the changing of blank contaminants to non-detects. If non-detects are dropped out, the mean concentration may increase slightly. If blank contaminants are eliminated, mean concentrations of a given contaminant would decrease. The risk assessment recognizes these uncertainties related to defining the true extent of biota contamination.

Many of the exposure assumptions used in the risk assessment were based on communications with Mr. Jock. The risk assessment report explicitly refers to interviews conducted with Mr. Jock and summarizes the pertinent information provided by Mr. Jock in a

publicly available document (the risk assessment report itself). Risk assessors are encouraged to obtain site-specific inputs whenever possible. Professional judgement pertaining to the reliability and credibility of the interviewee is used and a comparison to similar sites is made before final exposures parameters are selected. This type of research and consensus was performed for the Reynolds Risk Assessment.

The toxicity section of the HHA is fully consistent with EPA guidance. Toxicity values are presented in Table 4-7 of the HHA. Per EPA risk assessment guidance, EPA's Integrated Risk Information System (IRIS) was the preferred source of toxicity values; otherwise, EPA's Health Effects Assessment Summary Tables (HEAST) or EPA's Environmental Criteria and Assessment Office (ECAO) were consulted for toxicity information. Section 4.3 of the HHA also includes two tables outlining potential carcinogenic and noncarcinogenic effects associated with contaminants of concern. In addition, Appendix D of the risk assessment includes toxicity profiles for all RMC contaminants of concern. The toxicity profiles include information on the chemicals' use; chemical and physical properties; fate and transport; pharmacokinetics; carcinogenic effects; noncarcinogenic effects (e.g., systemic effects, teratogenic and other developmental effects, and mutagenic effects); ecotoxicity; and applicable standards, criteria and guidelines.

The uncertainties associated with the use of the currently available slope factor for PCBs are recognized in the Reynolds Risk Assessment. EPA also recognizes that PCB congeners may vary as to their potency in producing biological effects and that there is some evidence that mixtures containing more highly chlorinated biphenyls are more potent inducers of hepatocellular carcinoma in rats than mixtures containing less chlorine by weight (IRIS, 1993/Kimbrough, 1987 and Schaeffer et al., 1984). However, EPA has not currently adopted guidance which evaluates the toxic equivalents for various PCB congeners. In addition, EPA is currently reviewing but has not adopted the cross species scaling factor for carcinogenic risk assessment (daily amount administered per unit of body mass raised to the $3/4$ power, i.e., $\text{mg/kg}^{3/4} (\text{day})$ (EPA, 1992)). The risk assessment was prepared in accordance with the most current EPA Superfund guidance and IRIS which assumes Aroclor 1260 is representative of all PCB mixtures. IRIS toxicity values are based on the consensus of various EPA Work Groups. These Work Groups are continually reviewing toxicity information as it becomes available and updating toxicity values to minimize uncertainties associated with the estimation of risks to human health.

The assumptions used for sediment exposure are considered conservative but realistic. If current land use changes children and adults may have access to the contaminated sediments in the vicinity of the RMC Site.

5.2.4 Comment: RMC states that the use of National Oceanic and Atmospheric Administration (NOAA) values as criteria for the evaluation of contaminant concentrations in sediments is inappropriate. RMC points out that these values are derived from field samples containing mixtures of contaminants, and that they are explicitly not intended as regulatory guidelines. RMC believes that these guidelines result in an overstatement of risk, and that they are not truly applicable since they are primarily based on marine and estuarine studies.

Response: The Ecological Risk Assessment (ERA) evaluation of sediments has been revised to include a comparison of organic non-ionic contaminants with sediment criteria derived through the equilibrium partitioning approach. NOAA sediment guidelines were still used to assess inorganic contaminants. For organic contaminants lacking adequate effects data, sediment effects level reported by Tetra Tech (1986) were used. These effect levels appear to be roughly comparable to sediment criteria derived through the equilibrium partitioning approach (i.e., sediment samples that exceeded Tetra Tech effect concentrations also exceeded criteria derived from the equilibrium partitioning approach).

5.2.5 Comment: RMC objects to the use of data on background levels of metals in soils in the eastern United States as sediment ecological risk criteria. RMC states that the chemical differences between terrestrial soils and sediments and the biological differences between terrestrial and aquatic biota make a direct comparison inappropriate.

Response: The ERA has used typical surficial soil concentrations for several inorganic contaminants lacking sediment guidelines (e.g., aluminum, fluoride, selenium, vanadium) to initially screen potential sediment contaminants of concern. These levels were used since background sediment concentrations and effect levels were not available for inorganics. The table and discussion regarding sediment concentrations and potential risk clearly indicate that although a variety of contaminants are driving risk, total PCBs, PAHs, and TDBF are the primary contaminants of concern. It is also evident that concentrations of aluminum, fluoride, selenium, and vanadium are not anticipated to result in significant risk to ecological receptors.

5.2.6 Comment: RMC is concerned that the Proposed Plan does not adequately address ecological impacts associated with dredging.

Response: The baseline risk assessment does not address risks associated with various remedial alternatives; therefore, ecological impacts associated with dredging have not been formally evaluated. However, long-term impacts associated with leaving sediment contaminants (particularly PCBs) in place are expected to be greater than temporary impacts associated with dredging.

5.2.7 Comment: RMC believes that the ERA is not entirely consistent with EPA guidance. Specifically, the problem formulation step of the study does not include a conceptual site model (CSM), which describes how a source (or stressor) might affect potential receptors.

Response: The guidance listed, "Framework for Ecological Risk Assessment" (EPA, 1992) although containing useful information, is not a mandatory document for conducting ecological risk assessments. The ERA is consistent with previous ecological risk assessments conducted by EPA Region II. Presenting a conceptual site model will not alter the results of the ERA.

5.2.8 Comment: RMC states that some of the conclusions in the ecological risk assessment may be inappropriate because they are based on an index intended to evaluate organic pollution rather than inorganic contamination.

Response: Although the Hilsenhoff Biotic Index (HBI) has currently only been evaluated for organic pollutants, it may also be applicable for additional pollutants. In any event, conclusions of the ERA regarding impacts to the benthic community would not change if the HBI were not used in the risk assessment. Evidence of benthic community impairment also included hyperdominance by pollution tolerant taxa, imbalance in composition of functional feeding groups, and reductions in benthic invertebrate diversity and taxa richness. It is important to note that the primary contaminant of concern at the Site is an organic contaminant, PCBs.

5.2.9 Comment: RMC notes that references for many assumptions were not well documented. Specific examples include the basis for assuming a three percent lipid content in the white sucker fish and the bioconcentration factor criterion for contaminants of concern (COCs) of 300.

Response: The percent lipid content of the white sucker was not measured; therefore, an assumed three percent lipid content was selected based on professional judgement. COCs were selected based on frequency of detection, comparison with background concentrations, and relative toxicity. The selection of COCs based on bioconcentration potential was not included as a criteria in the draft final ERA.

5.2.10 Comment: RMC disagrees with some of the ERA methodology. In particular, RMC states that adding individual surface water risk indices which did not exceed criteria led to misleading total risk indices, and that geometric means rather than arithmetic means should have been used to calculate exposure concentrations.

Response: Due to the uncertainty associated with chemical interactions and effects on aquatic receptors, it was conservatively assumed that risk from various contaminants may be cumulative for aquatic receptor species. Although individual contaminants may not pose a risk by themselves, interaction with other related contaminants may result in adverse impacts. Geometric means were used in evaluating exposure concentrations.

5.2.11 Comment: RMC commented that the characterization of risk to fish is poor. In addition, little mention is made of the fact that fish are mobile. RMC points out that birds and fish are not likely to feed in the vicinity of the most contaminated area 100 percent of time. RMC states that an unrealistic conversion factor was used to evaluate body concentration of PCBs in fish.

Response: Information regarding contaminant body burden concentrations within fish and associated adverse effects are sparse in the scientific literature. However, the ERA indicated that the potential for risk to fisheries has been clearly identified.

In addition, although fish may move in and out of contaminated portion of the Reynolds Study Area, the fact that risk was evaluated based on detected fish tissue concentrations confirms that fish are exposed to PCB contamination within the study area.

Data regarding home ranges of the selected indicator species within the Reynolds Study Area were unavailable. Therefore, it was assumed that the indicator species foraged entirely within the Reynolds Study Area. Due to the large size of the Reynolds Study Area, it is conceivable that this area could provide all foraging requirements for the selected indicator species.

EPA believes that the conversion factor is realistic. In addition, using the conversion factor suggested by Sloan (NYSDEC) also results in a fish whole body concentration much greater than recommended for the protection of piscivorous wildlife. The conclusion is the same: existing PCB concentrations in fish present a significant risk to piscivorous ecological receptors.

5.2.12 Comment: RMC is concerned that high background contaminant concentrations in environmental media and prey items were not considered in the ERA.

Response: PCB concentrations were modeled within prey items that inhabit the Reynolds Study Area. Risk from elevated "background" concentrations was not the objective of the ERA and is therefore not quantified in the ERA.

5.2.13 Comment: RMC expressed concern that toxicity data for the Little Brown Bat is extrapolated from other species.

Response: An objective of an ERA is to evaluate risks to a variety of different feeding guilds and trophic levels, not just to those species where toxicity data may be available. Unfortunately, toxicity data for most wildlife species is currently unavailable. Therefore, extrapolation from other species (usually laboratory species) becomes necessary.

5.2.14 Comment: RMC expressed concern that limited data on environmental media were used.

Response: All available information was used to characterize risk within the ERA. Due to a variety of factors (including time and cost), risk assessments are often based on limited sample data.

5.2.15 Comment: RMC claims that fish whole body rather than fillet data should have been used in the ecological assessment. RMC suggests that a more rigorous study be conducted to formulate more specific conclusions regarding fish contamination.

Response: Fish whole body concentrations of PCBs from spot tail shiners were used to assess risk to piscivorous avian species (king fisher and bittern). Fillet data was converted to whole body concentrations to assess risk to the mink since whole body data regarding PCB

concentrations were unavailable. Using an alternative conversion factor suggested by Sloan (NYSDEC) also results in elevated whole body PCB concentrations that present a risk to piscivorous mammals. It is unlikely that additional studies would affect the conclusions of the ERA that existing fish PCB concentrations present a risk to piscivorous wildlife.

5.2.16 Comment: RMC states that the limitations and uncertainties associated with the exposure and risk assessments are not expressed except in the Limitations Section. These limitations include the limited amount of data, the conservative estimates of exposure to birds and fish, and the extrapolations from other species.

Response: The ERA is consistent with previous risk assessments conducted by EPA. Uncertainties associated with the risk assessment are discussed in the Risk Characterization portion of the ERA.

5.2.17 Comment: EPA's cleanup levels are inconsistent with actual risk levels at the Site. RMC's risk assessment demonstrates that a more realistic risk-based cleanup level should be in the range of up to three orders of magnitude greater than EPA's.

In addition, the Proposed Plan indicates that proper implementation of all alternatives would result in acceptable risks. Therefore, EPA's selected remedy amounts to a higher cost for no extra safety. EPA has not properly examined cost versus benefit in choosing the remedial alternative. If EPA's 10^{-4} risk level is accurate, it would correspond to a 10 ppm cleanup level. The estimated volume of sediments above 10 ppm would be significantly less than the volume above EPA's proposed cleanup criteria of 1 ppm, which equates to a significant reduction in remediation costs.

Response: The 1×10^{-5} cancer risk discussed on page 8, paragraph 1 of the Proposed Plan, was calculated based on assumed ingestion of contaminated sediments by fishermen. In response to this comment, EPA has re-evaluated the site cleanup levels based on the most likely scenario for contaminant exposure, which is based on ingestion of contaminated fish by local residents. Under this scenario and based on reasonable worst-case assumptions, a 1 ppm PCB level in sediments would equate to a cancer risk on the order of 10^{-4} .

The 1 ppm PCB cleanup level is identical to that selected by EPA for contaminated sediment associated with the G.M. Site which is immediately downstream of the RMC facility. For the G.M. Site, EPA estimated that a 1 ppm PCB cleanup level in sediments is associated with a 10^{-4} (1 in 10,000) excess cancer risk to humans. For the RMC Study Area Site, EPA estimates that a 1 ppm PCB cleanup level in sediments is associated with an excess cancer risk to humans on the order of 10^{-4} (1 in 10,000). There is a variation in estimated residual cancer risks between the G.M. and RMC Study Area Sites due to uncertainties associated with estimating the effect of varying sediment PCB concentrations on area fish.

It should be noted that federal and New York State sediment quality criteria guidance indicate that PCB cleanup levels well below 1 ppm are required to achieve protection of the environment since PCBs pose a significant ecological risk. While EPA would prefer a lower cleanup level which would be associated with a 10^{-6} cancer risk, EPA has significant

concerns as to the technical practicability of achieving a PCB cleanup level below 1 ppm in this area of the St. Lawrence River. In selecting the 1 ppm cleanup goal, EPA has balanced its desire for a very low cleanup level which will minimize residual risk with the constraints posed by the limitations of dredging as a means of removing sediment with the further intent of selecting treatment as a principal element over containment. EPA believes that a 1 ppm cleanup goal in the St. Lawrence River provides an acceptable measure of protection of human health.

5.2.18 Comment: RMC opposes the 10 ppm PCB treatment level for dredged contaminated sediments. Since dredged materials would be managed on-site, EPA's 10 ppm PCB treatment level is inconsistent and excessive when compared to the on-site waste management approach outlined in NYSDEC's Record of Decision, which requires a 25 ppm PCB treatment level for North Yard soils.

In addition, EPA's 10 ppm PCB treatment level is overly conservative with respect to the Toxic Substances Control Act (TSCA) ARAR, which requires that PCB-contaminated sediments greater than 50 ppm be either incinerated, disposed of in a chemical waste landfill, or disposed of by another EPA approved method. Sediments with greater than 500 ppm PCBs may have to be treated, but disposal in a landfill may be approved by the EPA Regional Administrator.

Treatment of sediments with greater than 500 ppm PCBs is consistent with the approach presented for Alternative J. Treatment of sediments with less than 500 ppm is not cost effective and would not result in real risk reductions.

Response: EPA has determined that a 25 ppm PCB treatment level is consistent with the State's on-site waste management approach. Accordingly, EPA's selected remedy for the Reynolds Study Area includes a 25 ppm PCB treatment level, rather than the 10 ppm level in its Proposed Plan.

However, EPA does not agree that a 500 ppm PCB treatment level is appropriate for dredged contaminated sediments. Contaminated sediments represent the principal threat in the Reynolds Study Area. In accordance with CERCLA and the NCP, generally EPA's goal is to permanently treat principal threats whenever possible. EPA generally uses containment for less contaminated material. Accordingly, EPA has determined that a 25 ppm PCB treatment threshold results in treatment of the most highly contaminated sediments. In addition, EPA has determined that sediments with PCB concentrations below 25 ppm may be disposed of with a minimum of long-term maintenance.

The selected remedy is cost-effective because it has been demonstrated to provide overall effectiveness proportional to its costs. The present worth cost of the selected alternative, Alternative G(A), which includes a 25 ppm treatment threshold, is \$ 35.1 million. The present worth cost of Alternative G(B), which includes a 10 ppm treatment threshold, is \$ 36.7 million. The present worth cost of Alternative I(A), which incorporates a 500 ppm treatment threshold, is \$ 35.8 million. The present worth cost of Alternative I(B), which incorporates a 50 ppm treatment threshold, is \$ 37.9 million. Thus, EPA has selected the least expensive alternative which provides for permanent removal and treatment of the majority of the principal threat

posed by contaminated sediments. In addition, a comparison of the costs of Alternatives G(A), I(A), and I(B) demonstrates that it is more expensive to construct a landfill for disposal of sediments with PCB concentrations between 25 and 500 ppm than it is to treat such sediments. Therefore, Alternative G(A) is more cost-effective than Alternative I.

5.2.19 Comment: The Proposed Plan does not adequately characterize the problems associated with dredging with regard to the NCP-specified criteria of short-term effectiveness and implementability. Dredging poses significant short-term risks due to suspension and migration of contaminated sediments. Silt curtains are not effective in preventing redeposition at the point of dredging, and their ability to control suspension and migration of sediments is questionable. EPA's proposed remedy would result in the greatest short-term impacts, whereas alternatives requiring less dredging (Alternative J) would have less short-term impacts. In addition, the current in the Reynolds Study Area may carry the resuspended sediment towards the center of the river, where higher currents would carry and redeposit the contaminants downstream.

Furthermore, EPA's recommended cleanup level of 1 ppm is not likely to be achievable using available dredging technology, even with multiple passes. Irregularities of the river bed (e.g., variable slopes, thick vegetation, and boulders) will severely impact the ability of dredging equipment to meet the remedial goals. For this reason, Alternative J, which incorporates a combination of dredging to 500 ppm and containment of the other areas, is more implementable.

Response: Please see EPA's response to comment 4.4.1.

After carefully balancing the specific characteristics of the Site against the nine criteria as outlined in the NCP, EPA has determined that the long-term effectiveness and permanence afforded by the selected alternative off-set any short-term risks posed by the selected alternative and the higher costs of the selected remedy. EPA recognizes that there may be some difficulties associated with the suspension of contaminants during dredging. However, dredging has been used effectively at another Superfund site in New Bedford Harbor, Massachusetts, to remove PCB-contaminated sediments from an estuary.

There are several factors which EPA believes will contribute to the effectiveness of dredging as a means of removing sediment with PCB concentrations above 1 ppm from this area of the St. Lawrence River. First, the area to be dredged is fairly shallow and is located adjacent to the shore of the St. Lawrence River. Second, the use of engineering controls such as sheet pile walls has been shown to substantially reduce sediment suspension. Third, the selection of the dredging technique (e.g., a hydraulic dredge), can be made with the goal of minimizing sediment suspension. Fourth, the public health and environmental impacts resulting from sediment dredging (which are of relatively short duration) are lower than the current long-term risks posed by the contaminated sediment. Finally, in the event that monitoring indicates that there are any downstream depositional areas which collect resuspended sediments, they can be dredged to remove those resuspended sediments. The iterative process of sampling, excavating and re-sampling is contemplated as an integral part of the remedial action.

5.2.20 Comment: RMC opposes EPA's method of evaluation in the Proposed Plan. To ensure an appropriate balance of costs and risk reductions, EPA should have given greater consideration to other alternatives (beyond Alternative J) involving combinations of dredging and in-situ containment. In addition, the Proposed Plan does not indicate the uncertainties of the sediment volume estimates, which were obtained from the AA report. Also, EPA has biased the costs for its preferred alternative to the low side by issuing its preferred alternative without inclusion of a landfill, despite the fact that all other alternatives with some treatment include a landfill. Finally, since ATP is a proprietary process, the Proposed Plan should refer to the generic process name "thermal desorption" instead.

Response: EPA's selected alternative does not involve a combination of dredging and containment. EPA's selected alternative involves dredging and treatment of dredged/excavated material with PCB concentrations above 25 ppm by thermal desorption. Untreated sediments (with PCB concentrations between 1 ppm and 25 ppm) and treatment residuals (which are expected to be non-hazardous and to have PCB concentrations below 10 ppm) will be disposed on-site, in the Black Mud Pond, and covered. EPA's selected remedy provides for permanent removal and treatment of contaminated sediments. However, in its Proposed Plan, EPA recognized the potential difficulties of dredging to 1 ppm, and allowed for contingency cleanup activities, such as in-situ containment, in the event that the cleanup levels cannot be achieved. Although containment of contamination is less difficult than excavation or dredging and treatment of contamination, EPA prefers technologies in which treatment that permanently and significantly reduces the volume, toxicity or mobility of the PCBs is a principal element. Further, there are questions as to the long-term reliability of in-situ containment at this site.

Regarding the volume estimates in its Proposed Plan, EPA presented a rough approximation of the area which must be addressed to meet these cleanup goals. Prior to dredging, additional sediment and surface water sampling will be conducted to better delineate the extent of the area to be dredged and to serve as baseline monitoring data.

EPA did not bias the costs for its selected alternative. All of the alternatives involving thermal desorption treatment to 25 ppm PCBs, including EPA's selected alternative, allowed for disposal of treated materials with a soil cover, unless tested and found hazardous, in which case EPA included costs for an engineered landfill. The remedial alternatives developed for the Site are consistent with EPA's PCB Guidance. For instance, according to this guidance, soils with PCB concentrations in the 10 to 25 ppm range may be disposed on an industrial facility with minimal long-term management controls. Accordingly, EPA has evaluated an alternative for the RMC Site which includes disposal of sediments with PCB concentrations between 10 and 25 ppm in the Black Mud Pond, rather than in an engineered landfill (Alternative G). The PCB Guidance also recommends that soils with higher concentrations of PCBs be disposed at an industrial facility in an engineered containment system which may include a cover and liner system. Accordingly, EPA has evaluated alternatives which include disposal of untreated sediments (Alternative D) or treated sediments with PCB concentrations between 50 and 500 ppm in an engineered landfill (Alternative I). In addition, several of the other alternatives evaluated (including Alternatives E, F, and J) include options for disposal in the Black Mud Pond or in an engineered landfill depending on whether the material is a hazardous waste.

Finally, EPA acknowledges that ATP is a proprietary process whose generic process name is thermal desorption. However, EPA took its information directly from the AA report, which was prepared by RMC. EPA notes the comment and acknowledges that the thermal desorption system to be used at the Site may not be limited to ATP.

5.2.21 Comment: In-situ containment presents a lower overall short-term risk to humans and the environment compared to dredging, and provides equivalent long-term protection. RMC cites prior in-situ containment successes for PCBs around the country; the U.S. Army Corp of Engineers' extensive work evaluating in-situ containment; and the conservative containment design proposed by RMC. Mass transfer models show that the time for the contaminants to migrate to the surface of the containment material would take hundreds and perhaps thousands of years, during which time the containment material would facilitate natural biodegradation of PCBs. State of the art geotechnical materials and techniques, such as concrete revetment and geotextile material and webbing, would ensure the isolation of the contaminated sediments from the river environment.

Implementation of in-situ containment would include an extensive, long-term monitoring program to ensure the integrity of the containment material. RMC notes EPA's concern in the Proposed Plan that monitoring of in-situ containment would be more difficult than monitoring in upland areas. The Proposed Plan disregards the fact that sophisticated subaqueous monitoring capabilities are available.

Response: Please see EPA's response to comment 4.1.12.

5.2.22 Comment: Alternative J fulfills the requirements of the NCP better than EPA's proposed alternative, which may be technically infeasible, have greater adverse short-term impacts, take longer to implement, and cost more without being proportionally more effective. As stated in the Proposed Plan, Alternative J would be protective of human health and the environment; comply with ARARs; provide a higher degree of permanence than the strictly containment alternatives; reduce toxicity, mobility and volume of the contaminated sediments; have less short-term impacts; and is more implementable than EPA's proposed alternative.

Response: EPA recognizes that several of the remedial alternatives evaluated pose fewer short-term risks than the remedial alternative selected by EPA. After carefully balancing the specific characteristics of the Site against the nine criteria as outlined in the NCP, EPA has determined that the long-term effectiveness, permanence, and protectiveness of public health and the environment afforded by the selected alternative offset any short-term risks posed by the selected alternative.

5.2.23 Comment: Based on the hydrodynamic data collected to date, the contamination detected in the mouth of the Grasse River is not attributable to the RMC plant. Similarly, it is likely that sediment contamination detected between the Grasse River and the RMC outfall area is not attributable to RMC. The Proposed Plan calls for additional sampling in these upriver areas to determine if dredging is necessary. While these areas were included in the Reynolds Study Area, they should not be included in the proposed area of RMC remediation.

Response: EPA's remedial strategy in the Massena area was developed with the goal of achieving a comprehensive remediation of areas of the St. Lawrence, Grasse, and Raquette Rivers which were affected by contamination from the ALCOA, G.M. and RMC facilities. To this end, EPA, in its Unilateral Administrative Orders, defined areas, known as the ALCOA and Reynolds Study Areas, which were to be investigated and, if necessary, remediated by each industry.

EPA does not agree that the hydrodynamic data collected to date demonstrates conclusively that any contamination in the mouth of the Grasse River and between the Grasse River and the RMC outfall is not attributable to RMC. Therefore, prior to dredging, additional sediment and surface water sampling will be conducted to better delineate the extent of the area to be dredged and to serve as baseline monitoring data.

5.2.24 Comment: RMC claims that the EPA slope factor for PCBs used by TRC Environmental Corporation (contractor to EPA for the risk assessment) to estimate carcinogenic risk significantly overestimates the upper-bound risks associated with exposure to PCBs. RMC states that EPA's calculation of this slope factor does not incorporate current toxicological information regarding the tumorigenic potency of different PCB mixtures (Aroclors). In addition, RMC states that the model and scaling factor used to extrapolate between animal studies and potential human effects are inappropriately applied for PCBs. RMC suggests the use of alternative slope factors, including an alternative slope factor for the predominant Aroclor in river sediments, Aroclor 1242, of 0.2 kg-day/mg, more than 38 times lower than the slope factor used in the draft risk assessment.

Response: The uncertainties associated with the use of the currently available slope factor for PCBs are recognized in the risk assessment. EPA also recognizes that PCB congeners may vary as to their potency in producing biological effects and that there is some evidence that mixtures containing more highly chlorinated biphenyls are more potent inducers of hepatocellular carcinoma in rats than mixtures containing less chlorine by weight (IRIS, 1993/Kimbrough, 1987 and Schaeffer et al., 1984). However, EPA has not currently adopted guidance which evaluates the toxic equivalents for various PCB congeners. In addition, EPA is currently reviewing but has not adopted the cross species scaling factor for carcinogenic risk assessment (daily amount administered per unit of body mass raised to the 3/4 power, i.e., $\text{mg/kg}^{3/4} (\text{day})$ (EPA, 1992)). The risk assessment was prepared in accordance with the most current EPA Superfund guidance and IRIS which assumes Aroclor 1260 is representative of all PCB mixtures. IRIS toxicity values are based on the consensus of various EPA Work Groups. These Work Groups are continually reviewing toxicity information as it becomes available and updating toxicity values to minimize uncertainties associated with the estimation of risks to human health.

If carcinogenic risks were recalculated using the proposed slope factors, risks associated with sediment exposures would still be greater than 10^{-4} (4.1×10^{-4}) for PCBs. While the difference between the TRC risk estimates and this recalculated value is nearly one order of magnitude, risks associated with PCB contaminated fish show a lesser degree of difference when applying the RMC proposed slope factors. The predominant Aroclors in fish (Yellow Perch) collected by RMC in the study area are 1254 and 1260. Therefore, carcinogenic risk estimates would only be reduced by approximately two to four times with the application of

the proposed slope factors.

5.2.25 Comment: RMC claims that the exposure assumptions in the draft human risk assessment are unreasonably conservative and result in an overestimation of risk. These assumptions include a lifetime (70-year) exposure duration and an exposure frequency of 39 weeks per year for residents and 50 weeks per year for fishermen. RMC states that most householders in the United States do not reside at the same location for an entire lifetime, and that due to the cold climate in the study area, most people would not be exposed to sediment contamination for as long as 39 weeks per year. In addition, RMC commented that the rates of ingestion of contaminated sediment and fish tissue were greatly overestimated. RMC recommends a sediment ingestion rate of 59 mg/day and 43 mg/day for children and adults, respectively, as compared to the values of 200 mg/day and 100 mg/day used in the risk assessment. Lastly, RMC claims that dermal contact exposure assumptions related to sediment exposures are also overestimated.

Response: In determining exposure parameters utilized in a risk assessment, EPA strives to obtain site-specific data instead of relying on standard default values. Representatives of the St. Regis Mohawk Tribe were interviewed to learn about fishing habits on the St. Lawrence and Raquette Rivers in the vicinity of RMC. These interviews revealed that some families continue the traditional consumption of locally caught fish as their primary diet and that Mohawk fishermen fish year round.

No site-specific data were available pertaining to fish ingestion rates; therefore, the EPA default value for subsistence exposures was used (i.e., 132 grams/day) (EPA, 1989a). This value assumes that fish consumption would be approximately equivalent to the average consumption of red meat; fish consumption might be expected to be even higher if one assumes fish is consumed at levels equal to the combined average of red meat, poultry, and fish/shellfish (i.e., 180 grams/day) (EPA, 1989b). In addition, since the development of the RMC risk assessment, the results of a 1992 New York State Department of Health (NYSDOH) survey of fish consumption by Mohawk women have been released. The NYSDOH study indicates a fish ingestion rate of 200 grams/day (NYSDOH, 1992).

The assumption that the local population resides in the same location for 70 years also is a site-specific value obtained through interviews with the Mohawk Tribe; it is not unlikely for members of the Mohawk Tribe to remain on the reservation for a lifetime according to Mr. Jock, St. Regis Mohawk Tribe Environmental Program.

Sediment exposure rates are conservative but considered realistic. EPA recognized that fishermen arms and hands may not be exposed during the colder months of the year, due to the use of protective clothing. However, exposure may increase during warmer months since greater areas of bare skin may be exposed (e.g., torso and legs). Therefore, assuming sediment exposure to arms and hands year round is not considered an overestimate of risk. The seasonal differences in exposures are assumed to balance using this assumption.

The values used are upper bound values for soil and dust ingestion. However, in the absence of currently EPA-approved values for sediment ingestion, the standard default values

of 200 mg/kg (child) and 100 mg/kg (adult) were used. Note that risk values would decrease by less than an order of magnitude using the RMC's suggested ingestion rate.

5.2.26 Comment: Since individual sample data were not provided in the baseline risk assessment report, RMC questions whether appropriate statistical methods were used to calculate media concentrations of contaminants. Specifically, RMC questions the assumption that the data were distributed log normally.

Response: Normality tests were performed by TRC to determine the distribution of the data. Data evaluated were selected based on sample size and detection frequency within a sample group. TRC analyzed sediment data in the study area (Aroclor 1242, chrysene, and benzo(6) fluoranthene) and preferred fish species in the Reynolds Study Area (PCBs). The normality tests reveal that the data are distributed log normally.

5.2.27 Comment: RMC states that the baseline risk assessment does not include an adequate quantitative analysis of uncertainty. RMC suggests the use of a quantitative method such as the Monte Carlo simulation to provide more meaningful information regarding potential risk. RMC reports that for sediment ingestion by fishermen, such a simulation results in lifetime cancer risk values considerably lower than those calculated from the reasonable maximum exposure (RME) in the baseline risk assessment.

Response: EPA currently requires the incorporation of a central tendency analysis in the uncertainty analysis of a risk assessment. Risk assessors are requested to calculate risks for the pathway generating the greatest risk using average (50th percentile) parameters (e.g., ingestion rates, exposure duration). This exercise was performed as part of the Reynolds risk assessment. Nearly an order of magnitude difference in carcinogenic risks and a three-fold difference in total noncarcinogenic Hazard Indices were observed. The Monte Carlo simulation proposed and presented by RMC provides a risk probability distribution which presents additional information. However, unless site-specific conditions warrant such an approach, generally EPA has not adopted the Monte Carlo approach for Superfund risk assessments.

5.2.28 Comment: RMC reports a number of inconsistencies among reported data and ambiguously presented material in the baseline risk assessment. Concerns include minor discrepancies between text and appendix tables and confusion pertaining to the fish samples utilized in the quantitative risk assessment.

Response: Necessary changes were incorporated into the Final Risk Assessment to address RMC's concerns.

5.3 St. Regis Mohawk Tribe

The comments summarized in this section were received from the St. Regis Mohawk Tribe Environment Division.

5.3.1 Comment: The PCB cleanup level of 1 ppm will not adequately protect human health or the environment due to risks from residual contamination.

Response: Please see EPA's response to comment 4.3.1.

5.3.2 Comment: EPA's investigation collected only 13 samples from an approximately 2000 x 400 foot stretch of the Raquette River. This number of samples is inadequate to provide the basis of a remedial decision. The samples were taken in or near the main current area, rather than from bends or banks that accumulate PCB-contaminated sediments. In addition, the detection of PCBs well above detection limits in surface water sample W5-1 should be viewed as evidence of potential contamination rather than a "false positive" or "anomaly." Therefore, the Tribe recommends additional sampling of the Raquette River system, including samples from: the river; any areas of obvious sediment accumulation; sediments at the mouths of both tributaries; and supplemental fish sampling.

Response: Of the 17 sediment samples and three water samples taken in the Raquette River, only one, water sample W5-1, showed PCB contamination (2.3 ppb). Location W5-1 is a background station located upstream of the two tributaries that enter the Raquette River from the RMC Site. Therefore, this reported concentration is believed to be a laboratory false positive. However, in responding to this comment, RMC is currently collecting additional biota data from the Raquette River.

Samples taken in the Raquette River were from areas agreed upon by the Tribe during the work planning process. Sediment sampling in the Raquette River included samples taken adjacent to both banks of the river and in depositional areas.

5.3.3 Comment: Noting that thermal desorption may be ineffective on cyanide and heavy metal removal, the Tribe states that EPA's plans for disposal of treated sediments and the necessity for a landfill will depend on the residual sediment contamination levels following treatment.

Response: Please see EPA's response to comment 4.1.3.

5.3.4 Comment: Contamination upstream of the Site should be studied further. Upstream detections may have originated from RMC, due to a substantial westward current along the south shore from RMC towards the Snell Lock. PCB levels were detected in water samples at the most western drainage ditch to the St. Lawrence River. Further investigation should extend to the cove at outfalls 002/003, given the disparity between the sediment contaminant levels reported by RMC and the higher levels found by the NYSDEC Wildlife Pathology

Laboratory.

Response: EPA's selected remedy provides for additional sampling to better delineate the extent of the area to be dredged. Such sampling will include the upriver portion of the Reynolds Study Area, especially in reach 3A in the vicinity of sample A9 and near the mouth of the Grasse River, to determine whether dredging is warranted in these areas.

5.3.5 Comment: The contamination extending northeast to the channel off Survey Marker #9 (Figure 9, WCC 1991) may indicate a reason to sample bottom sediments in the channel itself downstream of this area.

Response: Previous hydrodynamic studies indicate that the amount of sediment in the channel is extremely limited. Further, data indicate that PCB concentrations decrease rapidly away from the RMC outfalls.

5.3.6 Comment: It is unclear how EPA derived the volume of sediments above 1 ppm PCBs in the Reynolds Study Area. There appears to be a discrepancy between the ARS report, which estimates a volume of 74,000 cubic yards, and the Proposed Plan, which estimates a volume of 51,000 cubic yards. EPA may be scaling down the amount of contaminated sediments to be dredged without looking at the risks to the environment.

Response: The sediment volume estimates were modified in the AA report. EPA believes that the volume of contaminated sediments was inflated, resulting in an overly conservative and expensive estimate of remediation costs. In modifying the sediment volume estimates, EPA instructed RMC to exclude sediment from the area adjacent to sampling point A9, pending the results of additional sampling. EPA's selected remedy provides for additional sampling in the upriver portion of the Reynolds Study Area, especially in reach 3A in the vicinity of sample A9 and near the mouth of the Grasse River, to determine whether dredging is warranted in these areas.

5.4 New York State Department of Environmental Conservation (NYSDEC)

The comments summarized below were received from NYSDEC.

5.4.1 Comment: While NYSDEC accepts EPA's proposed cleanup level of 1 ppm PCBs, NYSDEC encourages RMC to eliminate as much residual contamination as possible by pursuing the lowest cleanup level that is feasible under existing conditions. This is in RMC's best interest since the State will pursue monetary damages against RMC and others for natural resources damages resulting from residual risks after remediation.

Response: No response necessary.

5.4.2 Comment: EPA's disposal alternative for treatment residuals and untreated sediments is inadequate given the significant concentrations of metals, at levels which exceed NYSDEC soil cleanup standards, that would remain following treatment. The disposal area would need additional containment controls, such as a liner and enhanced cap.

NYSDEC suggests that EPA utilize the Black Mud Pond on the RMC facility for disposal of treated residuals and untreated sediments. NYSDEC's Record of Decision called for capping and groundwater monitoring of the Black Mud Pond. There may be adequate volume available to accommodate the treated residuals and untreated sediments for use as fill in order to bring the Black Mud Pond up to proper grade for effective capping. The Black Mud Pond inorganic contaminants are similar to those found in the St. Lawrence River sediments. Utilizing Black Mud Pond would consolidate similar contaminants into one area while realizing cost savings related to eliminating construction, maintenance and monitoring of a new disposal area, and substantially reducing the volume of fill material needed for the Black Mud Pond.

Response: EPA agrees. Please see EPA's response to comment 4.1.3.

5.4.3 Comment: EPA's decision for sediment treatment is based on the level of PCBs, PAHs and TDBFs. However, the sediments may contain other Site contaminants which would qualify the material as hazardous. NYSDEC suggests that untreated sediments be tested for hazardous waste characteristics and evaluated as to whether they constitute listed hazardous wastes.

Response: Untreated sediments (i.e., sediments in their current state) were tested during the ARS and were determined to be non-hazardous. These materials will be tested again prior to disposal. However, based on the results of ARS testing, EPA does not anticipate that they will be hazardous.

5.4.4 Comment: NYSDEC recommends that sheet piling be installed around the dredging area to improve the effectiveness of the silt curtains in minimizing sediment suspension during dredging. EPA requires such controls at the nearby G.M. Site.

Response: During remedial design, EPA will consider the installation of sheet piling as well as other techniques to control migration of resuspended sediments during dredging.

5.4.5 Comment: The Proposed Plan should state that all water removed from sediments or generated during the treatment process will be discharged to the St. Lawrence River in compliance with the terms of RMC's State Pollution Discharge Elimination System (SPDES) permit and any other binding requirements between Reynolds and New York State.

Response: As stated in the decision document, all water that is removed from sediments or generated during the treatment process would be discharged to the St. Lawrence River in compliance with substantive SPDES requirements.

5.5 Canadian Review Panel
(Comprised of Environment Canada, Health and Welfare Canada and the Ontario Ministry of Environment and Energy)

The comments summarized below were received from the Canadian Review Panel.

5.5.1 Comment: The ARS underestimated the extent and degree of contamination in the St. Lawrence River. Specifically, the high analytical detection limits and the lack of information on both biological uptake and distribution of other contaminants (PAHs, TDBF, aluminum, cyanide, and fluoride) were noted. The assumption that the distribution patterns for all contaminants are the same is not adequately supported in the background documents. In addition, contaminants other than PCBs may not be removed adequately using EPA's proposed alternative. There is a risk of water column contamination with cyanide, aluminum and fluoride during remediation. More elutriate testing is needed to evaluate the threat of aluminum and cyanide, which exceeded guidelines.

Finally, the evaluation of sediment quality in the Raquette River may be inaccurate because the sampling was conducted in zones prone to erosion rather than depositional zones.

Response: EPA mapped the areas where PCBs, PAHs and TDBFs were found in order to determine the area of contamination to be removed. EPA's decision for remediation of the Reynolds Study Area is based on sampling data taken during the ARS, and on knowledge of RMC's past disposal practices in that area. EPA believes that it has sufficient information upon which to base its remedial decision for the Reynolds Study Area. EPA agrees that more elutriate testing is needed to evaluate the threat of aluminum and cyanide.

With regard to the Raquette River, please see EPA's response to comment 5.3.2.

5.5.2 Comment: The review panel supports EPA's proposed cleanup level of 1 ppm PCBs. The dredging zones should be well delineated before initiation of dredging because the dredging operation will mix contaminated and non-contaminated sediment, thereby reducing the concentrations. Cleanup strategies should include removal of other contaminants (e.g., PAHs, metals) to below guideline levels.

Response: Prior to dredging, additional sediment and surface water sampling will be conducted to better delineate the extent of the area to be dredged and to serve as baseline monitoring data. In regard to EPA's cleanup strategy, based on the results of its risk assessment, EPA has established cleanup levels for contaminated sediment in the Reynolds Study Area which are protective of human health and the environment. The cleanup levels for PCBs, PAHs, and TDBFs will also remove the threat from other contaminants such as cyanide and fluoride since these contaminants are found within the area that is planned for remediation.

5.5.3 Comment: The review panel expressed concern about the potential for suspension and downstream transport of contaminated sediment during dredging, and questioned the reliability of silt curtains to prevent transport of water-borne contaminants, dissolved metals, and fine particles. The review panel recommends that a pilot scale dredging project be implemented, and a contingency plan put in place, prior to full-scale dredging. Canadian input to the contingency plan is requested. The review panel also recommends that other technologies (e.g., modified bucket dredge) be investigated as they may prove to cause less sediment suspension than the mudcat and cutter head dredges proposed in the AA report.

The AA report proposal that the remaining sediments (PCB sediments less than 500 ppm) will be left in place and capped with a sand layer (18 inches thick) may provide inadequate chemical isolation, and should be thicker.

Response: After carefully balancing the specific characteristics of the Site against the nine criteria as outlined in the NCP, EPA has determined that the long-term effectiveness and permanence afforded by the selected alternative off-set any short-term risks posed by the selected alternative and the higher costs of the selected remedy. EPA recognizes that there may be some difficulties associated with the suspension of contaminants during dredging. However, dredging has been used effectively at another Superfund site in New Bedford Harbor, Massachusetts, to remove PCB-contaminated sediments from an estuary.

EPA is sensitive to concerns regarding the implementation of dredging. Therefore, an initial dredging program will be conducted in a manner which will identify site-specific information and operating parameters such as dredging rates and depths, sediment removal efficiencies, silt curtains and sheet piling effectiveness, sediment dewatering methods, and sediment suspension and settling characteristics. This information will be evaluated and used as appropriate in modifying operating procedures to improve the effectiveness of the removal program.

There are several factors which EPA believes will contribute to the effectiveness of dredging as a means of removing sediment from the St. Lawrence River. First, the area to be dredged is fairly shallow and is located adjacent to the shore of the St. Lawrence River. Second, the use of engineering controls such as sheet pile walls has been shown to substantially reduce sediment suspension. Third, the selection of the dredging technique (e.g., a hydraulic dredge), can be made with the goal of minimizing sediment suspension. Fourth, the public health and environmental impacts resulting from sediment dredging (which are of relatively short duration) are likely to be lower than the current risks posed by the contaminated sediment. Finally, in the event that monitoring indicates that there are any downstream depositional areas which collect resuspended sediments, they can be dredged to remove those resuspended sediments. The iterative process of sampling, excavating and re-sampling is contemplated as an integral part of the remedial action.

In regards to the thickness of the in-situ containment material: the proposal in the AA report was developed by RMC's consultant and represents RMC's proposal, not EPA's. EPA's selected alternative does not include in-situ containment. In-situ containment would only be considered if technical constraints make it impracticable to dredge the sediments sufficiently to achieve the Site's cleanup levels.

Canadian input will be sought during design of the dredging monitoring program.

5.5.4 Comment: Since thermal desorption treatment will not remove inorganics and has not been evaluated for TDBFs, the review panel recommends that soil washing or some form of volume reduction be considered as a preliminary treatment step. The review panel also requests more information on the commercial incinerator that will be used.

Response: Thermal desorption will remove organic compounds, such as PCBs, PAHs and TDBFs, from the sediments, but will not remove the inorganic compounds, such as aluminum, cyanide and fluoride. Treated sediment and the remaining untreated sediments will be disposed in the Black Mud Pond on the RMC facility. EPA does not anticipate that the treated sediments will be hazardous waste.

In addition, contaminants condensed in the thermal desorption process would be transported off-site and burned at a commercial incinerator. Information regarding the location and type of commercial incinerator will be developed during remedial design.

5.5.5 Comment: The review panel recommends additional measures for the disposal of treatment residuals and untreated sediments, such as a leachate collection system and regular monitoring program. Treated sediments should be tested for residual contaminants.

Response: Please see EPA's response to comment 4.1.3.

5.5.6 Comment: The review panel recommends implementation of a monitoring plan that allows for continuous monitoring during dredging, stringent controls, minimization of dredge material losses and suspension at the dredge site. Implementation of health and safety plans that would decrease the short-term risks to downstream users of the river are also recommended.

Environment Canada would require monitoring of emissions from the thermal desorption system for organics, conventionals (e.g., metals), and proper operation (e.g., temperature, oxygen). The review panel prefers that ambient air monitoring be conducted at the perimeter of the excavation/treatment site for the same parameters. The review panel also requests the opportunity to review and comment on the thermal desorption permit application to ensure that there are adequate monitoring programs and emissions controls in place.

The review panel recommends continuous monitoring (at least every three months) and regular maintenance of the disposal area.

Response: EPA employs stringent environmental controls when implementing remediation at Superfund sites. EPA's selected remedy includes development of a dredging monitoring plan to provide for sampling during dredging in order to measure any environmental impacts. It will also include a contingency plan which will describe measures to control and/or minimize the impacts of dredging on the environment. During dredging, EPA will monitor the river, using such techniques as turbidity analysis, to determine if there is any increase of sediment

suspension. If monitoring shows an increase in sediment suspension, then EPA will discontinue dredging and reevaluate that option. In addition, in the event that monitoring indicates that there are any downstream depositional areas which collect resuspended sediment, those areas can be dredged to remove the resuspended sediment. The iterative process of sampling, excavation, and resampling is contemplated as an integral part of the remedial action.

Emissions from the thermal desorption system will comply with all federal and State air emissions requirements. In addition, groundwater downgradient of the disposal area (Black Mud Pond) will be monitored and the cover will be maintained. Because this alternative would result in contaminants remaining on-site above health-based levels, CERCLA requires that the Site be reviewed at least once every five years. If justified by the review, remedial actions may be implemented to remove or treat the wastes.

The Canadian government is not afforded the same rights as States in the Superfund process. However, EPA has sought Canadian government input in the Superfund process for this Site in the past and is committed to seeking Canadian input on monitoring of remedial actions in the future.

5.6 Cornwall Environmental Resource Center (CERC)

The comments summarized in this section were received from CERC.¹

5.6.1 Comment: CERC finds the EPA excess cancer risk to Canadians of 1 in 100,000 to be totally unacceptable. U.S. health risk calculations and standards indicate that more than 25 Canadians will continue to face excess carcinogenic risk resulting from inadequate EPA cleanup levels.

Response: The NCP mandates EPA to establish cleanup goals that are consistent with risk estimates between 10^{-4} and 10^{-6} .

5.6.2 Comment: CERC expressed concern about the concentrations of PCBs, PAHs, and aluminum in both the surface water and sediments near the RMC facility. The contamination in the Reynolds Study Area provides justification for a thorough examination of contamination in Canadian aquatic areas.

Response: EPA's intention in developing its remedial plans in the Massena area is to address hotspots of contamination in the St. Lawrence River adjacent to the outfalls of the major Massena industries. EPA does not intend to perform a detailed investigation of Canadian waters in part because contaminants may be entering the system from sources other than the Massena industries.

5.6.3 Comment: CERC recommends that all cleanup levels be consistent and uniform rather than contaminant-specific.

Response: Based on its risk assessment, EPA has established cleanup levels for contaminated sediment in the Reynolds Study Area which are protective of human health and the environment. The cleanup levels (e.g., 1 ppm for PCBs, 10 ppm for PAHs, and 1 ppb for TDBFs) are based on the toxicity of each contaminant.

5.6.4 Comment: Canadian ARARs were not sought prior to development of EPA's Proposed Plan. CERC requests that all further actions related to EPA's Proposed Plan be discontinued until such time as Canadian ARARs have been taken into consideration.

Response: EPA recognizes the potential impacts of the Site on Canadian citizens and has, within the constraints of the Superfund regulations, endeavored to involve all interested Canadian citizens and local officials, as well as their U.S. counterparts and members of the Mohawk nation, in its decision-making process. However, the Canadian government is not afforded the same rights as States in the Superfund process. However, EPA has sought Canadian government input in the Superfund process for this Site in the past and is committed to seeking Canadian input on monitoring of remedial actions in the future.

5.6.5 Comment: EPA's preferred alternative is unacceptable since it does not provide for the full protection of the Canadian people or the Canadian environment. EPA's preferred alternative only provides for partial treatment. The preferred alternative fails to provide adequate storage for the remaining contaminated residues since it only allows for a vegetated soil cover. When combined with the stored contaminants from the Black Mud Pond and North Yard, these would constitute a major ongoing environmental threat to the Canadian people and environment.

CERC prefers a modified version of Alternative F, which includes treatment of sediments containing levels higher than 1 ppm, and storage of materials below 1 ppm in earthquake proof vaults.

Response: Please see EPA's response to comment 4.1.3.

EPA notes that the Black Mud Pond will be capped in conformance with the requirements of the January 22, 1992 New York State Record of Decision.

5.6.6 Comment: No consideration has been given to the potential for seismic disturbances in this geographic location. In the past year (1992), there were two such disturbances having epicenters in the St. Lawrence River directly in front of the RMC facility. Any remaining sediments should be vaulted in a manner similar to that of the adjacent ALCOA facility.

Response: Under the Uniform Building Codes, the area around the St. Lawrence Seaway is classified as being in a Level III earthquake zone. Earthquakes in a Level III zone are described as causing potential major structural damage. As a result, any structure, including the Black Mud Pond cap, will be designed for earthquake loading. For example, design of any containment structure may include soil compaction to lessen the potential impacts of an earthquake.

In the event of an earthquake or other such catastrophe, EPA or NYSDEC will evaluate the containment system at the Site to determine whether it has been affected. If the containment system has been affected, RMC will repair it. It should be noted that surface structures, such as caps or covers, can be visually monitored following an earthquake and easily repaired.

5.6.7 Comment: CERC expressed concerns with potential suspension and migration of contaminants into the Canadian aquatic environment during dredging, and suggested building a coffer dam around the impaired area prior to commencing work.

Response: Please see EPA's responses to comments 4.1.6 and 5.4.4.

5.6.8 Comment: EPA, in its second from last paragraph in the Proposed Plan, has set the scene for possible avoidance of its responsibilities to complete the sediment cleanup in accordance with its prescribed plan.

Response: EPA's intention in the Proposed Plan was to acknowledge that there are potential problems associated with dredging this area of the St. Lawrence River. Therefore, an initial dredging program will be conducted in a manner which will identify site-specific information and operating parameters such as dredging rates and depths, sediment removal efficiencies, silt curtains and sheet piling effectiveness, sediment dewatering methods, and sediment suspension and settling characteristics. This information will be evaluated and used as appropriate in modifying operating procedures to improve the effectiveness of the removal program.

5.6.9 Comment: It is CERC's belief that EPA has avoided selecting a remedy of full clean-up due to the higher cost. CERC's position is that dollar costs must be secondary to the needs of the human health and environmental stability.

Response: The NCP requires that EPA balance all of the remedial alternatives evaluated in the AA according to the nine criteria defined in the NCP, including balancing overall effectiveness to cost to ensure that the remedy is cost effective.

The selected remedy is cost-effective because it has been demonstrated to provide overall effectiveness proportional to its costs. The present worth cost of the selected alternative, Alternative G(A), which includes a 25 ppm treatment threshold, is \$ 35.1 million. The present worth cost of Alternative G(B), which includes a 10 ppm treatment threshold, is \$ 36.7 million. The present worth cost of Alternative I(A), which incorporates a 500 ppm treatment threshold, is \$ 35.8 million. The present worth cost of Alternative I(B), which incorporates a 50 ppm treatment threshold, is \$ 37.9 million. Thus, EPA has selected the least expensive alternative which provides for permanent removal and treatment of the majority of the principal threat posed by contaminated sediments. In addition, a comparison of the costs of Alternatives G(A), I(A), and I(B) demonstrates that it is more expensive to construct a landfill for disposal of sediments with PCB concentrations between 25 and 500 ppm than it is to treat such sediments. Therefore, Alternative G(A) is more cost-effective than Alternative I.

5.7 Massena Industrial Development Corporation (MIDC)

The comments summarized below were received from the MIDC.

5.7.1 Comment: EPA's Proposed Plan should be put on hold until the public has had a chance to review the draft risk assessment.

Response: Please see EPA's response to comment 4.2.3.

5.7.2 Comment: MIDC requested answers to the following specific questions about the draft risk assessment, and/or a copy of the draft risk assessment:

- a. Does it take into account recent and current PCB toxicity research?
- b. What exposure durations and frequencies are used?
- c. Does it suggest children and adults will ingest sediments? If so, how much?
- d. Does it suggest that all fish consumed come only from the site in question, or from the general area?
- e. Is the assessment site-specific or based on regional data?

Response:

- a. The risk assessment, in accordance with current EPA risk guidance, applies toxicological data provided in IRIS.
- b. A fisherman is assumed to be exposed to sediments 350 days per year over the course of a lifetime. A local resident's exposure to sediments is assumed to be 143 and 78 days per year respectively for a child and an adult. Residents are assumed to live in the study area vicinity for 70 years. Mohawk Nation residents are assumed to ingest fish daily over a lifetime.
- c. The risk assessment assumes the incidental ingestion of sediments during recreational activities along the river bank. EPA's default values for incidental soil ingestion of 200 mg/kg and 100 mg/kg for children and adults, respectively, are used as estimates of sediment ingestion.
- d. The risk assessment evaluated two scenarios: less mobile fish that would be expected to be limited to the study area and more mobile fish who might be caught throughout the area along the St. Lawrence and Raquette Rivers.
- e. Site-specific parameters were considered where possible. As mentioned above, fish species not expected to migrate from the Reynolds Study Area were sampled and evaluated in the risk assessment. The sediment evaluation was based solely on Reynold's Study Area data. NYSDEC fish data from several locations in the St. Lawrence, Raquette, and Grasse Rivers were used to provide a broader estimate of fish ingestion risks associated with PCB contamination in the St. Lawrence River basin.

5.7.3 Comment: MIDC opposes dredging of the St. Lawrence River based on: the high short-term risks of dredging; the natural, in-situ biodegradation characteristics of PCBs; and the higher costs involved with the combination of dredging and in-situ containment in the event that dredging alone does not remove sediments to the 1 ppm PCB level. MIDC supports RMC's suggested approach of dredging and treating sediments above 500 ppm PCBs and in-situ containment of the lower residuals. MIDC believes that RMC can monitor the in-situ containment material over the long term, and that the RMC plan would have the fewest short-term effects.

Response: Please see EPA's responses to comments 4.4.1 and 5.2.19.

5.7.4 Comment: MIDC comments that if the sediments can be contained while protecting human health and the environment (if indeed human health and the environment are truly at risk), then RMC should not be required to experiment with a new and unproven costly alternative. Although EPA states that its preferred alternative is one of the least expensive alternatives which results in permanent removal, it could become the most expensive if dredging does not attain the cleanup levels and in-situ containment is required.

Response: Please see EPA's response to comment 4.1.12.

5.7.5 Comment: EPA's proposed remedy is far more expensive than RMC's suggested approach, which achieves the same risk reduction as EPA's. MIDC questions how EPA can balance risk and cost when the risk assessment is not in final form. EPA has doubled the cleanup costs by requiring cleanup levels that are significantly lower than at other similar CERCLA sites.

Response: Please see EPA's responses to comments 4.2.3 and 4.4.1.

5.7.6 Comment: MIDC recommends that cleanup begin at the most upstream facility, and proceed downstream. This will prevent any potential for upstream contaminants to recontaminate cleaned areas.

Response: Please see EPA's response to comment 4.1.4.

5.7.7 Comment: It appears that EPA's proposed remedy, given its high cost and stringent standards, does not consider the local economy, and particularly the economic benefits that Reynolds Metals Company brings to the Massena area.

Response: Please see EPA's response to comment 4.4.1.

5.7.8 Comment: MIDC encourages EPA to reevaluate its disposal and remediation regulations for PCBs. PCBs may have fewer health effects than originally thought. MIDC cites recent criticism over the validity of using the results of animal studies to classify PCBs,

and the limitations in applying the results of animal studies to humans. Clinical research on past worker exposure to PCBs, which showed only minor dermatological effects, was noted. If no adverse effects have been found in groups of workers who have been in direct contact with concentrated PCBs, then it is unclear how EPA justifies the expense of remediating a chemical in such minute quantities. Furthermore, EPA has lumped all PCBs in the same risk class as 1260 PCBs (a probable carcinogen), even though there is no scientific evidence that PCB molecules with less chlorine content than the 1260s pose risk to human health or the environment. EPA may be regulating remediation of PCB deposits and sources that pose no harm to human health and the environment, at an enormous cost to U.S. corporations and the public.

Response: Please see EPA's responses to comments 5.2.3 and 5.2.24.

5.8 Aluminum Company of America (ALCOA)

The comments summarized below were received from ALCOA.

5.8.1 Comment: A PCB cleanup goal of 1 ppm is not likely to be technically achievable with dredging. Problems associated with sediment suspension, physical limitations of dredging, and irregularities of the river bed (e.g., boulders), are noted. Dredging activities at other sites (e.g., New Bedford Harbor, Sheboygan River, Shiawasse River, Willametter River, and Dwamish Waterway) have resulted in highly variable final residual PCB concentrations that generally averaged between 10 to 50 ppm PCBs. If EPA believes armoring after dredging may be required, it should have been included in the AA report. ALCOA recommends implementation of a field scale remedial program to determine the technical limitations of dredging at the Reynolds Study Area prior to a final remedial decision.

Response: Please see EPA's responses to comments 4.1.11, 5.2.1, 5.2.19 and 5.5.3.

5.8.2 Comment: A PCB cleanup goal of 1 ppm is unjustifiably stringent given that the risks associated with the Site appear to be significantly overstated.

Response: Please see EPA's response to comment 5.2.17.

5.8.3 Comment: The Eastern U.S. soil background survey data that were used in the draft risk assessment are not appropriate for extrapolation to sediments.

Response: Please see EPA's response to comment 5.2.5.

5.8.4 Comment: ALCOA questions whether EPA followed the NCP in producing the draft risk assessment. It is unclear whether the draft risk assessment was done in a timely manner, consistent with EPA guidance documents.

Response: Please see EPA's response to comment 4.2.3.

5.8.5 Comment: It is unclear whether EPA has appropriately balanced the potential risks of dredging with the potential benefits. Since silt containment systems are not 100% effective, especially in areas with currents greater than 2 feet/second, there is the problem of sediment suspension. In addition, extensive dredging would destroy the existing sediment habitat and eliminate benthic organisms which are an essential component of the ecosystem.

Response: EPA recognizes that several of the remedial alternatives evaluated pose fewer short-term risks than the remedial alternative selected by EPA. After carefully balancing the specific characteristics of the Site according to the nine criteria as outlined in the NCP, EPA has determined that the long-term effectiveness, permanence, and protectiveness of public health and the environment afforded by the selected alternatives offset any short-term risks posed

by the selected alternative.

Because the areas to be dredged are primarily depositional in nature, EPA believes that sediment habitat and benthic organisms placement will occur naturally following the completion of dredging. The dredged area will be monitored following the completion of dredging. If habitat restoration and/or benthic repopulation are necessary, they may be required based on the results of monitoring data.

5.8.6 Comment: Armoring could provide an effective alternative which meets CERCLA evaluation criteria at a significantly lower cost than removal alternatives. In its Proposed Plan, EPA indicates that armoring may be required regardless of the alternative selected, which is likely given the cleanup goals. However, the costs for such armoring should be included in the AA report for the alternatives which consider removal because this cost consideration would affect the current analysis. ALCOA notes that in-situ containment and anaerobic biodegradation of PCBs in sediment, as observed in the Upper Hudson River (New York), Silver Lake (Pittsfield, Massachusetts), Waukegan Harbor (Illinois), Sheboygan River (Wisconsin) and the Acushnet River (New Bedford, MA), could provide for a permanent solution at the Site.

Response: Please see EPA's response to comment 4.1.12.

5.8.7 Comment: If sediment is removed, treatment should not be required. Treatment of PCB-contaminated sediments is not required to meet ARARs or current regulatory requirements, including TSCA.

If EPA requires treatment at the Site, the treatment goals are unnecessarily stringent. The treatment residuals should not have to be less than concentrations similar to other material being disposed at the RMC facility (i.e., less than 10 ppm). In addition, it would not be cost effective, or result in significant risk reduction, to treat material slightly greater than 10 ppm to under 10 ppm (e.g., 13 ppm treated to 8 ppm). Although thermal desorption shows promise, EPA should allow RMC to select a treatment technology through evaluation and competitive bidding.

Finally, EPA should reevaluate Alternative D because it is significantly more cost effective and could be equally protective as any alternative using thermal desorption.

Response: The treatment levels specified in the decision document were selected by EPA to ensure protection of human health and the environment. The remedial alternatives developed for the Site are consistent with EPA's PCB Guidance. For instance, according to this guidance, soils with PCB concentrations in the 10 to 25 ppm range may be disposed on an industrial facility with minimal long-term management controls. Accordingly, EPA has evaluated an alternative for the RMC Site which includes disposal of sediments with PCB concentrations between 10 and 25 ppm in the Black Mud Pond, rather than in an engineered landfill (Alternative G). The PCB Guidance also recommends that soils with higher concentrations of PCBs be disposed on an industrial facility in an engineered containment system which may include a cover and liner system. Accordingly, EPA has evaluated

alternatives which include disposal of untreated sediments (Alternative D) or treated sediments with PCB concentrations between 50 and 500 ppm in an engineered landfill (Alternative I). In addition, several of the other alternatives evaluated (including Alternatives E, F, and J) include options for disposal in the Black Mud Pond or in an engineered landfill depending on whether the material is a hazardous waste.

In its Proposed Plan, EPA discussed the proprietary process "ATP" whose generic name is thermal desorption. However, EPA took its information directly from the AA report, which was prepared by RMC. The thermal desorption system to be used at the Site may not be limited to ATP.

5.8.8 Comment: EPA should have considered additional combination alternatives that include removing and disposing material at an achievable PCB cleanup level (i.e., 25, 50 or 500 ppm) and armoring of other select sediment areas. This and Alternative J could provide an optimum balance among the nine criteria.

Response: Please see EPA's responses to comments 5.2.19 and 5.2.20.

5.8.9 Comment: It is unnecessary to link the ALCOA, G.M. and RMC sediment areas of concern in a coordinated cleanup effort because there are unique ecosystems associated with each of the areas. Linking the areas will also make it difficult from a community acceptance perspective to develop cleanup plans for the Grasse and Raquette Rivers differently than for the St. Lawrence River.

Response: EPA's selected alternatives and cleanup objectives are site-specific to accommodate varying site conditions. However, EPA's objective is to coordinate the dredging activities at the RMC Site with the dredging activities of the other Massena area facilities to the greatest extent possible. To that end, EPA will utilize a phased approach that will begin with dredging PCB hotspots, or areas with the highest PCB contamination at the most upstream facility and proceed downstream.

5.8.10 Comment: Many of the highly conservative assumptions used in the HHA are attributed to a personal communication--K. Jock (1991). Further information must be provided to justify the appropriateness of the information and assumptions utilized.

Response: Please see EPA's response to comment 5.2.3.

5.8.11 Comment: ALCOA questions the relatively small cost difference (\$0.9 million) between Alternative I, removing sediment above 10 ppm PCBs with treatment of materials greater than 500 ppm, and Alternative G, removing and treating materials greater than 10 ppm, when there is such a significant difference in volume.

Response: Alternative I includes costs for construction of an engineered hazardous waste landfill cell while Alternative G includes costs for on-site disposal in an unlined area with a soil cover. The difference in the degree of long-term management required under each alternative is based on the PCB concentration in the material to be contained (10 ppm versus 500 ppm).

5.8.12 Comment: If the volume of sediment (both depth and areal extent) to be removed should expand significantly on the basis of additional sampling, then it would increase costs and, in turn, change the AA. In-situ containment costs, on the other hand, would not be affected by sediment depth, only areal extent.

Response: Costs in the Proposed Plan and decision document may vary based on information gathered during remedial design and remedial action. EPA's estimates are considered to be + 50% and - 30% of actual final remediation costs.

5.8.13 Comment: ALCOA questions the inconsistency with materials management for EPA's proposed alternative--Alternative G--which is the only remedial option that does not include the construction of an engineered containment facility which meets hazardous waste requirements.

Response: The remedial alternatives developed for the Site are consistent with EPA's PCB Guidance. For instance, according to this guidance, soils with PCB concentrations in the 10 to 25 ppm range may be disposed on an industrial facility with minimal long-term management controls. Accordingly, EPA has evaluated an alternative for the RMC Site which includes disposal of sediments with PCB concentrations between 10 and 25 ppm in the Black Mud Pond, rather than in an engineered landfill (Alternative G). The PCB Guidance also recommends that soils with higher concentrations of PCBs be disposed on an industrial facility in an engineered containment system which may include a cover and liner system. Accordingly, EPA has evaluated alternatives which include disposal of untreated sediments (Alternative D) or treated sediments with PCB concentrations between 50 and 500 ppm in an engineered landfill (Alternative I). In addition, several of the other alternatives evaluated (including Alternatives E, F, and J) include options for disposal in the Black Mud Pond or in an engineered landfill depending on whether the material is a hazardous waste.

5.8.14 Comment: EPA's concerns about the feasibility of ensuring the integrity of in-situ containment material due to the river currents in the area adjacent to the RMC facility are unwarranted. The ARS showed slow-current characteristics in this area, which could be similar to those found in a harbor or lake.

Response: EPA has determined that dredging is an effective way of removing the volume of contaminated sediments in the river system based on limited previous experience at other Superfund sites and federal projects. In addition, dredging of sediments is a permanent remedy, which allows treatment to reduce toxicity, mobility, and volume of PCBs.

In addition, although sediment containment with a graded cover would reduce the erosive force of the flowing river water and would limit movement of contaminants into the

environment, its long-term effectiveness is dependent upon the adequacy and reliability of the sediment cover. Long-term monitoring and maintenance of contained sediments would be difficult to achieve because the cover is located underwater. Because the sediments are submerged, the contained underwater sediments would require periodic inspections by divers. In addition, several rounds of sampling might be required to detect underwater containment cell leakage, since any leaking contamination would be diluted. Further, if underwater monitoring revealed that cap repairs were necessary, such repairs could likely only be undertaken in late spring or in summer. Little information is available on the frequency with which maintenance would be needed or on the probability of cover failure. If the sediment cover fails, risks on the order of 10^{-2} would be present immediately since contaminated sediments would reenter the river system and be available to contaminate fish and wildlife. Sediment dredging, on the other hand, would permanently remove the long-term risks from contaminated sediments.

Although containment of contamination is less difficult than excavation or dredging and treatment of contamination, EPA prefers technologies in which treatment that permanently and significantly reduces the volume, toxicity or mobility of the PCBs is a principal element.

5.8.15 Comment: ALCOA questions whether the \$190,000/year operation and maintenance cost of Alternative B includes operation and maintenance costs beyond the five year review.

Response: In addition to costs for the five year review, the estimate includes operation and maintenance costs for 30 years.

5.8.16 Comment: There appears to be an inconsistency between Alternative E, where incinerator ash would be required to have PCB levels at or below 2 ppm, and the other alternatives, which would require treatment to 10 ppm only.

Response: TSCA guidance generally requires that incinerators treat solids to levels below 2 ppm PCBs.

5.8.17 Comment: The additional sampling proposed for the upriver portion of the Reynolds Study Area is not necessary since existing data indicate that PCB concentrations in this area are 1 ppm.

Response: EPA's selected remedy provides for additional sampling in the upriver portion of the Reynolds Study Area, especially in reach 3A in the vicinity of sample A9 and near the mouth of the Grasse River, to determine whether dredging is warranted in these areas. Additional sampling is warranted in these areas since PCBs were detected in isolated samples from these areas at concentrations as high as 6.2 ppm.

5.8.18 Comment: EPA should clarify that the data obtained by NYSDEC that exhibits low levels of PCBs in three water samples was obtained by an unapproved analytical method, rendering the data irrelevant.

Response: The method used by NYSDEC in analyzing its water samples is identical to that required for SPDES analyses by NYSDEC. While this is not the method routinely used by EPA in its PCB water analyses, the data obtained through such analyses are by no means irrelevant.

5.8.19 Comment: ALCOA claims that the exposure assumptions in the draft human risk assessment are unreasonably conservative and result in an overestimation of risk. These assumptions include a lifetime (70-year) exposure duration and an exposure frequency of 39 weeks per year for residents and 50 weeks per year for fishermen. ALCOA also claims that dermal contact exposure assumptions related to sediment exposures are also overestimated.

Response: Please see EPA's response to comment 5.2.25.

5.9 General Motors (G.M.)

The comments summarized below were received from G.M..

5.9.1 Comment: EPA's selection of a 1.0 PCB cleanup criterion for sediments of the St. Lawrence River is unnecessarily stringent. Cleanup levels need to reflect site-specific data, as analyzed through appropriate risk assessment techniques. G.M. believes that inappropriate and ultraconservative exposure scenarios, and inappropriate PCB toxicity factors were used. The costs of attempting to meet EPA's proposed cleanup levels will be extremely disproportionate to the benefits achieved.

Response: Please see EPA's response to comment 5.2.17.

5.9.2 Comment: There is no evidence available to indicate that removal of sediments to a 1.0 ppm PCB cleanup level is technically feasible. EPA should either define the basis of evidence, or should adopt a cleanup level which is believed to be achievable based on experience at similar sites. EPA should explain how it will determine whether the selected 1 ppm cleanup level for sediment remediation is achievable or is technically impracticable.

G.M. recommends implementation of a pilot dredging program to determine a technically feasible cleanup level.

Response: Please see EPA's responses to comments 4.1.11 and 5.5.3.

5.9.3 Comment: Since EPA considers in-place armoring (containment) of sediments an acceptable post-removal approach (following dredging), its use should be considered for broader application in lieu of dredging. A containment approach alone should be selected since it can provide short and long-term protection to human health and the environment and reduces the short-term risks associated with sediment suspension and migration. In addition, armoring will enhance natural degradation of PCBs, resulting in reduced potential toxicity. Proper design of the containment and monitoring systems would eliminate or greatly reduce EPA's concern with the operation and maintenance issues and provide a cost-effective remedial program.

Response: Please see EPA's response to comment 4.1.12.

5.9.4 Comment: Since physical site conditions vary from site to site, remedial approaches and cleanup objectives should be based on site-specific considerations. The programs developed from these site-specific analyses should be coordinated to provide technical control and resource coordination.

Response: After careful consideration of RMC's site-specific characteristics, EPA evaluated and balanced each remedial alternative according to the nine criteria set forth in the NCP. In addition, EPA also evaluated its selected remedy for consistency with the PCB Guidance.

EPA recognizes that every Superfund site is different (different physical characteristics, contaminants, pathways of exposure, media); thus, EPA evaluates and selects an appropriate remedial alternative for each site on a site-by-site basis in light of available guidance and regulations.

EPA's objective is to coordinate the cleanup efforts at the RMC Site with the cleanup of the other Massena area facilities to the greatest extent possible. To that end, EPA will utilize a phased approach that will begin with dredging PCB hotspots, or areas with the highest PCB contamination, at the most upstream facility and proceed downstream.

5.9.5 Comment: If sediment removal is required, then only the higher concentrations of PCBs (e.g., 500 ppm or higher) should be treated, consistent with the EPA's PCB Guidance. Lower levels of PCBs do not warrant aggressive and costly treatment and can be appropriately contained at the RMC facility. G.M. notes the effective containment of similar materials at other sites. The more treatment activities that EPA requires, the more chance for accidents and breakdowns in the treatment system. Furthermore, total remedial costs will be extremely sensitive to changes in the identified volume of sediments over 10 ppm, rendering the entire remedy cost-ineffective under the NCP.

Response: Please see EPA's response to comment 5.2.18.

5.9.6 Comment: EPA's Proposed Plan should be based on a complete and final risk assessment. The Proposed Plan should be withdrawn until the risk assessment is finalized.

Response: Please see EPA's response to comment 4.2.3.