



Great Falls Update

Chris Sorensen
Environmental Program
Coordinator



Washout Flow

(30 loads) (1 day) (1500 gallon/
washout)=45,000 gallons/day average
flow.

Field Testing

- pH 12.2, 12.3, 12.4 downstream

































Permit Limits

- pH 5.5-9.0 su
- Total Suspended Solids
 - Surcharge >100 lbs/day
- Metals per City ordinance
- Oil and Grease 100 mg/l
- Flow
- Berms must remain in place

Self Imposed BMP's

- Washout limited to 500 gallons water
- Off loading solids before washout









GreenGuard®
STYRENE INSULATION BOARD

Thickness	1	1 1/2	2	3
R-Value	5.0	7.5	10.0	15.0

and intensity. Protect foam insulation from exposure to direct sunlight. The insulation must be installed in accordance with the instructions on the product label. Dept. of Energy Chapter 7640, COMC 12722-1, U.S. GreenGuard®



Mill every 16 inches.

Before installing
Certificate A183
sources during

ACTIV
ing Products



What's on The Horizon?

- Possible Hospital Permitting
- 500 beds on two campuses.
- In House laundry
- Possibly 7 outfalls on Main Campus
- No Chemical Inventory

Two Tanneries Discovered during Industrial Survey





